Green Elimber LVXIII





The LV800 is the largest of the Green Climber remote controlled Slope Mowers. The LV800 comes standard with a 61" carbide teethed forestry head, a remote-controlled winch, and a protective forestry package. This compact, powerful slope mower is ideal for aggressive land clearing or light forestry.



side shifting attachment head



vertical shifting attachment head



extend-able tracks





Forestry mulcher with rotating blades UT-F

- Cutting Capacity: up to 8" Diameter
- Hydraulically opening hood
- Rounded corners
- Height adjustable slides
- Roller adjustable in height
- Reinforced support sleds
- Quick hydraulic coupling
- Reinforced hammers with 360 ° rotation





Forestry shredder with fixed tools

- Cutting Capacity: up to 8" Diameter
- Forest rotor with fixed tools
- with tungsten carbide
- Anti-wear steel frame and rollers
- Hydraulically opening hood
- Reinforced support sleds
- Quick hydraulic coupling
- Jointed reinforced plate attachment



TECHNICAL SPECIFICATIONS					
Dry net weight	3,750 LBS				
Max work gradient	60°, all directions				
Accessory side shifting Hydraulic + manual	+ 20" Hyd. / + 23" Mech.				
Hydraulic Connection Style	Faster Quick Connect Couplings				
Speed	6 MPH				
Engine: Kohler KDI 2504 TCR Diesel	Tier 4 Final Turbocharged, common rail intercooler				
EPA Compliant	USA & California Emissions compliant				
Number of Cylinders	4				
Engine Max. power kW (hp) @rpm	55.4 (75) @2200				
Engine torque (Nm@rpm)	300.0@1500				
Attachment Shifting/Tilting	Hydraulic				
Engine Cooling	Liquid				
Fuel tank	14 Gallon				
Reversible radiator fan	Yes				
Driving commands	Single joystick use to drive and steer				
Track adjustable width	1910mm (open)> 1510 (closed)				
Full floating attachment system	Yes				
Pre-Filter Style	Vortex				
Removable metal protection	yes				
roll-bar	yes				
Total Hydraulic Flow	60 Gal				
Hydraulic Auxiliary lines	3, proportional				
Main attachment hydraulic flow	26 Gal @ 350 Bar				
Towing hook	Yes				
Remote controlled winch	Yes				
Remote control frequency	2.4Ghz				

FORESTRY HEAD TECHNICAL SPECIFICATIONS

	1					
model	Working width	Total width	Weight	Oil flow	Cutting Style	RPM
Fixed teeth flail	50 Inches	57 Inches	490 kg 1080 LBS	105L/min	Carbide Tip Fixed	up to 3300
Fixed teeth flail	60 Inches	67 Inches	540kg 1180 LBS	105L/min	Carbide Tip Fixed	up to 3300
Fixed teeth flail	69 Inches	76 Inches	640 kg 1400 LBS	105L/min	Carbide Tip Fixed	up to 3300
Revolving hammers flail UTF	58-70 Inches	61-75 Inches	450/550 kg 900/1100 LBS	105L/min	revolving hammers	up to 3300

