



## TOOL CARRIER

- 73-inch (1.85-m) hinge pin height provides the flexibility to perform an extensive range of tasks.
- Roomy, ride-on platform absorbs shock, reduces fatigue and keeps you out of dirt, mud and debris.
- Dual-element remote air cleaner provides outstanding filtration even in dusty conditions.
- Optional self-leveling kit—an exclusive feature—ensures that the attachment is level, so work can be more accurate and efficient.
- Kickstand for quick and easy attachment to and removal from the power unit.
- Exclusive traction-assist feature provides extra drawbar on demand, enabling you to push more, pull more and traverse soft ground with minimal tire slippage.
- 4-bar linkage on bucket curl increases rollback and dump angles so you can move materials more efficiently.
- Standard attachment plate provides maximum versatility; accepts more than 40 quick-change attachments.

### DIMENSIONS

	U.S.	METRIC
Mobile length	91.5 in	2.32 m
Tie-down length	29.8 in	757 mm
Length, max	91.5 in	2.32 m
Attachment length	45.7 in	1.16 m
Mobile height	53.5 in	1.36 m
Tie-down height	46.1 in	1.17 m
Attachment height, max	81.8 in	2.08 m
Bucket height, max	96 in	2.44 m
Hinge pin height	73 in	1.85 m
Dump clearance	55.5 in	1.41 m
Width	36 in	914 mm
Attachment width	23 in	584 mm
Angle of departure	25°	
Dump angle	53°	
Rollback angle	18°	
Unit mass	1,889 lb	856.8 kg
Attachment mass	373 lb	169 kg
Tipping capacity	864 lb	391.9 kg
Rated operating capacity (50% of tipping capacity)	432 lb	196 kg

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

## VIBRATORY PLOW

- Variable blade pitch allows operator to change the angle of the leading edge of the blade to be more or less aggressive, to match soil conditions.
- Accepts standard Ditch Witch® vibratory plow blades, eliminating the need to purchase new blades.
- Optional reel carrier provides efficient installation of cable with minimal jobsite restoration.
- Optional sod cutter and skid shoes provide greater versatility and minimize restoration.
- Ergonomically designed operator's station features soft-touch, color-coded controls that are easy to learn and provide smooth, easy operation.
- 9-gallon (34.06-L) fuel tank enables you to work long hours without having to refuel; the tank's molded-in sight glass allows you to keep an eye on fuel consumption.
- Convenient cargo tray is large enough to store a water bottle, work gloves, cell phone, or assorted tools.
- Optional quad tracks for maximum stability and performance.

### DIMENSIONS

	U.S.	METRIC
Mobile length	104.8 in	2.66 m
Tie-down length	101.8 in	2.59 m
Attachment length	55.5 in	1.41 m
Mobile height	56 in	1.42 m
Tie-down height	43 in	1.09 m
Attachment height, max	56 in	1.42 m
Operating depth	20 in	508 mm
Cover depth	18 in	457 mm
Width	36 in	914 mm
Attachment width	18 in	457 mm
Angle of departure	25°	
Angle of approach	30°	
Unit mass	1,839 lb	834.2 kg
Attachment mass w/blade	348 lb	157.9 kg

### OPERATION

Plow vibrator force @ 1,600 rpm	4,600 lb	20.46 kN
Material diameter, max		
Pulled	3 in	76 mm
Fed	1 in	25 mm

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.