

Joe Green

New vehicle (2024 NPR Gas Crew Cab, 1D3 150"WB, 88.5"CA, 12,000 GVWR. White, Standard model specifications with power windows and door locks

Selected Model a	-		
	Code	Description	Weight
Model			
	1D3	NPR Gas Crew Cab 150"WB, 88.5"CA	
	04	White, Standard model specifications with power	
Vahiala Annliaation		windows and door locks	
Vehicle Application	DO2	Truck Application	0.0 lba
Tires	RQ2	Truck Application	0.0 lbs
Tires	I5H	LRR (low rolling resistance)	0.0 lbs
Engino	ISH	LRR (low rolling resistance)	0.0 108
Engine	LOT	CMDT 6.6L (400 CID) \/9 gassline angine: 250 HD at	0.0 lba
	L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise	0.0 lbs
		fuel control direct injection technology; electronic	
		throttle control; overhead valves with variable valve	
		timing; heavy duty cast-iron cylinder block with six-	
		bolt main-bearing cap; cast aluminum cylinder	
		heads; forged steel crankshaft; stainless steel	
		exhaust manifold.	
Transmission			
	MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up	0.0 lbs
		converter and overdrive. Ratios: Gear and Ratios	
		4.027, 2.364 ,1.532, 1.152, 0.0852, 0.667, Rev.	
		3.064:1	
Wheelbase			
	IB1	150 inches, includes ladder type channel frame. Full	0.0 lbs
		C section straight frame 33.5 inches wide. Yield	
		strength 44,000 psi; section modulus 7.20in3 RBM	
Air Cleaner		316,800 lb./ft./in. per rail. 88.5"CA	
All Cleaner	IZNIV	Dry paper single element. Air element conjeter	0.0 lba
	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	0.0 lbs
Alternator		Standard with all restriction gauge.	
Alternator	KW7	170 Amp. output with integral regulator.	0.0 lbs
Battery	IXVV7	170 Amp. output with integral regulator.	0.0 103
Dattery	IL3	Single Delco 12-V maintenance free 750 CCA frame	0.0 lbs
	iLJ	mounted battery box	0.0 103
Exhaust			
	I41	Single horizontal aluminized steel with catalytic	0.0 lbs
	171	converter and oxygen sensor devices.	0.0 103
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral	0.0 lbs
		hydraulic power steering. Ratio 18.8-20.9:1.	
Front Suspension			
•	ID4	6,830 lb. capacity. Semi-elliptical tapered leaf	0.0 lbs
		springs. Includes shock absorbers and stabilizer bar.	
Front Wheels			
	RBY	16" X 6", 6-hole disc, painted white.	0.0 lbs
Front Tires			
	153169	215/85R16E (10 ply) tubeless Radial, all season	0.0 lbs
		tread.	3.3 183

Current report content is based on data as of 2023-04-18 08:43:04. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



Joe Green

New vehicle (2024 NPR Gas Crew Cab, 1D3 150"WB, 88.5"CA, 12,000 GVWR. White, Standard model specifications with power windows and door locks

Selected Mode	Code	Description	\A/a:-b
	Code	Description	Weight
Rear Suspension			
	I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.	0.0 lbs
Rear Axle			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs
Ratio			
	066	4.100:1	0.0 lbs
Rear Wheels			
	RBZ	16" X 6", 6-hole disc, painted white.	0.0 lbs
Rear Tires			
	153134	215/85R16E (10 ply) tubeless Radial, all season tread.	0.0 lbs
Fuel Tank			
	A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	0.0 lbs
Seat			
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs
Brakes			
	IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	0.0 lbs
Air Conditioning			
	C60	Air conditioner	0.0 lbs
Power Windows & Do	oor Locks		
	ILO	Yes	0.0 lbs
Model Option			
	04	White, Standard model specifications with power windows and door locks	0.0 lbs
Accessories			
	IX2 8RP	Rear body dome lamp switch AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.1 lbs 0.0 lbs

Current report content is based on data as of 2023-04-18 08:43:04. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



Joe Green

New vehicle (2024 NPR Gas Crew Cab, 1D3 150"WB, 88.5"CA, 12,000 GVWR. White, Standard model specifications with power windows and door locks

Standard	Equipment Summary
Code	Description
Vehicle Appl	·
RQ2	Truck Application
Tires	The state of the s
I5H	LRR (low rolling resistance)
Engine	
L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.
Transmissio	n
MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364 ,1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1
Wheelbase	
IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA
Air Cleaner	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.
Alternator	
KW7	170 Amp. output with integral regulator.
Battery	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box
Exhaust	
I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspe	nsion
ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.
Front Wheels	3
RBY	16" X 6", 6-hole disc, painted white.
Front Tires	
153169	215/85R16E (10 ply) tubeless Radial, all season tread.
Rear Suspen	sion
18J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.
Rear Axle	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
066	4.100:1
Rear Wheels	
RBZ	16" X 6", 6-hole disc, painted white.
Rear Tires	
153134	215/85R16E (10 ply) tubeless Radial, all season tread.
Fuel Tank	
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Brakes	
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking
_	the content is because at the content of 2002 04 40 00 42 04 Amura of content

Current report content is based on data as of 2023-04-18 08:43:04. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



Joe Green

New vehicle (2024 NPR Gas Crew Cab, 1D3 150"WB, 88.5"CA, 12,000 GVWR. White, Standard model specifications with power windows and door locks

Standard Equipment Summary					
Code	Description				
	brake. Non-asbestos semi metallic linings are standard.				
Air Conditio	ning				
C60	Air conditioner				
Power Windows & Door Locks					
IL0	Yes				
Model Option	on Control of the Con				
04	White, Standard model specifications with power windows and door locks				
Accessories					
IX2	Rear body dome lamp switch				
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO				

Current report content is based on data as of 2023-04-18 08:43:04. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



Joe Green

New vehicle (2024 NPR Gas Crew Cab, 1D3 150"WB, 88.5"CA, 12,000 GVWR. White, Standard model specifications with power windows and door locks

Warranty

Warranty Limitations: Time or Mileage, Whichever Col	mes First	
New Truck Warranty	Time in Years	Vehicle Miles
Basic	3	36,000
Engine Transmission Drive Axle	5	75,000
Frame Rails	3	36,000
Traine Naiis	5*	Unlimited*
Corrosion (Rust Through)	4	Unlimited
	3	36,000
Deceleide Accietance	•	30,000
Roadside Assistance	5^{\dagger}	75,000 [†]
Roadside Assistance Emission Warranty		
	$\mathit{5}^{\dagger}$	75,000 [†]
Emission Warranty	5 [†] Time in Years	75,000 [†] Vehicle Miles
Emission Warranty Emissions Defect Warranty - Federal Emissions Performance Warranty - Federal	5 [†] Time in Years 5	75,000 [†] Vehicle Miles 50,000
Emission Warranty Emissions Defect Warranty - Federal	5 [†] Time in Years 5 5	75,000 [†] Vehicle Miles 50,000 50,000
Emission Warranty Emissions Defect Warranty - Federal Emissions Performance Warranty - Federal	5 [†] Time in Years 5 5	75,000 [†] Vehicle Miles 50,000 50,000
Emission Warranty Emissions Defect Warranty - Federal Emissions Performance Warranty - Federal Emissions Defect Warranty (NPR model) - California**	5 [†] Time in Years 5 5 7	75,000 [†] Vehicle Miles 50,000 50,000 50,000 70,000

^{*}After 3 years or 36,000 miles (whichever comes first), labor and parts coverage is 50% for up to 5 years.

The warranty coverages are determined by the mileage of the vehicle and the number of years from the delivery date. The warranty coverages are limited by whichever occurs first. Please see your authorized Isuzu dealer for warranty details.

Current report content is based on data as of 2023-04-18 08:43:04. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

[†]Tows related to powertrain issues may be covered for up to 5 years or 75,000 miles (whichever comes first).

^{**}Please see warranty booklet for coverage details.