



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2024 NQR Gas Crew Cab, 1S3 150"WB, 88.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

## Selected Model and Options

	Code	Description	Weight
Model			
	1S3 04	NQR Gas Crew Cab 150"WB, 88.5"CA White, Standard model specifications with power windows and door locks	
Vehicle Application			
	RQ2	Truck Application	0.0 lbs.
Tires			
	I5H	LRR (low rolling resistance)	0.0 lbs.
Engine			
	L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.	0.0 lbs.
Transmission			
	Y6V	Allison 1000 RDS 6-speed automatic transmission w/o PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	0.0 lbs.
Wheelbase			
	IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA	0.0 lbs.
Air Cleaner			
	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	0.0 lbs.
Battery			
	IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	0.0 lbs.
Exhaust			
	I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	0.0 lbs.
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Front Tires			
	I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	0.0 lbs.
Rear Axle			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.
Ratio			
	011	5.571:1	0.0 lbs.
Rear Wheels			

Current report content is based on data as of 2023-04-18 09:54:11. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2024 NQR Gas Crew Cab, 1S3 150"WB, 88.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

## Selected Model and Options

	Code	Description	Weight
	IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Rear Tires			
	I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	0.0 lbs.
Fuel Tank			
	A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	0.0 lbs.
Seat			
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.
Air Conditioning			
	C60	Air conditioner	0.0 lbs.
Power Windows & Door Locks			
	IL0	Yes	0.0 lbs.
Model Option			
	04	White, Standard model specifications with power windows and door locks	0.0 lbs.
Accessories			
	IX2	Rear body dome lamp switch	0.1 lbs.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.

Current report content is based on data as of 2023-04-18 09:54:11. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2024 NQR Gas Crew Cab, 1S3 150"WB, 88.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

## Standard Equipment Summary

Code	Description
<b>Vehicle Application</b>	
RQ2	Truck Application
<b>Tires</b>	
I5H	LRR (low rolling resistance)
<b>Engine</b>	
L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.
<b>Transmission</b>	
Y6V	Allison 1000 RDS 6-speed automatic transmission w/o PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1
<b>Wheelbase</b>	
IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA
<b>Air Cleaner</b>	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.
<b>Battery</b>	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box
<b>Exhaust</b>	
I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.
<b>Front Axle</b>	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
<b>Front Wheels</b>	
IB9	19.5" x 6", 6-hole disc, painted white
<b>Front Tires</b>	
I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread
<b>Rear Axle</b>	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
<b>Ratio</b>	
011	5.571:1
<b>Rear Wheels</b>	
IC1	19.5" x 6", 6-hole disc, painted white
<b>Rear Tires</b>	
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.
<b>Fuel Tank</b>	
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.
<b>Seat</b>	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
<b>Air Conditioning</b>	
C60	Air conditioner
<b>Power Windows &amp; Door Locks</b>	
IL0	Yes
<b>Model Option</b>	
04	White, Standard model specifications with power windows and door locks
<b>Accessories</b>	
IX2	Rear body dome lamp switch

Current report content is based on data as of 2023-04-18 09:54:11. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2024 NQR Gas Crew Cab, 1S3 150"WB, 88.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

## Standard Equipment Summary

Code	Description
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2023-04-18 09:54:11. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# ISUZU TRUCK OF FAYETTEVILLE

Joe Green

New vehicle (2024 NQR Gas Crew Cab, 1S3 150"WB, 88.5"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

## Warranty

**Warranty Limitations:** *Time or Mileage, Whichever Comes First*

<i>New Truck Warranty</i>	<i>Time in Years</i>	<i>Vehicle Miles</i>
<i>Basic</i>	3	36,000
<i>Engine</i>	5	75,000
<i>Transmission</i>		
<i>Drive Axle</i>		
<i>Frame Rails</i>	3	36,000
	5*	Unlimited*
<i>Corrosion (Rust Through)</i>	4	Unlimited
<i>Roadside Assistance</i>	3	36,000
	5†	75,000†
<i>Emission Warranty</i>	<i>Time in Years</i>	<i>Vehicle Miles</i>
<i>Emissions Defect Warranty - Federal</i>	5	50,000
<i>Emissions Performance Warranty - Federal</i>	5	50,000
<i>Emissions Defect Warranty (NPR model) - California**</i>	3	50,000
	7	70,000
<i>Emissions Defect Warranty (NPR-HD model) - California**</i>	5	50,000
<i>GHG Emission</i>	5	50,000
<i>Tires</i>	2	24,000

\*After 3 years or 36,000 miles (whichever comes first), labor and parts coverage is 50% for up to 5 years.

†Tows related to powertrain issues may be covered for up to 5 years or 75,000 miles (whichever comes first).

\*\*Please see warranty booklet for coverage details.

The warranty coverages are determined by the mileage of the vehicle and the number of years from the delivery date. The warranty coverages are limited by whichever occurs first. Please see your authorized Isuzu dealer for warranty details.