

Joe Green

New vehicle (2024 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

| | Code | Description | Weight |
|---------------------|------|--|---------------------------------------|
| Model | Godo | Boompton | · · · · · · · · · · · · · · · · · · · |
| | 1V3 | NRR Gas Crew Cab 150"WB, 88.5"CA | |
| | 04 | White, Standard model specifications with power | |
| | 01 | windows and door locks | |
| Vehicle Application | | | |
| | RQ2 | Truck Application | 0.0 lbs |
| Tires | | The second secon | |
| | I5H | LRR (low rolling resistance) | 0.0 lbs |
| Engine | | | |
| | L8T | GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold. | 0.0 lbs |
| Transmission | | | |
| | Y6V | Allison 1000 RDS 6-speed automatic transmission w/o PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1 | 0.0 lbs |
| Wheelbase | | | |
| | IB1 | 150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA | 0.0 lbs |
| Air Cleaner | | | |
| | KNX | Dry paper single element. Air cleaner canister standard with air restriction gauge. | 0.0 lbs |
| Battery | | | |
| | IL3 | Single Delco 12-V maintenance free 750 CCA frame mounted battery box | 0.0 lbs |
| Exhaust | | | |
| | 141 | Single horizontal aluminized steel with catalytic converter and oxygen sensor devices. | 0.0 lbs |
| Front Axle | | | |
| | IZ6 | "I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1. | 0.0 lbs |
| Front Wheels | | | |
| | IB9 | 19.5" x 6", 6-hole disc, painted white | 0.0 lbs |
| Front Tires | | | |
| | I8B | 225/70R19.5G (14 ply) tubeless Radial, all season tread | 0.0 lbs |
| Rear Axle | | | |
| | ID3 | Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings. | 0.0 lbs |
| Ratio | | | |
| | 011 | 5.571:1 | 0.0 lbs |

Current report content is based on data as of 2023-04-18 10:23:30. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



Joe Green

New vehicle (2024 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

| Selected Model and C | Opti | ons | |
|---------------------------------------|------|---|----------|
| Cod | de | Description | Weight |
| IC | C1 | 19.5" x 6", 6-hole disc, painted white | 0.0 lbs. |
| Rear Tires | | | |
| IS | | 225/70R19.5G (14 ply) tubeless Radial, all season tread. | 0.0 lbs. |
| Fuel Tank | | | |
| A | | 38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill. | 0.0 lbs. |
| Seat | | | |
| AC | | Driver seat is reclining high back. Two single occupant fold down seats with tray backs. | 0.0 lbs. |
| Air Conditioning | | | |
| Ce | 60 | Air conditioner | 0.0 lbs. |
| Power Windows & Door Locks | ; | | |
| II | IL0 | Yes | 0.0 lbs. |
| Model Option | | | |
| (| | White, Standard model specifications with power windows and door locks | 0.0 lbs. |
| Accessories | | | |
| I) | X2 | Rear body dome lamp switch | 0.1 lbs. |
| 8F | | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO | 0.0 lbs. |



Joe Green

New vehicle (2024 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

| Standard | Equipment Summary |
|---------------|--|
| Code | Description |
| Vehicle App | • |
| RQ2 | Truck Application |
| Tires | The state of the s |
| I5H | LRR (low rolling resistance) |
| Engine | (* * 5 ***** **) |
| L8T | GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold. |
| Transmissio | n |
| Y6V | Allison 1000 RDS 6-speed automatic transmission w/o PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1 |
| Wheelbase | |
| IB1 | 150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA |
| Air Cleaner | |
| KNX | Dry paper single element. Air cleaner canister standard with air restriction gauge. |
| Battery | |
| IL3 | Single Delco 12-V maintenance free 750 CCA frame mounted battery box |
| Exhaust | |
| I41 | Single horizontal aluminized steel with catalytic converter and oxygen sensor devices. |
| Front Axle | |
| IZ6 | "I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1. |
| Front Wheel | |
| IB9 | 19.5" x 6", 6-hole disc, painted white |
| Front Tires | |
| I8B | 225/70R19.5G (14 ply) tubeless Radial, all season tread |
| Rear Axle | |
| ID3 | Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings. |
| Ratio | |
| 011 | 5.571:1 |
| Rear Wheels | |
| IC1 | 19.5" x 6", 6-hole disc, painted white |
| Rear Tires | |
| I9B | 225/70R19.5G (14 ply) tubeless Radial, all season tread. |
| Fuel Tank | |
| A17 | 38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill. |
| Seat | |
| AQB | Driver seat is reclining high back. Two single occupant fold down seats with tray backs. |
| Air Condition | • |
| C60 | Air conditioner |
| | ows & Door Locks |
| IL0 | Yes |
| Model Optio | |
| 04 | White, Standard model specifications with power windows and door locks |
| Accessories | |
| IX2 | Rear body dome lamp switch |



Joe Green

New vehicle (2024 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

Standard Equipment Summary

| Code | Description |
|------|--|
| 8RP | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO |



Joe Green

New vehicle (2024 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

Warranty

| Warranty Limitations: Time or Mileage, Whichever Comes First | | | | | | | |
|---|---------------------------------|---|--|--|--|--|--|
| New Truck Warranty | Time in Years | Vehicle Miles | | | | | |
| Basic | 3 | 36,000 | | | | | |
| Engine Transmission Drive Axle | 5 | 75,000 | | | | | |
| Frame Rails | 3 | 36,000 | | | | | |
| Traine Nails | 5* | Unlimited* | | | | | |
| Corrosion (Rust Through) | 4 | Unlimited | | | | | |
| Dandaida Ansistanaa | 3 | 36,000 | | | | | |
| Roadside Assistance | _ | _ | | | | | |
| | $\mathit{5}^{\dagger}$ | 75,000 [†] | | | | | |
| Emission Warranty | 5 ^r Time in Years | 75,000 ^T Vehicle Miles | | | | | |
| Emission Warranty Emissions Defect Warranty - Federal | | , | | | | | |
| | Time in Years | Vehicle Miles | | | | | |
| Emissions Defect Warranty - Federal Emissions Performance Warranty - Federal | Time in Years 5 | Vehicle Miles 50,000 | | | | | |
| Emissions Defect Warranty - Federal | Time in Years 5 5 | Vehicle Miles 50,000 50,000 | | | | | |
| Emissions Defect Warranty - Federal Emissions Performance Warranty - Federal | Time in Years 5 5 | Vehicle Miles 50,000 50,000 50,000 | | | | | |
| Emissions Defect Warranty - Federal Emissions Performance Warranty - Federal Emissions Defect Warranty (NPR model) - California** | Time in Years 5 5 7 | Vehicle Miles 50,000 50,000 50,000 70,000 | | | | | |

^{*}After 3 years or 36,000 miles (whichever comes first), labor and parts coverage is 50% for up to 5 years.

The warranty coverages are determined by the mileage of the vehicle and the number of years from the delivery date. The warranty coverages are limited by whichever occurs first. Please see your authorized Isuzu dealer for warranty details.

[†]Tows related to powertrain issues may be covered for up to 5 years or 75,000 miles (whichever comes first).

^{**}Please see warranty booklet for coverage details.