2023 Vac Con Titan Dual Engine Truck

TPD3615E/1300	Includes: Roots 824 RCS PD Blower Free Air up
	to 5197 CFM (4000CFM at 18" HG), Hydrostatic
	Drive and Cyclone Separator, 15 CY Debris Tank,
	1300 Gal H2O, 6X4, Extended Frame

Hinge type / Body Prop Permanently mount debris body prop (hinge-type)

Vacuum System (as specified by Model Number)

Vacuum Drive: hydrostatic driven via transfer case

1/4" Corten steel debris tank

Hydraulic rear door locks

6" knife valve with 10' lay flat hose

Debris tank dumping: minimum 50 degree, hydraulic cylinder lift- power up/power down

Cross-linked polyethylene water tanks

Automatic vacuum breaker and overfill protection

8" vacuum intake hose

6 Way hydraulic boom with 230 degree rotation and joystick control

60gpm/2000psi water pump system

Water pump drive: Standard Aux Engine 5.7 GM gasoline powered

400' high pressure jet rodder hose

Heavy-duty dual roller level wind guide (aluminum)

Hose guide (Tiger Tail)

30" leader hose

20gpm/750psi wash-down system w/hand-gun and 25' of hose

1 each sanitary and penetrator nozzles

25' aluminum suction pipe(1-3', 2-5', 1-6' and 1-6.5' catch basin nozzle) w/quick clamps

ICC lighting LED

PPG Ambershield zinc primed, PPG Delfleet single stage polyurethane paint, and PPG Ambershield textured black paint

12 month standard warranty for module

5# Fire Extinguisher

Set Triangles

5 year centrifugal compressor (fans) warranty

5 year debris tank warranty

10 year water tank warranty

Two boxes 35" Tall x 24" wide x 14.5" deep (6cyl JD or Cat C4.4 will only be able to fit one 35" box.) - These two toolboxes are standard on units with 1000 gallons of fresh water except for 5yd units.

Behind Cab Boom Support Chassis frame mounted 711-55997A Boom Cradle Assembly with 711-55619 bumper mounted boom docking assembly

Plastic engraved decals - adhesive type (ilo standard, remove as selectable option)

Dump High

Flat Style Rear Door

Front mounted 600' capacity (1" hose)/hydraulic fixed hose reel

36 cubic feet (96" wide Storage box behind cab), Steel, - Standard with 1300 and 1500 gallon units, 5yd units with 1000 gallons

Rear bumper with built in tow hooks

800 gallon units include two tool boxes, 35" tall, x 14" wide, x 24"deep

Centrifugal Compressor Quiet Silencer, Class 4, 304 Stainless Steel Construction, 14in x 40in with 8in discharge