2023 Vac Con Titan Dual Engine Truck

TPD3650/850	Includes: Roots 824 RCS PD Blower Free Air up
	to 5197 CFM (4000CFM at 18" HG), Hydrostatic
	Drive and Cyclone Separator, 5 CY Debris Tank,
	850 Gal H2O, 4X2, Non-Extended Frame

Hinge type / Body Prop Permanently mount debris body prop (hinge-type)

Vacuum System (as specified by Model Number)

Vacuum Drive: hydrostatic driven via transfer case

1/4" Corten steel debris tank

Hydraulic rear door locks

6" knife valve with 10' lay flat hose

Debris tank dumping: minimum 50 degree, hydraulic cylinder lift- power up/power down

Cross-linked polyethylene water tanks

Automatic vacuum breaker and overfill protection

8" vacuum intake hose

6 Way hydraulic boom with 230 degree rotation and joystick control

60gpm/2000psi water pump system

Water pump drive: Standard Aux Engine 5.7 GM gasoline powered

400' high pressure jet rodder hose

Heavy-duty dual roller level wind guide (aluminum)

Hose guide (Tiger Tail)

30" leader hose

20gpm/750psi wash-down system w/hand-gun and 25' of hose

1 each sanitary and penetrator nozzles

25' aluminum suction pipe(1-3', 2-5', 1-6' and 1-6.5' catch basin nozzle) w/quick clamps

ICC lighting LED

PPG Ambershield zinc primed, PPG Delfleet single stage polyurethane paint, and PPG Ambershield textured black paint

12 month standard warranty for module

5# Fire Extinguisher

Set Triangles

5 year centrifugal compressor (fans) warranty

5 year debris tank warranty

10 year water tank warranty

Two boxes 35" Tall x 24" wide x 14.5" deep (6cyl JD or Cat C4.4 will only be able to fit one 35" box.) - These two toolboxes are standard on units with 1000 gallons of fresh water except for 5yd units.

Behind Cab Boom Support Chassis frame mounted 711-55997A Boom Cradle Assembly with 711-55619 bumper mounted boom docking assembly

Plastic engraved decals - adhesive type (ilo standard, remove as selectable option)

Dump High

Flat Style Rear Door

Front mounted 600' capacity (1" hose)/hydraulic fixed hose reel

36 cubic feet (96" wide Storage box behind cab), Steel, - Standard with 1300 and 1500 gallon units, 5yd units with 1000 gallons

Rear bumper with built in tow hooks

800 gallon units include two tool boxes, 35" tall, x 14" wide, x 24"deep

Centrifugal Compressor Quiet Silencer, Class 4, 304 Stainless Steel Construction, 14in x 40in with 8in discharge