

ZT7000

COMMERCIAL



MODEL NUMBER	9997010	9997011	9997064	9997065
ENGINE				
Model	Kaw FX1000V	Kaw FX1000V	Kaw FX1000V EFI	Kaw FX1000V EFI
Horsepower	35.0 hp (26.0 kW)	35.0 hp (26.0 kW)	38.5 hp (28.7 kW)	38.5 hp (28.7 kW)
Displacement	60.9 cu. in. (999 cc)	60.9 cu. in. (999 cc)	61.0 cu. in. (999 cc)	61.0 cu. in. (999 cc)
Fuel Capacity	15.0 gal. (56.7 L)	15.0 gal. (56.7 L)	15.0 gal. (56.7 L)	15.0 gal. (56.7 L)
Air Filter	Canister Air Filter	Canister Air Filter	Canister Air Filter	Canister Air Filter
ELECTRICAL				
Charging System	15 amp	15 amp	15 amp	15 amp
Clutch	250 lbf. (1112 N)	250 lbf. (1112 N)	250 lbf. (1112 N)	250 lbf. (1112 N)
DECK				
Mower Deck	AirFX Cutting System	AirFX Cutting System	AirFX Cutting System	AirFX Cutting System
Leading Edge	Adjustable, Front Lip Standard	Adjustable, Front Lip Standard	Adjustable, Front Lip Standard	Adjustable, Front Lip Standard
Width	61.0 in. (1549 mm)	72.0 in. (1828 mm)	61.0 in. (1549 mm)	72.0 in. (1828 mm)
Adjustable Anti-Scalp Rollers	6	7	6	7
Cutting Height	1.0-5.5 in. (25-139 mm)	1.0-5.5 in. (25-139 mm)	1.0-5.5 in. (25-139 mm)	1.0-5.5 in. (25-139 mm)
Blade Tip Speed	18,500 fpm @ 3550 Engine rpm	18,152 fpm @ 3550 Engine rpm	18,500 fpm @ 3550 Engine rpm	18,152 fpm @ 3550 Engine rpm
Discharge Chute	Flexible Molded Polymer	Flexible Molded Polymer	Flexible Molded Polymer	Flexible Molded Polymer
FRAME				
Front and Rear	1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame	1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame	1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame	1.5- x 2.5-inch Steel Tubing; Welded Steel Reinforced Frame
Machine Length	87.0 in. (2209 mm)	87.0 in. (2209 mm)	87.0 in. (2209 mm)	87.0 in. (2209 mm)
Machine Weight (wet)	1500 lb. (680 kg)	1541 lb. (698 kg)	1500 lb. (680 kg)	1541 lb. (698 kg)
TRANSMISSION				
Type	HG ZT-5400 2-Speed Hydrostatic Transaxles	HG ZT-5400 2-Speed Hydrostatic Transaxles	HG ZT-5400 2-Speed Hydrostatic Transaxles	HG ZT-5400 2-Speed Hydrostatic Transaxles
Pump Displacement	0.9 cu. in. (16 cc)	0.9 cu. in. (16 cc)	0.9 cu. in. (16 cc)	0.9 cu. in. (16 cc)
Oil Capacity	1.4 gal. (5.9 qt.) each	1.4 gal. (5.9 qt.) each	1.4 gal. (5.9 qt.) each	1.4 gal. (5.9 qt.) each
Forward Speed	19.0 mph (30.5 km/hr.)*	19.0 mph (30.5 km/hr.)*	19.0 mph (30.5 km/hr.)*	19.0 mph (30.5 km/hr.)*
Reverse Speed	7.5 mph (12.0 km/hr.):**	7.5 mph (12.0 km/hr.):**	7.5 mph (12.0 km/hr.):**	7.5 mph (12.0 km/hr.):**
WHEELS				
Drive Wheel Size	26 x 12-12	26 x 12-12	26 x 12-12	26 x 12-12
Front Caster Wheel Size	15 x 6.5-6, No-Flat	15 x 6.5-6, No-Flat	15 x 6.5-6, No-Flat	15 x 6.5-6, No-Flat
Caster Arm Attachment	Bolt-On	Bolt-On	Bolt-On	Bolt-On
SEAT				
Description	Extra-High Back, Full Mechanical Suspension Seat	Extra-High Back, Full Mechanical Suspension Seat	Extra-High Back, Full Mechanical Suspension Seat	Extra-High Back, Full Mechanical Suspension Seat
Fore-Aft Adjustment	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever	Seat Slide Lever
WARRANTY				
	3-year/2,000-hour Limited Warranty			

*0-13.0 mph cutting; 13.0-19.0 mph transport

**5.0-7.5 mph transport