

OPTIMUS

Z

8kWh

ZERO TURN STAND-ON MOWER



THE FASTEST, MOST CAPABLE ZERO TURN STAND-ON MOWER. PERIOD.



THE ULTIMATE PRODUCTIVITY MACHINE. RUNTIME: 5 HRS AND COVERAGE: 7 ACRES PER FULL CHARGE



CLASS-LEADING 22HP AND 352CC GAS ENGINE EQUIVALENT CAPABLE OF SUSTAINING A CONSTANT 19K FPM BLADE SPEED. NEVER BOGS DOWN



ESTIMATED 3-YEAR SAVINGS OF \$3,533 COMPARED TO THE LEADING GAS-POWERED 60" STAND-ON ZERO TURN

COVERAGE UP TO 7 ACRES	RUNTIME UP TO 5HRS	HP EQUIVALENT 22HP/352cc	CHARGE TIME 3 HOURS	MAX CUTTING SPEED 10MPH	CONSTANT BLADE SPEED 19K FPM	SLOPE CAPABILITY 25°
---------------------------	-----------------------	-----------------------------	------------------------	----------------------------	---------------------------------	-------------------------

OPTIMUS Z
ZERO TURN STAND-ON MOWER

THE ULTIMATE PRODUCTIVITY
MACHINE FOR ALL-DAY
COMMERCIAL USE



SAVINGS STORY OVER 3 YEARS
ZERO TURN STAND-ON MOWER

82 VOLT LITHIUM ION		GAS
\$12,999	INITIAL INVESMENT	\$8,399
\$432	FUEL COST	\$7,934
\$0	SERVICE & MAINTENANCE COST	\$631
\$13,431	3-YEAR OWNERSHIP COST	\$16,964

\$3,533 IN SAVINGS

LEARN MORE: [COMMERCIAL.GREENWORKSTOOLS.COM](https://commercial.greenworkstools.com)

greenworks
COMMERCIAL

OPTIMUS Z

Model	CZ36S8X	CZ32S8X
General		
MSRP	\$12,999	\$12,999
Mower Warranty	5 year or 2000hrs	5 year or 2000hrs
Optimus Lithium Battery System™		
Battery	82V, 8kWh	82V, 8kWh
Charger & Charging Time	3.3kW (3 Hours to Charge)	3.3kW (3 Hours to Charge)
PowrTraq Smart Drive System™		
Motors	High-Torque Commercial	High-Torque Commercial
Power System	(2) 5kW Hub Motors	(2) 5kW Hub Motors
Transmission	Planetary Gearset	Planetary Gearset
Tires	12" Front Tires/20" Rear Tires	12" Front Tires/20" Rear Tires
19K Constant Smart Cutting System™		
Deck Size (in)	36" Fab 9-Gauge Steel Deck	32" Fab 9-Gauge Steel Deck
Power System	(3) Continuous 1.8kW Blade Motors	(3) Continuous 1.8kW Blade Motors
Cutting Heights	1" to 5"	1" to 5"
Cutting System	Side Discharge & Mulch	Side Discharge & Mulch
Deck Depth (in)	5"	5"
Blade Material	.204" Heat-Treated Steel	.204" Heat-Treated Steel
Spindle Housings	7.5" Diameter Cast Aluminum w/Blade Retainer	7.5" Diameter Cast Aluminum w/Blade Retainer
Features		
Technology	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports
Speed Control	Adjustable	Adjustable
Lighting	Standard 360 Degree LED Lighting	Standard 360 Degree LED Lighting
Operator Platform	Foldable With Bumper Cushions	Foldable With Bumper Cushions
Parking Brake	Integrated Transmission Automatic	Integrated Transmission Automatic
Dimensions		
Weight (lbs)	925	917
Deflector Width (in)	50.4	46.9
Length (in)	67.5	67.5
Length w/Platform Up (in)	65	65
Deck Clearance Width(in)	37.1	33.1

PRICES SUBJECT TO CHANGE | SEE YOUR LOCAL GREENWORKS® COMMERCIAL DEALER FOR DETAILS