





**18**kWh





THE FASTEST, MOST CAPABLE ZERO TURN STAND-ON MOWER. PERIOD.



THE ULTIMATE PRODUCTIVITY MACHINE. RUNTIME: 6.5 HRS AND COVERAGE: 16 ACRES PER FULL CHARGE.



CLASS-LEADING 51HP AND 816CC GAS ENGINE EQUIVALENT CAPABLE OF SUSTAINING A CONSTANT 19K FPM BLADE SPEED. NEVER BOGS DOWN



ESTIMATED 3-YEAR SAVINGS OF \$16,800 COMPARED TO THE LEADING GAS-POWERED 60" STAND-ON ZERO TURN

COVERAGE
UP TO 16 ACRES

RUNTIME
UP TO 6.5HRS

HP EQUIVALENT 51HP/816cc

CHARGE TIME
2.5 HOURS
WITH RAPID CHARGER

MAX CUTTING SPEED 12MPH

CONSTANT BLADE SPEED 19K FPM

SLOPE CAPABILITY 25°

LEARN MORE: COMMERCIAL.GREENWORKSTOOLS.COM



## **SAVINGS STORY OVER 3 YEARS**

ZERO TURN STAND-ON MOWER

SC VOLTES		GAS
\$ <b>21,999</b>	INITIAL INVESMENT	<sup>\$</sup> 14,399
\$ <b>1,296</b>	FUEL COST	\$23,803
\$ <b>0</b>	SERVICE & MAINTENANCE COST	\$ <b>1,893</b>
\$23,295	3-YEAR OWNERSHIP COST	\$40,095

**\$16,800 IN SAVINGS** 





Model	CZ60S18X	CZ52S18X	CZ48S18X
General			
MSRP	\$21,999	\$21,999	\$21,999
Mower Warranty	5 year or 2000hrs	5 year or 2000hrs	5 year or 2000hrs
Optimus Lithium Bat	tery System™		
Battery	82V, 18kWh	82V, 18kWh	82V, 18kWh
Charger & Charging Time	3.3kW (6 Hours to Charge) 8kW (2.5 Hours to Charge)	3.3kW (6 Hours to Charge) 8kW (2.5 Hours to Charge)	3.3kW (6 Hours to Charge) 8kW (2.5 Hours to Charge)
PowrTraq Smart Driv	⁄e System™		
Motors	High-Torque Commercial	High-Torque Commercial	High-Torque Commercial
Power System	(2) 5kW Hub Motors	(2) 5kW Hub Motors	(2) 5kW Hub Motors
Transmission	Planetary Gearset	Planetary Gearset	Planetary Gearset
Tires	13" Front Tires/24" Rear Tires	13" Front Tires/24" Rear Tires	13" Front Tires/24" Rear Tires
19K Constant Smart	Cutting System™		
Deck Size (in)	60" Fab 7-Gauge Steel Deck	52" Fab 7-Gauge Steel Deck	48" Fab 7-Gauge Steel Deck
Power System	(3) Continuous 1.8kW Blade Motors	(3) Continuous 1.8kW Blade Motors	(3) Continuous 1.8kW Blade Motors
Cutting Heights	1" to 5"	1" to 5"	1" to 5"
Cutting System	Side Discharge & Mulch	Side Discharge & Mulch	Side Discharge & Mulch
Deck Depth (in)	5.5	5.5	5.5
Blade Material	.204" Heat-Treated Steel	.204" Heat-Treated Steel	.204" Heat-Treated Steel
Spindle Housings	7.5" Diameter Cast Aluminum w/Blade Retainer	7.5" Diameter Cast Aluminum w/Blade Retainer	7.5" Diameter Cast Aluminum w/Blade Retainer
Features			
Technology	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports
Speed Control	Adjustable	Adjustable	Adjustable
Lighting	Standard 360 Degree LED Lighting	Standard 360 Degree LED Lighting	Standard 360 Degree LED Lighting
Operator Platform	Foldable With Bumper Cushions	Foldable With Bumper Cushions	Foldable With Bumper Cushions
Parking Brake	Integrated Transmission Automatic	Integrated Transmission Automatic	Integrated Transmission Automatic
Dimensions			
Weight (lbs)	1459	1426	1408
Deflector Width (in)	73.5	65.4	61
Length (in)	72.2	69.4	69.4
Length w/Platform Up (in)	69.7	66.9	66.9
Deck Clearance Width(in)	61.1	53.1	49