







THE FASTEST, MOST CAPABLE ZERO TURN RIDE-ON MOWER. PERIOD.



THE ULTIMATE PRODUCTIVITY MACHINE. RUNTIME: 6.5 HRS AND COVERAGE: 16 ACRES PER FULL CHARGE.



CLASS-LEADING 51HP AND 816CC GAS ENGINE EQUIVALENT CAPABLE OF SUSTAINING A CONSTANT 19K FPM BLADE SPEED. NEVER BOGS DOWN



ESTIMATED 3-YEAR SAVINGS OF \$17,207 COMPARED TO THE LEADING GAS-POWERED 60" RIDE-ON ZERO TURNOD.

COVERAGE
UP TO 16 ACRES

RUNTIME
UP TO 6.5HRS

HP EQUIVALENT 51HP/816cc

CHARGE TIME
2.5 HOURS
WITH RAPID CHARGER

MAX CUTTING SPEED 12MPH

CONSTANT BLADE SPEED 19K FPM

SLOPE CAPABILITY 25°

LEARN MORE: COMMERCIAL.GREENWORKSTOOLS.COM



SAVINGS STORY OVER 3 YEARS

ZERO TURN RIDE-ON MOWER

		GAS
\$ 22,999	INITIAL INVESMENT	^{\$} 15,806
\$ 1,296	FUEL COST	\$23,803
\$ 0	SERVICE & MAINTENANCE COST	\$ 1,893
\$ 24,295	3-YEAR OWNERSHIP COST	^{\$} 41,502

\$17,207 IN SAVINGS





Model	CZ60R18X	CZ52R18X	CZ48R18X
General			
MSRP	\$ 22,999	\$ 22,999	\$ 22,999
Mower Warranty	5year or 2000hrs	5year or 2000hrs	5year or 2000hrs
Optimus Lithium Bat	tery System™		
Battery	82V, 18kWh	82V, 18kWh	82V, 18kWh
Charger & Charging Time	3.3kW (6 Hours to Charge) 8kW (2.5 Hours to Charge)	3.3kW (6 Hours to Charge) 8kW (2.5 Hours to Charge)	3.3kW (6 Hours to Charge) 8kW (2.5 Hours to Charge)
PowrTraq Smart Driv	ve System™		
Motors	High-Torque Commercial	High-Torque Commercial	High-Torque Commercial
Power System	(2) 5kW Hub Motors	(2) 5kW Hub Motors	(2) 5kW Hub Motors
Transmission	Planetary Gearset	Planetary Gearset	Planetary Gearset
Tires	13" Front Tires/24" Rear Tires	13" Front Tires/24" Rear Tires	13" Front Tires/24" Rear Tires
19K Constant Smart	: Cutting System™		
Deck Size (in)	60" Fab 7-Gauge Steel Deck	52" Fab 7-Gauge Steel Deck	48" Fab 7-Gauge Steel Deck
Power System	(3) Continuous 1.8kW Blade Motors	(3) Continuous 1.8kW Blade Motors	(3) Continuous 1.8kW Blade Motors
Cutting Heights	1" to 5"	1" to 5"	1" to 5"
Cutting System	Side Discharge & Mulch	Side Discharge & Mulch	Side Discharge & Mulch
Deck Depth (in)	5.5	5.5	5.5
Blade Material	.204" Heat-Treated Steel	.204" Heat-Treated Steel	.204" Heat-Treated Steel
Spindle Housings	7.5" Diameter Cast Aluminum w/Blade Retainer	7.5" Diameter Cast Aluminum w/Blade Retainer	7.5" Diameter Cast Aluminum w/Blade Retainer
Features			
Technology	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports	5" Glove-Safe Touchscreen, ETO Output, (2) USB-A/C ports
Speed Control	Adjustable	Adjustable	Adjustable
Lighting	Standard 360 Degree LED Lighting	Standard 360 Degree LED Lighting	Standard 360 Degree LED Lighting
Operator Seat	4" Travel Suspension + Armrests	4" Travel Suspension + Armrests	4" Travel Suspension + Armrests
ROPS Profile/PIN Type	Square Tube/Pin w/Lanyard	Square Tube/Pin w/Lanyard	Square Tube/Pin w/Lanyard
Parking Brake	Integrated Transmission Automatic	Integrated Transmission Automatic	Integrated Transmission Automatic
Dimensions			
Weight (lbs)	1473	1440	1422
ROPS Height Folded (in)	46.7	46.7	46.7
ROPS Height Upright (in)	72.5	72.5	72.5
Deflector Width (in)	61.1	53.1	49
Length (in)	73.8	71	71