

CURBTENDER TITAN 40FEL STANDARD FEATURES

12 YD HOPPER & 28 YD BODY CAPACITIES

FULL EJECT

AIR-OVER-HYDRAULIC CONTROLS W/ JOYSTICK

HOT SHIFT PTO, GEAR PUMP, & OVERSPEED PROTECTION

8,000# ARMS

54" FORKS

DUAL HOPPER DOORS

FRONT-OF-BODY SCREEN ENCLOSURE

10 GA BODY SIDES

ALL LED BODY LIGHTS

QUAD SMART LAMPS ON TAILGATE- WIG WAG

DUAL MID-BODY FLOOD LIGHTS

COLOR LCD REAR VISION CAMERA SYSTEM

20# EXTERIOR FIRE EXTINGUISHER & BRACKET

FACTORY MOUNTING

FACTORY PAINTING- PERFORMANCE WHITE


DELIVERY ANYWHERE IN NC

1 YEAR BODY & HYDRAULIC WARRANTY


1 YEAR CYLINDER WARRANTY

\$176,919.00

TITAN



TITAN



Body Specifications	40 CU. YD.	44 CU. YD.
A: LENGTH OF BODY	296"	318"
B: LENGTH OF BODY TO TAILGATE RAISED	353"	375"
C: HEIGHT OF BODY ABOVE CHASSIS FRAME	111"	111"
D: HEIGHT OF TAILGATE RAISED ABOVE CHASSIS FRAME	195"	195"
E: LENGTH OF BODY WITH ARMS DOWN W/ FORKS STOWED	408"	430"
F: LENGTH OF BODY WITH ARMS DOWN W/ FORKS EXTENDED	455"	477"
G: HEIGHT ABOVE CHASSIS FRAME ARMS UP W/ FORKS STOWED	121"	121"
H: HEIGHT ABOVE CHASSIS FRAME ARMS UP W/ FORKS EXTENDED	179"	179"
J: APPX. OVERALL LENGTH (REAR TAILGATE TO CHASSIS FRONT BUMPER)	385"	407"
HOPPER CAPACITY	12 CU. YD.	12 CU. YD.
BODY WEIGHT	17,360 LBS	17,720 LBS.

Minimum Chassis Requirements

MINIMUM GVWR	66,000 LBS.	66,000 LBS.
FRONT AXLE	20,000 LBS.	20,000 LBS.
REAR AXLE	46,000 LBS.	46,000 LBS.
CAB TO TRUNNION	191"	210"

Standard Performance

- Pack panel cycle: 20 seconds
- Full ejection of packed material: 31 seconds
- Arm Cycle: 12 seconds
- Tailgate opening: 10 seconds
- 1,000 lbs per cubic yard compaction

Body Construction

- Body curved floor: 3/16" Hardox 450
- Body side: 10 gauge ASTM 715-80
- Body roof: 10 gauge ASTM 715-80
- Hopper floor: 1/4" Hardox
- Hopper Sides: 3/16" Hardox
- Tailgate construction: 10 gauge ASTM A715-80
- Hopper wind and front screen
- Hinged access door (24")
- Full eject design
- Cab shield with hinged extension
- Roof access ladder (curbside)

Pack Panel

- Lower face: 1/4" 100,000 PSI
- Upper face: 3/16" ASTM A715-80 100,000 PSI

Arms and Forks

- Bolt-on arms, load rated 8,000 lbs. (4.5" cylinders)
- Torque tube bearings: (4) Split Bearings Blocks /w

Bushings

- Forks: ASTM A514 at 1 1/2" x 43" long forks
- Automatic "up arm" deceleration valve

Hydraulic Control System


- Air over hydraulic controls
- Pump: 55 GPM at 1,500 RPM
- Reservoir capacity: 75 gal. (fixed) or 40 gal. (w/ service hoist)
- Suction Strainer: 100 mesh
- Return filter: 10 micron
- System working pressure: 2,500 PSI max.
- Under body hydraulic valves
- Pump fluid stop blocks standard

Optional XP Controls Package

- Electronically controlled variable displacement pump
- Ultra efficient hydraulic system
- CANBUS & Multiplex Controls
- In-Cab Diagnostics
- Auto-Level, Auto-Dump Arms
- Container Shake Feature

Additional Options

- Body slides: 7 gauge or 1/8" Hardox
- Residential, Short, or Long forks
- Residential carry can
- 10,000 lbs. load rated arms
- "Cardboard Special" Package - 6.125" Bore Pack Cylinders



www.curbtender.com

701 PERFORMANCE DRIVE, CEDAR FALLS, IA 50613

PHONE: 319.266.1721, FAX: 319.266.8207

©2019 Curbtender Inc., All Rights Reserved. Specifications subject to change.