

## **GALFAB OR-75-174S072 ROLL-OFF HOIST**

GALFAB OR-75-174S072 CABLE HOIST  
STANDARD POSITION LIFT CYLINDERS  
HYDRAULIC OIL TANK ON DRIVER SIDE FRAME RAIL  
5-SPOOL VALVE FOR TARP CONTROL INTEGRATION  
2-LEVER INSIDE AIR CONTROLS ON CUSTOM PEDESTAL  
HOT SHIFT PTO  
DIRECT-MOUNT HYDRAULIC PUMP  
PROGRAMMED THROTTLE LIMIT  
STEEL TANDEM AXLE FENDERS WITH HEAVY  
DUTY TUBULAR BRACKETS & GUSSETS  
LED MID-BODY TURN SIGNALS  
CABLE HOOK HOLDER  
AUXILIARY RATCHET STRAP REAR CONTAINER HOLD DOWNS  
AIR-OPERATED AUTO-FOLDING ICC BUMPER- ACTIVATES  
WHEN THE PTO IS ENGAGED/DISENGAGED  
FULL STEEL REAR BUMPER WITH RECESSED LED LIGHTS  
SHORT MUD FLAPS ATTACHED TO BUMPER  
DUAL REAR BUMPER WORK LIGHTS WITH STEEL GUARDS  
LCD COLOR REAR VISION CAMERA SYSTEM WITH STEEL GUARD  
48" LOCKABLE STEEL TOOL BOX ON PASSENGER SIDE  
HOIST-UP & BACK-UP ALARM  
TAG LIGHT  
MOUNTED  
PAINTED GLOSS BLACK  
DELIVERED NC STATEWIDE

\$61,900.00




## OR SERIES OUTSIDE RAIL HOIST

The Outside Rail roll-off hoist is the most commonly used hoist in the industry today. GALFAB offers this hoist with an 8" mainframe and 2" subframe or the very popular 10" sub frameless hoist.

Available in 60k and 75k pound models to fit any application.



Visit our website: [GALFAB.com](http://GALFAB.com) | Follow us on social media



| Call Today: 574-946-7767



# OR SERIES MODELS

Model	Capacity	CA	CA with tarp	Length	Dump Angle	Up (sec)*	Down (sec)*	On (sec)*	Off (sec)*	Lift Cylinder	Winch Cylinder	Container Length ft	Apx Weight lbs
OR60174S072	60,000	174"	186"	23'3"	48°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR60174S072R	60,000	174"	186"	23'3"	48°	27	15	41	28	6" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR60174T121	60,000	174"	186"	23'3"	48°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7225
OR75174S072F7	75,000	174"	186"	23'3"	48°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR75174S072R7	75,000	174"	186"	23'3"	48°	37	23	41	28	7" x 4" x 72" DA	7" x 4" x 79.5" DA	18'-22'	7550
OR75174T121	75,000	174"	186"	23'3"	48°	35	29	41	28	6"-5"-4" x 121" DAT	7" x 4" x 79.5" DA	18'-22'	7350
OR60194S072	60,000	194"	206"	24'11"	48°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR60194S072R	60,000	194"	206"	24'11"	48°	27	15	46	31	6" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR60194T121	60,000	194"	206"	24'11"	48°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8075
OR75194S072F7	75,000	194"	206"	24'11"	48°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR75194S072R7	75,000	194"	206"	24'11"	48°	37	23	46	31	7" x 4" x 72" DA	7" x 4" x 89.5" DA	20'-24'	7850
OR75194T121	75,000	194"	206"	24'11"	48°	35	29	46	31	6"-5"-4" x 121" DAT	7" x 4" x 89.5" DA	20'-24'	8075

\* Cycle Times are Factory developed and controlled by PTO output, oil viscosity, human and mechanical efficiency, and may vary accordingly.

CAUTION: This Equipment Should be Operated by Properly Trained Personnel. Improper Use, Misuse, or Lack of Maintenance Could Cause Injury to Persons or Property. Photos used in this brochure are illustrative only. We reserve the right to make changes at any time without notice. Information contained within this literature is believed to be the most accurate available at the time of printing.

