

SWAPLOADER 400 SERIES HOOK LIFT

ALL STANDARD FEATURES

PROPER PTO/PUMP

OVERSPEED PROTECTION

INSIDE CONTROLS 2-LEVER INSIDE AIR CONTROLS

FULL STEEL TANDEM AXLE FENDERS

SHORT MUD FLAPS ATTACHED TO REAR BUMPER

END OF FRAME COVER PLATE

BUMPER W/ RECESSED LED LIGHTS

DUAL REAR WORK LIGHTS W/ STEEL GUARDS

COLOR LCD REAR VISION CAMERA SYSTEM

48" TOOL BOX ON CURBSIDE

BACK-UP ALARM

TAG LIGHT

MOUNTED

PAINTED GLOSS BLACK


DELIVERED NC STATEWIDE

SEE TABLE

MODEL		LIST PRICE
400 SERIES		
SL-330 FIXED JIB		\$ 60,919.00
SL-330 ADJUSTABLE JIB		\$ 61,966.00
SL-400 FIXED JIB		\$ 61,991.00
SL-400 ADJUSTABLE JIB		\$ 63,938.00
SL-406 FIXED JIB		\$ 62,952.00
SL-406 ADJUSTABLE JIB		\$ 63,999.00
SL-412 FIXED JIB		\$ 59,926.00
SL-412 ADJUSTABLE JIB		\$ 60,973.00

ALL-MODEL SPECIFICATIONS

MODEL		SL-75	SL-105	SL-160	SL-212	SL-214	SL-220	SL-222	SL-240	
MODEL DESCRIPTION	DUMP CAPACITY (INCLUDING CONTAINER)	7,500 lb	10,500 lb	16,000 lb	20,000 lb	20,000 lb	22,000 lb	22,000 lb	24,000 lb	
	DUMP ANGLE	56°	58°	56°	58°	57°	53°	53°	53°	
	LIFT CAPACITY (INCLUDING CONTAINER)	7,500 lb	10,500 lb	16,000 lb	20,000 lb	20,000 lb	22,000 lb	22,000 lb	24,000 lb	
	HOIST WEIGHT	FIXED ADJ.	1,250 lb N/A	1,680 lb N/A	2,325 lb 2,467 lb	2,520 lb 2,640 lb	2,720 lb 2,860 lb	4,100 lb 4,330 lb	4,050 lb 4,280 lb	3,900 lb 4,200 lb
GENERAL DIMENSIONS (SEE DIAGRAM)	HOOK TO REAR ROLLER (D/M, A)	114.38"	116.00"	139.63"	138.00"	153.63"	193.81"	179.81"	159.81"	
	HOOK HEIGHT (D/M, B)	FIXED ADJ.	35.63" N/A	35.63" N/A	35.63" 35.63" / 53.88"	35.63" 35.63" / 53.88"	35.63" 35.63" / 53.88"	53.88" 53.88" / 61.75"	53.88" 53.88" / 61.75"	53.88" 53.88" / 61.75"
	HOIST HEIGHT (D/M, C)	5.25"	5.5"	7.5"	7.5"	7.5"	9"	9"	9"	
	HOIST CG (D/M, D)	59.7"	58.1"	70.65"	64.0"	80.3"	97.8"	95.2"	88.0"	
	OPTIMUM BODY LENGTHS (D/M, E)	10' - 12'	10' - 12'	12' - 14'	12' - 14'	14' - 16'	18' - 20' ❶	16' - 18'	14' - 16'	
	POTENTIAL BODY LENGTHS (D/M, E) ❶	9' - 13'	10' - 13'	10' - 15'	10' - 16'	12' - 18'	14' - 22'	14' - 20'	12' - 18'	
	BODY LONGSILL WIDTH ❷	41.63" / 39.00"	41.63"	41.63" / 40.50"	41.63" / 40.50"	41.63" / 40.50"	41.63" / 40.50"	41.63" / 40.50"	41.63" / 40.50"	
HYDRAULIC SYSTEMS	HYDRAULIC PUMP TYPE (CID)	Gear (0.85)	Gear (1.86)	Gear (2.96)	Gear (2.96)	Gear (2.96)	Gear (4.46)	Gear (4.46)	Gear (4.46)	
	FLOW @ PUMP RPM ❸	3.1 GPM @ 1,000 RPM	7.2 GPM @ 1,000 RPM	11.4 GPM @ 1,000 RPM	11.4 GPM @ 1,000 RPM	11.4 GPM @ 1,000 RPM	17.4 GPM @ 1,000 RPM	17.4 GPM @ 1,000 RPM	17.4 GPM @ 1,000 RPM	
	RELIEF PRESSURE	3,250 PSI	3,250 PSI	3,250 PSI	3,250 PSI	3,250 PSI	2,800 PSI	2,800 PSI	2,800 PSI	
	HYDRAULIC RESERVOIR	7 gal	15 gal	15 gal	15 gal	15 gal	25 gal	25 gal	25 gal	
LIFT CYLINDER	TYPE	ALL MODELS INCORPORATE DOUBLE ACTING CYLINDERS WITH DUAL BUILT-IN COUNTERBALANCE VALVE.								
	QUANTITY	1	2	2	2	2	2	2	2	
	BORE	Ø 4"	Ø 4"	Ø 5"	Ø 5.5"	Ø 5.5"	Ø 6"	Ø 6"	Ø 6"	
	STROKE	38"	38"	43"	46"	54"	54"	54"	54"	
JIB CYLINDER	TYPE	❺	MODELS INCORPORATE A SINGLE, DOUBLE ACTING CYLINDER WITH A SINGLE BUILT-IN COUNTERBALANCE VALVE.							
	QUANTITY	2	1	1	1	1	1	1	1	
	BORE	Ø 1.5"	Ø 2.5"	Ø 3"	Ø 3"	Ø 3"	Ø 3.5"	Ø 3.5"	Ø 3.5"	
	STROKE	20"	24"	32"	32"	36"	48"	34"	30"	
TRUCK SPECS (RECOMMENDED)	GVW RANGE ❹	14,000 lb - 16,000 lb	16,000 lb - 19,000 lb	18,000 lb - 26,000 lb	25,000 lb - 35,000 lb	25,000 lb - 35,000 lb	25,000 lb - 35,000 lb	25,000 lb - 35,000 lb	25,000 lb - 35,000 lb	
	CAB-AXLE DIM. (SINGLE AXLE) ❷	84" - 96"	84" - 96"	108" - 120"	108" - 120"	120" - 138"	156" - 174"	142" - 160"	130" - 144"	
	CAB-TRUNNION DIM. (TAND-EM AXLE) ❷	N/A	N/A	N/A	N/A	N/A	150" - 162"	130" - 142"	120" - 132"	
	CLEAR FRAME RAIL ❸	126"	130"	153"	156"	172"	216"	202"	184"	
	FRAME HEIGHT	up to 38"	up to 40"	up to 40"	up to 40"	up to 40"	up to 43"	up to 43"	up to 43"	
PTO SPECS (RECOMMENDED)	PUMP MOUNT ❹	Direct Mount SAE A, 2 Bolt	Direct Mount SAE B, 2 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	
	TORQUE REQUIRED	40 ft-lbf	80 ft-lbf	125 ft-lbf	125 ft-lbf	125 ft-lbf	200 ft-lbf	200 ft-lbf	200 ft-lbf	



SL-2418	SL-330	SL-400	SL-406	SL-412	SL-518	SL-520	SL-650
24,000 lb	33,000 lb	40,000 lb	40,000 lb	40,000 lb	54,000 lb	50,000 lb	65,000 lb
57°	58°	58°	55°	60°	57°	57°	54°
24,000 lb	33,000 lb	40,000 lb	40,000 lb	40,000 lb	53,000 lb	50,000 lb	65,000 lb
3,040 lb	5,170 lb	5,290 lb	5,920 lb	4,780 lb	6,600 lb	7,055 lb	8,050 lb
N/A	5,330 lb	5,450 lb	6,085 lb	4,930 lb	6,840 lb	7,310 lb	N/A
118.00"	167.50"	167.50"	209.75"	143.50"	201.00"	222.75"	226.50"
53.88"	61.75"	61.75"	61.75"	61.75"	61.75"	61.75"	61.75"
N/A	61.75" / 53.88"	61.75" / 53.88"	61.75" / 53.88"	61.75" / 53.88"	61.75" / 53.88"	61.75" / 53.88"	N/A
9"	11"	11"	11"	11"	12"	12.5"	13"
63.8"	88.8"	88.8"	114.0"	75.6"	108.0"	118.0"	125.0"
10' - 12'	14' - 16'	14' - 16'	18' - 20'	12' - 14'	18' - 20' ①	20' - 22'	20' - 22'
10' - 13'	12' - 18'	12' - 18'	16' - 22'	12' - 15'	15' - 22'	17' - 24'	17' - 24'
41.63" / 40.50"	40.50" / 41.63"	40.50" / 41.63"	40.50" / 41.63"	40.50" / 41.63"	40.50" / 41.63"	40.50" / 41.63"	40.50" / 41.63"
Gear (4.46)	Gear (3.83)	Gear (3.83)	Gear (3.83)	Gear (3.83)	Gear (4.46)	Gear (4.46)	Gear (4.46)
17.4 GPM @ 1,000 RPM	22.3 GPM @ 1,500 RPM	22.3 GPM @ 1,500 RPM	22.3 GPM @ 1,500 RPM	22.3 GPM @ 1,500 RPM	26.0 GPM @ 1,500 RPM	26.0 GPM @ 1,500 RPM	26.0 GPM @ 1,500 RPM
2,800 PSI	3,500 PSI	3,500 PSI	3,500 PSI	3,500 PSI	3,500 PSI	3,500 PSI	3,500 PSI
25 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal	30 gal
ALL MODELS INCORPORATE DOUBLE ACTING CYLINDERS WITH DUAL BUILT-IN COUNTERBALANCE VALVE.							
2 ④	2 ④	2 ④	2	2 ④	2	2	2
Ø 5.5"	Ø 5.5"	Ø 6"	Ø 6.5"	Ø 6"	Ø 7"	Ø 7"	Ø 7.5"
39"	60"	60"	74"	56"	74"	82"	82"
MODELS INCORPORATE A SINGLE, DOUBLE ACTING CYLINDER WITH A SINGLE BUILT-IN COUNTERBALANCE VALVE.							
1 ④	1 ④	1 ④	1	1 ④	1	1	1
Ø 4"	Ø 4"	Ø 4"	Ø 4"	Ø 4"	Ø 4.5"	Ø 4.5"	Ø 4.5"
24"	38"	38"	52"	30"	48"	52"	52"
25,000 lb - 35,000 lb	33,000 lb or greater	45,000 lb or greater	45,000 lb or greater	45,000 lb or greater	50,000 lb or greater	50,000 lb or greater	55,000 lb or greater
84" to 96"	142" - 156"	N/A	N/A	N/A	N/A	N/A	N/A
N/A	130" - 138"	130" - 138"	174" - 180"	102" - 114"	165" - 174"	176" - 190"	172" - 190"
134"	191"	191"	232"	169"	225"	245"	249"
up to 43"	up to 43"	up to 43"	up to 45"	up to 45"	up to 45"	up to 45"	up to 45"
Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt	Direct Mount SAE B, 4 Bolt
200 ft-lbf	200 ft-lbf	200 ft-lbf	200 ft-lbf	200 ft-lbf	230 ft-lbf	230 ft-lbf	230 ft-lbf

- ① Hoist potential body length range may not conform with I.C.C. bumper regulations or may not achieve maximum dump angle depending on truck chassis height. Shorter bodies available on some models with use of a shelf assembly or CVS system. Contact your SwapLoader distributor for more information.
- ② Maximum outside to outside long sill width.
- ③ Pump RPM and Flow are dependent on engine RPM and PTO ratio.
- ④ Polished nitrided cylinder rod.
- ⑤ Counterbalance valve manifold.
- ⑥ A lower GVW will limit your payload potential.
- ⑦ Optimum CA/CT dimension will be influenced by type of loads carried and turning radius requirements.
- ⑧ Clear frame dimension given is the overall length of hoist plus 5" for cab clearance and rear light bar mounting. Additional frame length may be necessary for other accessories such as cab guard, tarper, exhaust system, etc.
- ⑨ PTO/Pump rotation as determined by transmission.