

NCSA Heavy Equipment Contract 24-08-0421

Item Number: 899

Model Number: J4

Group: Crushing Equipment

Make: McCloskey International

MSRP: \$1,008,105.00

Model: Jaw


Discount 6%: (\$60,486.3)

Total Net Price: \$947,618.70

Price Does Not Include Freight

Commonwealth Equipment * 36 Hazleton St * Ashley PA 18706 Phone: 877-217-4474 * commonwealthequipment.com






SPECIFICATIONS



McCloskey **J4**



J4Jan 2023, issue 001



DESCRIPTION

Heavy duty track mounted Crusher with following features:

- 1060mm (42") wide x 700mm (28") single toggle jaw.
- Choice of CAT or Volvo, LRC or T4F/Stage V engines.
- HD crawler tracks.
- Integrated hydraulic folding hopper.
- Integrated hydraulic folding stockpiling conveyors.
- I-beam plate fabricated chassis construction.
- Large gap between crusher discharge and main conveyor feedboot.
- Open chassis design for ease of maintenance.
- Fast setup time.
- Quick release jaw for transport.

DIMENSIONS AND WEIGHTS

Length – transport 15.80 m (51' - 8")Width – transport 2.90 m (9' - 6")Height – transport 3.50 m (11' - 5.8")

Weight (estimated) 51,280Kgs (113,050lbs) inc. magnet & dirt conveyor

CAPACITIES

Diesel tank capacity 535 L (141 US gal) Hydraulic tank capacity 1030 L (272 US gal)

CRUSHING CHAMBER

Feed opening WxD 1060 x 700mm, (42" x 28")

Crusher speed 280 rpm Crusher stroke 34mm

Crusher Drive Hydraulic V Belts
Min opening 70mm (2.8")
Max opening 200mm (8")
Maximum feed size 560mm (22")

Crusher weight (bare) 15,650kg (34,500 lbs)
Closed side setting adjustment Hydraulic wedges

Motor Kawasaki axial piston 530cc/rev


Flow rate 416 Lpm (110 US gpm)

Speed sensorYESLevel sensorUltrasonicLoad sensorYESCSS sensorYESReversibleYES



J4

Jan 2023, issue 001



LONG PAN FEEDER

Feeder width 1064mm (41.9") Feeder length 4247mm (167.2")

Grizzly section opening Tapered 35-75mm (1.4" – 3")

Grizzly section length 1590mm (62.6")
Drive Hydraulic

Motor David Brown MCC 2208 58.7cc/rev

Flow rate 63.5 Lpm (16.8 US gpm)

Adjustable speed YES – via electrical proportional Variable speed YES – via electrical proportional

Maximum speed 975rpm

SHORT PAN FEEDER TO SUIT PRESCREEN (option)

Feeder width 1064mm (41.9")
Feeder length 2190mm (86.2")
Drive Hydraulic

Motor David Brown MCC 2208 58.7cc/rev

Flow rate 63.5 Lpm (16.8 US gpm)

Adjustable speed YES – via electrical proportional Variable speed YES – via electrical proportional

Maximum speed 975rpm

DOUBLE DECK GRIZZLY PRE SCREEN (option)

Prescreen width (inside wear plates) 1064mm (41.9") Prescreen length overall 2215mm (7' - 3")

Grizzly section opening Tapered 35-75mm (1.4" – 3")

Grizzly section length 1950mm (76.8")

Bottom deck mesh 1493mm x 1060 (58.8" x 41.7")

Drive Hydraulic

Motor David Brown MCC 2208 58.7cc/rev


Flow rate 65.9Lpm (17.4 US gpm)

Adjustable speed NO
Auto stop start system YES
Maximum speed 975rpm



J4

Jan 2023, issue 001



HOPPER

Length overall 4175mm (13' – 8.3")

Width 2342mm (8') Volume 5.8m³ (7.6yd³)

Material 15mm Hardox side plates.
Locking system Hydraulic side locking wedges.

SIDE CONVEYOR

Stockpile height 3440 mm (11' - 3.6") to belt crown

 Belt width
 650mm (26")

 Belt spec
 EP 400/3 3+1.5

 Drive drum dia.
 235mm (9.25")

Tail drum dia. 220mm (8.6") - spoked

Motor OMH400

Flow rate 43.8 Lpm (11.6 US gpm)

Adjustable speed YES
Maximum speed 107 rpm

MAIN CONVEYOR

Stockpile height 3912mm (12' – 10") to belt crown

Belt width 1200mm (48")

Belt spec Plain 630/2 9+3 Toughflex

Drive drum dia. 333mm (13.1")

Tail drum dia. 287mm (11.3") – spoked

Motor OMV630


Flow rate 79.4 Lpm (21.0 US gpm)

Maximum speed 123 rpm
Angle adjustable YES
Quick release YES
Dust covers YES

Low maintenance position YES (both ends)



J4Jan 2023, issue 001



POWERUNIT AND HYDRAULICS

Engine option 1 Volvo D11 T4F/Stage V, 270 kW (360 Hp)
Engine option 2 CAT C9.3B T4F/Stage V, 310 kW (416 Hp)

Engine option 3 CAT C9.3 LRC, 310 kW (416 Hp)

Engine speed 1800 rpm

Flywheel Pump1 (jaw) Kawasaki K5V160DTP

Flywheel Pump2 (main conveyor/prescreen)

PTO Pump3 (panfeeder/side conv & magnet/pilot)

Pump4 (rock hammer)

Turolla 45/36

Turolla 35/23/9.5

Hydreco 36 (Optional)

693.5 Lpm (183.2 US Gpm)

Hydraulic tank capacity

1030 L (272 US Gals)

Hydraulic tank ratio 1.49 : 1
Hydraulic Oil cooler YES

ELECTRICS

Emergency stops 4 off, 2 feeder, 2 powerunit

Chassis cabling Armored cable
Start Siren YES – 10 sec delay

Control panel Tedd Engineering / DSE 12"

Engine shutdowns:

Low oil pressure

High water temp

Air filter blockage (selectable)

Fuel contamination Low hydraulic tank level High hydraulic oil temperature


Radio control tracks and feeder STANDARD

Pendant track control YES – plugged in control cabinet



Attachment to chassis

J4Jan 2023, issue 001



TRACKS

Track spec D4 components Width 400mm (15.7")

Length 3800 mm (12' - 5.5") crs

Height 817mm (32")

Gearbox Bonfiglioli 711 (or equivalent)

Ratio 144:1

Motor Rexroth A2FE90
Speed max 1.50 Kph (0.93 Mph)
Flow rate 152 Lpm (40.2 US gpm)

Three speed system selectable at control panel with smooth start / stop.

Bolt On for quick change

Multiple speeds control panel with smooth sta

SAFETY FEATURES

External belt alignment points
External grease points
Engine safety shutdown systems
Full safety guarding for nip points



J4Jan 2023, issue 001



