There's nothing techs can't do. Perform the job right the first time, every time.

All Rotary Wheel Service Equipment now carries an industry-leading 3 year warranty.

VALUE PRICE

PROFESSIONAL COMBO SET #RW1150180C

Designed for shops servicing high-performance tire / rim packages on vehicles.

Includes:

#RWC1150.30IB tire changer and #RWB380.3DTECB wheel balancer

R1150 LEVERLESS TIRE CHANGER

Max tire width: 15" Max wheel diameter: 30 Max tire diameter: 45" Service specialty and 19" rims* Rotation motor: 2 Hp invemotor Max breaker opening: 15" Voltage required: 220 volt / 60 Hz / 10 Ships with NEMA L6-20P plug Air supply: 115 - 145 psi Features:

- · Lever less mounting and demounting
- 220-volt motor with true variable control speed, pedal-operated
- Simple 2 button controlsPneumatic wheel lift
- · Wheel centering adapter
- Pedal-operated inflation with gauge and balancing valve
- Three-position expandable base
- Tire paste lubricant and brush

R140i Series services



*Optional equipment may be required

R180 PRO 3D AUTO WHEEL BALANCER

Max tire width: 22" Max wheel diameter: 30" Max tire diameter: 44" Voltage required: 110 volt / 60 Hz / 10 Cycle time: 6 seconds Rotation speed: <100 Assembly weight: 176 lbs.

Features

- Laser pointer indicates exact positioning for weights
- · Guided balancing procedure on display
- · Fully automatic wheel dimension entry
- · Auto start hood feature
- · Auto stop on top / auto indexing
- Standard with passenger tire and light truck collet and cone kits

Dimensions:

Height: 57.125" / 66.5" with hood up Width: 53.625 Depth: 30.375" / 35.625" with hood up

R180 PRO 3D AUTO services:







Optional equipment may be required





