

R560 MOBILE HD

MOBILE CHANGER / DESIGNED FOR SMALL SHOPS

SERVICE TIRE DIAMETERS UP TO 51"


WORKSHOP SERVICE / FAST CYCLE TIMES

Easy to use changer.

This easy-to-use mobile changer is designed for closed vans or small workshops. Controls are protected on changer console and the hydraulic clamping and chucking table are suitable for agricultural tires with optional VSG108A22 wheel disc.

FEATURES


- Service steel and alloy rims
- Hydraulic clamping / chucking table
- Tire paste lubricant and brush
- Ships with NEMA L6-20P plug



HYDRAULIC UP and DOWN MOVEMENT
4" minimum clamping
13" minimum height



STANDARD ROLLER
Easy setting for tubeless tires



HYDRAULIC CLAMPING
Designed to clamp a variety of wheels, the chucking table is able to move and up and down. Suitable for agriculture tires.



STANDARD aluminum tool for tube tires

STANDARD ACCESSORIES



VSG108A2 / Standard clamp protections for alloy rims / 4 x kit

VSG108A3 Tire Lever

OPTIONAL ACCESSORIES



VSG90A6
Aluminum rim clamp

VSG108A22
Disc for wheels with lock ring

VSG108A25
Steel rim clamp

VSG108A34
Pneumatic bead pushing device

B5308000
Long bead lifting lever

Site Requirements: 220V / 1Ø / 60 Hz power supply




Lit# Rotary R560 Changer Cutsheet.2021.11

©2021 VEHICLE SERVICE GROUP™, Printed in U.S.A., All Rights Reserved. Unless otherwise indicated, ROTARY, VEHICLE SERVICE GROUP™, DOVER and all other trademarks are property of Dover Corporation and its affiliates.

Product specifications, part numbers, images and component descriptions are subject to change without notice or liability. ROTARY WHEEL SERVICE EQUIPMENT now carries a 3 year warranty. See website for details.



TIRE DIMENSIONS



R560 services:



Optional equipment may be required

TECHNICAL DATA	R560
Chucking unit rotation motor	1.5 Hp / 1.1 kW
Hydraulic drive unit motor	2.7 Hp / 2 kW
Rim diameter	11" - 27"
Maximum tire diameter	51" (1300mm)
Max. tire width	37.4" (950mm)
Bead breaker power	3,597 Ft/Lbs / 16000 N
Maximum assembly weight	2,645 lbs (1200 kg)
Chuck rotation speed (rev/min)	8
Max. torque to chuck	1253 Ft/Lbs (1700 Nm)
Power supply*	220v / 1Ø / 60 Hz



SCAN CODE FOR PRODUCT VIDEO