

2024 Isuzu NQR Crew Cab Diesel



Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



LILLEY ISUZU TRUCK

Troy Ward | 252-217-7887 | tward@lilleyinternational.com

2024 Isuzu NQR Crew Cab Diesel (2024 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description	Weight
Model			
	3S3	NQR Crew Cab Chassis 150"WB, 88.5"CA	
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	
Tires			
	I5H	LRR (low rolling resistance)	0.0 lbs.
Engine			
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	0.0 lbs.
Transmission			
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	0.0 lbs.
Wheelbase			
	IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 88.5"CA	0.0 lbs.
Air Cleaner			
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	0.0 lbs.
Alternator			
	I2C	140 AMP. with integral regulator.	0.0 lbs.
Battery			
	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	0.0 lbs.
Exhaust			
	IX7	Single horizontal with DPF/SCR exhaust system	0.0 lbs.
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	0.0 lbs.
Front Suspension			
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	0.0 lbs.
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Front Tires			
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	0.0 lbs.
Rear Suspension			
	ID9	14,550 lbs. capacity. Semi-elliptical main and	0.0 lbs.

Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



LILLEY ISUZU TRUCK

Troy Ward | 252-217-7887 | tward@lilleyinternational.com

2024 Isuzu NQR Crew Cab Diesel (2024 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description	Weight
Rear Axle		auxiliary multi-leaf springs. Includes shock absorbers.	
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	0.0 lbs.
Ratio	098	5.125:1	0.0 lbs.
Rear Wheels	IC1	19.5" x 6", 6-hole disc, painted white	0.0 lbs.
Rear Tires	YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	0.0 lbs.
Fuel Tank	I4I	30 Gallon Stainless Steel In-Rail Fuel Tank	0.0 lbs.
Seat	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	0.0 lbs.
Brakes	K40	Butterfly valve type exhaust brake	0.0 lbs.
	IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	0.0 lbs.
Air Conditioning	C60	Air conditioner	0.0 lbs.
Power Windows & Door Locks	IL0	Yes	0.0 lbs.
Floor Mats	IQ6	Standard Floor Mats	0.0 lbs.
Model Option	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	0.0 lbs.
Assistance System	I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	0.0 lbs.
Accessories	IX2	Rear body dome lamp switch	0.1 lbs.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	0.0 lbs.

Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.




LILLEY ISUZU TRUCK

Troy Ward | 252-217-7887 | tward@lilleyinternational.com

2024 Isuzu NQR Crew Cab Diesel (2024 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Weight Distribution



Front Wt.	5,422.00 lbs.	67%
Rear Wt.	2,728.00 lbs.	33%
GVWR	17,950.00 lbs.	
GVW	8,150.00 lbs.	
Remaining Payload Weight	9,800.00 lbs.	

Driver/Passenger Weight	350.0 lbs.
Rear Passengers	600.0 lbs.
Wheelbase (WB)	150 inches
Cab-to-Axle (CA)	88.5 inches
Body Length	
Body Weight	
Back of Cab (BOC)	5.3 inches

**** You must fill in body length and weight to enable body and payload weight calculations.**

Weight (lbs.)	Front	Rear	Total
Chassis	4,678.00	2,522.00	7,200.00
Chassis Equipment	0.00	0.00	0.00
Subtotal	4,678.00	2,522.00	7,200.00
Driver/Passengers	744.00	206.00	950.00
Body/Body Equipment	0.00	0.00	0.00
Payload	0.00	0.00	0.00
Total	5,422.00	2,728.00	8,150.00
GAWR/GVWR	6,830.00	12,980.00	17,950.00
GCWR			23,950.00

Chassis Equipment:

Code	Item	Center of Gravity	Front Axle	Rear Axle	Total
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning		0.00 lbs.	0.00 lbs.	0.00 lbs.
141	30 Gallon Stainless Steel In-Rail Fuel Tank		0.00 lbs.	0.00 lbs.	0.00 lbs.

Driver/Passengers:

	Center of Gravity	Front Axle	Rear Axle	Total
Driver	front axle	350.00 lbs.	0.00 lbs.	350.0 lbs.
Rear Passengers	10 inches in front of the back of cab	394.00 lbs.	206.00 lbs.	600.00 lbs.

Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



LILLEY ISUZU TRUCK

Troy Ward | 252-217-7887 | tward@lilleyinternational.com

2024 Isuzu NQR Crew Cab Diesel (2024 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Warranty

Warranty Limitations: *Time or Mileage, Whichever Comes First*

New Truck Warranty		Time in Years	Vehicle Miles
Basic		3	Unlimited
Engine		3	Unlimited
<ul style="list-style-type: none">TransmissionDrive AxleDriveshaftFront Axle / BeamCrossmembersFlywheel HousingClutch Housing		3	Unlimited
Frame Rails		3 5*	Unlimited Unlimited*
Corrosion (Rust Through)		4	Unlimited
Roadside Assistance		3 5†	Unlimited 100,000†
Emission Warranty		Time in Years	Vehicle Miles
Emission Control System		5	110,000
Emission Performance		5	50,000
GHG Emission		5	50,000
Tires		2	24,000

After 3 years labor and parts coverage is 50% for up to 5 years.

†Tows related to emissions issues may be covered for up to 5 years or 110,000 miles (whichever comes first).

The warranty coverages are determined by the mileage of the vehicle and the number of years from the delivery date. The warranty coverages are limited by whichever occurs first. Please see your authorized Isuzu dealer for warranty details.

Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



LILLEY ISUZU TRUCK

Troy Ward | 252-217-7887 | tward@lilleyinternational.com

2024 Isuzu NQR Crew Cab Diesel (2024 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Turning Circle

Specification Summary	
Model	3S354
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Wheelbase	
IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail.
Front Wheels	
IB9	19.5" x 6", 6-hole disc, painted white
Front Tires	
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season

Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.




LILLEY ISUZU TRUCK

Troy Ward | 252-217-7887 | tward@lilleyinternational.com

2024 Isuzu NQR Crew Cab Diesel (2024 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Turning Circle



A: Inside Wheel Cut Angle: 46.50°

B: Minimum turning diameter, Curb to Curb: 45.30'

Curb to Curb diameter is measured from the outside of the front tire.

C: Minimum turning diameter, Wall to Wall: 50.20'

Wall to Wall diameter is measured from the outermost part of the cab.

Current report content is based on data as of 2023-04-20 10:21:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.