

Prepared For:
North Carolina Sheriffs' Association
Kaylyn Mitman
323 W Jones St.
Raleigh, NC 27603-1365
(919)743 - 7433
Reference ID: N/A

Presented By:
LILLEY INTERNATIONAL
Nick Timper
US HWY 17 BY PASS
WILLIAMSTON NC 27892 -
(252)792-4192

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2024 LT625 6x4 (LT62F)

APPLICATION:	General Freight Regional Haul (DayCab)
MISSION:	Requested GCWR: 80000. Calc. GCWR: 95000. Calc. GVWR: 52350 Calc. Start / Grade Ability: 18.91% / 1.19% @ 65 MPH Calc. Geared Speed: 88.3 MPH
DIMENSION:	Wheelbase: 197.00, CA: 122.40, Axle to Frame: 53.00
ENGINE, DIESEL:	{Cummins X15 450} Efficiency Series, EPA 2021, 450HP @ 1700 RPM, 1650 lb-ft Torque @ 950 RPM, 1700 RPM Governed Speed, 461 Peak HP (Max)
TRANSMISSION, MANUAL:	{Eaton Endurant EEO-16F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid
CLUTCH:	{Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity
AXLE, FRONT NON-DRIVING:	{Meritor MFS-13-143A} Wide Track, I-Beam Type, 13,200-lb Capacity
AXLE, REAR, TANDEM:	{Meritor MT-40-14X-3CFR} Single Reduction, Amboid Gearing in Rear-Rear Axle, 40,000-lb Capacity, .374"(9.5mm) Wall Housing Thickness, R Wheel Ends Gear Ratio: 3.08
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G HDL2 DL ECO PLUS (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM:	{International} Ride Optimized Suspension (IROS), 40,000-lb Capacity, 52" Axle Spacing, 9.25" Ride Height, with Shock Absorbers
PAINT:	Cab schematic 100HX Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
Base Chassis, Model LT625 6x4 with 197.00 Wheelbase, 122.40 CA, and 53.00 Axle to Frame.	7953/6382	14335
TOW HOOK, FRONT (2) Frame Mounted	22/0	22
FRAME RAILS WITH TAPERED REAR	0/0	0
FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.125" x 3.580" x 0.312" (257.2mm x 90.9mm x 8.0mm); 367.4" (9333mm) Maximum OAL	67/68	135
BUMPER, FRONT Contoured, Aluminum, Stainless Steel Clad, with Black Plastic Filler Panels, Less Valance Panel for Increased Ground Clearance	50/-8	42
WHEELBASE RANGE 187" (475cm) Through and Including 219" (555cm)	-189/-5	-194
AXLE, FRONT NON-DRIVING {Meritor MFS-13-143A} Wide Track, I-Beam Type, 13,200-lb Capacity	88/0	88
SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers	62/0	62
<u>Includes</u>		
: SPRING PINS Rubber Bushings, Maintenance-Free		
BRAKE SYSTEM, AIR Dual System for Tractor Applications	0/0	0
<u>Includes</u>		
: BRAKE LINES Color and Size Coded Nylon		
: BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm		
: DRAIN VALVE Manually Operated (On Wet Tank Only)		
: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster		
: GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab		
: HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel		
: HOSE TENDER Back of Cab Mounted		
: PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel		
: PARKING BRAKE VALVE Combination Valve for Tractor and Trailer		
: QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle		
: TRACTOR PROTECTION VALVE		
<u>Notes</u>		
: Front and Rear Dust Shields not Included		
: Rear Axle is Limited to 40,000-lb GAWR with Code 04092 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered		
HOSE TENDER with Triple Spring Brackets Mounted in Common with Cab Side Extender Bracket Driver Side	4/2	6
AIR BRAKE ABS {Wabco AntiLock Brake System} 6-Channel (6 Sensor/6 Modulator) Electronic Stability Program, with Automatic Traction Control	5/2	7
AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration	0/0	0
BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 Sqli Spring Brake	0/14	14
<u>Includes</u>		
: BRAKE CHAMBERS, POSITION (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb.		
: BRAKE CHAMBERS, POSITION (4) Rear Parking; WITH TRUCK BRAKES: All 6x4, 6x6; WITH TRACTOR BRAKES: 6x4 & 6x6 with Rear Tandem Axles 46,000-lb. or Greater or GVWR of 54,000-lb. or Greater		
BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 Sqli	4/0	4
BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	1/0	1
SLACK ADJUSTERS, FRONT {Gunite} Automatic	14/0	14

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
SLACK ADJUSTERS, REAR {Gunitex} Automatic	0/28	28
AIR COMPRESSOR {Cummins} 18.7 CFM	-2/0	-2
AIR TANK, AUXILIARY for Transmission Air Supply, Frame Mounted Under Right Rail, Under Cab	20/6	26
AIR TANK Polished Aluminum, with Straight Thread O-Ring Ports	-15/-11	-26
AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail	0/0	0
DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks	2/0	2
TRAILER HOSES {Phillips} Coiled, Polar Air Hose, 15' Working Length, 24" Tractor Lead Length, 11" Trailer Lead Length, Aluminum Glad Hands with Polyurethane Seals and Power Grips	-2/-1	-3
BRAKES, REAR {Meritor 16.5X7 Q-PLUS LW} Air S-Cam Type, Fabricated Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 20,000-lb Capacity per Axle	0/83	83
BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity	-23/0	-23
PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type	0/30	30
STEERING COLUMN Tilting and Telescoping	0/0	0
STEERING WHEEL 4-Spoke; 18" Dia., Black Leather Wrapped	-1/0	-1
STEERING GEAR {Sheppard HD94} Power	0/0	0
POWER STEERING OIL COOLER Remote Mounted	4/0	4
DRIVELINE SYSTEM {Dana Spicer} Service Free SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4	0/0	0
AFTERTREATMENT COVER Polished Aluminum	8/3	11
EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab	52/40	92
ENGINE COMPRESSION BRAKE {Cummins} Interbrake For Cummins Signature/ISX/X15 Engines; Furnished with Engine	0/0	0
TAIL PIPE (1) Turnback Type, Bright	2/0	2
MUFFLER/TAIL PIPE GUARD (1) Bright Stainless Steel	19/12	31
EXHAUST HEIGHT 10'	0/0	0
ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0

Includes

- : DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab
- : HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel
- : HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever
- : HORN, ELECTRIC Single
- : PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light
- : POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel
- : STARTER SWITCH Electric, Key Operated
- : TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature
- : TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted
- : WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever
- : WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted
- : WIRING, CHASSIS Color Coded and Continuously Numbered

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
HORN, ELECTRIC (2) Disc Style	0/0	0
ALTERNATOR {Delco Remy 28SI} Brush Type, 12 Volt, 200 Amp Capacity, Pad Mount, with Remote Sense	-2/0	-2
BATTERY SYSTEM {JCI} Maintenance-Free, (4) 12-Volt 2800CCA Total, Top Threaded Stud	57/33	90
SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door	2/0	2
SPEAKERS (2) 6.5" Dual Cone Mounted in Doors	0/0	0
CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, Two Antennas and Antenna Bases with Wiring on Both Side Mirrors	1/0	1
RADIO AM/FM/WB/SiriusXM/Clock/Bluetooth/USB Input/Auxiliary Input	0/0	0
TRAILER LIGHTING CABLE {Phillips LECTRACOIL 30-9921S} Coiled, 15' Length, 48" Tractor Lead and 12" Trailer Lead, with Plastic Plug	14/9	23
TRAILER SOCKET 7-Way; with Battery Fed Circuit to Center Pin, with 30 Amp Fuse and Relay Controlled by Switch with Indicator Light on Instrument Panel Fed From Hot Battery Feed, When Parking Brake Is Applied, Not Wired Thru Key Switch	7/0	7
STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn, Tail and Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes License Plate Light	-2/14	12
COLLISION MITIGATION SYSTEM Omit	-4/0	-4
STOP-LIGHT WIRING MODIFIED Stop-Lights Turned on When Engine Compression Brake, Exhaust Brake or Retarder is Activated	0/0	0
BATTERY BOX COVER Polished Aluminum	13/5	18
WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0
BATTERY DISCONNECT SWITCH {Joseph Pollak} for Cab Power Disconnect Switch, Disconnects Power to Power Distribution Center (PDC), Does Not Disconnect Charging Circuits, Lever Operated, Cab Mounted	4/0	4
TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on	0/0	0
STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection	0/0	0
HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	0/0	0
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
TOGGLE SWITCH, AUXILIARY (2) with Two 30-Amp Circuit Breakers	0/0	0
BATTERY BOX Aluminum, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Under Cab	-34/-11	-45
HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord	0/0	0
SWITCH, MARKER INTERRUPT for Marker Lights and Headlights, Located in Steering Wheel	0/0	0
BATTERY WIRING MODIFICATION Battery Discharge Protection System; Control thru Body Controller	0/0	0
FOG LIGHTS (2) Clear Lens, Halogen, Rectangular, with White Light Source	2/0	2
CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console	0/0	0
HEADLIGHTS LED, with Daytime Running Lights, Automatic Twilight Controlled	0/0	0
QUARTER FENDERS for Rear Wheels, Mirror-Finished Stainless Steel, Frame Mounted	0/18	18

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
LOGOS EXTERIOR Model Badges	0/0	0
LOGOS EXTERIOR, ENGINE Badges	0/0	0
GRILLE Chrome	0/0	0
FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
<u>Includes</u>		
: BUG SCREEN Front End; Mounted Behind Grille		
: HOOD TILT ASSIST Includes Torsion Bar Spring System		
FENDER EXTENSIONS Painted	0/0	0
PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
<u>Includes</u>		
: PAINT SCHEMATIC ID LETTERS "HX"		
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
INTELLIGENT FLEET CARE Telematics Device with Over the Air Programming; Includes Five Year Data Plan, Advanced Preventive Maintenance, Fleet Health Monitor Reporting and International 360	0/0	0
FIFTH WHEEL, AIR SLIDE {Fontaine SL6NWB775024} 24" Slide, 7.75" Above Top of Frame, Left Hand Release	0/29	29
SAFETY TRIANGLES	6/0	6
MUD FLAP HOLDER Spring Loaded, Bright Finish, 45-Degree End, with Red and White Reflective Tape, Less Flaps	0/-6	-6
MUD FLAPS, REAR Black Poly, with International Logo, Less Holders	0/8	8
CLUTCH {Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity	0/0	0
ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
BLOCK HEATER, ENGINE {Phillips} 120V/1500W	2/0	2
<u>Includes</u>		
: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door		
ENGINE, DIESEL {Cummins X15 450} Efficiency Series, EPA 2021, 450HP @ 1700 RPM, 1650 lb-ft Torque @ 950 RPM, 1700 RPM Governed Speed, 461 Peak HP (Max)	622/55	677
FAN DRIVE {Horton Drivemaster} Two-Speed Type, Direct Drive, with Residual Torque Device for Disengaged Fan Speed	2/0	2
AIR CLEANER Single Element, Engine Mounted	0/0	0
<u>Includes</u>		
: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted		
EMISSION, CALENDAR YEAR {Cummins X15} EPA, OBD and GHG Certified for Calendar Year 2023	0/0	0
FAN OVERRIDE Manual; with Electric Switch on Instrument Panel, (Fan On with Switch On)	0/0	0
HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type	0/0	0
RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System	0/0	0
CARB IDLE COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler	0/0	0
CRUISE CONTROL Predictive, Includes GPS Enhanced Cruise Control; Includes Module, Antenna and Wiring	0/0	0
CARB EMISSION WARR COMPLIANCE Federal, Does Not Comply with CARB Emission Warranty	0/0	0
TRANSMISSION, MANUAL {Eaton Endurant EEO-16F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid	0/0	0
TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1
TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints	0/0	0
PTO LOCATION Customer Intends to Install PTO at Bottom of Transmission	0/0	0
SHIFT CONTROL PARAMETERS {Eaton Endurant} Automated Manual Transmission, Performance Calibration	0/0	0
PDL WARNING BUZZER Power Divider Lock	0/0	0
SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab	6/2	8
AXLE, REAR, TANDEM {Meritor MT-40-14X-3CFR} Single Reduction, Amboid Gearing in Rear-Rear Axle, 40,000-lb Capacity, .374"(9.5mm) Wall Housing Thickness, R Wheel Ends . Gear Ratio: 3.08	0/0	0
<u>Includes</u>		
: POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light		
<u>Notes</u>		
: When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance		
SUSPENSION, REAR, AIR, TANDEM {International} Ride Optimized Suspension (IROS), 40,000-lb Capacity, 52" Axle Spacing, 9.25" Ride Height, with Shock Absorbers	0/0	0
AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 50 thru 64.99 Pints	0/0	0
FUEL TANK STRAPS Bright Finish Stainless Steel	0/0	0
DEF TANK COVER Stainless Steel	3/1	4
FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor	-5/0	-5
<u>Includes</u>		
: LOCATION FUEL/WATER SEPARATOR Mounted Left Rail in Wheel Well		
FUEL HEATER {Cummins} Omit Plumbing for TRV on Cummins Engines	-2/0	-2
FUEL TANK Top Draw, Non-Polished Aluminum, 26" Dia, 120 US Gal (454L), Mounted Right Side, Back of Cab/Under Sleeper	5/16	21
DEF TANK 10.6 US Gal (40L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper	0/0	0
CAB Conventional, Day Cab	0/0	0
<u>Includes</u>		
: CLEARANCE/MARKER LIGHTS (5) Flush Mounted		
: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window		
: CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area		
: COURTESY LIGHT (2) Driver and Passenger Door Mounted		
: DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console		
: FLOOR COVERING Rubber, Black		
: GLASS, ALL WINDOWS Tinted		

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
: GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side		
: GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side		
: INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color		
: READING LIGHT, CAB Located in Overhead Console		
: STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		
CAB SIDE EXTENDERS (FAIRINGS) for Use with Day Cab, with Integral Grab Handle Left Side	27/8	35
AIR CONDITIONER with Integral Heater and Defroster	0/0	0
<u>Includes</u>		
: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps		
GAUGE CLUSTER Premium Level; English with English Electronic Speedometer	0/0	0
<u>Includes</u>		
: GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for		
: GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure		
: WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)		
GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	0/0	0
GAUGE, OIL TEMP, ENGINE	1/0	1
GAUGE, OIL TEMP, REAR AXLE	1/0	1
GAUGE, LOAD INDICATING REAR Text Message in Cluster Display, for use with Rear Air Suspension	0/0	0
IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster	0/0	0
VIRTUAL GAUGE, AIR APPLICATION Requires Premium Cluster	0/0	0
SEAT, DRIVER {National 2000 Model 195} Air Suspension, High Back, Vinyl Boxing with Cloth Facing, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Way Front Cushion Adjust, 3-14 Degree Back Angle Adjust	2/0	2
SEAT, PASSENGER {National 2000} Non Suspension, High Back, Vinyl Boxing with Cloth Facing, 11 Degree Back Angle	2/0	2
MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	1/0	1
<u>Notes</u>		
: Mirror Dimensions are Rounded to the Nearest 0.5"		
MIRROR, CONVEX, LOOK DOWN Right Side, Bright, 6" x 10.5"	3/0	3
CAB INTERIOR TRIM Classic, for Day Cab	0/0	0
<u>Includes</u>		
: DOOR TRIM, INTERIOR Black Handle		
: INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels		
: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap		
MONITOR, TIRE PRESSURE Omit	-11/-2	-13
WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0
KEYLESS ENTRY SYSTEM REMOTE with Panic and Auxiliary Buttons, Includes One Key Fob (Transmitter)	2/0	2
LOW WASHER FLUID INDICATOR	1/0	1

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
INSTRUMENT PANEL Wing Panel	0/0	0
ACCESS, CAB AND FRAME Bright Aluminum, Driver & Passenger Sides, Two Steps per Door; Left Side Frame Access Step, Includes One Flush Mounted Deck Plate and Black Grab Handle, for use with Day Cab or Sleeper Cab	51/23	74
WHEELS, FRONT {Accuride 43644} DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
WHEELS, REAR {Accuride 43644} DUAL DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
TIRE VALVE CAP Flo-Thru Design	0/0	0
WHEEL COVER, REAR Aerodynamic, 22.5", Black	0/0	0
WHEEL BEARING, FRONT, LUBE {EmGard FE-75W-90} Synthetic Oil	0/0	0
PAINT FENDER EXTENSIONS Single Color; Same as Number One Cab Schematic Color	0/0	0
(8) TIRE, REAR 11R22.5 Load Range G HDL2 DL ECO PLUS (CONTINENTAL), 491 rev/mile, 75 MPH, Drive	0/192	192
(2) TIRE, FRONT 11R22.5 Load Range G AH37 (HANKOOK), 501 rev/mile, 75 MPH, All-Position	16/0	16
FIFTH WHEEL LOCATION On Rear Axle Centerline	0/0	0
Services Section:		
WARRANTY Standard for LT/RH Series, Effective with Vehicles Built January 2, 2016 or Later, CTS-2010A	0/0	0
Total Component Weight:	8939/7039 (lbs)	15978 (lbs)
2023 Surcharge Included In Price	0/0	0
Total Body Allied:	0/0 (lbs)	0 (lbs)

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.