

Prepared For:

North Carolina Sheriffs' Association
Kaylyn Mitman
323 W Jones St.
Raleigh, NC 27603-1365
(919)743 - 7433
Reference ID: N/A

Presented By:

LILLEY INTERNATIONAL
Nick Timper
US HWY 17 BY PASS
WILLIAMSTON NC 27892 -
(252)792-4192

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2024 RH613 6x4 (RH61F)

APPLICATION:	General Freight Regional Haul (DayCab)
MISSION:	Requested GCWR: 80000. Calc. GCWR: 110000. Calc. GVWR: 58350 Calc. Start / Grade Ability: 18.61% / 1.37% @ 65 MPH Calc. Geared Speed: 88.6 MPH
DIMENSION:	Wheelbase: 187.00, CA: 124.20, Axle to Frame: 63.00
ENGINE, DIESEL:	{International A26} EPA 2021, 450HP @ 1700 RPM, 1700 lb-ft Torque @ 900 RPM, 1800 RPM Governed Speed, 450 Peak HP (Max)
TRANSMISSION, MANUAL:	{Eaton Endurant EEO-17F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid
CLUTCH:	{Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity
AXLE, FRONT NON-DRIVING:	{Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,350-lb Capacity
AXLE, REAR, TANDEM:	{Meritor RT-46-160P} Single Reduction, 46,000-lb Capacity, with Lube Oil Pump, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends Gear Ratio: 3.21
CAB:	Conventional, Day Cab
TIRE, FRONT:	(2) 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position
TIRE, REAR:	(8) 11R22.5 Load Range G G572 1AD (GOODYEAR), 496 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, AIR, TANDEM:	{Hendrickson HAS-460-55} 46,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers
PAINT:	Cab schematic 100HW Location 1: 9219, Winter White (Std) Chassis schematic N/A

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
Base Chassis, Model RH613 6x4 with 187.00 Wheelbase, 124.20 CA, and 63.00 Axle to Frame.	8132/6200	14332
FRAME RAILS WITH TAPERED REAR	0/0	0
FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 466.5" (11850mm) Maximum OAL	88/157	245
BUMPER, FRONT 3-Piece, Aerodynamic, Plastic, Molded Dark Gray	0/0	0
DECK PLATE Aluminum, (1) Section, Flush Mounted, Quick to Release	10/0	10
WHEELBASE RANGE 187" (475cm) Through and Including 219" (555cm)	0/0	0
AXLE, FRONT NON-DRIVING {Meritor MFS-12-143A} Wide Track, I-Beam Type, 12,350-lb Capacity	6/0	6
SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 12,350-lb Capacity, with Shock Absorbers	0/0	0
<u>Includes</u> : SPRING PINS Rubber Bushings, Maintenance-Free		
BRAKE SYSTEM, AIR Dual System for Tractor Applications	0/0	0
<u>Includes</u> : BRAKE LINES Color and Size Coded Nylon : BRAKE PRESSURE INDICATOR Low Air Pressure Warning Light and Audible Alarm : DRAIN VALVE Manually Operated (On Wet Tank Only) : GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster : GLAD HANDS (2) One for Service and One for Emergency; Trailer Hoses from Cab : HAND CONTROL VALVE, AIR with Self Return Handle, for Trailer Brakes, Mounted in Instrument Panel : HOSE TENDER Back of Cab Mounted : PARKING BRAKE CONTROL Yellow and Red Knobs, Located on Instrument Panel : PARKING BRAKE VALVE Combination Valve for Tractor and Trailer : QUICK RELEASE VALVE On Rear Axle for Spring Brake Release: 1 for Forward Rear Axle : TRACTOR PROTECTION VALVE		
AIR BRAKE ABS {Wabco AntiLock Brake System} 6-Channel (6 Sensor/6 Modulator) Electronic Stability Program, with Automatic Traction Control	1/0	1
AIR DRYER {Bendix AD-HF} with Heater, Includes Pressure Protection Circuits, Safety Valve, Integral Purge Tank, Governor Pressure Settings 110 psi Cut-In/130 psi Cut-Out, Integrated PuraGuard Coalescing Filtration	0/0	0
BRAKE CHAMBERS, REAR AXLE {Bendix EverSure} 30/30 SqiIn Spring Brake	0/0	0
<u>Includes</u> : BRAKE CHAMBERS, POSITION (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb. : BRAKE CHAMBERS, POSITION (4) Rear Parking; WITH TRUCK BRAKES: All 6x4, 6x6; WITH TRACTOR BRAKES: 6x4 & 6x6 with Rear Tandem Axles 46,000-lb. or Greater or GVWR of 54,000-lb. or Greater		
BRAKE CHAMBERS, FRONT AXLE {Bendix} 24 SqiIn	0/0	0
BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake	1/0	1
SLACK ADJUSTERS, FRONT {Gunite} Automatic	0/0	0
SLACK ADJUSTERS, REAR {Gunite} Automatic	0/0	0
AIR COMPRESSOR {Bendix BA-921 Head Unload} 15.9 CFM	0/0	0
TRAILER HOSES {Philatron} Coiled, Stallion Hose, 15' Working Length, 7" Tractor Lead Length, 7" Trailer Lead Length, Aluminum Glad Hands with Polyurethane Seals and Hand Holds	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
AIR TANK, AUXILIARY for Transmission Air Supply, Frame Mounted Under Right Rail, Under Cab	19/5	24
AIR TANK LOCATION (2) Mounted Under Battery Box, Outside Left Rail, Under Cab; Perpendicular to Rail	0/0	0
DRAIN VALVE (2) {Berg} with Pull Chains, for Air Tanks	2/0	2
BRAKES, FRONT {Meritor 16.5X5 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity	0/0	0
BRAKES, REAR {Meritor 16.5X8.625 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 8.625", 23,000-lb Capacity per Axle	0/68	68
PARK BRAKE CHAMBERS, ADDITIONAL (2) Spring Brake Type	0/30	30
STEERING COLUMN Tilting and Telescoping	0/0	0
STEERING WHEEL 4-Spoke; 18" Dia., Black Leather Wrapped	-1/0	-1
STEERING GEAR {Sheppard HD94} Power	0/0	0
POWER STEERING OIL COOLER Remote Mounted	7/-1	6
DRIVELINE SYSTEM {Dana Spicer} SPL250 Main Driveline with SPL170 Interaxle Shaft, for 6x4	0/0	0
AFTERTREATMENT COVER Aluminum	8/3	11
EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab	75/18	93
ENGINE COMPRESSION BRAKE by Jacobs; for N13/A26 Engines, with Selector Switch and On/Off Switch	0/0	0
TAIL PIPE (1) Turnback Type, Bright	1/0	1
EXHAUST HEIGHT 13' 3"	3/0	3
MUFFLER/TAIL PIPE GUARD (1) Aluminum	12/7	19
ELECTRICAL SYSTEM 12-Volt, Standard Equipment	0/0	0
<u>Includes</u>		
: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab		
: HAZARD SWITCH Push On/Push Off, Located on Instrument Panel to Right of Steering Wheel		
: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever		
: HORN, ELECTRIC Single		
: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light		
: POWER SOURCE Cigar Type Receptacle with Cap, USB Port, Located in Instrument Panel		
: STARTER SWITCH Electric, Key Operated		
: TURN SIGNAL SWITCH Manual Cancelling with Lane Change Feature		
: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted		
: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever		
: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted		
: WIRING, CHASSIS Color Coded and Continuously Numbered		
HORN, ELECTRIC (2) Disc Style	0/0	0
ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount	0/0	0
BATTERY SYSTEM {Fleetrite} Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud	0/0	0
SPEAKER, AUXILIARY, CB RADIO with Jack for CB; Mounted Left Side Above Driver's Door	2/0	2
SPEAKERS (2) 6.5" Coax Mounted in Doors, (2) 5.25" Coax Mounted in B-Pillars	4/0	4

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
CB RADIO Accommodation Package, Header Mounted, Feeds from Accessory Side of Ignition Switch, Includes Power Source, One Antenna and Antenna Base with Wiring on Left Side Mirror	1/0	1
RADIO AM/FM/WB/Clock/Bluetooth/USB Input/Auxiliary Input	0/0	0
BACK-UP ALARM Electric, 102 dBA	0/3	3
TRAILER LIGHTING CABLE {Phillips LECTRACOIL 30-9921S} Coiled, 15' Length, 48" Tractor Lead and 12" Trailer Lead, with Plastic Plug	15/8	23
STOP, TURN, TAIL & B/U LIGHTS {Truck Lite} Super 44, with LED Lights for Stop, Turn, Tail and Backup Lights, with Power Module, "International" Termination and Less Junction Box, Includes License Plate Light	-7/19	12
COLLISION MITIGATION SYSTEM Omit	-4/0	-4
JUMP START STUD Remote Mounted	2/0	2
<u>Includes</u>		
: JUMP START STUD Mounted to Battery Box		
POWER SOURCE, TERMINAL TYPE 2-Post	1/0	1
POWER SOURCE, SPECIAL {Phillips} Socket, Single Terminal, for Power Lift Gate Feed, Battery Feed Thru 150 Amp Circuit Breaker, To Operate Lift Gate On Trailer, Includes a 15' Power Cable Coiled In Cab	15/0	15
WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time	0/0	0
BATTERY DISCONNECT SWITCH {Joseph Pollak} for Cab Power Disconnect Switch, Disconnects Power to Power Distribution Center (PDC), Does Not Disconnect Charging Circuits, Lever Operated, Cab Mounted	4/0	4
TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights	0/0	0
HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn on if Windshield Wipers are turned on	0/0	0
STARTING MOTOR {Delco Remy 39MT} 12 Volt, Gear Reduced, with Thermal Over-Crank Protection	0/0	0
HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position	0/0	0
CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses	0/0	0
BATTERY BOX Aluminum, 30" Wide, 2-4 Battery Capacity, Mounted Left Side Under Cab	-33/-11	-44
BATTERY BOX COVER Plastic	0/0	0
HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord	0/0	0
SWITCH, MARKER INTERRUPT for Marker Lights and Headlights, Located in Steering Wheel	0/0	0
HEADLIGHTS Halogen, with Daytime Running Lights, Automatic Twilight Controlled	-12/1	-11
CONNECTOR, DASH, CENTER PANEL Cab Wiring for TMC RP1226 Vehicle Accessory Connector; Includes 14-pin Connector with Switched Power, Battery Power, Ignition Power, Ground & Body 250K Datalink, Connector Located Behind Instrument Panel Center Console	0/0	0
QUARTER FENDERS for Rear Wheels, Mirror-Finished Stainless Steel, Frame Mounted	0/18	18
LOGOS EXTERIOR Model Badges	0/0	0
LOGOS EXTERIOR, ENGINE Badges	0/0	0
GRILLE Chrome	0/0	0
FRONT END Tilting, Fiberglass, with Three Piece Construction	0/0	0
<u>Includes</u>		
: BUG SCREEN Front End; Mounted Behind Grille		

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
: HOOD TILT ASSIST Includes Torsion Bar Spring System		
FENDER EXTENSIONS Painted	0/0	0
PAINT SCHEMATIC, PT-1 Single Color, Design 100	0/0	0
<u>Includes</u>		
: PAINT SCHEMATIC ID LETTERS "HW"		
PAINT TYPE Base Coat/Clear Coat, 1-2 Tone	0/0	0
INTELLIGENT FLEET CARE Telematics Device with Over the Air Programming; Includes Five Year Data Plan, Advanced Preventive Maintenance, Fleet Health Monitor Reporting and International 360	0/0	0
FIFTH WHEEL, AIR SLIDE {Fontaine SL7LWB725024} 24" Slide, Cast Top Plate, 7.25" Above Top of Frame, Left Hand Release	0/94	94
MUD FLAP HOLDER Spring Loaded, Painted Black, with Red and White Reflective Tape, Less Flaps	0/0	0
MUD FLAPS, REAR Black Poly, with International Logo, Less Holders	0/8	8
CLUTCH {Eaton Fuller 430MM} Maintenance Free, Self-Adjusting, 17" (430 mm) Dia Single Plate, Diaphragm Spring, Organic, 5-Spring Coaxial 254mm Damper with Pre-Damper, 2"-18 Tooth Spline, Pneumatic Push Type Control, 1850 lb-ft (2508 Nm) Torque Capacity	0/0	0
ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection	0/0	0
ENGINE, DIESEL {International A26} EPA 2021, 450HP @ 1700 RPM, 1700 lb-ft Torque @ 900 RPM, 1800 RPM Governed Speed, 450 Peak HP (Max)	0/0	0
FAN DRIVE {Horton Drivemaster} Automatic On/Off Type, with Normally Closed Temperature Control	0/0	0
AIR CLEANER Single Element	0/0	0
<u>Includes</u>		
: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted		
EMISSION, CALENDAR YEAR {International A26} EPA, OBD and GHG Certified for Calendar Year 2023	0/0	0
HOSE CLAMPS, RADIATOR HOSES {Gates} Shrink Band Type	0/0	0
COLD STARTING EQUIPMENT Automatic; with Engine ECM Control	0/0	0
RADIATOR DRAIN & FILL FITTING SPECIAL; To Vacuum Out or Fill the Cooling System from the Bottom of Radiator, for Use with Quick-Connect Radiator Drain Tool or Shop Coolant Evacuation-Fill System	0/0	0
CARB IDLE COMPLIANCE Federal, Does Not Comply with California Clean Air Idle Regulations	0/0	0
RADIATOR Aluminum, Welded, Down Flow, Front to Back System, 1325 SqIn, with 806 SqIn Charge Air Cooler	0/0	0
CRUISE CONTROL Predictive, Includes GPS Enhanced Cruise Control; Includes Module, Antenna and Wiring	0/0	0
CARB EMISSION WARR COMPLIANCE Federal, Does Not Comply with CARB Emission Warranty	0/0	0
TRANSMISSION, MANUAL {Eaton Endurant EEO-17F112C} 12-Speed Fully Automated Manual, Aluminum Clutch Housing, Overdrive, Mechatronic Shift Controls, Pneumatic Clutch Actuation, Internal Lube Oil Pump, Hill Start Aid	0/0	0
TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission	1/0	1
TRANSMISSION OIL {EmGard 40W} Synthetic; 1 thru 21.99 Pints	0/0	0
PTO LOCATION Customer Intends to Install PTO at Bottom of Transmission	0/0	0
SHIFT CONTROL PARAMETERS {Eaton Endurant} Automated Manual Transmission, Economy Calibration	0/0	0

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab	4/4	8
AXLE, REAR, TANDEM {Meritor RT-46-160P} Single Reduction, 46,000-lb Capacity, with Lube Oil Pump, Driver Controlled Locking Differential in Rear-Rear Axle, 200 Wheel Ends . Gear Ratio: 3.21	0/580	580
<u>Includes</u> : POWER DIVIDER LOCK Electric over Air Operated, Cab Control with Indicator Light		
SUSPENSION, REAR, AIR, TANDEM {Hendrickson HAS-460-55} 46,000-lb Capacity, 55" Axle Spacing, 9.5" Ride Height, with Shock Absorbers	0/144	144
AXLE, REAR, LUBE {EmGard FE-75W-90} Synthetic Oil; 65 thru 89.99 Pints	0/0	0
AXLE SHAFT MODIFICATION Axle Shaft Flanges Modified for 0.625" Diameter Drive Studs with Solid Type Cone-Locks	0/0	0
FUEL TANK (2) Top Draw, Non-Polished Aluminum, 26" Dia, 100 US Gal (379L); Total Capacity 200 US Gal (757L), with Dual Supply and Return Lines, Less Equalizer Line, Mounted Left and Right Side, Back of Cab/ Under Sleeper	50/66	116
FUEL/WATER SEPARATOR {Racor} Fuel Pre-Filter and Filter Base, Includes Water-In-Fuel Sensor	-6/0	-6
<u>Includes</u> : LOCATION FUEL/WATER SEPARATOR Mounted Left Rail in Wheel Well		
DEF TANK 15.9 US Gal (60L) Capacity, Frame Mounted Outside Left Rail, Back of Cab/Under Sleeper	3/1	4
CAB Conventional, Day Cab	0/0	0
<u>Includes</u> : CLEARANCE/MARKER LIGHTS (5) Flush Mounted : COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window : CONSOLE, CENTER Includes Two Cup Holders and One Additional Storage Area : COURTESY LIGHT (2) Driver and Passenger Door Mounted : DOME LIGHT, CAB Rectangular, Door and Instrument Panel Mounted Switch Activated, Timed Theater Dimming, Center Mounted, Integral to Console : FLOOR COVERING Rubber, Black : GLASS, ALL WINDOWS Tinted : GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side : GRAB HANDLE, CAB INTERIOR (4) "B" Pillar and Door Mounted, Two Each Side : INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color : READING LIGHT, CAB Located in Overhead Console : STORAGE POCKET, DOOR (2) Full Length, Driver and Passenger Door		
AIR CONDITIONER with Integral Heater and Defroster	0/0	0
<u>Includes</u> : HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps		
GAUGE CLUSTER Base Level; English with English Electronic Speedometer	0/0	0
<u>Includes</u> : GAUGE CLUSTER DISPLAY: Base Level (3" Monochromatic Display), Premium Level (5" LCD Color Display); Odometer, Voltmeter, Diagnostic Messages, Gear Indicator, Trip Odometer, Total Engine Hours, Trip Hours, MPG, Distance to Empty/Refill for : GAUGE CLUSTER Speedometer, Tachometer, Engine Coolant Temp, Fuel Gauge, DEF Gauge, Oil Pressure Gauge, Primary and Secondary Air Pressure : WARNING SYSTEM Low Fuel, Low DEF, Low Oil Pressure, High Engine Coolant Temp, Low Battery Voltage (Visual and Audible), Low Air Pressure (Primary and Secondary)		
GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster	0/0	0
GAUGE, AIR APPLICATION	1/0	1

<u>Description</u>	<u>F/R Wt</u> (lbs)	<u>Tot Wt</u> (lbs)
GAUGE, LOAD INDICATING REAR Text Message in Cluster Display, for use with Rear Air Suspension	0/0	0
GAUGE, VOLTMETER Auxiliary Gauge, Located in Center Panel. Standard Cluster Also Includes Digital Voltage Readout	0/0	0
SEAT, DRIVER {National 2000 Model 195} Air Suspension, High Back, with Mordura Cloth, 2 Arm Rests, Isolator, 7" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 3-14 Degree Back Recline	2/0	2
SEAT, PASSENGER {National 2000} Non Suspension, High Back, Mordura Cloth, 2 Arm Rests 11 Degree Back Angle	7/1	8
MIRROR, CONVEX, HOOD MOUNTED (2) Right and Left Sides, Bright	12/-1	11
MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Turn Signals, Bright Heads, Black Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width	1/0	1
<u>Notes</u>		
: Mirror Dimensions are Rounded to the Nearest 0.5"		
SEAT BELT All Orange; 1 to 3	0/0	0
CAB INTERIOR TRIM Classic, for Day Cab	0/0	0
<u>Includes</u>		
: DOOR TRIM, INTERIOR Black Handle		
: INSTRUMENT PANEL TRIM Black, Black Gauges with Black Bezels		
: SUN VISOR (2) Padded Vinyl; 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Toll Ticket Strap		
MONITOR, TIRE PRESSURE Omit	-12/-1	-13
WINDOW, POWER (2) and Power Door Locks, Left and Right Doors, Includes Express Down Feature	0/0	0
INSTRUMENT PANEL Wing Panel	0/0	0
SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color, with Integral LED Clearance/Marker Lights	16/1	17
AERODYNAMIC PACKAGE Includes Roof Air Deflector, Cab Side Extenders; for Day Cab, Paint and Install at the Plant	102/66	168
ACCESS, CAB AND FRAME Aluminum, Driver & Passenger Sides, Two Steps per Door; Left Side Frame Access Step, Includes One Flush Mounted Deck Plate and Black Grab Handle, for use with Day Cab or Sleeper Cab	40/21	61
WHEELS, FRONT {Accuride 43644} DISC; 22.5x8.25 Rims, Standard Polish Aluminum, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/0	0
WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs	0/216	216
WHEEL COVER, REAR Aerodynamic, 22.5", Black	0/0	0
PAINT FENDER EXTENSIONS Single Color; Same as Number Two Cab Schematic Color	0/0	0
(8) TIRE, REAR 11R22.5 Load Range G G572 1AD (GOODYEAR), 496 rev/mile, 75 MPH, Drive	0/64	64
(2) TIRE, FRONT 11R22.5 Load Range H ENDURANCE RSA (GOODYEAR), 496 rev/mile, 75 MPH, All-Position	14/0	14
FIFTH WHEEL LOCATION On Rear Axle Centerline	0/0	0
Services Section:		
WARRANTY Standard for LT/RH Series, Effective with Vehicles Built January 2, 2016 or Later, CTS-2010A	0/0	0

<u>Description</u>	<u>F/R Wt</u>	<u>Tot Wt</u>
	(lbs)	(lbs)
Total Component Weight:	8587/7789	16376
	(lbs)	(lbs)
	(lbs)	(lbs)

The weight calculations included in this proposal are an estimate of future vehicle weight. The actual weight as manufactured may be different from the estimated weight. Navistar, Inc. shall not be liable for any consequences resulting from any differences between the estimated weight of a vehicle and the actual weight.