



- Palfinger C70L77 hydraulic loader with dual standup controls, pilot operated joysticks, load holding valves and 6 ton rotator
- 23" debris grapple attachment
- PTO/pump with steel hydraulic reservoir
- 24" steel pass through operator platform mounted behind cab with step access from street and curb side
- 18' (24 cu. yd.) DOMEX 100W front tapered dump body with underbody mounted hoist
- DOT LED standard lighting package
- Front grill/bumper, crane stabilizer and rear body mounted strobe lights
- 18"X18"X36" black steel toolbox, underbody frame mounted
- Mudflaps
- ICC bumper
- All steel fabrication and body painted gloss black enamel
- Package compatible with non-CDL chassis



EPSILON REFUSE LOADERS

Customized solutions, to grow your business

6

LIFETIME EXCELLENCE

YOUR SOLUTIONS


The market offers various choices when it comes to selecting your equipment provider and we know it's not an easy decision. Your challenges every day in the field matter, and that's why we put so much passion into our loaders. Trust our expertise and rely on our wide product portfolio to configure the right loader - customized for your needs across timber, refuse, rail, scrap and off-road applications.

By investing in EPSILON, you are selecting well established machines, a trusted global brand, and a reliable partner. With EPSILON you have a partner who understands your application and creates solutions to improve your comfort and productivity.

A-Line: Traditional A-Frame design with up to 32' of reach available Z-Line: The compact loader folds away when stowed increasing bed space, saving operational time when dumping, and keeps the loader safe from debris during transport L-Line: An H-frame design with numerous control options, long reaches, and out/down stabilizers



segment.





Our main guiding principal is to make you more successful with the help of our advanced machines, market experience, technical skills and committed employees.


TO LOCATE A DISTRIBUTOR NEAR YOU VISIT WWW.PALFINGER.COM



THE BULK WASTE SOLUTION

M100L/C70L

Both the M100 and C70 feature a long main boom designed for maximum protection with a top mounted outer boom cylinder. The main lift cylinder is protected by a heavy-duty steel guard, and the EPSCOPE/ EPSLINK provide unmatched protection with internal routed hoses and components. The double rack slewing system provides an industry leading torque rating and features like the linkage system provide the best weight to lift ratio in its class.





- Ergonomic arm rests w/fold down joysticks
- Safety frame and cover
- Large seat area
- Additional electric switches

CUSTOMIZED SOLUTIONS TO MEET EVERY APPLICATION

- Non CDL packages available
- Body sizes ranging from 24 to 54 cubic yard capacity
- DOMEX or HARDOX construction
- Double acting, underbody scissor hoist
- Dump body control valve mounted on driver's side
- Pneumatic dump body controls located on operator station

CONFIGURATIONS & FEATURES





RADIO REMOTE CONTROL Provides the operator freedom to control the loader from a distance and greater control of the loading area

FLEXIBILITY Stabilizers range from 0 to 180 degree tilt



2,072	25	3,726	13,276	425	2,900 - 2x13
 3,280	23,6	4,010	17,701	425	3,118 - 1x21

- Heavy duty behind cab operator pass through platform
- RPM +/- controls at both operator stations
- High visibility strobe lights mounted on stabilizers with in cab switch
- 42" Refuse grapple with high wear resistant, easy replaceable blades
- Grapple/Rotator feature Protect Connect mounting system
- User friendly equipment data system



DOUBLE RACK SLEWING SYSTEM

Sealed in an oil bath. Two solid round racks with sectionalized pistons and end of stroke suppression provide the ultimate in slewing power



Epsilon Refuse Loaders. 04/18

PALFINGER INC.

7942 Dorchester Rd. Niagara Falls, ON L2G 7W7 Canada T + 1 800 567 1554 info@palfingerna.com

Products shown in the leaflet are partially equipped with optional features and do not always correspond to the standard version. Country-specific regulations must be observed. Dimensions may vary. Subject to product changes and improvements.

PALFINGER.COM