

## ProMaster Model Year 2023 3500 Chassis

\*\*Meets all KKK, CARB and Commission on Accreditation of Ambulance Services (CAAS GVS), including all change notices.

## 1. ENGINE

- a. 3.6-Liter V6 24-Valve VVT Engine Gas Engine
- b. Upfit Interface Connector and Upgraded Components for Ambulance Build
- c. Heavy-Duty 220 amp. Alternator
- d. 3 Maintenance Free Heavy-Duty batteries,
- e. Manufacturer's heavy-duty engine cooling.

#### 2. TRANSMISSION

- a. Transmission: 9-Speed Automatic 948TE Transmission with overdrive
- b. Manufacturer's Heavy-Duty Transmission Cooling.

# 3. AXLES

948TE Front Drive Transaxle, Heavy Duty Rear Axle
 Manufacturer's Recommended Drive Axle Ratio & Set-up for Ambulance Duty & Weight

### 4. STANDARD EQUIPMENT

## **FUNCTIONAL/SAFETY FEATURES**

- a. Supplemental Front Seat–Mounted Side Air Bags
- b. Supplemental Side-Curtain Front Air Bags
- c. Drowsy Driver Detection
- d. Traffic Sign Recognition
- e. Speed Control
- f. Electronic Park Brake
- g. Full-Speed Forward-Collision Warning Plus
- h. Pedestrian/Cyclist Emergency Braking
- i. Multi-Collision Braking
- j. Electronic Stability Control
- k. Crosswind Assist
- I. Electronic Roll Mitigation
- m. Trailer Sway Damping
- n. All-Speed Traction Control
- o. ParkView® Rear Back–Up Camera
- p. Tire Pressure Monitoring Display
- q. Push-Button Start
- r. Remote Keyless-Entry
- s. Speed-Sensitive Power-Locks
- t. Ram Connect (Connected Services) with Trial
- u. Global Telematics Box Module (TBM)
- v. 24–Gallon Fuel Tank with ~350-Mile Range
- w. 220-Amp Alternator
- x. 95–Amp Battery

## 5. INTERIOR FEATURES

- a. 4–Way Manual Adjustable Driver Seat
- b. 4–Way Manual Adjustable Front Passenger Seat
- c. Cluster 3.5-Inch TFT Black and White Display

# FR CONVERSIONS

# FR Conversions Elite Type II Ambulance

- d. Uconnect 5 with 7-Inch Touch Screen Display
- e. SiriusXM® with 6-Month Radio Sub Call 800-643-2112
- f. Bluetooth® Handsfree Phone and Audio
- g. Google Android Auto™
- h. Apple CarPlay®
- i. 4 Speakers
- j. Steering-Wheel-Mounted Audio Controls
- k. Media Input Hub
- I. Remote USB Port Charge-Only
- m. Instrument Panel 12-Volt Power Outlet
- n. Upfit Interface Connector
- o. Air Conditioning
- p. Power Windows with Front One–Touch–Down Feature
- q. Telescoping Steering Column

## 6. EXTERIOR FEATURES

- a. BSW All-Season Radial Tires 16-inch t LT225/75R16E
- b. Tire sealant and Compressor
- c. 16-Inch x 6.0-Inch Steel Wheels
- d. 260-Degree Opening Rear Hinged Doors
- e. Heated Power Folding Mirrors

### 7. CHASSIS, FRAME, CAB

- a. 9350 Lbs. GVWR
- b. 159" wheelbase
- c. Front Clearance Lamps
- d. Rear Clearance Lamps
- e. Halogen Headlamps
- f. Front Fog Lamps
- g. Daytime Running Headlamps
- h. Power Folding Heated-Mirrors
- i. Under Seat Storage Tray
- j. Locking Glove Box
- k. Chrome Grille
- I. Passenger Sliding Door with Fixed Tinted Window
- m. 260-Degree Rear Hinged Doors with Deep Tinted Glass

## 8. MODULAR BODY CONSTRUCTION

- a. The Ambulance Body and Patient Compartment Dimensions 76" H x 73.4" W x 148" L
- \*\*Exceeding size requirements of this specification and those of paragraph 3.10.1 and the cot fastener system to meet or exceed requirements of paragraph 3.11.6 of the current KKK-A-1822F and Commission on Accreditation of Ambulance Services (CAAS GVS), including all change notices.

Crash Tested as an Ambulance, Pull Tested, Balanced

5yr 100,000-mile warranty

Exterior Color: Bright White Clear Coat Exterior Paint Interior Color: Black Interior Color



### Flooring

- 3/4" Marine Grade Plywood Flooring-Tongue and grooved joints with Bondo and sanded finish 100215-01-XXXXX
- Altro Safety Vinyl-Floor, Zodiac Smooth, Capricorn FL-00014-06 O Meets R12 or R11 levels of slip resistance
- 2 (ea.) Entry way floor receiver trim in Hard anodized aluminum, Black with "FR Ambulance" stencil 100279-70-XXXXX O
   Maximizes and Preserves Door Seal Integrity <u>against tailpipe emissions</u>
- Threshold Etched No-Slip, Fire House Grade Aluminum Diamond Plate Grade & Thickness O No-Trip Recessed -mounted flush into flooring
- Diamond Plate Baseboard Protection

#### **HVAC Features**

Webasto Vancouver FM RC AC System - 33,000 BTU rear HVAC System with OEM tie-in AC-AMB-00001-01 
 Dual Control: Cab & Compartment O No-Idle feature maintains temperature for 20-30 minutes in severe climates

## **Standard Seating and Retention systems**

#### **Operator Seat Rear Facing**

- WM1814 Seamless Attendant Seat 6 Back with 3 Point Black Belt, 1009 Color Gun Metal Grey ST-AMB-00001-01 o Retractable Harness
- WM1934 Standard 8-way Swivel Base with 45 Stops, 9.568 Inches Tall ST-AMB-00002-01

#### Squad Side

The vehicle come standard with a single flip-up swivel seat and adjacent workstation (OP-A-00103-02) EVS First Safe Line Advanced Flip Bottom/Fold Down Seat) \*\*Squad bench options and additional seating options availible.

#### Standard Electrical & Lighting

- SWITCH Emergency Cutoff Master red cover / red Backlit LED, mounted to front command console EL-00800-06
- DS4010DR AMBULANCE VOLTMETER Double Voltmeter, Range F•10 60V DC, RED Backlit LED, Monitors OEM battery and Aftermarket system, mounted on front command console EL-00800-17
- A-PRC702-AX-15 PROGRAMMABLE RELAY POWER CENTER (PRPC) FOR RAM PROMASTER- 

   Main computer controller for Ambulance subsystems VC-00033-01
- CHROME/BLACK BASE COWL VENT cover VT-2758-A03 VC-00156
- Exhaust Attwood Blower motor EL-00802-05
- Shore-Power Connection KUSSMAUL WP Auto Eject 120 Volts AC, 20 Amps Color WHITE EL-00802-03 Auto Close Cover
- Xantrex Freedom 806-1840 HF 1800 Inverter/Charger 2000-Watt Inverter Charger EL-00802-02 
   o with in-line battery conditioner for front of the vehicle
- Two MARINE/RV DUAL-PURPOSE BATTERY, Aux BATTERY, INTERSTATE 24M-DP AP-00063 O Deep Cycle Quick Charge
  - with in-line battery conditioner for front of the vehicle O
     Smart System w/ both front and back batteries working in tandem
- In Cabinet WHITE LED LITE STRIP FLEXIBLE W/SINGLE TERM
   TQ E41-W03V-1, mounted on 45 degree bracket for maximum illumination EL-00521
- 8" EV White Red Interior Light Chrome Trim 3 stage (high, Low, RED) TQ E08-WCR0-1 EL-00518
- 5 (ea) 8" EV White Light Chrome Trim 2 stage (high low) TQ E08-WC10-1 EL-00519



## Lights & Sirens

- FENIEX TRITON 100W SPEAKER, FEN-S-2009- Front mounted EL-LT-00001-02
- FENIEX 4200 CONTROL SWITCH BOX, FEN-C-4200-DL EL-LT-00001-04
- FENIEX STORM PRO 200W SIREN, FEN-C-4015 EL-LT-00001-06
- FENIEX FUSION 60 IN EXTERIOR LIGHT BAR SINGLE COLOR, RED, with White Alley lights FEN-FN-6016 EL-LT-00001-03
- 4 (ea.) Thin Light head, High output, Red LED above fender flares I600-R EL-LT-00002-04
- 4 (ea) Thin Light head, High output, Red LED in Front Grill I600-R EL-LT-00002-04
- 4 (ea) Thin Light head, High output, Red LED on rear doors I600-R EL-LT-00002-04
- 6 (ea) High output RED LED Light 1" x 6" on upper body at each corner EL-LT-00002-08
- 6 (ea) High output Clear LED Light 1" x 6" on upper body at each corner at oblique angle as scene lights EL-LT-00002-09
- 2 (ea) Hellfire pandora 12 LED high output RED- mounted in rear view mirrors facing forward EL-LT-00002-03
- 2 (ea) Hellfire pandora 12 LED high output AMBER- mounted in rear center over rear doors EL-LT-00002-09
- 2 (ea) LED Indicator lights in main command console for rear doors open and sliding doors open indicators EL-00801-01
- Rear controller switch bank with back lit LED, Laser etched indicators Including (1) StreetSide 3 position switch for interior lights (High, Low Off) (1) Curbside 3 position switch for interior lights (High, Low Off)
- (1) Night light switch (1) Cabinet LED light switch (1) Inverter On switch (1) Vent switch (1) Suction switch with white cover (1) Oxygen On switch with green backlit LED indicator EL-00800-07

### Outlets

- Leviton Decora 20 Amp 125-Volt Combination Duplex Outlet w/ dual USB Outlet, White, Mounted in Action area EL-00805-02
- Leviton Decora 15 Amp Duplex Outlet, 15 Amp Duplex Outlet w/ dual USB, White, Mounted In action Area EL-00805-01
- Leviton Decora 15 Amp Duplex Outlet, 15 Amp Duplex Outlet, White, Mounted On front bulkhead cabinet EL-00805-01
- Leviton Decora 15 Amp Duplex Outlet, 15 Amp Duplex Outlet, White, mounted above squad bench EL-00805-01
- Dual USB outlet Front Bulkhead

#### Standard Cabinetry

- 0.7-cubic-foot security safe with electronic lock and 2 emergency override keys SQ-05000-02
- Front cabinet set- O All aluminum 18Ga construction
  - O Integrated Main O2 holder door with quick release and Frosted Lexan cover 100227-03-XXXXX
  - backboard storage behind the bulkhead, splint storage, and an additional scoop stretcher storage
     compartment. O
     (1) ALS cabinet Poly Carbonate Doors w/ Slam Locks O
     1 internal adjustable shelf and O
     1 fixed upper shelf / 2<sup>nd</sup> workstation O
     Padded safety corners and edges
- Main Cabinet frame assembly Street Side. All Aluminum Construction. 100227-01-XXXXX O
   Double insulated
  - (3) large lower cabinets,
  - (4) small upper cabinets,
  - (1) large vertical cabinet,
  - (1) ALS slide out monitor mount cabinet
- 10 (ea) Framed door covers for main cabinet assembly with easy slide and latch. O CASS and NFPA 1917 Compliant for equipment retention DR-04007 O Poly Carbonate Impact Doors Rated to 80lbs per Square Inch
- ullet Street Side Rear Facing Accommodation for Medical Air or Secondary O2 System ullet
  - O Also suitable for fire hooks, dog bones poles and etc.
- Front Console with integrated clipboard storage and 2 stainless cup holders. O
- All aluminum construction with Black Smoked Hard Anodized Aluminum Facia 100227-07-XXXXX
  - O Suitable for "Ram Desk" Mounts & Supplementary Electrical
- 7" x 36 3/116 Above Command console gloves storage covered with magnetic hinged Lexan cover in smoked Lexan PN-00500
- In-door, Rear, Street Side sharps storage pocket in hard Anodized aluminum 100272-27-XXXXX



- In-door, Rear, Curb Side Gloves storage pocket in hard Anodized aluminum 100272-26-XXXXX
- Rear Facing Stair Chair Cubby
- Main command center Top in Corian Gray Lite Matte 36.5 x 14.5 1/2 Inch Thick PN-00501
- Easy Access Control Panel

### **Running Boards:**

- RUNNING BOARD PASSENGER SIDE, Firehouse Diamond tread, with rounded edges and Sure grip emboss on tread, 8" tread depth 100279-22-XXXXX
- RUNNING BOARD Drivers SIDE, Firehouse Diamond tread, with rounded edges and Sure grip emboss on tread, 8" tread depth 100279-26-XXXXX

#### Rear Bumper

Heavy Duty Additional, Full Length Flip-Up Rear, Firehouse Diamond Tread Bumper 100279-28-XXXXX o with rounded edges and o No-Slip Sure Grip emboss tread, o 8" tread depth o 14" step

### O2 and Suction Equipment:

 QR-SOFD - Slide-out, Flip-down Slide Assembly. Medical Oxygen, QUIC-RELEASE. EMS, G to T Cylinder Storage, Gas Cylinder Storage SQ-00221-01

<50lbs

Lift


- O Single Hand Lock / Unlock Actuation
- QR-MV Multiversal Bracket. Medical Oxygen, QUIC- RELEASE. EMS, G to T Cylinder Storage, Gas Cylinder Storage. Ambulance SQ00221-02
- Sure-lok Double Oxygen Bottle Holder SL-5401 SQ-00220-02

### Dual / Redundant O2 and Suction

- Z-TH0303MO Triple Rail Unit, ○
   (2) Oxygen (1) Vacuum w/ 1/4" Barb- In main Action Area SQ-00400-02
- Z-TH02MVO Double Rail Unit, O
   (1) Oxygen (1) Vacuum w/ 1/4" Barb- Above squad bench SQ-00400-03
- Z-TH0105FA High Pressure Gauge Front Assembly For Oxygen 0-4000PSI SQ-00400-01
- P-REG-L250-OXY Regulator AM 250 series Oxygen SQ-00400-04
- SB90120-RT SSCOR suction Pump Onboard SQ-00401-03
- 22002- Canister Holder (SSCOR board) mounted in action area SQ-00401-02
- Main O2 System electrical disconnect with 12-volt 200 AMP solenoid EL-00025 O Solenoid Controlled Regulator shuts O2 automatically when not in use O Digital O2 gauge with low Alarm O Manual Bypass

## Misc. Equipment and Mounts

- 1 (ea) 5LB. ABC FIRE EXTINGUISHER WITH VEHICLE BRACKET, RECHARGEABLE- 1 mounted in rear SQ-00302
- Front Bulkhead with sliding glass window and lock
- Sliding Glass Door Ratchet Lock with Chrome Finish, Keyed DR-07000
- 2 (ea) IV2008-1 Recessed, Ceiling Mount Dual IV Hanger with Velcro, mounted above cot area SQ-05000-01
- GRABRAIL-CEILING 100297-02-XXXXX
- GRABRAIL-ENTRY, SIDE, AMBULANCE 100297-05-XXXXX





- GRABRAIL-ENTRY, REAR 100297-08-XXXXX
- Tailpipe turned StreetSide



Redacted 3500 Drawlings.pdf