

RANGER 1000 EPS Sagebrush Green

Polaris Model #R23TAE99A1



Key Specifications

61	62.5"	12"
HP	WIDTH	GROUND CLEARANCE

ENGINE & DRIVETRAIN

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder SOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	61 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

DIMENSIONS

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,000 lbs (453.6 kg); California 600 lb (272.2 kg)
Dry Weight	1,485 lb (673.6 kg)
Fuel Capacity	11.35 gal (43 L)
Ground Clearance	12 in (30.5 cm)
GVW	3,600 lb (1,632.9 kg)
Hitch Towing Rating	2,500 lb (1,134 kg)
Hitch Type	Standard 2 in (5 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 76 in. (305 x 158 x 193 cm)
Payload Capacity	1,500 lb (680.4 kg); California 1,100 lb (498.9 kg)
Person Capacity	3
Wheelbase	81 in (206 cm)

BRAKES

Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
Parking Brake	Park In-Transmission

ADDITIONAL SPECIFICATIONS

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride®
Color / Graphics	Sagebrush Green
Electronic Power Steering	Standard
Instrumentation	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
Lighting	Halogen Headlamps, 55W Low Beam, 60W High Beam, Dual LED Taillamps
Other Standard Features	Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port
RIDE COMMAND+	Available
Tilt Steering	Standard

TIRES / WHEELS

Front Tires	25 x 10-12; Carlisle 489
Rear Tires	25 x 11-12; Carlisle 489
Tire Ply Rating	4 Ply Rated
Wheels	Stamped Steel

SUSPENSION

Front Suspension	Dual A-Arm 10 in. (25.4 cm) Travel
Rear Suspension	Dual A-Arm, IRS 10 in. (25.4 cm) Travel
Turning Radius	13.3 ft (406.4 cm)