

First Choice Fire & Safety Inc.

One (1) == Custom Cab Side Mount Pumper - 10.000 12/04/06 ==

Y__N__

One (1) Instructions To Bidders - Pumper Fire Apparatus
00-A0-1000

Y__N__

INSTRUCTIONS TO BIDDERS

The purpose of these instructions and specifications are to describe the requirements, construction, and delivery of a Fire Fighting Apparatus as outlined herein for the _____ here after referred to as the "Purchaser".

Bid envelopes shall be plainly labeled _____.

Bids will only be considered from companies which have an established reputation in the field of fire apparatus construction and have been in business for a minimum of twenty-five (25) years.

Each bidder shall furnish satisfactory evidence of his ability to construct the apparatus specified, and shall state the location of the factory where the apparatus is to be built. The bidder shall also show that they are in a position to render prompt service and furnish replacement parts for said apparatus.

It is the bidder's responsibility to see that their proposals arrive on time. Late proposals, facsimiles, telegrams, or telephone bids will not be considered.

The purchaser reserves the right to accept or reject any or all bids on such basis as the purchaser deems to be in its best interest.

All bid prices shall remain effective for 45 calendar days from the bid opening date.

The apparatus is to be of current year of manufacture and is to be new.

The bid price shall not include any local, state, or federal taxes.

DELIVERY

Each bidder shall clearly state the delivery date of the vehicle in calendar days. This shall be after receipt of the signed contract.

INTENT OF SPECIFICATIONS

First Choice Fire & Safety Inc.

It is the intent of these specifications to cover the furnishing and delivery to the purchaser a complete unit equipped as herein specified, with a view of obtaining the best results and the most acceptable apparatus for the purchaser.

These specifications cover only the general requirements as to the type of construction and test to which the apparatus must conform. Minor details of construction and materials where not otherwise specified are left to the discretion of the contractor, who shall be solely responsible for the design and construction of all features.

All equipment and components shall comply with the National Fire Protection Association Pamphlet 1901 (2016 Edition), Standard for Automotive Fire Apparatus, for Pumper Fire Apparatus Equipped with a Fire Pump. In addition, the apparatus shall also comply with all federal, state, ICC, and DOT regulations, standards, and laws relating to commercial vehicles as well as to the fire apparatus.

Loose equipment shall be provided only as stated in the following pages.

LIABILITY

The bidder, if his/her bid is accepted, shall defend any and all suits and assume liability for the use of any patented process, device or article forming a part of the apparatus or any appliance furnished under the contract to the extent allowable under the law.

COMMERCIAL GENERAL LIABILITY INSURANCE

Each bidder shall supply proof of product liability and facility insurance equal to or exceeding \$5,000,000. This shall be provided as part of the proposal.

GENERAL REQUIREMENTS

This specification package, along with any herein listed exceptions, shall be submitted as a part of the bidder's entire bid proposal. Do not detach or omit these sheets.

Proposal specifications must be on the manufacturer's own standard forms. In no case shall a bidder photocopy these specifications as his proposal specifications.
"NO EXCEPTIONS"

First Choice Fire & Safety Inc.

Each bidder is required to provide in his bid to the purchaser a complete and accurate description of his own apparatus in the exact sequence of these specifications.

EXCEPTIONS, VARIATIONS, OR CLARIFICATIONS

These specifications are based upon performance criteria which have been developed by the purchaser as a result of extensive research and careful analysis of the data. Subsequently, these specifications reflect the only type of fire apparatus that is acceptable at this time. Therefore, major exceptions to the specifications will not be accepted.

All bidders shall place a "Y" for yes or a "N": for no next to each and every paragraph in the column provided on the right-hand edge of the paper, indicating compliance or noncompliance with that paragraph of the specifications.

A number shall be inserted next to the paragraph which relates to an explanation on page(s) entitled "Exceptions" that the bidder shall include with their proposal specifications.

Any exception shall be clearly defined with details as to the proposed alternative, referencing manufacturer and model where appropriate. Descriptive literature shall be provided to help evaluate the exception. A general exception cannot be taken for any paragraph. A full word for word Written Comparison shall be included within the bid for any exception listed. Each exception shall be considered by the degree of impact and total effect on the bid. Proposals taking total exception to the specifications shall not be considered by the purchaser.
"NO EXCEPTIONS"

The purchaser shall determine which (if any) exceptions are acceptable and this determination shall be final.

The purchaser shall assume that failure to cite an exception indicates full compliance with the specifications. Should the equipment not comply with all requirements of this document, the equipment shall be rejected at the final inspection. All equipment shall be inspected for material, workmanship, and compliance with the specifications prior to acceptance. All equipment found to be in noncompliance shall be identified and the purchaser reserves the right to accept or reject the specific items. The noncompliant rejected equipment shall be replaced or reworked to meet the requirements of this document at no additional cost to the purchaser.

The bidder shall have thirty (30) days after delivery to fulfill that part(s) of the specifications which does not comply to the original outlined specifications. Bidder shall incur all expenses of pickup and redelivery of the apparatus.

First Choice Fire & Safety Inc.

CONSTRUCTION

The materials specified are considered absolute minimum. Exceptions will not be accepted or permitted since all raw materials of the specified type are available to all manufacturers. Since all manufacturers have the ability to shear, break, and weld as these specifications require, all basic design requirements shall be complied with.

The apparatus shall be constructed with due consideration to the nature and distribution of the load to be sustained and to the general character of service to which the apparatus is to be subjected when placed in service. All parts of the apparatus shall be of adequate strength to withstand the general service under full load. The apparatus shall be so designed that the various parts are readily accessible for lubrication, inspection, adjustment, and service.

One (1)
00-BP-0200

Bid Bond

Y__N__

BID BOND

A bid bond will be submitted with the bidder's proposal. The bond will be for an amount equal to 10% of the proposed bid price. Failure to provide an acceptable, valid bid bond with the proposal will result in the immediate rejection of the bidder's proposal.

One (1)
00-E1-0200

Apparatus Documentation NFPA 4.20

Y__N__

DATA REQUIRED OF THE CONTRACTOR - NFPA 4.20

NFPA 4.20.1 Fire Apparatus Documentation

The contractor will supply, at the time of delivery, at least one (1) copy of the following documents:

- (1) The manufacturer's record of apparatus construction details, including the following information:
 - a. Owner's name and address
 - b. Apparatus manufacturer, model and serial number
 - c. Chassis make, model, and serial number
 - d. GAWR of front and rear axles and GVWR
 - e. Front tire size and total rated capacity in pounds
 - f. Rear tire size and total rated capacity in pounds
 - g. Chassis weight distribution in pounds with water and manufacturer-mounted equipment front and rear
 - h. Engine make, model, serial number, rated horsepower, and related speed and governed speed; and if so equipped, engine transmission PTO(s) make, model, and gear ratio

First Choice Fire & Safety Inc.

- i. Type of fuel and fuel tank capacity
 - j. Electrical system voltage and alternator output in amps
 - k. Battery make, model, and capacity in cold crank amps (CCA)
 - l. Transmission make, model, and serial number; and if so equipped, chassis transmission PTO(s) make, model, and gear ratio.
 - m. Ratios of all driving axles.
 - n. Maximum governed road speed
 - o. Pump make, model, rated capacity in gallons per minute (liters per minute where applicable) and serial number
 - p. Pump transmission make, model, serial number, and gear ratio
 - q. Auxiliary pump make, model, rated capacity in gallons per minute, (liters per minute where applicable) and serial number
 - r. Water tank certified capacity in gallons or liters
 - s. Aerial device type, rated vertical height in feet (meters), rated horizontal reach in feet (meters), and rated capacity in pounds (kilograms)
 - t. Paint manufacturer and paint number(s)
 - u. Company name and signature of responsible company representative
 - v. Weight documents from a certified scale showing actual loading on the front axle, rear axles(s), and over all fire apparatus (with the water tank full but without personnel, equipment, and hose)
-
- (2) If the apparatus is a mobile foam fire apparatus, the certification of foam tank capacity
 - (3) Certification of compliance of the optical warning system
 - (4) Siren manufacturer's certification of the siren
 - (5) Written load analysis and results of the electrical system performance tests
 - (6) Certification of slip resistance of all stepping, standing and walking surfaces
 - (7) If the apparatus has a fire pump, the pump manufacturer's certification of suction capability
 - (8) If the apparatus has a fire pump, and special conditions are specified by the purchaser, the pump manufacturer's certification of suction capacity under the special conditions
 - (9) If the apparatus has a fire pump, a copy of the apparatus manufacturer's approval for stationary pumping applications
 - (10) If the apparatus has a fire pump, the engine manufacturer's certified brake horsepower curve for the engine furnished, showing the maximum governed speed
 - (11) If the apparatus has a fire pump, the pump manufacturer's certification of the hydrostatic test (12) If the apparatus has a fire pump, the certification of inspection and test for fire pump.
 - (13) If the apparatus is equipped with an auxiliary pump, the apparatus manufacturer's certification of the hydrostatic test

First Choice Fire & Safety Inc.

- (14) When the apparatus is equipped with a water tank, the certification of water tank capacity
- (15) If the apparatus has an aerial device, the certification of inspection and test for the aerial device
- (16) If the apparatus has an aerial device, all the technical information required for inspection to comply with NFPA 1911
- (17) If the apparatus has a foam proportioning system, the foam proportioning system manufacturer's certification of accuracy and the final installer's certification the foam proportioning system meets this standard
- (18) If the apparatus has a CAFS, the documentation of the manufacturer's pre-delivery tests
- (19) If the apparatus has a line voltage power source, the certification of the test for the power source
- (20) If the apparatus is equipped with an air system, air tank certificates, the SCBA fill station certification, and the results of the testing of the air system installation
- (21) Any other required manufacturer test data or reports
Operation & Service Documentation - NFPA 2016

One (1)
00-E1-0300

Y___N___

OPERATION AND SERVICE DOCUMENTS - NFPA 4.20.2

NFPA 4.20.2.1 - The contractor shall deliver with the fire apparatus complete operation and service documentation covering the completed apparatus as delivered and accepted.

The documentation shall address at least the inspection, service and operations of the fire apparatus and all major components thereof.

The contractor shall also deliver with the fire apparatus the following documentation for the entire apparatus and each major operating system or major component of the apparatus:

- (1) Manufacturer's name and address
- (2) Country of manufacture
- (3) Source for service and technical information
- (4) Parts replacement information
- (5) Descriptions, specifications, and ratings of the chassis, pump (if applicable) and the aerial device (if applicable)
- (6) Wiring diagrams for low-voltage and line voltage systems to include the following information:
 - (a) Pictorial representations of circuit logic for all electrical components and wiring
 - (b) Circuit identification
 - (c) Connector pin identification
 - (d) Zone location of electrical components

First Choice Fire & Safety Inc.

- (e) Safety interlocks
- (f) Alternator-battery power distribution circuits
- (g) Input/output assignment sheets or equivalent circuit logic implemented in multiplexing systems
- (7) Lubrication charts
- (8) Operating instructions for chassis, any major components such as pump or aerial device, and any auxiliary systems
- (9) Precautions related to multiple configurations of aerial devices, if applicable
- (10) Instructions regarding the frequency and procedure for recommended maintenance
- (11) Overall apparatus operating instructions
- (12) Safety considerations
- (13) Limitations of use
- (14) Inspection procedures
- (15) Recommend service procedures
- (16) Troubleshooting guide
- (17) Apparatus body, chassis, and other component manufacturers' warranties
- (18) Special data required by this standard
- (19) A material safety data sheet (MSDS) for any fluid that is specified for use on the apparatus
- (20) One (1) copy of the latest addition of FAMA's Fire Apparatus Safety Guide

NFPA 4.20.2.4 - The contractor will deliver with the apparatus all manufacturers' operations and service documents supplied with components and equipment that are installed or supplied by the contractor.

Highway Performance NFPA 2016

One (1)
00-E1-0400

Y___N___

HIGHWAY PERFORMANCE NFPA 4.15

NFPA 4.15.1 - The apparatus, when loaded to its estimated in-service weight, shall be capable of the following performance while on dry, paved roads that are in good condition:

1: Accelerating from 0 to 35 mph (55 km/hr) within 25 seconds on a 0 percent grade;

2: Attaining a speed of 50 mph (80 km/hr) on a 0 percent grade;

3: Maintaining a speed of at least 20 mph (32 km/hr) on any grade up to and including 6 percent.

NFPA 4.15.2 - The maximum top speed of fire apparatus with a GVWR over 26,000 lb (11,800 kg) shall not exceed either 68 mph (109 km/hr) or the

First Choice Fire & Safety Inc.

manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

NFPA 4.15.3 - If the combined water tank and foam agent tank capacities on the fire apparatus exceed 1250 gallons, or the GVWR of the vehicle is over 50,000 lb, the maximum top speed of the apparatus shall not exceed either 60 mph or the manufacturer's maximum fire service speed rating for the tires installed on the apparatus, whichever is lower.

One (1)
00-E1-0800

NFPA Tag Requirements

Y__N__

NFPA TAG REQUIREMENTS

A label that states the number of personnel the vehicle is designed to carry shall be located in an area visible to the driver.

A sign that reads "**OCCUPANTS MUST BE SEATED AND BELTED WHEN APPARATUS IS IN MOTION**" shall be provided and located in the chassis cab in an area that is visible from each seating position.

An accident prevention sign that states "**OVERALL HEIGHT OF APPARATUS __ INCHES**"

One "Final Stage Label" shall be attached to the drivers side door jamb. The label shall certify that the complete vehicle conforms to the federal motor vehicle safety standards, which have been previously fully certified by the incomplete vehicle manufacture or by the intermediate vehicle manufacture and have not been affected by the final stage manufacture.

An accident prevention sign that states "**DANGER: DO NOT RIDE ON REAR STEP WHILE VEHICLE IS IN MOTION - DEATH OR SERIOUS INJURY MAY RESULT**" shall be provided and installed at the rear of the apparatus.

A label stating "**DO NOT WEAR HELMET WHILE SEATED**" shall be visible from each seating location.

One (1)
00-E4-9900

Warranty (1) Year

Y__N__

WARRANTY

Each bidder shall include a copy of their warranty with the bid proposal. The following minimum warranties shall be provided, **NO EXCEPTION.**

First Choice Fire & Safety Inc.

The finest materials and utmost care go into the fabrication of each new apparatus. By using normal care, without abuse, this equipment will give you lasting service.

Each new motorized Fire and Rescue Apparatus is to be free from defects in material and workmanship, under normal use and service, for a period of one year. Our obligation under this warranty is limited to replacing or repairing, as the manufacturer may elect, any part or parts thereof, which, upon examination, would be determined to be defective. Such defective part or parts will be replaced free of charge, and without charge for installation, to the original purchaser.

All warranty work related to the apparatus (not including vehicle chassis) is to be performed at the manufacturer's factory or at an authorized service center.

This does not obligate the manufacturer to bear the costs of transportation charges and related expenses incurred in the replacement of parts.

BODY WARRANTY

The manufacturer shall warrant the entire stainless steel body against rust and/or full corrosion perforation and metal fatigue for a period of thirty (30) years from the date of delivery to the original purchaser, provided the apparatus is used in a normal and reasonable manner.

The term "body" shall be inclusive of the following:

- Hose bed side walls
- Compartments and compartment supports
- Compartment doors *except roll-up doors, when specified*
- Complete subframe including pump house framing

WATER TANK WARRANTY

The contracted tank manufacturer shall warrant that the tank provided shall be of first-class workmanship and that, under normal conditions, shall show no defects due to faulty design, workmanship, or material for the Lifetime of the vehicle to the original owner.

PUMP WARRANTY

The contracted pump manufacturer shall warrant that the pump provided shall be of first-class workmanship and that, under normal conditions, shall show no

First Choice Fire & Safety Inc.

defects due to faulty design, workmanship, or materials for a period of five (5) years.

PUMP PLUMBING WARRANTY

The galvanized or stainless steel plumbing components, as specified, and ancillary brass fittings used in the construction of the water/foam plumbing system shall be warranted for a period of ten (10) years or 100,000 miles. This covers structural failures caused by defective design or workmanship, or perforation caused by corrosion, provided the apparatus is used in a normal and reasonable manner. This warranty is extended only to the original purchaser for a period of ten years from the date of delivery.

12 VOLT ELECTRICAL WARRANTY

The 12 volt electrical system and ancillary components used in the construction of the apparatus shall be warranted for a period of five (5) years. This covers failures caused by defective design or workmanship, provided the apparatus is used in a normal and reasonable manner. This warranty is extended only to the original purchaser, for a period of five (5) years from the date of delivery.

Items specifically covered are:

- Electrical harnesses and harness installation
- Switches, circuit breakers, and relays
- LED Lighting: FMVSS required and warning lights
- Electrical connectors and connections, against corrosion or deterioration

Items excluded, as they are covered by specific warranties supplied by the manufacturer of the components:

- Chassis electrical systems and components installed by the chassis manufacturer.
- Batteries, battery chargers, two-way radio equipment, and similar equipment.
- Periodic cleaning and tightening of battery terminal connections.
- Accident, negligence, or unauthorized alteration of original equipment.

PAINT WARRANTY

The paint on the unit will be provided with a ten (10) year paint finish guarantee which will cover the finish for the following items:

- Peeling or delamination of the top coat and/or other layers of paint.
- Cracking or checking.
- Loss of gloss caused by defective finishes which are covered by this guarantee.

First Choice Fire & Safety Inc.

CHASSIS WARRANTY

Chassis shall be warranted by the chassis manufacturer as per the chassis manufacturer's issued warranty.

100% WARRANTY ON ALL OTHER ITEMS FOR ONE YEAR.

THIS WILL NOT APPLY

1. To normal maintenance services or adjustments.
2. To damage caused by negligence of normal maintenance.
3. To any vehicle which shall have been repaired or altered outside our factory in any way, so as, in our judgement, to affect its stability, nor which has been subjected to negligence, or accident, nor to any vehicle made by us which shall have been operated at a speed exceeding the factory-rated speed, or loaded beyond the factory-rated load capacity.
4. To major components such as purchased chassis and associated equipment furnished with chassis, signaling devices, generators, batteries, or other trade accessories, inasmuch as they are usually warranted separately by their respective manufacturers or to ancillary equipment used in rescue or firefighting.
5. To loss of time or use of vehicle, inconvenience or other incidental expenses.

THIS WARRANTY IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, WITH RESPECT TO QUALITY, MERCHANTABILITY, OR FITNESS FOR A PARTICULAR APPLICATION.

One (1)
00-E5-8000

Dimension Cover Sheet

Y___N___

OVERALL APPARATUS DIMENSIONS AND REQUIREMENTS

6. Wheelbase of chassis:
7. Cab-to-axle dimension of chassis:
8. Overall length of apparatus:
9. Overall width of apparatus body:

First Choice Fire & Safety Inc.

10. Overall height of apparatus:
11. Overall length of body including rear step:
12. Front overhang from center of front axle:
13. Rear overhang from center of rear axle:
14. Pump panel width:

One (1)
01-00-0000

Custom Cab Chassis Specifications

Y___N___

Specification

MODEL

The chassis shall be a Metro Star model. The cab and chassis shall include design considerations for multiple emergency vehicle applications, rapid transit and maneuverability. The chassis shall be manufactured for heavy duty service with the strength and capacity to support a fully laden apparatus, one hundred (100) percent of the time.

MODEL YEAR

The chassis shall have a vehicle identification number that reflects a 2023 model year.

COUNTRY OF SERVICE

The chassis shall be put in service in the country of United States of America (USA).

The chassis will meet applicable U.S.A. federal motor vehicle safety standards per CFR Title 49 Chapter V Part 571 as clarified in the incomplete vehicle book per CFR Title 49 Chapter V Part 568 Section 4 which accompanies each chassis. Spartan Chassis is not responsible for compliance to state, regional, or local regulations. Dealers should identify those regulations and order any necessary optional equipment from Spartan Chassis or their OEM needed to be in compliance with those regulations.

CAB AND CHASSIS LABELING LANGUAGE

First Choice Fire & Safety Inc.

The cab and chassis shall include the applicable caution, warning, and safety notice labels with text to be written in English. All applicable caution, warning, and safety notice labels shall be Innovative Controls brand. Where applicable to the location within the specific layout and label package of the cab and chassis, the labels shall include decorative chrome bezels. Designs shall include bezels that fit individual labels or packaged configurations of labels in certain common locations.

The following labels shall be Innovative Controls brand, each including a decorative chrome bezel (where applicable):

- Shoreline
- Aerial Stowed
- Aerial Breakers 2
- Air Conditioner
- Cab Tilt Plate
- Air Compressor Breaker
- Battery Conditioner Breaker
- Helmet Caution
- Horn Tag
- Q2B Tag
- Load Center Plate
- Not a Step Label
- Occupancy Tag
- Do Not Move
- Occupants Must Be Seated
- Do Not Stand
- Danger Do Not Weld
- Danger--Untrained Operator
- Def Tag, including any additional labels selected in the 2907- subcat
- Battery Direct
- Kneeling
- IFS Air Fault
- Engine Brake
- Retarder
- LR 100 Amp Node
- 300 Amp EPU
- 100 Amp Front O/R Node
- 100 Amp T/T Node
- 100 Amp RR O/R Node
- 10 Amp EPU
- Master Power

First Choice Fire & Safety Inc.

- 12 Volt Power
- Aerial Hours
- Pump In Drive
- Windshield Washer Fluid

APPARATUS TYPE

The apparatus shall be a pumper vehicle designed for emergency service use which shall be equipped with a permanently mounted fire pump which has a minimum rated capacity of 750 gallons per minute (3000 L/min). The apparatus shall include a water tank and hose body whose primary purpose is to combat structural and associated fires.

VEHICLE TYPE

The chassis shall be manufactured for use as a straight truck type vehicle and designed for the installation of a permanently mounted apparatus behind the cab. The apparatus of the vehicle shall be supplied and installed by the apparatus manufacturer.

VEHICLE ANGLE OF APPROACH PACKAGE

The angle of approach of the apparatus shall be a minimum of 8.00 degrees.

NFPA1901 Angle of Approach definition:

“To determine the angle of approach, place a thin steel strip against the front of the tires where they touch the ground or stretch a tight string from one front tire to the other at the front where they touch the ground. Determine the lowest point (component or equipment) on the vehicle forward of the front tire that would make the smallest angle of approach. Hang a plumb bob from the lowest point and mark the point on the ground where the point of the plumb bob touches. Measure the vertical distance from the ground to the point where the plumb bob was hung (distance V). Measure the horizontal distance from the plumb bob point to the steel strip or string running from front tire to front tire (distance H). Divide the vertical distance by the horizontal distance. The ratio of V/H is the tangent of the angle of approach. If the ratio is known, the angle of approach can be determined from a table of trigonometric functions of angles or from a math calculator. The standard requires a minimum angle of approach of 8.00 degrees: since the tangent of 8.00 degrees is 0.1405, if V divided by H is 0.1405 or larger, the angle of approach is 8.00 degrees or greater.”

AXLE CONFIGURATION

First Choice Fire & Safety Inc.

The chassis shall feature a 4 x 2 axle configuration consisting of a single rear drive axle with a single front steer axle.

GROSS AXLE WEIGHT RATINGS FRONT

The front gross axle weight rating (GAWR) of the chassis shall be 20,000 pounds.

This front gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

GROSS AXLE WEIGHT RATINGS REAR

The rear gross axle weight rating (GAWR) of the chassis shall be 27,000 pounds.

This rear gross axle weight rating shall be adequate to carry the weight of the completed apparatus including all equipment and personnel.

PUMP PROVISION

The chassis shall include provisions to mount a drive line pump in the middle of the chassis, behind the cab, more commonly known as the midship location.

WATER & FOAM TANK CAPACITY

The chassis shall include a carrying capacity of 750 gallons (2839 liters) to 1250 gallons (4732 liters). The water and/or foam tank(s) shall be supplied and installed by the apparatus manufacturer.

CAB STYLE

The cab shall be a custom, fully enclosed, MFD model with a 10.00 inch raised roof over the driver, officer, and crew area, designed and built specifically for use as an emergency response vehicle by a company specializing in cab and chassis design for all emergency response applications. The cab shall be designed for heavy-duty service utilizing superior strength and capacity for the application of protecting the occupants of the vehicle. This style of cab shall offer up to ten (10) seating positions.

The cab shall incorporate a fully enclosed design with side wall roof supports, allowing for a spacious cab area with no partition between the front and rear sections of the cab. To provide a superior finish by reducing welds that fatigue cab metal; the roof, the rear wall and side wall panels shall be assembled using a

First Choice Fire & Safety Inc.

combination of welds and proven industrial adhesives designed specifically for aluminum fabrication for construction.

The cab shall be constructed using multiple aluminum extrusions in conjunction with aluminum plate, which shall provide proven strength and the truest, flattest body surfaces ensuring less expensive paint repairs if needed. All aluminum welding shall be completed to the American Welding Society and ANSI D1.2-96 requirements for structural welding of aluminum.

All interior and exterior seams shall be sealed for optimum noise reduction and to provide the most favorable efficiency for heating and cooling retention.

The cab shall be constructed of 5052-H32 corrosion resistant aluminum plate. The cab shall incorporate tongue and groove fitted 6061-T6 0.13 & 0.19 inch thick aluminum extrusions for extreme duty situations. A single formed, one (1) piece extrusion shall be used for the "A" pillar, adding strength and rigidity to the cab as well as additional roll-over protection. The cab side walls and lower roof skin shall be 0.13 inch thick; the rear wall and raised roof skins shall be 0.09 inch thick; the front cab structure shall be 0.19 inch thick.

The exterior width of the cab shall be 94.00 inches wide with a minimum interior width of 88.00 inches. The overall cab length shall be 144.60 inches with 67.50 inches from the centerline of the front of the axle to the back of the cab.

The cab interior shall be designed to afford the maximum usable interior space and attention to ergonomics with hip and legroom while seated which exceeds industry standards. The crew cab floor shall be flat across the entire walking area for ease of movement inside the cab.

The cab shall offer an interior height of 57.50 inches from the front floor to the headliner and a rear floor to headliner height of 65.00 inches in the raised roof area, at a minimum. The cab shall offer an interior measurement at the floor level from the rear of the engine tunnel to the rear wall of the cab of 65.38 inches. All interior measurements shall include the area within the interior trimmed surfaces and not to any unfinished surface.

The cab shall include a driver and officer area with two (2) cab doors large enough for personnel in full firefighting gear. The front doors shall offer a clear opening of 40.25 inches wide X 53.50 inches high, from the cab floor to the top of the door opening. The cab shall also include a crew area with up to two (2) cab doors, also large enough for personnel in full firefighting gear. The rear doors shall offer a clear opening of 32.25 inches wide X 61.00 inches high, from the cab floor to the top of the door opening.

First Choice Fire & Safety Inc.

The cab shall incorporate a progressive two (2) step configuration from the ground to the cab floor at each door opening. The progressive steps are vertically staggered and extend the full width of each step well allowing personnel in full firefighting gear to enter and exit the cab easily and safely.

The first step for the driver and officer area shall measure approximately 11.50 inches deep X 31.13 inches wide. The intermediate step shall measure approximately 8.50 inches deep X 32.50 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 11.00 inches.

The first step for the crew area shall measure approximately 11.50 inches deep X 20.44 inches wide. The intermediate step shall measure approximately 10.25 inches deep X 22.75 inches wide. The height from the first step to the intermediate step and the intermediate step to the cab floor shall not exceed 12.80 inches.

OCCUPANT PROTECTION

The vehicle shall include the Advanced Protection System™ (APS) which shall secure belted occupants and increase the survivable space within the cab. The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The system components shall include:

- Driver steering wheel airbag
- Driver dual knee air bags (patent pending) with energy management mounting (patent pending) and officer knee airbag.
- Large driver, officer, and crew area side curtain airbags
- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around the occupants, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries
- Heavy truck Restraints Control Module (RCM) - receives inputs from the outboard sensors, selectively deploys APS systems, and records sensory inputs immediately before and during a detected qualifying event

First Choice Fire & Safety Inc.

- Integrated outboard crash sensors mounted at the perimeter of the vehicle - detects a qualifying front or side impact event and monitors and communicates vehicle status and real time diagnostics of all critical subsystems to the RCM
- Fault-indicating Supplemental Restraint System (SRS) light on the driver's instrument panel

Frontal impact protection shall be provided by the outboard sensors and the RCM. In a qualifying front impact event the outboard sensors provide inputs to the RCM. The RCM activates the steering wheel airbag, driver side dual knee airbags (patent pending), officer side knee airbag, and advanced seat belts for each occupant in the cab.

Rollover, side impact, and ejection mitigation shall be provided by the outboard sensors and the RCM. In qualifying rollover or side impact events the outboard sensors provide inputs to the RCM. The RCM activates the side curtain airbags and advanced seat belts for each occupant in the cab. The RCM measures roll angle, lateral acceleration, and roll rate to determine if a rollover event or side impact event is imminent or occurring.

In the event of a qualifying offset or other non-frontal impact, the RCM shall determine and intelligently deploy the front impact protection system, the side impact protection system, or both front and side impact protection systems based on the inputs received from the outboard crash sensors.

CAB FRONT FASCIA

The front cab fascia shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate which shall be an integral part of the cab.

The cab fascia will encompass the entire front of the aluminum cab structure from the bottom of the windshield to the bottom of the cab and shall be the "Classic" design.

The front cab fascia shall include two (2) molded plastic modules on each side accommodating a total of up to four (4) Hi/Low beam headlights and two (2) turn signal lights or up to four (4) warning lights. A chrome plated molded plastic bezel shall be provided on each side around each set of four lamps.

FRONT GRILLE

First Choice Fire & Safety Inc.

The front fascia shall include a box style, 304 stainless steel front grille 44.45 inches wide X 33.50 inches high X 1.50 inches deep. The grille shall include a minimum free air intake of 732.00 square inches. The upper portion of the grille shall be hinged to provide service access behind the grille.

CAB UNDERCOAT

There shall be a rubberized undercoating applied to the underside of the cab that provides abrasion protection, sound deadening and corrosion protection.

CAB SIDE DRIP RAIL

There shall be a drip rail along the top radius of each cab side. The drip rails shall help prevent water from the cab roof running down the cab side.

CAB PAINT EXTERIOR

The cab shall be painted prior to the installation of glass accessories and all other cab trim to ensure complete paint coverage and the maximum in corrosion protection of all metal surfaces.

All metal surfaces on the entire cab shall be ground by disc to remove any surface oxidation or surface debris which may hinder the paint adhesion. Once the surface is machine ground a high quality acid etching of base primer shall be applied. Upon the application of body fillers and their preparation, the cab shall be primed with a coating designed for corrosion resistance and surface paint adhesion. The maximum thickness of the primer coat shall be 2.00 mils.

The entire cab shall then be coated with an intermediate solid or epoxy surfacing agent that is designed to fill any minor surface defects, provide an adhesive bond between the primer and the paint and improve the color and gloss retention of the color. The finish to this procedure shall be a sanding of the cab with 360 grit paper followed by sealing the seams with SEM brand seam sealer.

The cab shall then be painted the specific color designated by the customer with an acrylic urethane type system designed to retain color and resist acid rain and most atmospheric chemicals found on the fire ground or emergency scene. The paint shall have a minimum thickness of 2.00 mils, followed by a clear top coat not to exceed 2.00 mils. The entire cab shall then be baked at 180 degrees for one (1) hour to speed the curing process of the coatings.

CAB PAINT MANUFACTURER

First Choice Fire & Safety Inc.

The cab shall be painted with PPG Industries paint.

CAB PAINT PRIMARY/LOWER COLOR

The lower paint color shall be PPG FBCH 71663 Red.

CAB PAINT WARRANTY

The cab and chassis shall be covered by a limited manufacturer paint warranty which shall be in effect for ten (10) years from the first owner's date of purchase or in service or the first 100,000 actual miles, whichever occurs first.

The warranty details can be found in the chassis warranty document.

CAB PAINT INTERIOR

The visible interior cab structure surfaces shall feature a black Spar-Liner spray on bedliner coating which shall mold to each surface of the cab interior. The Spar-Liner shall be environmentally friendly and chemically resistant.

CAB ENTRY DOORS

The cab shall include four (4) entry doors, two (2) front doors and two (2) crew doors designed for ease of entering and egress when outfitted with an SCBA. The doors shall be constructed of extruded aluminum with a nominal thickness of 0.13 inch. The exterior skins shall be constructed of 0.13 inch aluminum plate.

The doors shall include a double rolled style automotive rubber seal around the perimeter of each door frame and door edge which ensures a weather tight fit.

All door hinges shall be hidden within flush mounted cab doors for a pleasing smooth appearance and perfect fit along each side of the cab. Each door hinge shall be piano style with a 0.38 inch pin and shall be constructed of stainless steel.

CAB ENTRY DOOR TYPE

All cab entry doors shall be full length in design to fully enclose the lower cab steps. Entry doors shall include Pollak mechanical plunger style switches for electrical component activation.

CAB INSULATION

First Choice Fire & Safety Inc.

The cab ceiling and walls shall include 1.00 inch thick foam insulation. The insulation shall act as a barrier absorbing noise as well as assisting in sustaining the desired climate within the cab interior.

LH MID EMS COMPARTMENT

The cab shall include a compartment located in the middle of the wall above the left side wheel well. This compartment shall measure 17.00 inches wide X 43.00 inches high X 23.00 inches deep.

LH MID EMS EXTERIOR ACCESS

The cab shall include a hinged box pan door featuring a full length stainless steel piano style hinge and a bright aluminum tread plate inner panel located in the middle of the wall above the left side wheel well. The compartment shall have a clear door opening of 15.00 inches wide X 40.00 inches high.

LH MID EMS COMPARTMENT INTERIOR

The cab compartment located in the middle of the wall above the left side wheel well shall include solid aluminum walls with an interior access point rear facing. This compartment shall be finished to customer specification.

LH MID EMS INTERIOR ACCESS

The mid crew area cab left side EMS compartment shall be accessible from the inside of the cab through a ROM series IV roll up door. The compartment shall have a clear door opening of approximately 14.50 inches wide and as tall as possible in the available customer specified left EMS compartment height and access point.

LH MID EMS COMPARTMENT INTERIOR SHELVING

The left hand mid EMS compartment located in crew area of the cab shall include one (1) aluminum shelf which shall be secured using Unistrut channel on two (2) sides of the interior walls of the compartment. The shelf shall include a 1.00 inch lip around the edges. The shelf shall be finished the same as the interior of the compartment.

LH MID EMS COMPARTMENT DOOR HARDWARE

First Choice Fire & Safety Inc.

The left side EMS compartment door shall include a locking bent D-ring slam latch. There shall be a switch to activate the open compartment warning light in the cab in the event the door is left ajar.

MID EMS COMPARTMENT LIGHTING

The interior portion of each of the mid EMS compartments shall include compartment door activated LED lighting to illuminate all usable surfaces within each compartment.

MID EMS COMPARTMENT EXTERIOR FINISH

The EMS compartment exterior shall feature a black Spar-Liner spray on bedliner coating.

MID EMS COMPARTMENT INTERIOR FINISH

The EMS compartment interior shall feature a DA sanded finish.

LH EXTERIOR REAR COMPARTMENT

The cab shall offer an exterior compartment on the left side of the cab behind the rear door. The compartment opening shall be 10.00 inches wide X 31.19 inches high. The compartment size shall be 11.34 inches wide X 31.19 inches high X 21.19 inches deep. The compartment shall have a 10.63 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

LEFT HAND EXTERIOR REAR COMPARTMENT LIGHTING

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the left side of the cab. The strip light shall be 10.00 inches long and shall include three (3) bright white Gen3 LEDs.

LH EXTERIOR COMPARTMENT INTERIOR FINISH

The interior of the left hand exterior compartment shall have a DA sanded finish.

RH EXTERIOR REAR COMPARTMENT

First Choice Fire & Safety Inc.

The cab shall offer an exterior compartment on the right side of the cab behind the rear door. The compartment opening shall be 10.00 inches wide X 31.19 inches high. The compartment size shall be 11.34 inches wide X 31.19 inches high X 21.19 inches deep. The compartment shall have a 10.63 inch wide, 32.00 inch high and 1.50 inch thick hinged box pan style flush mount door with a bright aluminum tread plate inner panel and a bent D-ring slam latch. There shall be a switch to activate a light inside the compartment and the open compartment warning light in the cab in the event the door is left ajar.

RIGHT HAND EXTERIOR REAR COMPARTMENT LIGHTING

There shall be one (1) SoundOff Signal brand LED strip light installed to illuminate the exterior rear compartment on the right side of the cab. The strip light shall be 10.00 inches long and shall include three (3) bright white Gen3 LEDs.

RH EXTERIOR COMPARTMENT INTERIOR FINISH

The interior of the right hand exterior compartment shall have a DA sanded finish.

CAB STRUCTURAL WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY TERMS CAN BE FOUND IN THE CHASSIS WARRANTY DOCUMENT, WHICH CONTAINS THE COMPLETE STATEMENT OF THE WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The cab structure shall be warranted for a period of ten (10) years or one hundred thousand (100,000) miles which ever may occur first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

CAB TEST INFORMATION

The cab shall have successfully completed the preload side impact, static roof load application and frontal impact without encroachment to the occupant survival space when tested in accordance with Section 4 of SAE J2420 COE Frontal Strength Evaluation Dynamic Loading Heavy Trucks, Section 5 of SAE J2422 Cab Roof Strength Evaluation Quasi –Static Loading Heavy Trucks and ECE R29 Uniform

First Choice Fire & Safety Inc.

Provisions Concerning the Approval of Vehicles with regard to the Protection of the Occupants of the Cab of a Commercial Vehicles Annex 3 Paragraph 5.

The above tests have been witnessed by and attested to by an independent third party. The test results were recorded using cameras, high speed imagers, accelerometers and strain gauges. Documentation of the testing shall be provided upon request.

ELECTRICAL SYSTEM

The chassis shall include a single starting electrical system which shall include a 12 volt direct current multiplexing system, suppressed per SAE J551. The wiring shall be appropriate gauge cross link with 311 degree Fahrenheit insulation. All SAE wires in the chassis shall be color coded and shall include the circuit number and function where possible. The wiring shall be protected by 275 degree Fahrenheit minimum high temperature flame retardant loom. All nodes and sealed Deutsch connectors shall be waterproof.

APPARATUS WIRING PROVISION

An apparatus wiring panel shall be installed in the center dash area behind the rocker switch panel which shall include eight (8) open circuits consisting of three (3) 20 amp, one (1) 30 amp, three (3) 10 amp, and one (1) 15 amp circuit, with relays and breakers with trigger wires which shall be routed to the rocker switch panel.

MULTIPLEX DISPLAY

The multiplex electrical system shall include a Weldon Vista IV display which shall be located on the left side of the dash in the switch panel. The Vista IV shall feature a full color LCD display screen which includes a message bar displaying the time of day and important messages requiring acknowledgement by the user which shall all be displayed on the top of the screen in the order they are received. There shall be eight (8) push button virtual controls, four (4) on each side of the display for the on-board diagnostics. The display screen shall be video ready for back-up cameras, thermal cameras, and DVD.

The Vista IV display shall offer varying fonts and background colors. The display shall be fully programmable to the needs of the customer and shall offer virtually infinite flexibility for screen configuration options.

LOAD MANAGEMENT SYSTEM

First Choice Fire & Safety Inc.

The apparatus load management shall be performed by the included multiplex system. The multiplex system shall also feature the priority of sequences and shall shed electrical loads based on the priority list specifically programmed.

DATA RECORDING SYSTEM

The chassis shall have a Weldon Vehicle Data Recorder (VDR) system installed. The system shall be designed to meet NFPA 1901 and shall be integrated with the Weldon Multiplex electrical system. The following information shall be recorded:

- Vehicle Speed
- Acceleration
- Deceleration
- Engine Speed
- Engine Throttle Position
- ABS Event
- Seat Occupied Status
- Seat Belt Status
- Master Optical Warning Device Switch Position
- Time
- Date

Each portion of the data shall be recorded at the specified intervals and stored for the specified length of time to meet NFPA 1901 guidelines and shall be retrievable by connecting a laptop computer to the VDR system.

ACCESSORY POWER

The electrical distribution panel shall include two (2) power studs. The studs shall be size #10 and each of the power studs shall be circuit protected with a fuse of the specified amperage. One (1) power stud shall be capable of carrying up to a 40 amp battery direct load. One (1) power stud shall be capable of carrying up to a 15 amp ignition switched load. The two (2) power studs shall share one (1) #10 ground stud. A 225 amp battery direct power and ground stud shall be provided and installed on the chassis near the left hand battery box for OEM body connections.

EXTERIOR ELECTRICAL TERMINAL COATING

All terminals exposed to the elements will be sprayed with a high visibility protective rubberized coating to prevent corrosion.

First Choice Fire & Safety Inc.

ENGINE

The chassis engine shall be a Cummins L9 engine. The L9 engine shall be an in-line six (6) cylinder, four cycle diesel powered engine. The engine shall offer a rating of 450 horse power at 2100 RPM and shall be governed at 2200 RPM. The torque rating shall feature 1250 foot pounds of torque at 1200 RPM with 543 cubic inches (8.9 liters) of displacement.

The L9 engine shall feature a VGT™ Turbocharger, a high pressure common rail fuel system, fully integrated electronic controls with an electronic governor, and shall be EPA certified to meet the 2021 emissions standards using cooled exhaust gas recirculation and selective catalytic reduction technology.

The engine shall include an engine mounted combination full flow/by-pass oil filter with replaceable spin on cartridge for use with the engine lubrication system. The engine shall include Citgo brand Citgard 500, or equivalent SAE 15W40 CK-4 low ash engine oil which shall be utilized for proper engine lubrication.

A wiring harness shall be supplied ending at the back of the cab. The harness shall include a connector which shall allow an optional harness for the pump panel. The included circuits shall be provided for a tachometer, oil pressure, engine temperature, hand throttle, high idle and a PSG system. A circuit for J1939 data link shall also be provided at the back of the cab.

CAB ENGINE TUNNEL

The cab interior shall include an integrated engine tunnel constructed of 5052-H32 Marine Grade, 0.19 of an inch thick aluminum. The tunnel shall be a maximum of 41.50 inches wide X 25.50 inches high.

DIESEL PARTICULATE FILTER CONTROLS

There shall be two (2) controls for the diesel particulate filter. One (1) control shall be for regeneration and one (1) control shall be for regeneration inhibit.

ENGINE PROGRAMMING HIGH IDLE SPEED

The engine high idle control shall maintain the engine idle at approximately 1250 RPM when engaged.

ENGINE HIGH IDLE CONTROL

First Choice Fire & Safety Inc.

The vehicle shall be equipped with a virtual Vista button and an automatic high-idle speed control. It shall be pre-set so when activated, it will operate the engine at the appropriate RPM to increase alternator output. This device shall operate only when the engine is running and the transmission is in neutral with the parking brake set. The device shall disengage when the operator depresses the brake pedal, or the transmission is placed in gear, and shall be available to manually or automatically re-engage when the brake is released, or when the transmission is placed in neutral. There shall be an indicator on the Vista display and control screen for the high idle speed control.

ENGINE PROGRAMMING ROAD SPEED GOVERNOR

The engine shall include programming which will govern the top speed of the vehicle.

AUXILIARY ENGINE BRAKE

A compression brake, for the six (6) cylinder engine shall be provided. A cutout relay shall be installed to disable the compression brake when in pump mode or when an ABS event occurs. The engine compression brake shall activate upon 0% accelerator when in operation mode and actuate the vehicle's brake lights.

The engine shall utilize a variable geometry turbo (VGT) as an integrated auxiliary engine brake to offer a variable rate of exhaust flow, which when activated in conjunction with the compression brake shall enhance the engine's compression braking capabilities.

AUXILIARY ENGINE BRAKE CONTROL

An engine compression brake control device shall be included. The electronic control device shall monitor various conditions and shall activate the engine brake only if all of the following conditions are simultaneously detected:

- A valid gear ratio is detected.
- The driver has requested or enabled engine compression brake operation.
- The throttle is at a minimum engine speed position.
- The electronic controller is not presently attempting to execute an electronically controlled final drive gear shift.

The compression brake shall be controlled via an off/low/medium/high virtual button on the Vista display and control screen. The multiplex system shall remember and default to the last engine brake control setting when the vehicle is shut off and re-started.

First Choice Fire & Safety Inc.

ELECTRONIC ENGINE OIL LEVEL INDICATOR

The engine oil shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal. The warning shall activate in a low oil situation upon turning on the master battery and ignition switches without the engine running.

FLUID FILLS

The front of the chassis shall accommodate fluid fill for the engine oil through the grille. This area shall also accommodate a check for the engine oil. The transmission, power steering, and coolant fluid fills and checks shall be under the cab. The windshield washer fill shall be accessible through the front left side mid step.

ENGINE DRAIN PLUG

The engine shall include an original equipment manufacturer installed oil drain plug.

ENGINE WARRANTY

The Cummins engine shall be warranted for a period of five (5) years or 100,000 miles, whichever occurs first.

ENGINE PROGRAMMING REMOTE THROTTLE

The engine ECM (Electronic Control Module) discreet wire remote throttle circuit shall be turned off for use with a J1939 based pump controller or when the discreet wire remote throttle controls are not required.

ENGINE PROGRAMMING IDLE SPEED

The engine low idle speed will be programmed at 700 rpm.

ENGINE AIR INTAKE

The engine air intake system shall include an ember separator. This ember separator shall be designed to protect the downstream air filter from embers using a combination of unique flat and crimped metal screens packaged in a heavy duty galvanized steel frame. This multilayered screen shall trap embers and allow them to burn out before passing through the pack.

First Choice Fire & Safety Inc.

The engine air intake system shall also include an air cleaner mounted above the radiator. This air cleaner shall utilize a replaceable dry type filter element designed to prevent dust and debris from being ingested into the engine. A service cover shall be provided on the housing, reducing the chance of contaminating the air intake system during air filter service.

The air intake system shall include a restriction indicator light in the warning light cluster on the instrument panel, which shall activate when the air cleaner element requires replacement.

ENGINE FAN DRIVE

The engine cooling system fan shall incorporate a thermostatically controlled, Horton fully variable type fan drive with SmartClutch J-1939 CAN controller.

The variable speed fan clutch only engages at the amount needed for proper cooling to facilitate improved vehicle performance, cab heating in cold climates, and fuel economy. The fan clutch design shall be fail-safe so that if the clutch drive fails the fan shall engage to prevent engine overheating due to the fan clutch failure. The fan speed shall include a J-1939 CAN clutch controller to receive signal from the engine control module to activate at variable rates of speed. Variable speeds shall be set through thermostatic and engine speed signals to run as efficiently and quietly as required to maintain temperature.

ENGINE COOLING SYSTEM

There shall be a heavy-duty aluminum cooling system designed to meet the demands of the emergency response industry. The cooling system shall have the capacity to keep the engine properly cooled under all conditions of road and pumping operations. The cooling system shall be designed and tested to meet or exceed the requirements specified by the engine and transmission manufacturer and all EPA requirements. The complete cooling system shall be mounted to isolate the entire system from vibration or stress. The individual cores of the cooling system shall be mounted in a manner to allow expansion and contraction at various rates without inducing stress into the adjoining cores.

The cooling system shall be comprised of a charge air cooler to radiator serial flow package that provides the maximum cooling capacity for the specified engine as well as serviceability. The main components shall include a surge tank, a charge air cooler bolted to the front of the radiator, recirculation shields, a shroud, a fan, and required tubing.

First Choice Fire & Safety Inc.

The radiator shall be a down-flow design constructed with aluminum cores, plastic end tanks, and a steel frame. The radiator shall be equipped with a drain cock to drain the coolant for serviceability.

The cooling system shall include a one piece injected molded polymer fan with a three (3) piece fiberglass fan shroud.

The cooling system shall be equipped with a surge tank that is capable of removing entrained air from the system. The surge tank shall be equipped with a low coolant probe and rearward oriented sight glass to observe coolant in the system. A cold fill and observation line shall be included within the frame mounted translucent recovery bottle to monitor the level of the coolant. The surge tank shall have a dual seal cap that meets the engine manufacturer's pressure requirements and allows for expansion and recovery of coolant into a separate integral expansion chamber.

All radiator tubes shall be formed from aluminized steel tubing. Recirculation shields shall be installed where required to prevent heated air from reentering the cooling package and affecting performance.

The charge air cooler shall be a cross-flow design constructed completely of aluminum with cast tanks. All charge air cooler tubes shall be formed from aluminized steel tubing and installed with silicone hump hoses and stainless steel "constant torque" style clamps meeting the engine manufacturer's requirements.

The radiator and charge air cooler shall be removable through the bottom of the chassis.

ENGINE COOLING SYSTEM PROTECTION

The engine cooling system shall include a recirculation shield designed to act as a light duty skid plate below the radiator to provide additional protection for the engine cooling system from light impacts, stones, and road debris. The skid plate shall be painted to match the frame components.

ENGINE COOLANT

The cooling package shall include Extended Life Coolant (ELC). The use of ELC provides longer intervals between coolant changes over standard coolants providing improved performance. The coolant shall contain a 50/50 mix of ethylene glycol and de-ionized water to keep the coolant from freezing to a temperature of -34 degrees Fahrenheit.

First Choice Fire & Safety Inc.

Proposals offering supplemental coolant additives (SCA) shall not be considered, as this is part of the extended life coolant makeup.

ELECTRONIC COOLANT LEVEL INDICATOR

The instrument panel shall feature a low engine coolant indicator light which shall be located in the center of the instrument panel. An audible tone alarm shall also be provided to warn of a low coolant incident.

ENGINE PUMP HEAT EXCHANGER

A single bundle type coolant to water heat exchanger shall be installed between the engine and the radiator. The heat exchanger shall be designed to prohibit water from the pump from coming in contact with the engine coolant. This shall allow the use of water from the discharge side of the pump to assist in cooling the engine.

COOLANT HOSES

The cooling systems hose shall be formed silicone hose and formed aluminized steel tubing and include stainless steel constant torque band clamps.

ENGINE COOLANT OVERFLOW BOTTLE

A remote engine coolant overflow expansion bottle shall be provided in the case of over filling the coolant system. The overflow bottle shall capture the expansion fluid or overflow rather than allow the fluid to drain on the ground.

ENGINE EXHAUST SYSTEM

The exhaust system shall include an end-in end-out horizontally mounted single module after treatment device, and downpipe from the charge air cooled turbo. The single module shall include four temperature sensors, diesel particulate filter (DPF), urea dosing module (UL2), and a selective catalytic reduction (SCR) catalyst to meet current EPA standards. The selective catalytic reduction catalyst utilizes a diesel exhaust fluid solution consisting of urea and purified water to convert NOx into nitrogen, water, and trace amounts of carbon dioxide. The solution shall be mixed and injected into the system through the DPF and SCR.

The system shall utilize 0.07 inch thick stainless steel exhaust tubing between the engine turbo and the DPF. Zero leak clamps seal all system joints between the turbo and DPF.

First Choice Fire & Safety Inc.

The single module after treatment through the end of the tailpipe shall be connected with zero leak clamps. The discharge shall terminate horizontally on the right side of the vehicle ahead of the rear tires.

The exhaust system after treatment module shall be mounted below the frame in the outboard position.

DIESEL EXHAUST FLUID TANK

The exhaust system shall include a molded cross linked polyethylene tank for Diesel Exhaust Fluid (DEF). The tank shall have a capacity of six (6) usable gallons and shall be mounted on the left hand side of the chassis frame behind the batteries below the frame.

The DEF tank shall be designed with capacity for expansion in case of fluid freezing. Engine coolant, which shall be thermostatically controlled, shall be run through lines in the tank to help prevent the DEF from freezing and to provide a means of thawing the fluid if it should become frozen.

The tank fill tube shall be routed under the rear of the cab with the fill neck and splash guard accessible in the top rear step.

ENGINE EXHAUST ACCESSORIES

An exhaust temperature mitigation device shall be shipped loose for installation by the body manufacturer on the vehicle. The temperature mitigation device shall lower the temperature of the exhaust by combining ambient air with the exhaust gasses at the exhaust outlet.

ENGINE EXHAUST WRAP

The exhaust tubing between the engine turbo and the diesel particulate filter (DPF) shall be wrapped with a thermal cover in order to retain the necessary heat for DPF regeneration. The exhaust wrap shall also help protect surrounding components from radiant heat which can be transferred from the exhaust.

TRANSMISSION

The drive train shall include an Allison model EVS 3000 torque converting, automatic transmission which shall include electronic controls. The transmission shall feature two (2) 10-bolt PTO pads located on the converter housing.

First Choice Fire & Safety Inc.

The transmission shall include two (2) internal oil filters and Castrol TranSynd™ synthetic TES 295 transmission fluid which shall be utilized in the lubrication of the EVS transmission. An electronic oil level sensor shall be included with the readout located in the shift selector.

The transmission gear ratios shall be:

1st	3.49:1
2nd	1.86:1
3rd	1.41:1
4th	1.00:1
5th	0.75:1
6th	0.65:1 (if applicable)
Rev	5.03:1

TRANSMISSION MODE PROGRAMMING

The transmission, upon start-up, will automatically select a four (4) speed operation. The fifth speed over drive shall be available with the activation of the mode button on the shifting pad.

TRANSMISSION FEATURE PROGRAMMING

The Allison Gen V-E transmission EVS group package number 127 shall contain the 198 vocational package in consideration of the duty of this apparatus as a pumper. This package shall incorporate an automatic neutral with selector override. This feature commands the transmission to neutral when the park brake is applied, regardless of drive range requested on the shift selector. This requires re-selecting drive range to shift out of neutral for the override.

This package shall be coupled with the use of a split shaft PTO and incorporate pumping circuits. These circuits shall be used allowing the vehicle to operate in the fourth range lockup while operating the pump mode due to the 1 to 1 ratio through the transmission, therefore the output speed of the engine is the input speed to the pump. The pump output can be easily calculated by using this input speed and the drive ratio of the pump itself to rate the gallons of water the pump can provide.

A transmission interface connector shall be provided in the cab. This package shall contain the following input/output circuits to the transmission control module. The Gen V-E transmission shall include prognostic diagnostic capabilities. These capabilities shall include the monitoring of the fluid life, filter change indication, and transmission clutch maintenance.

First Choice Fire & Safety Inc.

<u>Function ID</u>	<u>Description</u>	<u>Wire</u>
<u>assignment</u>		
Inputs		
C	PTO Request	142
J	Fire Truck Pump Mode (4th Lockup)	122 / 123
Outputs		
C	Range Indicator	145 (4th)
G	PTO Enable Output	130
	Signal Return	103

ELECTRONIC TRANSMISSION OIL LEVEL INDICATOR

The transmission fluid shall be monitored electronically and shall send a signal to activate a warning in the instrument panel when levels fall below normal.

TRANSMISSION SHIFT SELECTOR

An Allison pressure sensitive range selector touch pad shall be provided and located to the right of the driver within clear view and easy reach. The shift selector shall have a graphical Vacuum Florescent Display (VFD) capable of displaying two lines of text. The shift selector shall provide mode indication and a prognostic indicator (wrench symbol) on the digital display. The prognostics monitor various operating parameters and shall alert you when a specific maintenance function is required.

TRANSMISSION PRE-SELECT WITH AUXILIARY BRAKE

When the auxiliary brake is engaged, the transmission shall automatically shift to second gear to decrease the rate of speed assisting the secondary braking system and slowing the vehicle.

TRANSMISSION COOLING SYSTEM

The transmission shall include a water to oil cooler system located in the cooling loop between the radiator and the engine. The transmission cooling system shall meet all transmission manufacturer requirements. The transmission cooling system shall feature continuous flow of engine bypass water to maintain uninterrupted transmission cooling.

TRANSMISSION DRAIN PLUG

The transmission shall include an original equipment manufacturer installed magnetic transmission fluid drain plug.

First Choice Fire & Safety Inc.

TRANSMISSION WARRANTY

The Allison EVS series transmission shall be warranted for a period of five (5) years with unlimited mileage. Parts and labor shall be included in the warranty.

PTO LOCATION

The transmission shall have two (2) power take off (PTO) mounting locations, one (1) in the 8:00 o'clock position and one (1) in the 4:00 o'clock position.

DRIVELINE

All drivelines shall be heavy duty metal tube and equipped with MSI 1710 series universal joints. The shafts shall be dynamically balanced prior to installation to alleviate future vibration. In areas of the driveline where a slip shaft is required, the splined slip joint shall be coated with Glide Coat[®]. The drivelines shall include Meritor brand u-joints with thrust washers.

DRIVELINE GUARDS

Two (2) driveline guard loops shall be provided and installed to support the driveline shafts for routine maintenance and in the event of a driveline component failure.

MIDSHIP PUMP / GEARBOX

A temporary jackshaft driveline and pump mounting brackets shall be installed by the chassis manufacturer to accommodate the midship split shaft pump as specified by the apparatus manufacturer.

MIDSHIP PUMP / GEARBOX MODEL

The midship pump/gearbox provisions shall be for a Waterous CSUC20 pump.

MIDSHIP PUMP GEARBOX DROP

The Waterous pump gearbox shall have a "C" (medium length) drop length.

MIDSHIP PUMP RATIO

The ratio for the midship pump shall be 2.27:1.

First Choice Fire & Safety Inc.

MIDSHIP PUMP LOCATION C/L SUCTION TO C/L REAR AXLE

The midship pump shall be located so the dimension from the centerline of the suction to the centerline of the rear axle is 80.00 inches.

PUMP SHIFT CONTROLS

One (1) pump shift control panel cutout for Innovative Controls shifter model 3001681 or 3001683 shall be provided on the center dash panel in the lower left-hand corner for customer installation of the pump shift controls.

FUEL FILTER/WATER SEPARATOR

The fuel system shall have a Fleetguard FS20121 fuel filter/water separator as a primary filter. The fuel filter shall have a drain valve.

A water in fuel sensor shall be provided and wired to an instrument panel lamp and audible alarm to indicate when water is present in the fuel/water separator.

A secondary fuel filter shall be included as approved by the engine manufacturer.

FUEL LINES

The fuel system supply and return lines installed from the fuel tank to the engine shall be reinforced nylon tubing rated for diesel fuel. The fuel lines shall be brown in color and connected with brass fittings.

ELECTRIC FUEL PRIMER

Integral to the engine assembly is an electric lift pump that serves the purpose of pre-filter fuel priming.

FUEL TANK

The fuel tank shall have a capacity of sixty-eight (68) gallons and shall measure 35.00 inches in width X 17.00 inches in height X 29.00 inches in length.

The baffled tank shall have a vent port to facilitate venting to the top of the fill neck for rapid filling without "blow-back" and a roll over ball check vent for temperature related fuel expansion and draw.

First Choice Fire & Safety Inc.

The tank is designed with dual draw tubes and sender flanges. The tank shall have 2.00 inch NPT fill ports for right or left hand fill. A 0.50 inch NPT drain plug shall be centered in the bottom of the tank.

The fuel tank shall be mounted below the frame, behind the rear axle. Two (2) three-piece strap hanger assemblies with “U” straps bolted midway on the fuel tank front and rear shall be utilized to allow the tank to be easily lowered and removed for service purposes. Rubber isolating pads shall be provided between the tank and the upper tank mounting brackets. Strap mounting studs through the rail, hidden behind the body shall not be acceptable.

FUEL TANK MATERIAL AND FINISH

The fuel tank shall be constructed of 12 gauge aluminized steel. The exterior of the tank shall be powder coated black and then painted to match the frame components.

All powder coatings, primers and paint shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 Method B, results to be 5B minimum. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794, results to be 5B minimum.

Any proposals offering painted fuel tanks with variations from the above process shall not be accepted. The film thickness of vendor supplied parts shall also be sufficient to meet the performance standards as stated above.

FUEL TANK STRAP MATERIAL

The fuel tank straps shall be constructed of ASTM A-36 steel. The fuel tank straps shall be powder coated black and then painted to match the frame components if possible.

FUEL TANK FILL PORT

The fuel tank fill ports shall be provided with two (2) left fill ports located one (1) in the forward position and one (1) in the middle position and the right fill port located in the middle position of the fuel tank.

FUEL TANK DRAIN PLUG

A 0.5 inch NPT magnetic drain plug shall be centered in the bottom of the fuel tank.

First Choice Fire & Safety Inc.

FRONT AXLE

The front axle shall be a Meritor Easy Steer Non drive front axle, model number MFS-20. The axle shall include a 3.74 inch drop and a 71.00 inch king pin intersection (KPI). The axle shall include a conventional style hub with a standard knuckle.

FRONT AXLE WARRANTY

The front axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

FRONT WHEEL BEARING LUBRICATION

The front axle wheel bearings shall be lubricated with oil. The oil level can be visually checked via clear inspection windows in the front axle hubs.

FRONT SHOCK ABSORBERS

Two (2) Bilstein inert, nitrogen gas filled shock absorbers shall be provided and installed as part of the front suspension system. The shocks shall be a monotubular design and fabricated using a special extrusion method, utilizing a single blank of steel without a welded seam, achieving an extremely tight peak-to-valley tolerance and maintains consistent wall thickness. The monotubular design shall provide superior strength while maximizing heat dissipation and shock life.

The ride afforded through the use of a gas shock is more consistent and shall not deteriorate with heat, the same way a conventional oil filled hydraulic shock would.

The Bilstein front shocks shall include a digressive working piston assembly allowing independent tuning of the compression and rebound damping forces to provide optimum ride and comfort without compromise. The working piston design shall feature fewer parts than most conventional twin tube and “road sensing” shock designs and shall contribute to the durability and long life of the Bilstein shock absorbers.

Proposals offering the use of conventional twin tube or “road sensing” designed shocks shall not be considered.

FRONT SUSPENSION

First Choice Fire & Safety Inc.

The front suspension shall include a ten (10) leaf spring pack in which the longest leaf measures 54.00 inch long and 4.00 inches wide and shall include a military double wrapped front eye. Both spring eyes shall have a case hardened threaded bushing installed with lubrication counter bore and lubrication land off cross bore with grease fitting. The spring capacity shall be rated at 21,500 pounds.

STEERING COLUMN/ WHEEL

The cab shall include a Douglas Autotech steering column which shall include a seven (7) position tilt, a 2.25 inch telescopic adjustment, and an 18.00 inch, four (4) spoke steering wheel located at the driver's position. The steering wheel shall be covered with black polyurethane foam padding.

The steering column shall contain a horn button, self-canceling turn signal switch, four-way hazard switch and headlamp dimmer switch.

ELECTRONIC POWER STEERING FLUID LEVEL INDICATOR

The power steering fluid shall be monitored electronically and shall send a signal to activate an audible alarm and visual warning in the instrument panel when fluid level falls below normal.

POWER STEERING PUMP

The hydraulic power steering pump shall be a TRW PS and shall be gear driven from the engine. The pump shall be a balanced, positive displacement, sliding vane type. The power steering system shall include an oil to air passive cooler.

FRONT AXLE CRAMP ANGLE

The chassis shall have a front axle cramp angle of 48-degrees to the left and 44-degrees to the right.

POWER STEERING GEAR

The power steering gear shall be a TRW model TAS 65 with an assist cylinder.

CHASSIS ALIGNMENT

The chassis frame rails shall be measured to insure the length is correct and cross checked to make sure they run parallel and are square to each other. The front and rear axles shall be laser aligned. The front tires and wheels shall be aligned and toe-in set on the front tires by the chassis manufacturer.

First Choice Fire & Safety Inc.

REAR AXLE

The rear axle shall be a Meritor model RS-25-160 single drive axle. The axle shall include precision forged, single reduction differential gearing, and shall have a fire service rated capacity of 27,000 pounds.

The axle shall be built of superior construction and quality components to provide the rugged dependability needed to stand up to the fire industry's demands. The axle shall include rectangular shaped, hot-formed housing with a standard wall thickness of 0.63 of an inch for extra strength and rigidity and a rigid differential case for high axle strength and reduced maintenance.

The axle shall have heavy-duty Hypoid gearing for longer life, greater strength and quieter operation. Industry-standard wheel ends for compatibility with both disc and drum brakes, and unitized oil seal technology to keep lubricant in and help prevent contaminant damage will be used.

REAR AXLE DIFFERENTIAL LUBRICATION

The rear axle differential shall be lubricated with oil.

REAR AXLE WARRANTY

The rear axle shall be warranted by Meritor for five (5) years with unlimited miles under the general service application. Details of the Meritor warranty are provided on the PDF document attached to this option.

REAR WHEEL BEARING LUBRICATION

The rear axle wheel bearings shall be lubricated with oil.

VEHICLE TOP SPEED

The top speed of the vehicle shall be approximately 68 MPH +/-2 MPH at governed engine RPM.

REAR SUSPENSION

The single rear axle shall feature a Reyco 79KB vari-rate, self-leveling captive slipper type conventional multi-leaf spring suspension, with 57.50 inch X 3.00 inch springs. One (1) adjustable and one (1) fixed torque rod shall be provided.

First Choice Fire & Safety Inc.

The rear suspension capacity shall be rated from 21,000 to 31,500 pounds.

TIRE INTERMITTENT SERVICE RATING

The chassis shall be rated using Intermittent Service ratings provided to the emergency vehicle market by the tire manufacturers as the basis for determining the maximum vehicle load and speed.

FRONT TIRE

The front tires shall be Michelin 425/65R22.5 "L" tubeless radial XFE regional tread.

The front tire stamped load capacity shall be 22,800 pounds per axle with a nominal speed rating of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum load capacity shall be 24,396 pounds per axle with a maximum speed of 65 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum speed capacity shall be 22,800 pounds per axle with a speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.

REAR TIRE

The rear tires shall be Michelin 12R-22.5 16PR "H" tubeless radial XDN2 all-weather tread.

The rear tire stamped load capacity shall be 27,120 pounds per axle with a nominal speed rating of 75 miles per hour when properly inflated to 120 pounds per square inch.

The Michelin Intermittent Service Rating maximum load capacity shall be 29,020 pounds per axle with a maximum speed of 75 miles per hour when properly inflated to 120 pounds per square inch.

First Choice Fire & Safety Inc.

The Michelin Intermittent Service Rating maximum speed capacity shall match the nominal speed rating.

The Michelin Intermittent Service Rating limits the operation of the emergency vehicle to no more than fifty (50) miles of continuous operation under maximum recommended payload, or without stopping for at least twenty (20) minutes. The emergency vehicle must reduce its speed to no more than 50 MPH after the first fifty (50) miles of travel.

REAR AXLE RATIO

The rear axle ratio shall be 5.13:1.

TIRE PRESSURE INDICATOR

There shall be electronic chrome LED valve caps shipped loose for installation by the OEM which shall illuminate with a red LED when tire pressure drops 8psi provided. The valve caps are self-calibrating and set to the pressure of the tire upon installation.

FRONT WHEEL

The front wheels shall be Alcoa hub piloted, 22.50 inch X 12.25 inch LvL One™ polished aluminum wheels. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts. The wheels shall feature one-piece forged strength and shall include Alcoa's Dura-Bright® finish as an integral part of the wheel surface. Alcoa Dura-Bright® wheels keep their shine without polishing. Brake dust, grime and road debris are easily removed by simply cleaning the wheels with soap and water.

REAR WHEEL

The rear wheels shall be Alcoa hub piloted, 22.50 inch X 8.25 inch LvL One™ aluminum wheels with a polished outer surface and Alcoa Dura-Bright® wheel treatment as an integral part of the wheel. The hub piloted mounting system shall provide easy installation and shall include two-piece flange nuts.

BALANCE WHEELS AND TIRES

All of the wheels and tires, including any spare wheels and tire assemblies, shall be dynamically balanced.

First Choice Fire & Safety Inc.

WHEEL TRIM

The front wheels shall include stainless steel lug nut covers and stainless steel baby moons shipped loose with the chassis for installation by the apparatus builder. The baby moons shall have cutouts for oil seal viewing when applicable.

The rear wheels shall include stainless steel lug nut covers and band mounted spring clip stainless steel high hats shipped loose with the chassis for installation by the apparatus builder.

The lug nut covers, baby moons, and high hats shall be RealWheels® brand constructed of 304L grade, non-corrosive stainless steel with a mirror finish. Each wheel trim component shall meet D.O.T. certification.

WHEEL GUARDS

The rear dual wheels shall include a plastic isolator approximately 0.04” thick installed between the inner and outer wheel to help prevent corrosion caused by metal to metal contact.

TIRE CHAINS

Insta-Chains, twelve (12) strand automatic ice chains shall be installed on the rear axle of the chassis to provide instant traction on ice and snow at speeds below 35 MPH.

TIRE CHAINS ACTIVATION

The tire chain system shall be activated by a virtual button on the Vista display and control screen. The virtual button shall display “Active” when the tire chains are engaged. The tire chains shall be interlocked with the transmission and shall engage only if the vehicle is traveling 30 MPH or less. After traveling over 30 MPH, the vehicle must be reduced to a speed below 5 MPH for the tire chains to be engaged or re-engaged. The virtual button, once the vehicle reaches 35 MPH shall be reset to “Inactive”. The vehicle must then reduce to a speed below 5 MPH to enable the tire chains virtual button.

BRAKE SYSTEM

A rapid build-up air brake system shall be provided. The air brakes shall include, at a minimum, a two (2) air tank, three (3) reservoir system with a total of 4152 cubic inch of air capacity. A floor mounted treadle valve shall be mounted inside the cab for graduated control of applying and releasing the brakes. An inversion

First Choice Fire & Safety Inc.

valve shall be installed to provide a service brake application in the unlikely event of primary air supply loss. All air reservoirs provided on the chassis shall be labeled for identification.

The rear axle spring brakes shall automatically apply in any situation when the air pressure falls below 25 PSI and shall include a mechanical means for releasing the spring brakes when necessary. An audible alarm shall designate when the system air pressure is below 60 PSI.

A four (4) sensor, four (4) modulator Anti-lock Braking System (ABS) shall be installed on the front and rear axles in order to prevent the brakes from locking or skidding while braking during hard stops or on icy or wet surfaces. This in turn shall allow the driver to maintain steering control under heavy braking and in most instances, shorten the braking distance. The electronic monitoring system shall incorporate diagonal circuitry which shall monitor wheel speed during braking through a sensor and tone ring on each wheel. A dash mounted ABS lamp shall be provided to notify the driver of a system malfunction. The ABS system shall automatically disengage the auxiliary braking system device when required. The speedometer screen shall be capable of reporting all active defaults using PID/SID and FMI standards.

Additional safety shall be accommodated through Automatic Traction Control (ATC) which shall be installed on the single rear axle. The ATC system shall apply the ABS when the drive wheels loose traction. The system shall scale the electronic engine throttle back to prevent wheel spin while accelerating on ice or wet surfaces.

A virtual style switch shall be provided and properly labeled “mud/snow”. When the switch is pressed once, the system shall allow a momentary wheel slip to obtain traction under extreme mud and snow conditions. During this condition the ATC light shall blink continuously notifying the driver of activation. Pressing the switch again shall deactivate the mud/snow feature.

The Electronic Stability Control (ESC) unit is a functional extension of the electronic braking system. It is able to detect any skidding of the vehicle about its vertical axis as well as any rollover tendency. The control unit comprises an angular-speed sensor that measures the vehicle’s motion about the vertical axis, caused, for instance, by cornering or by skidding on a slippery road surface. An acceleration sensor measures the vehicle’s lateral acceleration. The Controller Area Network (CAN) bus provides information on the steering angle. On the basis of lateral acceleration and steering angle, an integrated microcontroller calculates a theoretical angular speed for the stable vehicle condition.

First Choice Fire & Safety Inc.

FRONT BRAKES

The front brakes shall be Meritor EX225 Disc Plus disc brakes with 17.00 inch vented rotors.

REAR BRAKES

The rear brakes shall be Meritor 16.50 inch X 8.63 inch S-cam drum type. The brakes shall feature a cast iron shoe.

PARK BRAKE

Upon application of the push-pull valve in the cab, the rear brakes will engage via mechanical spring force. This is accomplished by dual chamber rear brakes, satisfying the FMVSS parking brake requirements.

PARK BRAKE CONTROL

A Meritor-Wabco manual hand control push-pull style valve shall operate the parking brake.

The parking brake actuation valve shall be mounted to the left side of the engine tunnel integrated into the transmission shift pod console within easy access of the driver.

REAR BRAKE SLACK ADJUSTERS

The rear brakes shall include Meritor automatic slack adjusters installed on the axle which features a simple, durable design offering reduced weight. The automatic slack adjusters shall feature a manual adjusting nut which cannot inadvertently be backed off and threaded grease fittings for easy serviceability.

REAR BRAKE DUST SHIELDS

The rear brakes shall be equipped with brake dust shields.

AIR DRYER

The brake system shall include a Wabco System Saver 1200 air dryer with an integral 100 watt heater with a Metri-Pack sealed connector. The air dryer incorporates an internal turbo cutoff valve that closes the path between the air compressor and air dryer purge valve during the compressor "unload" cycle. The turbo cutoff valve allows purging of moisture and contaminants without the loss

First Choice Fire & Safety Inc.

of turbo boost pressure. The air dryer shall be located on the right hand frame rail forward of the front wheel behind the right hand cab step.

FRONT BRAKE CHAMBERS

The front brakes shall be provided with MGM type 24 long stroke brake chambers.

REAR BRAKE CHAMBERS

The rear axle shall include TSE 30/36 brake chambers which shall convert the energy of compressed air into mechanical force and motion. This shall actuate the brake camshaft, which in turn shall operate the foundational brake mechanism forcing the brake shoes against the brake drum. The TSE Type 36 brake chamber has a 36.00 square inch effective area.

AIR COMPRESSOR

The air compressor provided for the engine shall be a Wabco[®] SS318 single cylinder pass-through drive type compressor which shall be capable of producing 18.7 CFM at 1200 engine RPMs. The air compressor shall feature a higher delivery efficiency translating to more air delivery per horsepower absorbed. The compressor shall include an aluminum cylinder head which shall improve cooling, reduce weight and decrease carbon formation. Superior piston and bore finishing technology shall reduce oil consumption and significantly increasing the system component life.

AIR GOVERNOR

An air governor shall be provided to control the cut-in and cut-out pressures of the engine mounted air compressor. The governor shall be calibrated to meet FMVSS requirements. The air governor shall be located on the air dryer bracket on the left frame rail behind the battery box.

AUXILIARY AIR RESERVOIR

One (1) auxiliary air reservoir with a 2084 cubic inch capacity shall be installed on the chassis to act as an additional reserve supply to the air system for air horn, air tool, or other non-service brake use. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

MOISTURE EJECTORS

First Choice Fire & Safety Inc.

Automatic moisture ejectors with a manual drain provision shall be installed on all reservoirs of the air supply system. The manual drain provision shall include an actuation pull cable coiled and tied at each drain valve. The supplied cables when extended shall be sufficient in length to allow each drain to be activated from the side of the apparatus.

AIR SUPPLY LINES

The air system on the chassis shall be plumbed with color coded reinforced nylon tubing air lines. The primary (rear) brake line shall be green, the secondary (front) brake line red, the parking brake line orange and the auxiliary (outlet) will be blue.

Brass compression type fittings shall be used on the nylon tubing. All drop hoses shall include fiber reinforced neoprene covered hoses.

AIR TANK SPACERS

There shall be spacers included with the air tank mounting. The spacers shall move the air tanks 1.50 inches inward towards the center of the chassis. This shall provide clearance between the air tanks and the frame for body U-bolt clearance.

REAR AIR TANK MOUNTING

If a combination of wheel base, air tank quantity, or other requirements necessitate the location of one or more air tanks to be mounted rear of the fuel tank, these tank(s) will be mounted perpendicular to frame.

WHEELBASE

The chassis wheelbase shall be 193.00 inches.

REAR OVERHANG

The chassis rear overhang shall be 42.00 inches.

FRAME

The frame shall consist of double rails running parallel to each other with cross members forming a ladder style frame. The frame rails shall be formed in the shape of a "C" channel, with the outer rail measuring 10.25 inches high X 3.50 inches deep upper and lower flanges X 0.38 inches thick with an inner channel of 9.44 inches high X 3.13 inches deep and 0.38 inches thick. Each rail shall be constructed

First Choice Fire & Safety Inc.

of 110,000 psi minimum yield high strength low alloy steel. Each double rail section shall be rated by a Resistance Bending Moment (RBM) minimum of 3,213,100 inch pounds and have a minimum section modulus of 29.21 cubic inches. The frame shall measure 35.00 inches in width.

Proposals calculating the frame strength using the “box method” shall not be considered.

Proposals including heat treated rails shall not be considered. Heat treating frame rails produces rails that are not uniform in their mechanical properties throughout the length of the rail. Rails made of high strength, low alloy steel are already at the required yield strength prior to forming the rail.

A minimum of seven (7) fully gusseted 0.25 inch thick cross members shall be installed. The inclusion of the body mounting, or bumper mounting shall not be considered as a cross member. The cross members shall be attached using zinc coated grade 8 fasteners. The bolt heads shall be flanged type, held in place by distorted thread flanged lock nuts. Each cross member shall be mounted to the frame rails utilizing a minimum of 0.25 inch thick gusset reinforcement plates at all corners balancing the area of force throughout the entire frame.

Any proposals not including additional reinforcement for each cross member shall not be considered.

All relief areas shall be cut in with a minimum 2.00 inch radius at intersection points with the edges ground to a smooth finish to prevent a stress concentration point.

The frame and cross members shall carry a lifetime warranty to the original purchaser. A copy of the frame warranty shall be made available upon request.

Proposals offering warranties for frames not including cross members shall not be considered.

FRAME WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY TERMS CAN BE FOUND IN THE CHASSIS WARRANTY DOCUMENT, WHICH CONTAINS THE COMPLETE STATEMENT OF THE WARRANTY. SPARTAN’S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

First Choice Fire & Safety Inc.

The frame and cross members shall carry a limited lifetime warranty to the original purchaser. The warranty period shall commence on the date the vehicle is delivered to the first end user.

FRAME PAINT

The frame rails shall be hot dip galvanized prior to assembly and attachment of any components. The components that shall be galvanized shall include:

- Main frame “C” channel or channels

The frame parts which are not galvanized shall be powder coated prior to any attachment of components. Parts which shall be powder coated shall include but are not limited to:

- Steering gear bracket
- Front splayed rails and fish plates
- Bumper extensions
- Cross members
- Cross member gussets
- Fuel tank mounting brackets
- Fuel tank straps (unless material/finish is specified in 3130 subcat)
- Air tanks (unless color coded tanks are specified in 3205 subcat)
- Air tank mounting brackets
- Exhaust mounting brackets
- Air cleaner skid plate
- Radiator skid plate
- Battery supports, battery trays and battery covers

Other non-galvanized under carriage components which are received from the suppliers with coatings already applied shall include but are not limited to:

- Suspension components
- Front and rear axles

All powder coatings, primers and paint used on the non-galvanized components shall be compatible with all metals, pretreatments and primers used. The cross hatch adhesion test per ASTM D3359 shall not have a fail of more than ten (10) squares. The pencil hardness test per ASTM D3363 shall have a final post-curved pencil hardness of H-2H. The direct impact resistance test per ASTM D2794 shall have an impact resistance of 120.00 inches per pound at 2 mils.

First Choice Fire & Safety Inc.

FRONT BUMPER

A one piece, two (2) rib wrap-around style, polished stainless steel front bumper shall be provided. The material shall be 10 gauge 304 stainless steel, 12.00 inches high and 99.00 inches wide.

FRONT BUMPER EXTENSION LENGTH

The front bumper shall be extended approximately 21.00 inches ahead of the cab.

FRONT BUMPER SUCTION PROVISION

The bumper apron shall include a 5.00 inch stainless steel pipe intended for use as a suction intake for the pump. The suction pipe shall be routed from the right hand front bumper area to the area rear of the front axle near the back of the cab.

The front of the suction pipe shall be designed to terminate vertically approximately 3.50 inches below the top surface of the bumper in the right hand outboard position.

The forward end of the suction pipe shall be finished with a 5.00 inch National Pipe Thread (NPT). The rear of the suction shall include a Victaulic groove for connecting to the pump plumbing. The suction pipe shall also include a 0.50 inch NPT port intended as a primer assist connection.

The apparatus manufacturer shall plumb the suction pipe to the pump and shall provide all valves as required.

FRONT BUMPER APRON

The 21.00 inch extended front bumper shall include an apron constructed of 0.19 inch thick embossed aluminum tread plate.

The apron shall be installed between the bumper and the front face of the cab affixed using stainless steel bolts attaching the apron to the top bumper flange.

FRONT BUMPER COMPARTMENT CENTER

The front bumper shall include a compartment in the bumper apron located in the center between the frame rails which may be used as a hose well. The compartment shall be constructed of 0.13 inch 5052-H32 grade aluminum and shall include drain holes in the bottom corners to allow excess moisture to escape. The compartment shall include a notched cover constructed of 0.19 inch thick

First Choice Fire & Safety Inc.

bright embossed aluminum tread plate. The notch shall be located in the left front portion of the cover and shall be 4.00 inches in length with a 2.00 inches wide radius.

FRONT BUMPER COMPARTMENT COVER HARDWARE

The front bumper compartment cover(s) shall include gas cylinder stays which shall hold the cover open. Each cover shall be held in the closed position via a D-ring style latch.

MECHANICAL SIREN

The front bumper shall include an electro mechanical Federal Q2B™ siren, which shall be streamlined, chrome-plated and shall produce 123 decibels of sound at 10.00 feet. The Q2B™ siren produces a distinctive warning sound that is recognizable at long distances. A unique clutch design provides a longer coast down sound while reducing the amp draw to 100 amps. The siren shall measure 10.50 inches wide X 10.00 inches high X 14.00 inches deep. The siren shall include mounting hardware designed to recess or flush mount.

MECHANICAL SIREN LOCATION

The siren shall be recess mounted on the left side of the front fascia of the bumper, in the inboard position.

MECHANICAL SIREN ACCESSORIES

The front of the siren shall include (2) stainless steel flat bars approximately 1.00 inch wide by 19.00 inches long. Each bar shall be placed vertically on the right and left side of the siren face wrapping around towards the back of the siren into the bumper extension offering protection to the Q2B siren.

AIR HORN

The front bumper shall include two (2) Hadley brand E-Tone air horns which shall measure 21.00 inches long with a 6.00 inch round flare. The air horns shall be trumpet style with a chrome finish on the exterior and a painted finish deep inside the trumpet.

AIR HORN LOCATION

The air horns shall be recess mounted in the front bumper fascia between the frame rails in the right and left outboard positions.

First Choice Fire & Safety Inc.

AIR HORN RESERVOIR

One (1) air reservoir, with a 2084 cubic inch capacity, shall be installed on the chassis to act as a supply tank for operating air horns. The reservoir shall be isolated with a 90 PSI pressure protection valve on the reservoir supply side to prevent depletion of the air to the air brake system.

ELECTRONIC SIREN SPEAKER

There shall be one (1) Cast Products Inc. model SA4301, 100 watt speaker provided. The speaker shall measure 6.20 inches tall X 7.36 inches wide X 3.06 inches deep. The speaker shall include a flat mounting flange which shall be polished aluminum.

ELECTRONIC SIREN SPEAKER LOCATION

The electronic siren speaker shall be located on the front bumper face on the right side outboard of the frame rail in the inboard position.

FRONT BUMPER TOW HOOKS

Two (2) heavy duty tow hooks, painted to match the frame components, shall be installed below the front bumper in the forward position, bolted directly to the underside of each chassis frame rail with grade 8 bolts.

CAB TILT SYSTEM

The entire cab shall be capable of tilting approximately 45-degrees to allow for easy maintenance of the engine and transmission. The cab tilt pump assembly shall be located on the right side of the chassis above the battery box.

The electric-over-hydraulic lift system shall include an ignition interlock and red cab lock down indicator lamp on the tilt control which shall illuminate when holding the "Down" button to indicate safe road operation.

It shall be necessary to activate the master battery switch and set the parking brake in order to tilt the cab. As a third precaution the ignition switch must be turned off to complete the cab tilt interlock safety circuit.

Two (2) spring-loaded hydraulic hold down hooks located outboard of the frame shall be installed to hold the cab securely to the frame. Once the hold-down hooks

First Choice Fire & Safety Inc.

are set in place, it shall take the application of pressure from the hydraulic cab tilt lift pump to release the hooks.

Two (2) cab tilt cylinders shall be provided with velocity fuses in each cylinder port. The cab tilt pivots shall be 1.90 inch ball and be anchored to frame brackets with 1.25 inch diameter studs.

A steel safety channel assembly, painted safety yellow shall be installed on the right side cab lift cylinder to prevent accidental cab lowering. The safety channel assembly shall fall over the lift cylinder when the cab is in the fully tilted position. A cable release system shall also be provided to retract the safety channel assembly from the lift cylinder to allow the lowering of the cab. The release system cable shall be extended 5.00 feet.

CAB TILT AUXILIARY PUMP

A manual cab tilt pump module shall be attached to the cab tilt pump housing.

CAB TILT ALARM

A Preco Matic model 1059 audible alarm shall be installed and shall automatically activate the pulsed warble sounding alarm when the cab tilt is actuated acting as a notification and warning.

CAB TILT CONTROL RECEPTACLE

The cab tilt control cable shall include a receptacle which shall be temporarily located on the right hand chassis rail rear of the cab to provide a place to plug in the cab tilt remote control pendant. The tilt pump shall include 8.00 feet of cable with a six (6) pin Deutsch receptacle with a cap.

The remote control pendant shall include 20.00 feet of cable with a mating Deutsch connector. The remote control pendant shall be shipped loose with the chassis.

CAB TILT NOISE DAMPENER

In an effort to reduce the amount of noise created by the cab tilt lock down system, sound dampening spray-on materials shall be utilized to insulate contact points in the system to help prevent metallic sounds from occurring while traversing rough roads.

CAB TILT LOCK DOWN INDICATOR

First Choice Fire & Safety Inc.

The cab dash shall include a message located within the dual air pressure gauge which shall alert the driver when the cab is unlocked and ajar. The alert message shall cease to be displayed when the cab is in the fully lowered position and the hold down hooks are secured and locked to the cab mounts.

In addition to the alert message an audible alarm shall sound when the cab is unlocked and ajar with the parking brake released.

CAB WINDSHIELD

The cab windshield shall have a surface area of 2825.00 square inches and be of a two (2) piece wraparound design for maximum visibility.

The glass utilized for the windshield shall include standard automotive tint. The left and right windshield shall be fully interchangeable thereby minimizing stocking and replacement costs.

Each windshield shall be installed using black self locking window rubber.

GLASS FRONT DOOR

The front cab doors shall include a window which is 27.00 inches in width X 26.00 inches in height. These windows shall have the capability to roll down completely into the door housing. This shall be accomplished using electric actuation. The left and right front door windows shall be controlled using a switch on each respective side inner door panel. The driver's door shall include a switch for each powered door window in the cab.

There shall be an irregular shaped fixed window which shall measure 2.50 inches wide at the top, 8.00 inches wide at the bottom X 26.00 inches in height, more commonly known as "cozy glass" ahead of the front door roll down windows.

The windows shall be mounted within the frame of the front doors trimmed with a black anodized ring on the exterior.

GLASS TINT FRONT DOOR

The windows located in the left and right front doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

First Choice Fire & Safety Inc.

GLASS REAR DOOR RH

The rear right hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the door panel ledge and on the driver's control panel.

GLASS TINT REAR DOOR RIGHT HAND

The window located in the right hand side rear window shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS REAR DOOR LH

The rear left hand side crew door shall include a window which is 27.00 inches in width X 26.00 inches in height. The window shall be a powered type and shall be controlled by a switch on the door panel ledge and on the driver's control panel.

GLASS TINT REAR DOOR LEFT HAND

The window located in the left hand side rear door shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

GLASS SIDE MID RH

The cab shall include a window on the right side behind the front and ahead of the crew door which shall measure 16.00 inches wide X 26.00 inches high. This window shall be fixed within this space and shall be rectangular in shape. The window shall be mounted using self locking window rubber. The glass utilized for this window shall include a green automotive tint unless otherwise noted.

GLASS TINT SIDE MID RIGHT HAND

The window located on the right hand side of the cab between the front and rear doors shall include a dark gray automotive tint which shall allow forty-five percent (45%) light transmittance. The dark tint shall aid in cab cooling and help protect passengers from radiant solar energy.

CLIMATE CONTROL

First Choice Fire & Safety Inc.

A ceiling mounted combination defroster and cabin heating and air conditioning system shall be located above the engine tunnel area. The system covers and plenums shall be of severe duty design made of aluminum which shall be coated with a customer specified interior paint. The design of the system's covers shall provide quick access to washable air intake filters as well as easy access to other serviceable items.

Six (6) adjustable louvers shall provide comfort for the front seat occupants and ten (10) adjustable louvers shall provide comfort for the rear crew occupants. The plenum shall be shortened to terminate in the mid crew area on cabs with 10.00 inch raised roofs and greater. This shortened plenum shall allow for the customer to utilize the upper rear center wall for compartmentation, equipment, or apparatus operations.

Separate front and rear blower motors shall be of brushless design and shall be controlled independently. It shall be capable of reducing the interior cabin air temperature from 122° F (+/- 3° F) to 80° F in thirty minutes with 50% relative humidity and full solar load as described in SAE J2646.

The system shall also provide heater pull up performance which meets or exceeds the performance requirements of SAE J1612 as well as defrost performance that meets or exceeds the performance requirements of SAE J381.

A gravity drain system shall be provided that is capable of evacuating condensate from the vehicle while on a slope of up to a 13% grade in any direction.

The air conditioning system plumbing shall be a mixture of custom bent zinc coated steel fittings and Aeroquip flexible hose with Aeroquip EZ-Clip fittings.

The overhead heater/defroster plumbing shall include an electronic flow control valve that re-directs hot coolant away from the evaporator, via a bypass loop, as the temperature control is moved toward the cold position.

Any component which needs to be accessed to perform system troubleshooting shall be accessible by one person using basic hand tools. Regularly serviced items shall be replaceable by one person using basic hand tools.

*****Spartan Motors Inc. recommends that the overall climate system performance be based off third-party testing in accordance to Society of Automotive Engineering standards as a complete system.***

First Choice Fire & Safety Inc.

Individual component level BTU ratings is not an accurate indicator of the performance capability of the completed system. System individual component BTU ratings:

- Air conditioning evaporator total BTU/HR: 82,000
- Air conditioning condenser total BTU/HR: 59,000
- Heater coil total BTU/HR: 98,000

Performance data specified is based on testing performed by an independent third-party test facility using a medium four-door 10" Raised roof Gladiator chassis equipped with an ISL engine.

CLIMATE CONTROL DRAIN

The climate control system shall include a gravity drain for water management. The gravity drain shall remove condensation from the air conditioning system without additional mechanical assistance.

CLIMATE CONTROL ACTIVATION

The heating, defrosting and air conditioning controls shall be in the center dash center switch panel, in a position which is easily accessible to the driver. The climate control shall be activated by a rotary switch.

HVAC OVERHEAD COVER PAINT

The overhead HVAC cover shall be painted with a multi-tone black-black texture finish.

A/C CONDENSER LOCATION

A roof mounted A/C condenser shall be installed centered on the cab forward of the raised roof against the slope rise.

A/C COMPRESSOR

The air-conditioning compressor shall be a belt driven, engine mounted compressor. The compressor shall be compatible with R134-a refrigerant.

***Spartan Motors Inc. recommends that the overall climate system performance be based off third-party testing in accordance to Society of Automotive Engineering standards as a complete system.*

First Choice Fire & Safety Inc.

Individual component level ratings are not an accurate indicator of the performance capability of the completed system.

Refrigerant Compressor displacement: 19.1 cubic inches per revolution.

UNDER CAB INSULATION

The underside of the cab tunnel surrounding the engine shall be lined with multi-layer insulation, engineered for application inside diesel engine compartments.

The insulation shall act as a noise barrier, absorbing noise thus keeping the decibel level in the cab well within NFPA recommendations. As an additional benefit, the insulation shall assist in sustaining the desired temperature within the cab interior.

The engine tunnel insulation shall measure approximately 0.30 inch thick including a multi-layer foil faced glass cloth and polyester fiber layer. The foil surface acts as protection against heat, moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The cab floor insulation shall measure approximately 0.30 inch thick including a multi-layer foil faced glass cloth and polyester fiber layer. The foil surface acts as protection against heat, moisture and other contaminants. The insulation shall meet or exceed FMVSS 302 flammability test.

The insulation shall be cut precisely to fit each section and sealed for additional heat and sound deflection. The insulation shall be held in place by acrylic pressure sensitive adhesive.

INTERIOR TRIM FLOOR

The floor of the cab shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive and aluminum trim molding. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

INTERIOR TRIM

The cab interior shall include trim on the front ceiling, rear crew ceiling, and the cab walls. It shall be easily removable to assist in maintenance. The trim shall be constructed of insulated vinyl over a hard board backing.

REAR WALL INTERIOR TRIM

First Choice Fire & Safety Inc.

The rear wall of the cab shall be trimmed with vinyl.

HEADER TRIM

The cab interior shall feature header trim over the driver and officer dash constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum.

TRIM CENTER DASH

The main center dash area shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate. There shall be four (4) holes located on the top of the dash near each outer edge of the electrical access cover for ventilation. The center dash electrical access cover shall include a gas cylinder stay which shall hold the cover open during maintenance.

TRIM LH DASH

The left hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 inch thick aluminum plate for a perfect fit around the instrument panel. For increased occupant protection the extreme duty left hand dash utilizes patent pending break away technology to reduce rigidity in the event of a frontal crash. The left hand dash shall offer lower vertical surface area to the left and right of the steering column to accommodate control panels.

TRIM RH DASH

The right hand dash shall be constructed of 5052-H32 Marine Grade, 0.13 of an inch thick aluminum plate and shall include a glove compartment with a hinged door and a Mobile Data Terminal (MDT) provision. The glove compartment size will measure 14.00 inches wide X 6.38 inches high X 5.88 inches deep. The MDT provision shall be provided above the glove compartment.

ENGINE TUNNEL TRIM

The cab engine tunnel shall be covered with a multi-layer mat consisting of 0.25 inch thick sound absorbing closed cell foam with a 0.06 inch thick non-slip vinyl surface with a pebble grain finish. The covering shall be held in place by a pressure sensitive adhesive.

The cab engine tunnel shall have an overlay of 5052-H32 aluminum plate which shall feature a Spar-Liner spray on bedliner coating, colored to match the cab paint interior finish color scheme. The aluminum plate shall be held down with

First Choice Fire & Safety Inc.

screws. All exposed seams shall be sealed with silicone caulk matching the color of the floor mat to reduce the chance of moisture and debris retention.

ENGINE TUNNEL ACCESSORIES

The engine tunnel shall feature a fabricated aluminum console which shall include a large storage bin with dividers and a map compartment. There shall be two (2) cup holders included in the console.

POWER POINT DASH MOUNT

The cab shall include two (2) 12 volt cigarette lighter type receptacles in the switch panel to provide a power source for 12 volt electrical equipment. The cab shall also include one (1) Blue Sea dual universal serial bus (USB) charging receptacle in the cab dash to provide a power source for USB chargeable electrical equipment. The USB port shall be capable of a 5 Volt-2.1 amp total output. The receptacles shall be wired battery direct.

STEP TRIM

Each cab entry door shall include a three step entry. The first step closest to the ground shall be constructed of SAE 304 stainless steel with embossed perforations and diamond shaped cutout. The perforations and cutouts shall allow water and other debris to flow through rather than becoming trapped within the stepping surface. The step shall feature a splash guard to reduce water and debris from splashing in to the step. The splash guard shall have drainage holes beneath the back of the step to allow debris and water to flow through rather than becoming trapped within the stepping surface. The stainless steel material shall have a number 8 mirror finish. The lower step shall be mounted to a frame which is integral with the construction of the cab for rigidity and strength. The middle step shall be integral with the cab construction and shall be trimmed with a Flex-Tred[®] adhesive grit surface material.

UNDER CAB ACCESS DOOR

The cab shall include an aluminum access door in the left crew step riser painted to match the cab interior paint with a push and turn latch. The under cab access door shall provide access to the diesel exhaust fluid fill.

INTERIOR DOOR TRIM

First Choice Fire & Safety Inc.

The interior trim on the doors of the cab shall consist of a two (2) piece panel constructed of SAE 304 stainless steel. The stainless steel shall have a brushed finish.

DOOR TRIM KICKPLATE

The inner door panels shall include a stainless steel kick plate which shall be fastened to the lower portion of door panel. The stainless steel kick plate shall include a number seven mirror finish.

DOOR TRIM CUSTOMER NAMEPLATE

The interior door trim on the front doors shall include a customer nameplate which states the vehicle was custom built for their Department.

CAB DOOR TRIM REFLECTIVE

The interior of each door shall include high visibility reflective tape. A white reflective tape shall be provided vertically along the rear outer edge of the door. The lowest portion of each door skin shall include a reflective tape chevron with red and white stripes and a Spartan logo. The chevron tape shall measure 6.00 inches in height.

INTERIOR GRAB HANDLE "A" PILLAR

There shall be two (2) rubber covered 11.00 inch grab handles installed inside the cab, one on each "A" post at the left and right door openings. The left handle shall be located 7.88 inches above the bottom of the door window opening and the right handle shall be located 2.88 inches above the bottom of the door window opening. The handles shall assist personnel in entering and exiting the cab.

INTERIOR GRAB HANDLE FRONT DOOR

Each front door shall include one (1) ergonomically contoured 9.00 inch cast aluminum handle mounted horizontally on the interior door panels. The handles shall feature a textured black powder coat finish to assist personnel entering and exiting the cab.

INTERIOR GRAB HANDLE REAR DOOR

A black powder coated cast aluminum assist handle shall be provided on the inside of each rear crew door. A 30.00 inch long handle shall extend horizontally

First Choice Fire & Safety Inc.

the width of the window just above the window sill. The handle shall assist personnel in exiting and entering the cab.

INTERIOR SOFT TRIM COLOR

The cab interior soft trim surfaces shall be gray in color.

INTERIOR TRIM SUNVISOR

The header shall include two (2) sun visors, one each side forward of the driver and officer seating positions above the windshield. Each sun visor shall be constructed of Masonite and covered with padded black vinyl trim.

INTERIOR FLOOR MAT COLOR

The cab interior floor mat shall be black in color.

HEADER TRIM INTERIOR PAINT

The metal surfaces in the header area shall feature a black Spar-Liner spray on bedliner coating.

TRIM CENTER DASH INTERIOR PAINT

The entire center dash and any accessory pods attached to the dash shall feature a black Spar-Liner spray on bedliner coating.

TRIM LEFT HAND DASH INTERIOR PAINT

The left hand dash shall feature a black Spar-Liner spray on bedliner coating.

TRIM RIGHT HAND DASH INTERIOR PAINT

The right hand dash shall feature a black Spar-Liner spray on bedliner coating.

ENGINE TUNNEL ACCESSORIES PAINT

The engine tunnel accessories shall feature a black Spar-Liner spray on bedliner coating.

DASH PANEL GROUP

First Choice Fire & Safety Inc.

The main center dash area shall include three (3) removable panels located one (1) to the right of the driver position, one (1) in the center of the dash and one (1) to the left of the officer position. The center panel shall be within comfortable reach of both the driver and officer.

SWITCHES CENTER PANEL

The center dash panel shall include six (6) switch positions in the upper left portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SWITCHES LEFT PANEL

The left dash panel shall include three (3) switches. There shall be one (1) headlight switch over one (1) windshield wiper/washer control switch and one (1) instrument lamp dimmer switch on the left hand portion of the panel. All switches shall have backlighting provided.

SWITCHES RIGHT PANEL

The right dash panel shall include two (2) rocker switch positions in the upper left hand portion of the panel.

A rocker switch with a blank legend installed directly above shall be provided for any position without a switch and legend designated by a specific option. The non-specified switches shall be two-position, black switches with a green indicator light. Each blank switch legend can be custom engraved by the body manufacturer. All switch legends shall have backlighting provided.

SEAT BELT WARNING

A Weldon seat belt warning system, integrated with the Vehicle Data Recorder system, shall be installed for each seat within the cab. The system shall provide a visual warning indicator in the Vista display and control screen(s), an indicator light in the instrument panel, and an audible alarm.

The warning system shall activate when any seat is occupied with a minimum of 60 pounds, the corresponding seat belt remains unfastened, and the park brake is

First Choice Fire & Safety Inc.

released. The warning system shall also activate when any seat is occupied, the corresponding seat belt was fastened in an incorrect sequence, and the park brake is released. Once activated, the visual indicators and audible alarm shall remain active until all occupied seats have the seat belts fastened.

SEAT MATERIAL

The Bostrom Firefighter seats shall include a covering of extra high strength, wear resistant fabric made of durable low seam Durawear Plus™ ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Durawear Plus™ meets or exceeds specification of the common trade name Imperial 1800. The material meets FMVSS 302 flammability requirements.

If applicable, Theatre style seats located in the cab shall be high strength, wear resistant fabric made of durable ballistic polyester. A PVC coating shall be bonded to the back side of the material to help protect the seats from UV rays and from being saturated or contaminated by fluids. Common trade names for this material are Imperial 1200 and Durawear.

SEAT COLOR

All seats supplied with the chassis shall be black in color. All seats shall include red seat belts.

SEAT BACK LOGO

The seat back shall include the “4-Guys” logo. The logo shall be centered on the standard headrest of the seat back and on the left side of a split headrest.

SEAT DRIVER

The driver's seat shall be an H.O. Bostrom 500 Series Firefighter Sierra model seat with air suspension. The four-way seat shall feature a 3.00 inches vertical travel air suspension and manual fore and aft adjustment with 5.00 inches of travel. The suspension control shall be located on the seat below the left front corner of the bottom cushion. The seat shall also feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment

First Choice Fire & Safety Inc.

feature to provide enhanced comfort and safety by allowing customized seat belt fit.

This model of seat shall have successfully completed the static load tests set forth by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208.

The materials used in construction of the seat shall also have successfully completed testing with regard to the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which dictates the allowable burning rate of materials in the occupant compartments of motor vehicles.

SEAT MOUNTING DRIVER

The driver's seat shall be installed in an ergonomic position in relation to the cab dash.

OCCUPANT PROTECTION DRIVER

The driver's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The driver's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the driver, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the driver's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to the driver in a qualifying event by covering the window and the upper portion of the door.

First Choice Fire & Safety Inc.

- Dual knee airbags (patent pending) with energy management mounting (patent pending) - protects the driver's lower body from dangerous surface contact injuries, acceleration injuries, and from intrusion as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

Steering wheel airbag - protects the driver's head, neck, and upper torso from contact injuries, acceleration injuries, and contact points with intrusive surfaces as a result of a collision.

SEAT OFFICER

The officer's seat shall be an H.O. Bostrom 500 Series Sierra model seat. The seat shall feature six-way electric positioning. The six (6) positions shall include up and down, fore and aft and front and rear tilt. The seat shall also feature integral springs to isolate shock.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt, automatic retractor and buckle as an integral part of the seat assembly. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches measured with the seat height adjusted to the lowest position of travel.

This model of seat shall have successfully completed the static load tests by FMVSS 207, 209, 210 and 302 in effect at the time of manufacture. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK OFFICER

The officer's seat shall feature a SecureAll™ SCBA locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

First Choice Fire & Safety Inc.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING OFFICER

The officer's seat shall offer a special mounting position which is 4.00 inches rearward of the standard location offering increased leg room for the occupant.

OCCUPANT PROTECTION OFFICER

The officer's position shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

The officer's seating area APS shall include:

- Advanced seat belt system - retractor pre-tensioner tightens the seat belt around the officer, securing the occupant in the seat and the load limiter plays out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.
- Large side curtain airbag - protects the officer's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to the officer in a qualifying event by covering the window and the upper portion of the door.

First Choice Fire & Safety Inc.

Knee airbags - protects the officer's lower body from dangerous surface contact injuries, acceleration injuries, and from contact points with intrusive surfaces as a result of a collision as well as locks the lower body in place so the upper body shall be slowed by the load limiting seat belt.

POWER SEAT WIRING

The power seat or seats installed in the cab shall be wired directly to battery power.

SEAT BELT ORIENTATION CREW

The crew position seat belts shall follow the standard orientation which extends from the outboard shoulder extending to the inboard hip.

SEAT REAR FACING OUTER LOCATION

The crew area shall include one (1) rear facing crew seat located directly behind the right side front seat.

SEAT CREW REAR FACING OUTER

The crew area shall include a seat in the rear facing outboard position which shall be a H.O. Bostrom 500 Series Firefighter model seat. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for this belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using

First Choice Fire & Safety Inc.

FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK REAR FACING OUTER

The rear facing outboard seat shall feature a Bostrom SecureAll™ self contained breathing apparatus (SCBA) locking system which shall store most U.S. and International SCBA brands and bottle sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the center of the bottom seat cushion for easy access and to eliminate hooking the release handle with clothing or other equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING REAR FACING OUTER

The rear facing outer seats shall offer a special mounting position 3.75 inches rearward of the standard mounting location offering additional room ahead of the seat.

OCCUPANT PROTECTION RFO

First Choice Fire & Safety Inc.

The rear facing outer seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each rear facing outer seating position APS shall include:

- APS advanced seat belt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - protects each occupant's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to each seating position with an airbag custom designed for each cab configuration.

SEAT FORWARD FACING OUTER LOCATION

The crew area shall include two (2) forward facing outboard seats, which include one (1) located next to the outer wall of the cab on the left side of the cab and one (1) located next to the outer wall on the right side of the cab.

SEAT CREW FORWARD FACING OUTER

The crew area shall include a seat in the forward facing outer position which shall be a H.O. Bostrom 500 Series Firefighter model seat. The seat shall feature a tapered and padded seat back and cushion.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

First Choice Fire & Safety Inc.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK FORWARD FACING OUTER

The forward facing outboard seat shall feature a SecureAll™ self contained breathing apparatus (SCBA) locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

SEAT MOUNTING FORWARD FACING OUTER

First Choice Fire & Safety Inc.

The forward facing outer seat shall be mounted inboard from the side wall for additional clearance facing the front of the cab.

OCCUPANT PROTECTION FFO

The forward facing outer seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each forward facing outer seating position APS shall include:

- APS advanced seatbelt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - protects each occupant's head, neck, and upper body from dangerous cab side surfaces and contact points with intrusive surfaces as a result of a collision as well as provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to each seating position with an airbag custom designed for each cab configuration.

SEAT FORWARD FACING CENTER LOCATION

The crew area shall include one (1) forward facing center crew seat located directly behind the engine tunnel in the center of the cab.

SEAT CREW FORWARD FACING CENTER

The forward facing center seat shall be a H.O. Bostrom 500 Series Firefighter model seat. The seat shall feature a tapered and padded seat, and cushion. The seat shall be mounted in a fixed position.

The seat shall feature an all belts to seat (ABTS) style of safety restraint. The ABTS feature shall include a three-point shoulder harness with the lap belt and automatic retractor as an integral part of the seat assembly. The buckle portion of the seat belt shall extend from the seat base towards the driver position within easy reach of the occupant. The ABTS feature shall also include the RiteHite™ shoulder adjustment feature to provide enhanced comfort and safety by allowing customized seat belt fit.

First Choice Fire & Safety Inc.

The minimum vertical dimension from the seat H-point to the ceiling for each belted seating position shall be 35.00 inches.

This model of seat shall have successfully completed the static load tests by FMVSS 207/210. This testing shall include a simultaneous forward load of 3000 pounds each on the lap and shoulder belts and twenty (20) times the weight through the center of gravity. This model of seat installed in the cab model, as specified, shall have successfully completed the dynamic sled testing using FMVSS 208 as a guide with the following accommodations. In order to reflect the larger size outfitted firefighters, the test dummy used shall be a 95th percentile hybrid III male weighing 225 pounds rather than the 50th percentile male dummy weighing 165 pounds as referenced in FMVSS 208. The model of seats shall also have successfully completed the flammability of materials used in the occupant compartments of motor vehicles as outlined in FMVSS 302, of which decides the burning rate of materials in the occupant compartments of motor vehicles.

SEAT BACK FORWARD FACING CENTER

The forward facing center seat shall feature a SecureAll™ self contained breathing apparatus (SCBA) locking system which shall be one bracket model and store most U.S. and International SCBA brands and sizes while in transit or for storage within the seat back. The bracket shall be easily adjustable for all SCBA brands and cylinder diameters. All adjustment points shall utilize similar hardware and adjustments shall be made with one tool.

The bracket shall be adjustable to compensate for different cylinder lengths without the use of tools. The adjustment shall be made by raising a lever and moving the top clamp vertically.

The bracket system shall be free of straps and clamps that may interfere with auxiliary equipment on SCBA units. The center guide fork shall keep the SCBA tank in place for a safe and comfortable fit in the seat back cavity. The SCBA unit simply needs to be pushed against the pivot arm to engage the patented auto-locking system. Once the lock is engaged, the top clamp shall surround the top of the SCBA tank for a secure fit in all directions.

The SecureAll™ shall include a release handle which shall be integrated into the seat cushion for quick and easy release. This shall eliminate the need for straps or pull cords to interfere with other SCBA equipment.

The seat back shall include a removable padded cover which shall be provided over the SCBA cavity.

First Choice Fire & Safety Inc.

OCCUPANT PROTECTION FFC

The forward facing center seat position(s) shall be equipped with the Advanced Protection System™ (APS). The APS shall selectively deploy integrated systems to protect against injuries in qualifying frontal impact, side impact, and rollover events. The increase in survivable space and security of the APS shall also provide ejection mitigation protection.

Each forward facing center seating position APS shall include:

- APS advanced seatbelt system - retractor pre-tensioners tighten the seat belts around each occupant, securing the occupants in seats and load limiters play out some of the seat belt webbing to reduce seat belt to chest and torso force upon impact as well as mitigate head and neck injuries.

Side curtain airbag - provides ejection mitigation protection to each occupant in a qualifying event by covering the windows and walls adjacent to crew seating with an airbag custom designed for each cab configuration.

SEAT FRAME FORWARD FACING

The forward facing center seating positions shall include a full width seat frame located and installed at the rear wall. The seat frame shall span the available space on the rear wall. The seat frame shall be 12.38 inches high X 22.00 inches deep. The seat frame shall be constructed of Marine Grade 5052-H32 0.19 inch thick aluminum plate. The seat box shall be painted with the same color as the remaining interior.

SEAT FRAME FORWARD FACING STORAGE ACCESS

There shall be one (1) access point to the storage area centered on the front of the seat frame. This access point shall be covered by a hinged door to allow access for storage in the seat box.

SEAT MOUNTING FORWARD FACING CENTER

The forward facing center seats shall be installed facing the front of the cab.

SEAT FRAME EXTERIOR REAR COMPARTMENT ACCESS

The seat frame shall be open to the exterior rear compartment on both the right hand side and the left hand side. This shall allow interior access to the left and right exterior rear compartments.

First Choice Fire & Safety Inc.

CAB FRONT UNDERSEAT STORAGE ACCESS DOOR

The right under seat storage area shall have a solid aluminum hinged door with non-locking latch.

SEAT COMPARTMENT DOOR FINISH

All underseat storage compartment access doors shall feature a black Spar-Liner spray on bedliner coating.

WINDSHIELD WIPER SYSTEM

The cab shall include a triple arm linkage wiper system which shall clear the windshield of water, ice and debris. There shall be two (2) windshield wipers; each shall be affixed to a radial arm. The wiper motor shall be activated by an intermittent wiper control located within easy reach of the driver's position.

ELECTRONIC WINDSHIELD FLUID LEVEL INDICATOR

The windshield washer fluid level shall be monitored electronically. When the washer fluid level becomes low the yellow "Check Message Center" indicator light on the instrument panel shall illuminate and the message center in the dual air pressure gauge shall display a "Check Washer Fluid Level" message.

CAB DOOR HARDWARE

The cab entry doors shall be equipped with exterior pull handles, suitable for use while wearing firefighter gloves. The handles shall be made of aluminum with a chrome plated finish.

The interior exit door handles shall be flush paddle type with a black finish, which are incorporated into the upper door panel.

All cab entry doors shall include locks which are keyed alike. The door locks shall be designed to prevent accidental lockout.

The exterior pull handles shall include a scuff plate behind the handle constructed of polished stainless steel to help protect the cab finish.

DOOR LOCKS

First Choice Fire & Safety Inc.

Each cab entry door shall include a manually operated door lock. Each door lock may be actuated from the inside of the cab by means of a red knob located on the paddle handle of the respective door or by using a TriMark key from the exterior. The door locks are designed to prevent accidental lock out.

DOOR LOCK LH EMS COMPARTMENT

The left hand side EMS compartment shall feature a manual door lock.

DOOR LOCK LH REAR CAB COMPARTMENT

The left hand side rear compartment shall feature a manual door lock.

DOOR LOCK RH REAR CAB COMPARTMENT

The right hand side rear compartment shall feature a manual door lock.

GRAB HANDLES

The cab shall include one (1) 18.00 inch knurled, anti-slip, one-piece exterior assist handle behind each cab door. The assist handle shall be made of SAE 304 stainless steel and be 1.25 inch diameter to enable easy grabbing with the gloved hand. Each assist handle shall include a stainless steel plate which saves the cab from scuffs through continued use of the handle.

REARVIEW MIRRORS

Retrac Aerodynamic West Coast style dual vision mirror heads model 613305 shall be provided and installed on each of the front cab doors.

The mirrors shall be mounted via 1.00 inch diameter tubular stainless steel arms to provide a rigid mounting to reduce mirror vibration.

The mirrors shall measure 8.00 inches wide X 19.00 inches high and shall include an integral convex mirrors installed in the mirror head below the flat glass to provide a wider field of vision. The flat and convex mirrors shall be motorized with remote horizontal and vertical adjustment. The control switches shall be mounted within easy reach of the driver. The flat and convex mirrors shall be heated for defrosting in severe cold weather conditions.

The mirrors shall be constructed of a vacuum formed chrome plated ABS plastic housing that is corrosion resistant and shall include the finest quality non-glare glass.

First Choice Fire & Safety Inc.

REARVIEW MIRROR HEAT SWITCH

The heat for the rearview mirrors shall be controlled through a virtual button on the Vista display and control screen.

TRIM FRONT

A polished stainless steel band shall be installed on the front of the cab and wrap around the cab radius, encompassing the headlamp and warning lamp bezels. The band shall extend from front door hinge to front door hinge with trim molding on the top and bottom edges.

EXTERIOR TRIM REAR CORNER

There shall be mirror finish stainless steel scuff plates on the outside corners at the back of the cab. The stainless steel plate shall be affixed to the cab using two sided adhesive tape.

TRIM REAR WALL EXTERIOR

The exterior rear wall of the cab shall include an overlay of 3003-H22 aluminum tread plate which shall be 0.07 inches thick. This overlay shall cover the entire rear wall of the cab.

CAB FENDER

Full width wheel well liners shall be installed on the extruded cab to limit road splash and enable easier cleaning. Each two-piece liner shall consist of an inner liner 16.00 inches wide made of vacuum formed ABS composite and an outer fenderette 5.00 inches wide made of polished aluminum.

MUD FLAPS FRONT

The front wheel wells shall have mud flaps installed on them.

CAB EXTERIOR FRONT & SIDE EMBLEMS

The cab shall include three (3) Spartan emblems. There shall be one (1) installed on the front air intake grille and one (1) emblem on each of the cab sides. The cab shall also include one (1) Advanced Protection System shield emblem on each front door.

First Choice Fire & Safety Inc.

IGNITION

A master battery system with a keyless start ignition system shall be provided. Each system shall be controlled by a one-quarter turn Cole Hersee switch, both of which shall be mounted to the left of the steering wheel on the dash. A chrome push type starter button shall be provided adjacent to the master battery and ignition switches.

Each switch shall illuminate a green LED indicator light on the dash when the respective switch is placed in the "ON" position.

The starter button shall only operate when both the master battery and ignition switches are in the "ON" position.

BATTERY

The single start electrical system shall include six (6) Harris BCI 31 925 CCA batteries with a 210 minute reserve capacity and 4/0 welding type dual path starter cables per SAE J541.

BATTERY TRAY

The batteries shall be installed within two (2) steel battery trays located on the left side and right side of the chassis, securely bolted to the frame rails. The battery trays shall be coated with the same material as the frame.

The battery trays shall include drain holes in the bottom for sufficient drainage of water. A durable, non-conducting, interlocking mat made by Dri-Dek shall be installed in the bottom of the trays to allow for air flow and help prevent moisture build up. The batteries shall be held in place by non-conducting phenolic resin hold down boards.

BATTERY BOX COVER

Each battery box shall include a steel cover which protects the top of the batteries. Each cover shall be coated the same as the battery box and shall include flush latches which shall keep the cover secure as well as a black powder coated handle for convenience when opening.

BATTERY CABLE

The starting system shall include cables which shall be protected by 275 degree F. minimum high temperature flame retardant loom, sealed at the ends with heat shrink and sealant.

First Choice Fire & Safety Inc.

The battery terminals shall not be utilized for auxiliary connections. The only acceptable auxiliary connections shall be for the cross over link from the left bank to the right bank, power for jumper studs and starter cables. All other auxiliary connections will use remote studs mounted in the battery box area. There shall be four (4) remote studs labeled as Common Power, Common Ground, Clean Power, and Clean Ground.

BATTERY JUMPER STUD

The starting system shall include battery jumper studs. These studs shall be located in the forward most portion of the driver's side lower step, 8.00 inches apart. The studs shall allow the vehicle to be jump started, charged, or the cab to be raised in an emergency in the event of battery failure.

ALTERNATOR

The charging system shall include a 320 amp Leece-Neville 12 volt alternator. The alternator shall include a self-exciting integral regulator.

STARTER MOTOR

The single start electrical system shall include a Delco brand starter motor.

BATTERY CONDITIONER

A Kussmaul Auto Charge 40 LPC battery conditioner shall be supplied. The battery conditioner shall provide a 40 amp output for the chassis batteries and a 15 amp output circuit for accessory loads. The battery conditioner shall be mounted in the cab in the LH rear facing outer seating position.

BATTERY CONDITIONER DISPLAY

A Kussmaul battery conditioner display shall be supplied. The battery conditioner display shall be mounted in front of the left side door just below the windshield.

CAB/CHASSIS ELECTRICAL OUTLET

There shall be a 120V 20A power pre-wired into the cab to a junction box behind the driver's seat. 12/3 wiring terminating in the junction box shall be routed to behind the cab on the chassis frame rails with a 15.00 feet long coil for connection to apparatus 120V power supply.

First Choice Fire & Safety Inc.

AUXILIARY AIR COMPRESSOR

A Kussmaul Auto Pump 120V air compressor shall be supplied. The air compressor shall be installed under the dashboard on the right-hand side, forward of the officer's seating position. The air compressor shall be plumbed to the air brake system to maintain air pressure.

ELECTRICAL INLET LOCATION

An electrical inlet shall be installed on the left hand side of the cab ahead of the front door.

ELECTRICAL INLET

A Kussmaul 20 amp super auto-eject electrical receptacle shall be supplied. It shall automatically eject the plug when the starter button is depressed.

A single item or an addition of multiple items must not exceed the rating of the electric inlet that it's connected to.

Amp Draw Reference List:

Kussmaul 40 LPC Charger - 5 Amps
Kussmaul 40/20 Charger - 8.5 Amps
Kussmaul 80 LPC Charger - 13 Amps
Kussmaul EV-40 - 6.2 Amps
Blue Sea P12 7532 - 7.5 Amps
Iota DLS-45/IQ4 - 11 Amps
1000W Engine Heater - 8.33 Amps
1500W Engine Heater - 12.5 Amps
120V Air Compressor - 4.2 Amps

ELECTRICAL INLET CONNECTION

The electrical inlet shall be connected to the battery conditioner and the air pump.

ELECTRICAL INLET COLOR

The electrical inlet connection shall include a yellow cover.

HEADLIGHTS

First Choice Fire & Safety Inc.

The cab front shall include four (4) rectangular LED headlamps with separate high and low beams mounted in bright chrome bezels. Each lamp shall include a heating system that de-ices the headlight.

HEADLIGHT LOCATION

The headlights shall be located on the front fascia of the cab directly above the front warning lights.

FRONT TURN SIGNALS

The front fascia shall include two (2) Whelen model 600 4.00 inch X 6.00 inch programmable amber LED turn signals which shall be installed in a polished aluminum radius mount housing above and outboard of the front warning and head lamps.

SIDE TURN/MARKER LIGHTS

The sides of the cab shall include two (2) Tecniq S170 LED side marker lights which shall be provided just behind the front cab radius corners. The lights shall be amber with black bezels.

MARKER AND ICC LIGHTS

In accordance with FMVSS, there shall be five (5) Tecniq S170 LED cab marker lamps designating identification, center and clearance provided. These lights shall be installed on the face of the cab within full view of other vehicles from ground level. The lights shall be amber with black bezels.

HEADLIGHT AND MARKER LIGHT ACTIVATION

The headlights and marker lights shall be controlled through a rocker switch within easy reach of the driver. There shall be a dimmer switch within easy reach of the driver to adjust the brightness of the dash lights. The headlamps shall be equipped with the "Daytime Running" light feature, which shall illuminate the headlights to 80% brilliance when the ignition switch is in the "On" position and the parking brake is released.

CORNERING LIGHTS

The bumper tail shall include two (2) Whelen 500 Series TIR6™ Super-LED® steady-on cornering lights with clear lenses, one (1) each side. Each light head shall illuminate when the respective side turn signal is activated.

First Choice Fire & Safety Inc.

GROUND LIGHTS

The ground lighting shall be activated when the parking brake is set, by the opening of the door on the respective cab side, and through a virtual button on the Vista display and control screen.

GROUND LIGHTS

Each door shall include a Tecniq T44 LED ground light mounted to the underside of the cab step below each door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

LOWER CAB STEP LIGHTS

The middle step located at each door shall include a Tecniq T44 LED light which shall activate with the opening of the respective door. The lights shall include a polycarbonate lens, a housing which is vibration welded and LEDs which shall be shock mounted for extended life.

INTERMEDIATE STEP LIGHTS

The intermediate step well area at each door shall include a TecNiq D06 LED light within a chrome housing. The Egress step lights shall provide visibility to the step well area for the first step exiting the vehicle. The Egress step lights shall activate with Entry step lighting.

UNDER BUMPER LIGHTS

There shall be two (2) 4.00 inch round LED ground lights mounted under the bumper. The lights shall include a polycarbonate lens, a housing which is vibration welded, and LEDs which shall be shock mounted for extended life. The under bumper ground lighting shall be interlocked with the park brake.

LIGHTBAR PROVISION

There shall be one (1) light bar installed on the cab roof. The light bar shall be provided and installed by Spartan Chassis. The light bar installation shall include a lowered mounting that shall place the light bar just above the junction box and wiring to a control switch on the cab dash.

CAB FRONT LIGHTBAR MODEL

First Choice Fire & Safety Inc.

The cab shall be provided with one (1) Whelen model F4N72 light bar. The light bar shall be 72.00 inches in length and feature eighteen (18) customizable pods.

See the light bar layout for specific details.

LIGHTBAR SWITCH

The light bar shall be controlled by a virtual button on the Vista display and control screen. This button shall be clearly labeled for identification.

FRONT SCENE LIGHTS

The front of the cab shall (1) Firetech Hi-Viz 72" brow light with marker lights included. Brow light shall include "Spot, Flood, and Scene" function.

FRONT SCENE LIGHTS ACTIVATION

The front scene lighting shall be activated by a virtual button on the Vista display and control screen.

SIDE SCENE LIGHTS

The side of the cab shall include two (2) Firetech model FT-GESM Guardian Elite LED scene lights, one (1) each side which shall be surface mounted with a chrome bezel.

SIDE SCENE LIGHT LOCATION

The scene lighting located on the left and right sides of the cab shall be mounted rearward of the cab "B" pillar in the 10.00 inch raised roof portion of the cab between the front and rear crew doors.

SIDE SCENE ACTIVATION

The scene lights shall be activated by two (2) virtual buttons on the Vista display and control screen(s), one (1) for each light.

INTERIOR OVERHEAD LIGHTS

The cab shall include a two-section, red and clear Weldon LED dome lamp located over each door. The dome lamps shall be rectangular in shape and shall measure

First Choice Fire & Safety Inc.

approximately 7.00 inches in length X 3.00 inches in width with a black colored bezel. The clear portion of each lamp shall be activated by opening the respective door and via the multiplex display and both the red and clear portion can be activated by individual push lenses on each lamp.

An additional incandescent three (3) light module with dual map lights shall be located over the engine tunnel which can be activated by individual switches on the lamp.

AUXILIARY DOME LIGHT LH

The cab shall include one (1) Whelen brand 60CREGCS 6.00 inch diameter red/clear type round shaped LED auxiliary dome light above the left hand front seat position. The red portion of the light shall be activated by a virtual button on the Vista display. The clear portion of the light shall be activated by opening of left front door and by a virtual button on the Vista display. The single virtual button on the Vista display and control screen shall also be provided for activation of this light which shall also activate any auxiliary dome lights specifying Vista activation. The light shall also be activated by individual switches located on the side of the light.

AUXILIARY DOME LIGHT RH

The cab shall include one (1) Whelen brand 60CREGCS 6.00 inch diameter red/clear type round shaped LED auxiliary dome light above the right hand front seat position. The red portion of the light shall be activated by a virtual button on the Vista display. The clear portion of the light shall be activated by opening of right front door and by a virtual button on the Vista display. The single virtual button on the Vista display and control screen shall also be provided for activation of this light which shall also activate any auxiliary dome lights specifying Vista activation. The light shall also be activated by individual switches located on the side of the light.

AUXILIARY DOME LIGHT MID CREW

The cab shall include two (2) Whelen brand 60CREGCS 6.00 inch diameter red/clear type round shaped LED auxiliary dome lights on the headliner in the middle of the crew area inboard of the outer seating positions. The red portion of each light shall be activated by a virtual button on the Vista display. The clear portion of each light shall be activated by opening the respective door and by a virtual button on the Vista display. The single virtual button on the Vista display and control screen shall also be provided for activation of this light which shall

First Choice Fire & Safety Inc.

also activate any auxiliary dome lights specifying Vista activation. The lights shall also be activated by individual switches located on the side of the light.

ENGINE COMPARTMENT LIGHT

There shall be a LED NFPA compliant light mounted under the engine tunnel for area work lighting on the engine. The light shall include a polycarbonate lens, a housing which is vibration welded and a bulb which shall be shock mounted for extended life. The light shall activate automatically when the cab is tilted.

DO NOT MOVE APPARATUS LIGHT

The front headliner of the cab shall include a flashing red TecNiq K50 LED light clearly labeled "Do Not Move Apparatus". In addition to the flashing red light, an audible alarm shall be included which shall sound while the light is activated.

The flashing red light shall be located centered left to right for greatest visibility.

The light and alarm shall be interlocked for activation when either a cab door is not firmly closed, or an apparatus compartment door is not closed, and the parking brake is released.

MASTER WARNING SWITCH

A master switch shall be included, as a virtual button on the Vista display and control screen which shall be labeled "E Master" for identification. The button shall feature control over all devices wired through it. Any warning device switches left in the "ON" position when the master switch is activated shall automatically power up.

HEADLIGHT FLASHER

An alternating high beam headlight flashing system shall be installed into the high beam headlight circuit which shall allow the high beams to flash alternately from left to right.

Deliberate operator selection of high beams will override the flashing function until low beams are again selected. Per NFPA, these clear flashing lights will also be disabled "On Scene" when the park brake is applied.

HEADLIGHT FLASHER SWITCH

First Choice Fire & Safety Inc.

The flashing headlights shall be activated through a virtual button on the Vista display and control screen.

INBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 series Super LED front warning lights in the left and right inboard positions. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the front fascia of the cab within a chrome bezel.

INBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the inboard positions shall be red with a clear lens.

OUTBOARD FRONT WARNING LIGHTS

The cab front fascia shall include two (2) Whelen 600 series Super LED Rota-Beam front warning lights in the left and right outboard positions. The lights shall be mounted to the front fascia of the cab within a chrome bezel. The lights shall be programmed to alternate the "WigWag 150" pattern.

OUTBOARD FRONT WARNING LIGHTS COLOR

The warning lights mounted on the cab front fascia in the outboard position shall be red with a clear lens.

FRONT WARNING SWITCH

The front warning lights shall be controlled through a virtual control on the Vista display and control screen. This switch shall be clearly labeled for identification.

INTERSECTION WARNING LIGHTS

The chassis shall include two (2) Whelen 600 series Super LED Rota-Beam intersection warning lights, one (1) each side. The left hand light shall be programmed to emit the "Rotator 150" clockwise flash pattern and the right hand shall be programmed to emit the "Rotator 150" counter clockwise flash pattern.

INTERSECTION WARNING LIGHTS COLOR

First Choice Fire & Safety Inc.

The intersection lights shall be red with a clear lens.

INTERSECTION WARNING LIGHTS LOCATION

The intersection lights shall be mounted on the side of the bumper in the rearward position.

SIDE WARNING LIGHTS

The cab sides shall include two (2) Whelen 600 series Super LED warning lights, one (1) on each side. The lights shall feature multiple flash patterns including steady burn for solid colors and multiple flash patterns for split colors. The lights shall be mounted to the sides of the cab within a chrome bezel.

SIDE WARNING LIGHTS COLOR

The warning lights located on the side of the cab shall be red with clear lens.

SIDE WARNING LIGHTS LOCATION

The warning lights on the side of the cab shall be mounted over the front wheel well forward from the center of the front axle.

SIDE AND INTERSECTION WARNING SWITCH

The side warning lights shall be controlled through a virtual button on the Vista display and control screen. This button shall be clearly labeled for identification.

TANK LEVEL LIGHTS

There shall be two (2) Whelen Strip-Light Plus XL tank lights surface mounted within a chrome bezel.

The light strips shall feature four (4) colors of LED lights to indicate the fluid level of a tank. The lights shall change in color to indicate the water level of the tank in ¼ tank increments, the colors shall change from green indicating a full tank to blue, amber, and red as the tank level drops.

TANK LEVEL LIGHTS ACTIVATION

An FRC remote large light driver shall be installed under the dash with the signal wire for the primary display routed to the rear of cab on the chassis.

First Choice Fire & Safety Inc.

The light activation shall be active with the park brake set and ignition on.

TANK LEVEL LIGHTS LOCATION

There shall be water level lights mounted on each side of the cab, behind the rear cab doors.

INTERIOR DOOR OPEN WARNING LIGHTS

The interior of each door shall include one (1) 15.87 inch long X 0.73 inch tall amber Weldon LED warning light. The light shall be located on the upper portion of the door frame to be visible when a person is standing in front of the door while entering or exiting the cab. Each light shall activate with a scrolling directional flash pattern which moves from inside to outside when the door is in the open position. This shall serve as a warning to oncoming traffic.

SIREN CONTROL HEAD

A Whelen 295SLSA1 electronic siren control head with hard wired microphone. The siren shall offer a selectable 100 or 200-watt output, radio broadcast, public address, and seventeen (17) Scan-Lock siren tones and hands free operation which shall allow the operator to turn the siren on and off from the steering wheel horn ring if a horn/siren selector switch option is also selected. The siren circuitry shall be placed behind the rocker switch panels under the electrical cover with a 30.00 inch loop for the OEM to route as desired. The siren shall default to "ON" when the master warning switch is activated.

STEERING WHEEL HORN BUTTON SELECTOR SWITCH

A virtual button on the Vista display and control screen shall be provided to allow control of either the electric horn or the air horn from the steering wheel horn button. The electric horn shall sound by default when the selector switch is in either position to meet FMCSA requirements.

AUDIBLE WARNING LH FOOT SWITCH

Two foot actuated switches shall be mounted in the front section of the cab for use by the driver. One (1) switch shall be wired to actuate the air horn(s) and one (1) switch the mechanical siren(s).

AIR HORN FOOT SWITCH LH

First Choice Fire & Safety Inc.

The air horn foot switch shall be a Linemaster model 491-S.

AIR HORN FOOT SWITCH LH LOCATION

The air horn foot switch shall be located on the left hand side accessible to the driver between the steering column and the door.

AIR HORN FOOT SWITCH LH POSITION

The air horn foot switch shall be positioned inboard of any other foot switch, if applicable.

MECHANICAL SIREN FOOT SWITCH LH

The mechanical siren foot switch shall be a Linemaster model 491-S.

MECHANICAL SIREN FOOT SWITCH LH LOCATION

The mechanical siren foot switch shall be located on the left hand side accessible to the driver between the steering column and the door.

MECHANICAL SIREN FOOT SWITCH LH POSITION

The mechanical siren foot switch shall be positioned outboard of any other foot switch, if applicable.

AUDIBLE WARNING LH FOOT SWITCH BRACKET

A 30.00 degree angled foot switch bracket, wide enough to accommodate (2) foot switches, shall be installed outboard of the steering column for specified driver accessible foot switch activations.

AUDIBLE WARNING RH FOOT SWITCH

A foot switch wired to actuate the mechanical siren(s) shall be mounted in the front section of the cab for use by the officer.

MECHANICAL SIREN FOOT SWITCH RH

The mechanical siren foot switch shall be a Linemaster model 491-S.

MECHANICAL SIREN FOOT SWITCH RH LOCATION

First Choice Fire & Safety Inc.

The mechanical siren foot switch shall be temporarily tied up with a coiled wire drop at the firewall inboard for installation by the customer on the right hand side accessible to the officer.

AIR HORN CIRCUIT INTERLOCK

The air horn shall only be active when master warning switch is on to prevent accidental engagement.

MECHANICAL SIREN BRAKE/AUXILIARY ACTIVATION

Two (2) red push button type momentary type siren brakes shall be provided in the switch panel on the dash.

MECHANICAL SIREN INTERLOCK

The siren shall only be active when master warning switch is on to prevent accidental engagement.

BACK-UP ALARM

A Preco-Matic model 1059 dual function, dual sound backup alarm shall be installed at the rear of the chassis with an auto-adjusting output level of 87 dB to 112 dB. The alarm shall automatically activate when the transmission is placed in reverse.

INSTRUMENTATION

An ergonomically designed instrument panel shall be provided. Each gauge shall be backlit with LED lamps. Stepper motor movements shall drive all gauges. The instrumentation system shall be multiplexed and shall receive ABS, engine, and transmission information over the J1939 data bus to reduce redundant sensors and wiring.

A twenty eight (28) icon lightbar message center with integral LCD odometer/trip odometer shall be included. The odometer shall display up to 999,999.9 miles. The trip odometer shall display 9,999.9 miles. The LCD message center screen shall be capable of custom configuration by the users for displaying certain vehicle status and diagnostic functions.

The instrument panel shall contain the following gauges:

First Choice Fire & Safety Inc.

One (1) three-movement gauge displaying vehicle speed, fuel level, and Diesel Exhaust Fluid (DEF) level. The primary scale on the speedometer shall read from 0 to 100 MPH, and the secondary scale on the speedometer shall read from 0 to 160 KM/H. The scale on the fuel and DEF level gauges shall read from empty to full as a fraction of full tank capacity. Red indicator lights in the gauge and an audible alarm shall indicate low fuel or low DEF at 1/8th tank level.

One (1) three-movement gauge displaying engine RPM, and primary and secondary air system pressures shall be included. The scale on the tachometer shall read from 0 to 3000 RPM. The scale on the air pressure gauges shall read from 0 to 150 pounds per square inch (PSI) with a red line zone indicating critical levels of air pressure. Red indicator lights in the gauge and an audible alarm shall indicate low air pressure.

One (1) four-movement gauge displaying engine oil pressure, coolant temperature, voltmeter, and transmission temperature shall be included. The scale on the engine oil pressure gauge shall read from 0 to 100 pounds PSI with a red line zone indicating critical levels of oil pressure. A red indicator light in the gauge and audible alarm shall indicate low engine oil pressure. The scale on the coolant temperature gauge shall read from 100 to 250 degrees Fahrenheit (°F) with a red line zone indicating critical coolant temperatures. A red indicator light in the gauge and audible alarm shall indicate high coolant temperature. The scale on the voltmeter shall read from 9 to 18 volts with a red line zone indicating critical levels of battery voltage. A red indicator light in the gauge and an audible alarm shall indicate high or low system voltage. The low voltage alarm shall indicate when the system voltage has dropped below 11.8 volts for more than 120 seconds in accordance with the requirements of NFPA 1901. The scale on the transmission temperature gauge shall read from 100 to 300 degrees °F with a red line zone indicating critical temperatures. A red indicator light in the gauge and an audible alarm shall indicate a high transmission temperature.

The light bar portion of the message center shall include twenty-eight (28) LED backlit indicators. The lightbar shall be split with fourteen (14) indicators on each side of the LCD message screen. The lightbar shall contain the following indicators and produce the following audible alarms when supplied in conjunction with applicable configurations:

RED INDICATORS

Stop Engine - indicates critical engine fault

Air Filter Restricted - indicates excessive engine air intake restriction

Park Brake - indicates parking brake is set

First Choice Fire & Safety Inc.

Seat Belt - indicates a seat is occupied and corresponding seat belt remains unfastened

Low Coolant - indicates critically low engine coolant

Cab Tilt Lock - indicates the cab tilt system locks are not engaged.

AMBER INDICATORS

Malfunction Indicator Lamp (MIL) - indicates an engine emission control system fault

Check Engine - indicates engine fault

Check Transmission - indicates transmission fault

Anti-Lock Brake System (ABS) - indicates anti-lock brake system fault

High exhaust system temperature – indicates elevated exhaust temperatures

Water in Fuel - indicates presence of water in fuel filter

Wait to Start - indicates active engine air preheat cycle

Windshield Washer Fluid – indicates washer fluid is low

DPF restriction - indicates a restriction of the diesel particulate filter

Regen Inhibit-indicates regeneration of the DPF has been inhibited by the operator

Range Inhibit - indicates a transmission operation is prevented and requested shift request may not occur.

SRS - indicates a problem in the supplemental restraint system

Check Message - indicates a vehicle status or diagnostic message on the LCD display requiring attention.

GREEN INDICATORS

Left and Right turn signal indicators

ATC - indicates low wheel traction for automatic traction control equipped vehicles, also indicates mud/snow mode is active for ATC system

High Idle - indicates engine high idle is active.

Cruise Control - indicates cruise control is enabled

OK to Pump - indicates the pump is engaged and conditions have been met for pump operations

Pump Engaged - indicates the pump transmission is currently in pump gear

Auxiliary Brake - indicates secondary braking device is active

BLUE INDICATORS

High Beam indicator

AUDIBLE ALARMS

Air Filter Restriction

Cab Tilt Lock

Check Engine

Check Transmission

First Choice Fire & Safety Inc.

Open Door/Compartment
High Coolant Temperature
High or Low System Voltage
High Transmission Temperature
Low Air Pressure
Low Coolant Level
Low DEF Level
Low Engine Oil Pressure
Low Fuel
Seatbelt Indicator
Stop Engine
Water in Fuel
Extended Left/Right Turn Signal On
ABS System Fault

BACKLIGHTING COLOR

The instrumentation gauges and the switch panel legends shall be backlit using red LED backlighting.

CAMERA REAR

One (1) Audiovox Voyager heavy duty box shaped HD camera shall be shipped loose for OEM installation in the body to afford the driver a clear view to the rear of the vehicle.

The camera system shall include a one-way communication device that shall be an integral part of the rear camera for the use of voice commands directly to the driver. The rear camera display shall activate when the vehicle's transmission is placed in reverse.

CAMERA DISPLAY

The camera system shall be wired to a single Weldon Vista display located on the driver's side dash. The camera system display can be activated through the Vista display panel.

CAMERA SPEAKER

The rear camera shall be wired to speaker(s) in the cab and shall audible to the driver and officer. There shall be a virtual button provided on the Vista display and control panel to deactivate the speaker(s).

First Choice Fire & Safety Inc.

COMMUNICATION ANTENNA

An antenna base, for use with an NMO type antenna, shall be mounted on the right hand front corner of the cab roof so not to interfere with light bars or other roof mounted equipment installed by Spartan Chassis. The antenna base shall be an Antenex model MABVT8 made for either a 0.38 inch or 0.75 inch receiving hole in the antenna and shall include 17.00 foot of RG58 A/U cable with no connector at the radio end of the cable. The antenna base design provides the most corrosion resistance and best power transfer available from a high temper all brass construction and gold plated contact design. The antenna base shall be provided by Spartan.

COMMUNICATION ANTENNA CABLE ROUTING

The antenna cable shall be routed from the antenna base mounted on the roof to the area behind and underneath the right hand front seat.

AUXILIARY COMMUNICATION ANTENNA

An auxiliary antenna base, for use with an NMO type antenna, shall be installed on the cab. The antenna base shall be an Antenex model MABVT8 and shall include 17.00 foot of RG58 A/U cable with no connector at the radio end of the cable. The antenna shall be mounted on the left hand front corner of the cab roof so not to interfere with light bars or other roof mounted equipment installed by Spartan Chassis. The antenna base shall be provided by Spartan.

AUXILIARY COMMUNICATION ANTENNA CABLE ROUTING

The auxiliary antenna cable shall be routed from the antenna base mounted on the roof to the area behind and underneath the right hand front seat.

CAB EXTERIOR PROTECTION

The cab face shall have a removable plastic film installed over the painted surfaces to protect the paint finish during transport to the body manufacturer.

FIRE EXTINGUISHER

A 2.50 pound D.O.T approved fire extinguisher with BC rating shall be shipped loose with the cab.

DOOR KEYS

First Choice Fire & Safety Inc.

The cab and chassis shall include a total of four (4) door keys for the manual door locks.

DIAGNOSTIC SOFTWARE OCCUPANT PROTECTION

Diagnostic software for the Spartan Advanced Protection System shall be available for free download from the Spartan Chassis website to Spartan authorized OEMs, dealers and service centers, as well as the vehicle owner.

The software has been validated to be compatible with the following RP1210 interface adapters:

- Dearborn Group DPA4 Plus
- Noregon Systems JPRO® DLA+
- Cummins INLINE5
- Cummins INLINE6
- NexIQ™ USB-Link™

The software and adapter utilize the SAE J1939-13 heavy duty nine (9) pin connector which is located below the driver's side dash to the left of the steering column.

WARRANTY

Summary of Warranty Terms:

THE FOLLOWING IS SUMMARY OF WARRANTY TERMS FOR INFORMATION ONLY. THE ACTUAL LIMITED WARRANTY DOCUMENT, WHICH IS ATTACHED TO THIS OPTION, CONTAINS THE COMPLETE STATEMENT OF THE SPARTAN FIRE CHASSIS LIMITED WARRANTY. SPARTAN'S RESPONSIBILITY IS TO BE ACCORDING TO THE TERMS OF THE COMPLETE LIMITED WARRANTY DOCUMENT.

The chassis manufacturer shall provide a limited parts and labor warranty to the original purchaser of the custom built cab and chassis for a period of twenty-four (24) months, or the first 36,000 miles, whichever occurs first. The warranty period shall commence on the date the vehicle is delivered to the first end user.

CHASSIS OPERATION MANUAL

There shall be two (2) digital copies of the chassis operation manual provided with the chassis. The digital data shall include a parts list specific to the chassis model.

First Choice Fire & Safety Inc.

ENGINE AND TRANSMISSION OPERATION MANUALS

The following manuals specific to the engine and transmission models ordered will be included with the chassis in the ship loose items:

- (1) Hard copy of the Engine Operation and Maintenance manual with digital copy
- (1) Digital copy of the Transmission Operator's manual
- (1) Digital copy of the Engine Owner's manual

CAB/CHASSIS AS BUILT WIRING DIAGRAMS

The cab and chassis shall include two (2) digital copies of wiring schematics and option wiring diagrams.

DRIVELINE LAYOUT CONFIRMATION

During the design phase of the chassis the Spartan Chassis driveline engineer shall submit the driveline layout to an OEM engineer to review the chassis design for any potential problems integrating the OEM body to the chassis. The OEM engineer shall provide approval to the driveline engineer prior to driveline bills of materials being released.

One (1)
04-06-0500

CM - Exhaust Heat Shield - Horizontal Exhaust

Y__N__

EXHAUST

The chassis horizontal exhaust pipe shall be equipped with a stainless steel heat shield to protect the body compartments.

One (1)
04-07-0500

The exhaust pipe shall discharge engine exhaust to the right side of the apparatus.
Mudflaps - Front & Rear

Y__N__

MUDFLAPS

Heavy-duty black rubber mudflaps shall be provided behind the front tires.

One (1)
04-08-1500

Black, anti-sail mudflaps shall be installed behind the rear wheels.
Rear Tow Bar

Y__N__

REAR TOW BAR

First Choice Fire & Safety Inc.

A two inch diameter, solid steel bar shall be suspended approximately 28" below the top of the rear chassis frame rail.

The tow bar shall be attached to the frame rail at each side using properly reinforced channel supports.

Tow bars that are attached to both the frame rails and the apparatus body will not be acceptable, due to undue stresses on the body, caused when the chassis frame flexes.

One (1)
04-09-2100

Front Bumper Compartment - Center with Lid

Y__N__

FRONT BUMPER COMPARTMENT - CENTER - WITH LID

A compartment shall be provided in the bumper apron, located in the center, between the frame rails, which may be used as a hose well. The compartment shall be constructed of .125 inch 5052-H32 grade aluminum, and shall include drain holes in the bottom corners to allow excess moisture to escape. The compartment will be sized to hold _____.

HINGED LID

The compartment shall include a hinged lid, constructed of aluminum diamond plate. The lid shall include a twist lock latch to secure the lid, and a gas spring rod to hold the lid open.

One (1)
04-10-0948

Helmet Holders - Chassis Supplied

Y__N__

HELMET HOLDERS

The required helmet holders will be supplied with the custom chassis.

One (1)
04-12-1900

Fuel Fill - Painted Stainless Steel

Y__N__

FUEL FILL

The fuel fill for the custom chassis shall be located in the left side rear fender area, and shall have a painted stainless steel door, labeled: "DIESEL FUEL ONLY".

One (1)
04-12-1910

Cab Tilt Control

Y__N__

CAB TILT CONTROL

A cab-tilt pendant control shall be provided and installed on the right side of the apparatus. The pendant shall be located directly behind the upper auxiliary pump access panel.

First Choice Fire & Safety Inc.

A cab tilt instruction plate shall be located as close as possible to the control pendant for ease of operation.

One (1)
07-00-0500

Pump Shift - Dash Mounted (Midship)

Y___N___

PUMP CONTROL

Provisions shall be made for placing the pump drive system in operation, using controls and switches that are identified, and within convenient reach of the operator.

A "PUMP ENGAGED" indicator shall be provided in the driving compartment and on the operator's panel to indicate that the pump shift process has been successfully completed. An "OK TO PUMP" indicator shall be provided in the driving compartment to indicate that the pump is engaged, the chassis transmission is in pump gear, and the parking brake is engaged.

The fire pump-shift system shall be equipped with a means to prevent unintentional movement of the control device from its set position. The system shall include a nameplate, indicating the chassis transmission shift selector position to be used for pumping, and located so that it can be easily read from the driver's position.

The system shall include the applicable NFPA standard interlocks, pump shift, and "OK TO PUMP" indicator lights in the cab and at the pump panel. The fire pump system shall be equipped with an interlock system to ensure that the pump drive system components are properly engaged in the pumping mode of operation, so that the pumping system can be safely operated from the pump operator's position.

If applicable, the secondary braking device shall be automatically disengaged for pumping operations.

One (1)
07-00-0500

Pump Shift - Dash Mounted (Midship)

Y___N___

PUMP CONTROL

Provisions shall be made for placing the pump drive system in operation, using controls and switches that are identified, and within convenient reach of the operator.

A "PUMP ENGAGED" indicator shall be provided in the driving compartment and on the operator's panel to indicate that the pump shift process has been successfully completed. An "OK TO PUMP" indicator shall be provided in the driving compartment to indicate that the pump is engaged, the chassis transmission is in pump gear, and the parking brake is engaged.

First Choice Fire & Safety Inc.

The fire pump-shift system shall be equipped with a means to prevent unintentional movement of the control device from its set position. The system shall include a nameplate, indicating the chassis transmission shift selector position to be used for pumping, and located so that it can be easily read from the driver's position.

The system shall include the applicable NFPA standard interlocks, pump shift, and "OK TO PUMP" indicator lights in the cab and at the pump panel. The fire pump system shall be equipped with an interlock system to ensure that the pump drive system components are properly engaged in the pumping mode of operation, so that the pumping system can be safely operated from the pump operator's position.

If applicable, the secondary braking device shall be automatically disengaged for pumping operations.

One (1)
07-04-2622

Pump System - HaleQMAX XS 1500 - GPM HALE

Y___N___

PUMP - HALE QMAX XS SERIES

1500 GPM SINGLE-STAGE MIDSHIP-MOUNTED CENTRIFUGAL PUMP

The pump must deliver the percentage of rated capacity at the pressure listed below:

- 100% of rated capacity at 150 PSI net pump pressure
- 100% of rated capacity at 165 PSI net pump pressure
- 70% of rated capacity at 200 PSI net pump pressure
- 50% of rated capacity at 250 PSI net pump pressure

PUMP ASSEMBLY

15. The pump shall be designed to mount on the chassis rails of commercial or custom truck chassis and have the capacity of 1,000 to 2,250 gallons per minute (U.S. GPM), NFPA-1901 rated performance.
16. The pump shall be driven by a driveline from the truck transmission. The engine shall provide sufficient horsepower and RPM to enable pump to meet and exceed its rated performance.
17. The entire pump shall be assembled at the pump manufacturer's factory, and hydrostatically tested to 600 PSI. The pump shall be tested at the pump

First Choice Fire & Safety Inc.

manufacturer's factory to confirm performance specs, as outlined by the latest edition of NFPA 1901. The pump shall be free from objectionable pulsation and vibration during testing and operation.

18. The pump body and related parts shall be constructed of fine-grain alloy cast iron with a minimum tensile strength of 30,000 PSI (2,069 bar). All metal moving parts in contact with water shall be of high-quality bronze or stainless steel. Pumps utilizing castings made of lower tensile strength cast iron are not acceptable.
19. Pump body shall be horizontally split, on a single plane, in two sections, for easy removal of entire impeller assembly, including wear rings and bearings, from beneath the pump, without disturbing piping or the mounting of the pump in chassis.
20. The pump body shall extend, as one piece, across the truck chassis from side to side, and incorporate discharge manifolding with a minimum of (12) 4" ports and (1) 3" port. Six additional/optional 3" ports are available/optional.
21. The pump shall have one double suction impeller and two opposed discharge volute cutwaters to eliminate radial unbalance. (No exceptions.)
22. The pump shaft shall be rigidly supported by three bearings for minimum deflection. One high lead bronze sleeve bearing shall be located immediately adjacent to the impeller, (on side opposite the gearbox). The sleeve bearing is to be lubricated by a force-fed, automatic oil lubricated design, pressure balanced to exclude foreign material. (No exceptions.) The remaining bearings shall be heavy-duty, deep-groove ball bearings in the gearbox, and they shall be splash lubricated.
23. The pump shaft shall have only one packing gland, located on the inlet side of the pump. It shall be of split design for ease of repacking. The packing gland shall be a full-circle threaded design to exert uniform pressure on packing, and to prevent uneven packing loading when tightened. (No exceptions.) It shall be easily adjusted, by hand, with rod or screwdriver, without special tools or wrenches required. The packing rings shall be made of a permanently lubricated, long-life graphic composition, and have sacrificial zinc foil separators to protect the pump shaft from galvanic corrosion (No exceptions.)
24. Pump impeller shall be constructed of hard, fine-grain bronze, and accurately machined and balanced. The vanes of the impeller intake eyes shall be designed to provide ample reserve capacity, utilizing minimum horsepower.

First Choice Fire & Safety Inc.

25. Impeller clearance rings shall be bronze, easily renewable without replacing impeller or pump volute body, and of wrap-around, double-labyrinth design for maximum efficiency. (No exceptions.)
26. The pump shaft shall be heat-treated, electric furnace, corrosion resistant stainless steel to be super-finished for long shaft life. Pump shaft shall be sealed with double-lip oil seal to keep road dirt and water out of gearbox.

GEARBOX

1. Pump gearbox shall be of sufficient size to withstand up to 16,000 lbs. ft. of drive through torque of the apparatus engine. The drive unit shall be designed with ample lubrication reserve, and to maintain proper operating temperature.
2. The gearbox driveshafts shall be of heat-treated chrome-nickel steel and at least 2-3/4 inches in diameter, on both the input and output driveshafts. They shall withstand the full torque of the engine.
3. All gears, both drive and pump, shall be made of the highest quality, electric furnace chrome nickel steel. Bores shall be ground to size and teeth integrated and hardened, to give an extremely accurate design for long life, smooth and quiet running, and high load carrying capability. An accurately cut spur design shall be provided to eliminate all possible end thrust. (No exceptions.)
4. The pump ratio shall be selected by the apparatus manufacturer to provide maximum performance with the engine and transmission selected.
5. If the gearbox is equipped with a power shift, the shifting mechanism shall be a heat-treated, hard-anodized aluminum power cylinder, with stainless steel shaft. An in-cab control for rapid shift shall be provided that locks in road or pump.
6. Three green warning lights shall be provided to indicate to the operator when the pump has completed the shift from "road" to "pump" position. Two green lights are to be located in the driver compartment and one green light on pump operator's panel adjacent to the throttle control.

One (1)
07-07-2200

Hale Anode System

Y___N___

HALE ANODE SYSTEM

Two (2) Hale anodes shall be installed in the pump to prevent damage caused by galvanic corrosion within the pump.

First Choice Fire & Safety Inc.

One (1) installed in the suction side of the pump and one (1) installed in the discharge side of the pump.

The anodes should be inspected every 12 months and replaced when over 75% of the zinc has been consumed. Performance of the anode life will vary with water quality and PH.

One (1)
07-07-2200

Hale Anode System

Y___N___

HALE ANODE SYSTEM

Two (2) Hale anodes shall be installed in the pump to prevent damage caused by galvanic corrosion within the pump.

One (1) installed in the suction side of the pump and one (1) installed in the discharge side of the pump.

The anodes should be inspected every 12 months and replaced when over 75% of the zinc has been consumed. Performance of the anode life will vary with water quality and PH.

One (1)
07-15-0000

Pump System - Hale Primer - ESP

Y___N___

HALE PRIMING PUMP

A Hale *ESP* environmentally-safe, oil-less primer shall be provided.

The priming pump will be a positive displacement vane-type, shall be electrically-driven, and shall conform to standards outlined in NFPA 1901.

One *PVG* priming control valve will both open the priming valve and start the priming motor.

One (1)
07-16-1002

Trident Auto Air Primer with Lift Gauge (Pump Only) 31.011.3

Y___N___

AUTOMATIC FIRE PUMP PRIMING SYSTEM WITH LIFT GAUGE

A Trident Model #31.011.3 automatic air-operated priming system shall be installed. The unit shall be of all brass and stainless steel construction, and designed for fire pumps of 1,250 GPM (4,690 LPM) or more. Due to corrosion exposure, no aluminum or vanes shall be used in the primer design. The primer shall be a three-barrel design with 3/4" NPT connection to the fire pump.

The primer shall be mounted above the pump impeller so that the priming line will automatically drain back to the pump. The primer shall also automatically drain when the panel control actuator is not in operation. The inlet side of the

First Choice Fire & Safety Inc.

primer shall include a brass 'wye' type strainer with removable stainless steel fine-mesh strainer to prevent entry of debris into the primer body.

AUTOMATIC PRIMER CONTROL WITH VACUUM GAUGE PANEL

The 12 volt primer control shall be an automatic-type, with a pump panel three-way switch to operate an air solenoid valve. The air valve shall direct air pressure from the air brake system to the primer. To prevent freezing, no water shall enter the primer valve control.

A vacuum gauge, 2" in diameter, with graduations from zero to 30 feet, shall be installed in the primer control panel. The gauge shall be physically connected to the vacuum side of the primer, and read only when the primer is running, so it will never see or be subject to damage from high pump intake pressures.

The automatic priming switch shall have three positions as follows:

- **Prime** - the lower position shall be a momentary "push-to-prime". The "Prime" position also allows the operator to "ramp" test the primer without the fire pump being engaged.
- **Off** - center position
- **Auto-Prime** - in the upper position, a green LED pilot light shall be illuminated when the switch is the "Auto-Prime" position. The *Auto-Prime* operates automatically when the pump pressure drops below 20 PSIG. The primer shuts off automatically when the pump pressure is re-established, and exceeds 20 PSIG. The *auto* mode only operates when the fire pump is engaged.

Warranty - The primer shall be covered by a five (5) year parts warranty.
Hale Standard Pump Warranty

One (1)
07-25-0000

Y___N___

HALE PRODUCT INC. STANDARD LIMITED PUMP WARRANTY

Hale Products, Incorporated ("Hale") hereby warrants to the original buyer that products manufactured by Hale are free of defects in material and workmanship for a period of five (5) years from the date the product is first placed into service or five and one-half (5-1/2) years from date of shipment by Hale, whichever period shall be first to expire. Within this warranty period Hale will cover parts and labor for the first two (2) years and parts only for years three (3) through five (5).

One (1)
09-70-0010

Fire Research - PumpBoss Series - PBA401-D00 - Cummins

Y___N___

10026-0002

First Choice Fire & Safety Inc.

PRESSURE GOVERNOR AND ENGINE MONITORING DISPLAY

Fire Research *PumpBoss* series PBA401-D00 pressure governor and monitoring display kit shall be installed. The kit shall include a control module, intake pressure sensor, discharge pressure sensor, and cables. The control module case shall be waterproof, and have dimensions not to exceed 6-3/4" high by 4-5/8". The control knob shall be 2" in diameter with no mechanical stops, have a serrated grip and a red *Idle* push button in the center. It shall not extend more than 1-3/4" from the front of the control module. Inputs for monitored engine information and outputs for engine control shall be on the J1939 databus. Inputs from the pump discharge and intake pressure sensors shall be electrical.

The following continuous displays shall be provided:

- *Engine RPM*; shown with four (4) daylight-bright LED digits, more than 1/2" high
- *Check Engine* and *Stop Engine* warning LEDs
- *Engine Oil Pressure*; shown on a dual-color (green/red) LED bar graph display
- *Engine Coolant Temperature*; shown on a dual-color (green/red) LED bar graph display
- *Transmission Temperature*: shown on a dual-color (green/red) LED bar graph display
- *Battery Voltage*; shown on a dual-color (green/red) LED bar graph display
- *Pressure* and *RPM* operating mode LEDs
- *Pressure / RPM* setting; shown on a dot-matrix message display
- *Throttle Ready* LED.

The dot-matrix message display shall show diagnostic and warning messages as they occur. It shall show monitored apparatus information, stored data, and program options, when selected by the operator. All LED intensity shall be automatically adjusted for day and nighttime operation.

The program shall store the accumulated operating hours, for the pump and engine, to be displayed with the push of a button. It shall monitor inputs and support audible and visual warning alarms for the following conditions:

- High Battery Voltage
- Low Battery Voltage (Engine Off)
- Low Battery Voltage (Engine Running)
- High Transmission Temperature
- Low Engine Oil Pressure
- High Engine Coolant Temperature
- Out of Water (visual alarm only)

First Choice Fire & Safety Inc.

- No Engine Response (visual alarm only).

The program features shall be accessed via push buttons, located on the front of the control module. There shall be a USB port, located at the rear of the control module, to upload future firmware enhancements.

The governor shall operate in two control modes, *Pressure* and *RPM*. No discharge pressure or engine RPM variation shall occur when switching between modes. A *Throttle Ready* LED shall light when the interlock signal is recognized. The governor shall start in *Pressure* mode, and set the engine RPM to idle. In *Pressure* mode, the governor shall automatically regulate the discharge pressure at the level set by the operator. In *RPM* mode, the governor shall maintain the engine RPM at the level set by the operator, except in the event of a discharge pressure increase. The governor shall limit a discharge pressure increase in *RPM* mode to a maximum of 30 psi. Other safety features shall include recognition of no-water conditions, with an automatic programmed response and a push button to return the engine to idle.

The pressure governor and display shall be programmed to interface with a Cummins engine.

One (1)
09-75-0020

Class 1- ENFO IV

Y__N__

CLASS 1 - ENFO IV

The apparatus shall be equipped with the Class 1 *ENFO IV* that provides the pump operator with information on the engine RPM, oil pressure, engine temperature and electrical system voltage. The *ENFO IV* utilizes the SAE-J1939 data bus for engine information on engines that support the J-1939 protocol.

Features:

- Engine RPM display
- System voltage display and alarm
- Engine oil pressure display and alarm
- Engine temperature display and alarm
- Meets NFPA 1901 requirements

One (1)
09-76-0025

Chassis-Supplied Throttle Control

Y__N__

REMOTE THROTTLE CONTROL - CHASSIS SUPPLIED

The throttle control furnished with the custom chassis shall be installed at the pump panel.

One (1)

Pump System Piping Stainless Steel & Class 1 Hose

Y__N__

10026-0002

05/23/22

First Choice Fire & Safety Inc.

10-01-0100

PIPING

All piping shall be heavy-duty, 304 grade, schedule 10 stainless steel or Class 1 high-pressure flexible hose. All stainless steel fittings shall be threaded or welded.

Class 1 flexible hose shall be Black SBR synthetic rubber hose with 300# working and 1200# burst pressure, with stainless steel fittings.

Whenever possible, sweep-type elbows shall be utilized, in order to reduce friction loss. Thread-in 45's and 90's will be used elsewhere.

Victaulic or rubber couplings shall be used, where necessary, to allow flexing of plumbing, which will prevent damage or loosening of the piping, which can occur with rigid plumbing.

All threaded joints shall have non-hardening type sealant for easy removal for repairs.

All piping, including intake and discharge lines, shall be hydrostatically tested. A vacuum test shall be applied to the pump, plumbing, and valves, to test for leaks. The system shall be tested, and shall show minimum loss of no more than 10 inches of vacuum over a 5 minute period, as required by NFPA section 16.13.6.4.

SYNFLEX SUCTION, DISCHARGE, PRESSURE AND CONTROL LINES

Small lines within the pump enclosure shall be constructed from Synflex hose. Uses include, but are not limited to, such lines as priming control, gauge lines, drain lines, air control valves, pump shift, supplemental cooling, foam flush, and air bleeder valves.

One (1)
10-01-0210

Fire Pump & Plumbing System Painting

Y___N___

FIRE PUMP & PLUMBING SYSTEM PAINTING

The fire pump and plumbing system shall be painted job color, or the lower color when a two paint scheme is specified. No exceptions.

One (1)
10-02-0000

Valves - All Akron HD 8000 Series w/ Stainless Steel Ball

Y___N___

AKRON VALVES

All pump intake and discharge valves shall be *AKRON 8000* heavy-duty swing-out series. The valves shall have an all-brass body with flow-optimizing stainless steel ball, and dual-polymer seats. The valves shall be capable of dual-directional

10026-0002

First Choice Fire & Safety Inc.

flow, while incorporating a self-locking ball feature, using an automatic friction lock design, and specially designed flow-optimizing stainless steel ball. All stainless steel parts must be 316 grade for increased resistance to corrosion. The valve shall not require the lubrication of seats or any other internal waterway parts, and be capable of swinging out of the waterway for maintenance by the removal of six bolts. The valves shall carry a ten (10) year manufacturers warranty. The valve shall be manufactured and assembled in the United States.
Elkhart Intake Relief Valve

One (1)
10-05-0000

Y__N__

INTAKE RELIEF VALVE

An Elkhart Brass intake relief valve shall be installed on the suction side of the pump. The valve shall be the preset type at 125 PSI and is adjustable from 75 to 250 PSI, and shall be designed to prevent vibration from altering the setting. The relief outlet shall be directed below the pump with the discharge terminating in a 2-1/2" male NST connection. The discharge shall be away from the pump operator and labeled "Do Not Cap".

One (1)
10-15-0400

U.L. Pump Certification Test

Y__N__

U.L. PUMP CERTIFICATION TEST

One (1) certification test shall be performed at the manufacturers on-site testing facility, by Underwriters Laboratories.

The certification shall include at minimum:

- A) Pumping Test - NFPA 16.13.2
- B) Pumping Engine Overload Test – NFPA 16.13.3
- C) Pressure Control System Test - NFPA 16.13.4
- D) Priming System Tests - NFPA 16.13.5
- E) Vacuum Test - NFPA 16.13.6
- F) Water Tank-To-Pump Flow Test - NFPA 16.13.7
- G) If Fire Pump is Driven by the Chassis Engine: Engine Speed Advancement Interlock Test – NFPA 16.13.8
- H) Gauge and Flowmeter Test – NFPA 16.13.9

A test plate shall be provided at the pump operator's position that gives the rated discharges and pressures, together with the speed of the engine, as determined by the certification test. The plate shall be completely engraved with all information at the factory, and attached to the vehicle prior to delivery. The original U.L. certificate shall be provided upon acceptance and payment of the apparatus in full.
Vented Lug Caps & Plugs

One (1)
10-15-0600

Y__N__

VENTED LUG CAPS AND PLUGS

10026-0002

05/23/22

First Choice Fire & Safety Inc.

All intake and discharge plugs and caps shall be vented-lug type, designed to relieve trapped pressure and help reduce possible operator injuries.

One (1)
12-01-1000

Suction - 6" With Long Handle Chrome Caps-Pair

Y___N___

STEAMER INLETS

Two (2) 6" steamer inlets shall be provided on the pump panels, one (1) on the left side and one (1) on the right side.

One (1)
12-07-0500

Both inlets shall have screens and chrome caps with long handles.
Suction - (1) 2-1/2" - Side Mount Panel - Left Side

Y___N___

SUCTION - LEFT SIDE

One (1) 2-1/2" suction valve shall be installed on the left side of the unit. The valve body shall be mounted behind the pump panel, with a 2-1/2" NST chrome inlet swivel, chrome plug and chain, and removable inlet strainer.

One (1)
12-07-1000

Suction - (1) 2-1/2" - Side Mount Panel - Right Side

Y___N___

SUCTION - RIGHT SIDE

One (1) 2-1/2" suction valve shall be installed on the right side of the unit. The valve body shall be mounted behind the pump panel, with a 2-1/2" NST chrome inlet swivel, chrome plug and chain, and removable inlet strainer.

One (1)
13-01-1500

Tank To Pump - 3" - Midship Pumps

Y___N___

TANK TO PUMP

There shall be one (1) 3" gated tank to pump line, piped to the tank sump.

Piping from the sump to the valve shall be 4" diameter.

The line shall be plumbed directly into the back of the pump for maximum efficiency.

A full-flow, inline ball valve, with check valve, shall be provided to prevent accidental pressurization of the water tank through the pump connection.

A control with a function plate will be located on the operator's panel.

One (1)
13-02-1000

Tank Fill - 2-1/2"

Y___N___

TANK FILL - 2-1/2"

There shall be a 2-1/2" tank refill line installed, with a 2-1/2" inline valve.

10026-0002

05/23/22

First Choice Fire & Safety Inc.

One (1)
14-01-1200

Valve shall be controlled at the pump operator's panel, and will be clearly marked "TANK REFILL/PUMP COOLER".

Booster Reel - Hannay - Steel - In Dunnage - Left Side

Y___N___

BOOSTER REEL

A Hannay steel booster reel with painted discs shall be installed over the pump compartment, left side.

The reel shall be constructed utilizing a steel welded base.

Rewind shall be a 12v electric motor that will chain-drive the reel drum.

The booster reel shall have an automatic brake to prevent the booster hose from unwinding.

Reel shall include 150' of 1" booster hose.

A TFT *Twister* model #DS1040 1" nozzle shall be provided.

A weatherproof push button switch shall be provided near the reel on the pump panel.

A gear-driven manual rewind shall be included.

Chrome rollers and guides shall be provided on the left side of the pump compartment.

The booster reel discharge control shall be located at the operator's control panel.

One (1)
14-02-0500

Crosslay - (2) 1.75" w/2" Plumbing - Double-Stack

Y___N___

CROSSLAY HOSEBEDS W/ 2" PLUMBING

Two (2) crosslays shall be installed over the pump compartment.

Each section of the crosslay shall be capable of holding 200' of 1.75" double-jacketed hose, in a double-stack load.

A 2" mechanical swivel with 1.5" NST hose connector shall be used in each crosslay, to allow deployment of hose in either direction.

Stainless steel rollers with nylon guides shall be mounted on both ends, and below the crosslays.

First Choice Fire & Safety Inc.

A 1/4" aluminum divider shall separate the crosslays, and poly-plas matting shall be used on the stainless steel crosslay floor.

One (1)
14-02-4600

Each crosslay shall be plumbed with 2" piping and a 2" valve, and shall be controlled at the operator's panel.

Crosslay - Hinged Lid

Y___N___

CROSSLAY LID

A polished aluminum diamond plate lid shall be provided over the crosslay(s).

The lid shall have full length stainless steel hinge with velcro straps to hold lid firmly in place.

One (1)
14-02-4610

Crosslay - Vinyl End Covers

Y___N___

CROSSLAY VINYL FLAPS

Black vinyl flaps shall be installed on each end of the crosslay to retain the hose load. The flaps shall be secured with 2" wide straps with Velcro fasteners.

Meets NFPA 15.10.5 - Any hose storage area shall be equipped with a positive means to prevent unintentional deployment of the hose from the top, side, front, and rear of the hose storage area while the apparatus is underway in normal operations.

One (1)
14-02-5000

Dunnage Compartment

Y___N___

DUNNAGE COMPARTMENT

The remaining area behind the crosslay(s) shall be used for additional storage space.

One (1)
14-02-5600

Close Off Panel Sides of Dunnage Compartment S/S

Y___N___

DUNNAGE COMPARTMENT

Each side of the dunnage compartment shall be enclosed with 12 gauge satin-finish stainless steel.

One (1)
14-05-1510

Sump Box - Floating - Left Side Running Board

Y___N___

SUMP BOX

The left side running board shall have a 12 gauge stainless steel floating sump box.

The sump box shall have matting and drain holes in the floor of the compartment.

First Choice Fire & Safety Inc.

It shall be capable of holding _____.

The hose shall be secured with Zico Quic-straps to prevent unintentional deployment of the hose per NFPA 15.10.5.

One (1)
14-05-2010

Sump Box - Floating - Right Side Running Board

Y__N__

SUMP BOX

The right side running board shall have a floating 12 gauge stainless steel floating sump box as large as possible.

The sump box shall have matting and drain holes in the floor of the compartment.

It shall be capable of holding _____.

The hose shall be secured with Zico Quic-straps to prevent unintentional deployment of the hose per NFPA 15.10.5.

One (1)
15-01-0700

Discharges - (2) 2-1/2" Left Side

Y__N__

DISCHARGES LEFT SIDE

Two (2) 2-1/2" discharges shall be located on the left side pump panel and be controlled from the operator's panel.

Discharge shall terminate with a 2-1/2" NST 30 degree turn down with chrome cap and retainer chain.

One (1)
15-02-0500

Discharge - (1) 2-1/2" Right Side

Y__N__

DISCHARGE RIGHT SIDE

One (1) 2-1/2" discharge shall be located on the right side pump panel and be controlled from the operator's panel.

Discharge shall terminate with a 2-1/2" NST 30 degree turn down with chrome cap and retainer chain.

One (1)
15-02-1500

Discharge - (1) 3" Right Side 3" NST x 4" 30 degree Storz adapter

Y__N__

DISCHARGE RIGHT SIDE

One (1) 3" discharge shall be located on the right side pump panel and be controlled from the operator's panel.

First Choice Fire & Safety Inc.

One (1)
15-03-0500

Discharge shall terminate with a 3" NST x 4" 30 degree Storz adapter with blind cap and retainer chain.
Discharge - 2-1/2" Left Front Hosebed

Y__N__

DISCHARGE LEFT FRONT HOSEBED

One (1) 2-1/2" discharge shall be piped to the left front of the hose bed and terminate with a 2-1/2" chrome male NST adapter.

One (1)
15-03-1500

Discharge shall be controlled from the operator's panel.
Discharge - 2-1/2" Left Rear Hosebed

Y__N__

2-1/2" LEFT REAR DISCHARGE

One (1) 2-1/2" discharge shall be piped to the left rear of the hosebed and be controlled from the operator's panel.

One (1)
15-06-2700

Discharge shall terminate with a 2-1/2" NST 30 degree turn down, with chrome cap and retainer chain.
Extension Pipe 18" TFT Extend-A-Gun

Y__N__

TFT EXTEND-A-GUN

A Task Force Tips, Extend-A-Gun, deck gun extender shall be supplied and connected to the deck gun discharge of the unit.

This will allow the deck gun to be lowered to a shorter travel height, yet still allow 360 degree use of the deck gun when fully extended 18 inches.

One (1)
15-08-0500

The Extend-a-gun will be wired to the hazard light in the cab.
Akron Slo-Clos 3" Valves

Y__N__

AKRON SLO-CLOZ

An Akron Slo-Cloz device shall be provided on each 3" discharge valve to limit the opening of the valve to no faster than 3 seconds per N.F.P.A. specifications.

The hydraulic device shall be operable from -40 deg. F to 140 deg. F.

The device shall be made of corrosion-resistant materials and shall not add more than 1-1/2" to the valve height.

One (1)
15-10-0500

Drain - Pump Master Valve

Y__N__

PUMP MASTER DRAIN

First Choice Fire & Safety Inc.

A master drain that will have the capacity to drain all lines and main pump at the same time. The master drain will be mounted on the left side panel and will be readily accessible.

One (1)
15-10-0700

Drain Valves - Side Discharges Innovative Controls Lift Lever

Y___N___

DRAIN VALVES

All side discharges and auxiliary suction drain valves shall be Innovative Controls 3/4" ball brass drain valves with chrome-plated lift lever handles and ergonomic grips. Each lift handle grip shall feature built-in color-coding labels and a verbiage tag identifying each valve, also supplied by Innovative Controls. The colors labels shall also include valve open and close verbiage. The drain valves shall located in the lower portion of the pump panels. All other discharges shall have Class 1 3/4" automatic bleeder drains.

One (1)
19-00-0100

Independent Pump Module

Y___N___

INDEPENDENT PUMP MODULE

The pump module shall be a self-supported structure mounted independently from the body and chassis cab. The pump module shall be fabricated and constructed from the same material as the body. The design shall allow for normal frame deflection without imposing stress on the pump module structure. The pump module shall consist of a welded tubular stainless steel frame work, properly braced to withstand chassis frame flexing. The pump module shall be bolted to the frame rails of the chassis.

One (1)
19-02-0000

Pump Panel - Side Control - Midship Pump - Class A

Y___N___

SIDE MOUNTED OPERATOR'S PANEL

CONSTRUCTION

The pump house shall be a properly supported structure mounted between the body and chassis cab and shall be bolted to the chassis frame rails. The panel shall be supported by 1-1/2" stainless steel tubing.

The pump and all of the pump mounted valves shall be completely enclosed by the pump house design.

Left and right side pump house panels shall consist of upper and lower stainless steel removable panels.

Stainless panels to be brushed satin finish 12 gauge 304 material to ensure longevity.

First Choice Fire & Safety Inc.

The left side of the pump house shall consist of an upper hinged panel containing all required gauges.

The lower panel shall contain left side specified discharges, inlets, drains, and pump controls.

The right side of the pump house shall consist of a double vertically hinged access door. The door will be swing open style with quick opening latch.

A separate lower panel shall contain the specified right side mounted discharges and inlets and their respective drains.

The bottom panel shall be fastened to the pump house with stainless steel bolts and shall be completely removable.

INNOVATIVE CONTROLS PUSH/PULL VALVE CONTROL HANDLES

For valve actuation, the apparatus pump panel shall be equipped with Innovative Controls side mount valve controls.

The ergonomically designed push-pull T-handle shall be chrome plated zinc with recessed labels for color coding and verbiage. The control rod, double laminated locking clips and rod housing shall be stainless steel and provide a true positive lock that will eliminate valve drift. Bronze and Teflon impregnated stainless steel bushings in both ends of rod housing shall minimize rod deflection, never need lubrication, and ensure consistent long term operation. Where required locking 1/4 turn push-pull T-handle controls will be provided.

The control assembly shall include a decorative chrome plated zinc panel mounting bezel and 4 mounting bolts.

IDENTIFICATION LABELS FOR PUMP PANEL

Innovative Controls verbiage label bezels shall be installed. The bezel assemblies will be used to identify apparatus components. These labels shall be designed and manufactured to withstand the specified apparatus service environment.

The verbiage label bezel assemblies shall include a chrome plated panel mount bezel with durable easy to read UV resistant polycarbonate inserts featuring the specified verbiage and color coding. The UV resistant polycarbonate verbiage and color inserts shall be sub-surface screen printed to eliminate the possibility of wear and protect the inks from fading. Both the insert labels and bezel shall be

First Choice Fire & Safety Inc.

backed with 3M permanent adhesive (200MP), which meets UL969 and NFPA standards.

SIDE MOUNTED OPERATOR'S PANEL

The following items shall be located on the left side pump panel:

*Individual 0-400# compound discharge gauges shall be provided for each 1.5" or larger discharge

*One (1) -30 to 400 psi master pressure gauge

*One (1) -30 to 400 psi master vacuum gauge

*One (1) engine oil pressure gauge with audible & visual alarm

*One (1) engine water temperature gauge with audible & visual alarm

*One (1) engine voltmeter

*One (1) waterproof engine tachometer

*Two (2) UL test connections

*One (1) master pump house lighting switch

*One (1) engine throttle control

*One (1) relief valve control and open indicator light

*One (1) primer control

*All discharge controls

*One (1) tank fill/pump bypass control

*One (1) tank to pump valve control

*One (1) pump ENGAGED indicator light

*One pump certification plate

First Choice Fire & Safety Inc.

One (1)
19-04-0020

*One liquid level meter with sensor in the water tank
Running Board - Aluminum Diamond Plate

Y__N__

RUNNING BOARDS

Running boards shall be provided on each side of the pump module and extend from the front of the side compartments forward to the back of the cab. Running boards shall be constructed of 1/8" aluminum diamond plate. The rear edge shall be formed upward 1-1/2" to provide a kick strip along the bottom of the pump panel. The outer edge shall be bent downward to provide a safety rail.

One (1)
19-10-1800

Running boards are supported by 1.50" structural stainless steel tubing welded to the panel framing and shall be able to support a minimum of 500 pounds. The running board stepping surface will comply with the latest version of NFPA 1901. Side Mount Pump Panel Lighting Standard

Y__N__

PANEL LIGHTING

The side mount pump panel shall be illuminated by four (4) TecNiq (model E10-W000-1) 6.00" LED lights with clear lens.

Lights shall be mounted across the top of the gauge panel and shall be protected by a full width polished stainless steel shield.

Lights are controlled by a master panel mounted lights switch.

One (1) side pump panel light shall illuminated when the pump is shifted into gear form inside the cab, affording the operator illumination when first approaching the control panel.

One (1)
20-01-1500

Gauges - 4.0" No-Shok Master Gauges

Y__N__

4.0" NOSHOK MASTER GAUGES

The master intake and master discharge gauges shall be 4" diameter No-Shok pressure gauges. Each gauge shall have a one-piece die-cast brass case that integrates the valve stem connection, movement support, and bourdon tube support into a single unit that eliminates distortion and leakage. Clear scratch resistant molded crystals with captive O-ring seals shall be used to ensure distortion free viewing and to seal the gauge. The gauges shall be filled with a synthetic mixture to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F. Each gauge shall meet ANSI B40.1 Grade 1A requirements with an accuracy of +/- 1% full scale and include a size appropriate phosphorous bronze

First Choice Fire & Safety Inc.

bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy.

A polished chrome-plated brass bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauges shall be installed into decorative chrome-plated mounting bezels that incorporate valve-identifying verbiage.

The master gauges shall be installed on the pump panel no more than 6 inches apart. The gauge on the left shall be the master pump intake gauge and display a range from -30 to 400 psi with Black graphics on a White background. The gauge on the right shall be the master pump discharge gauge and display a range from -30 to 400 psi with Black graphics on a White background.

One (1)
20-01-2200

Gauge - 2-1/2" No-Shok Discharge Gauges

Y___N___

2-1/2" NOSHOK GAUGES

The valve discharge gauges shall be 2 ½ " diameter No-Shok pressure gauges. Each gauge shall have a one-piece die-cast brass case that integrates the valve stem connection, movement support, and bourdon tube support into a single unit that eliminates distortion and leakage. Clear scratch resistant molded crystals with captive O-ring seals shall be used to ensure distortion free viewing and to seal the gauge. The gauges shall be filled with a synthetic mixture to dampen shock and vibration, lubricate the internal mechanisms, prevent lens condensation and ensure proper operation from -40°F to +160°F.

Each gauge shall exceed ANSI B40.1 Grade B requirements with an accuracy of +/- 1.5% full scale and include a size appropriate phosphorous bronze bourdon tube with a reinforced lap joint and large tube base to increase the tube life and gauge accuracy. A polished chrome-plated brass bezel shall be provided to prevent corrosion and protect the lens and gauge case. The gauges shall be installed into decorative chrome-plated mounting bezels that incorporate valve-identifying verbiage and color labels. The gauges shall display a range from 0 to 400 psi with Black graphics on a White background.

One (1)
20-03-0500

ICI SL-10 LED Water Level - Pump Panel

Y___N___

ICI WATER LEVEL MONITOR

An Innovative Controls SL-10 Series Tank Level Monitor System shall be installed. The system shall include an electronic display module, a pressure transducer-based sender unit, and a 10' connection cable. The display module shall show the volume of water in the tank using 10 superbright easy-to-see LEDs. Tank level indication is enhanced by the use of green LEDs at the full and

First Choice Fire & Safety Inc.

near-full levels, amber LEDs between $\frac{3}{4}$ and $\frac{1}{4}$ tank levels, and red LEDs at the near-empty and empty levels. A wide-angle diffusion lens in front of the LEDs creates a 180° viewing angle. The electronic display module shall be waterproof and shock resistant being encapsulated in a urethane-based potting compound. The potted display module shall be mounted to a chrome plated panel-mount bezel with a durable easy-to-read polycarbonate insert featuring blue graphics and a water icon.

All programming functions shall be accessed and performed from the front of the display module. The programming includes self-diagnostics, manual or self-calibration, and networking capabilities to connect remote slave displays. Low tank level warnings shall include flashing red LEDs starting below the $\frac{1}{4}$ level, down-chasing LEDs when the tank is almost empty, and an output for an audible alarm.

The display module shall receive an input signal from a pressure transducer. This stainless steel sender unit shall be installed on the outside of the water tank near the bottom. All wiring, cables and connectors shall be waterproof without the need for sealing grease.

Location of water tank level monitor shall be on the pump operators panel.

One (1)
20-03-6052

Whelen Plus XL Tank - Large 4 Light Display LED (3)

Y__N__

WHELEN TANK LEVEL LIGHTS

There shall be three (3) Whelen Strip-Light Plus XL tank lights surface mounted within a chrome bezel. Lights will be mounted vertically one (1) on each side of the body and one (1) on the rear of the body.

The light strips shall feature four (4) colors of LED lights to indicate the fluid level of a tank. The lights shall change in color to indicate the water level of the tank in $\frac{1}{4}$ tank increments, the colors shall change from green indicating a full tank to blue, amber, and red as the tank level drops.

One (1)
20-05-3000

Air Horn Button Pump Panel

Y__N__

AIR HORN BUTTON ON PANEL

An air horn button shall be installed on the pump operators panel.

This button will allow pump operator to activate air horns at any point in time. Button will be waterproof and marked properly.

One (1)
25-01-0500

Tank Fill - Akron 2-1/2 Right Rear

Y__N__

2-1/2" REAR DIRECT TANK FILL

10026-0002

05/23/22

First Choice Fire & Safety Inc.

There shall be one (1) 2.5" Akron Brass style 8825 valve provided and terminate with a Red Head 2.50" 30 degree chrome elbow, with Trident chrome plug with retainer chain. A 3/4" bleeder will be installed.

The valve will be installed on the rear of the tank to the right of the rear dump valve.

One (1)
35-04-1500

Water Tank Description - 1000 GAL. UPF

Y___N___

WATER TANK

The UPF Poly water tank shall be constructed of PT3™ polypropylene material. This material shall be a non-corrosive stress relieved thermoplastic and UV stabilized for maximum protection. Tank shell thickness may vary depending on the application and may range from 1/2" to 1" as required. Internal baffles are generally 3/8" in thickness.

The tank capacity shall be 1000 gallons and will be equipped with a 6" vent/overflow.

TANK CONSTRUCTION

The Poly water tank shall be of a specific configuration and is so designed to be completely independent of the body and compartments. Joints and seams shall be fused using nitrogen gas as required and tested for maximum strength and integrity. The tank construction shall include PolyProSeal™ technology wherein a sealant shall be installed between the plastic components prior to being fusion welded. This sealing method will provide a liquid barrier offering leak protection in the event of a weld compromise. The top of the booster tank is fitted with removable lifting assembly designed to facilitate tank removal. The transverse and longitudinal swash partitions shall be manufactured of a minimum of 3/8" PT3™ polypropylene. All partitions shall be equipped with vent and air holes to permit movement of air and water between compartments. The partitions shall be designed to provide maximum water flow. All swash partitions interlock with one another and are completely fused to each other as well as to the walls of the tank. All partitions and spacing shall comply with NFPA 1901. The walls shall be welded to the floor of the tank providing maximum strength as part of the tank's unique Full Floor Design™. Tolerances in design allow for a maximum variation of 1/8" on all dimensions.

CAPACITY CERTIFICATION

First Choice Fire & Safety Inc.

All water tanks shall be tested and certified as to capacity on a calibrated and certified tilting scale. Each tank shall be weighed empty and full to provide precise fluid capacity. Each Poly-Tank® III is delivered with a Certificate of Capacity delineating the weight empty and full and the resultant capacity based on weight.

TANKNOLOGY™ TAG

A tag shall be installed on the apparatus in a convenient location and contain pertinent information including a QR code readable by commercially available smart phones. The information contained on the tag shall include the capacity of the water and foam (s), the maximum fill and pressure rates, the serial number of the tank, the date of manufacture, the tank manufacturer, and contact information. The QR code will allow the user to connect with the tank manufacturer for additional information and assistance.

TANK LID

The tank cover shall be constructed of 1/2" thick PT3™ polypropylene and UV stabilized, to incorporate a multi-piece locking design, which allows for individual removal and inspection if necessary. The tank cover(s) shall be flush or recessed 3/8" from the top of the tank and shall be fused to the tank walls and longitudinal partitions for maximum integrity. Each one of the covers shall have hold downs consisting of 2" minimum polypropylene dowels spaced a maximum of 40" apart. These dowels shall extend through the covers and will assist in keeping the covers rigid under fast filling conditions. A minimum of two lifting dowels shall accommodate the necessary lifting hardware.

TANK FILL TOWER

The tank shall have a combination vent and manual fill tower. The fill tower shall be constructed of 1/2" PT3™ polypropylene and shall be a minimum dimension of 12" x 12" outer perimeter. The fill tower shall be blue in color indicating that it is a water-only fill tower. The tower shall be located in the left front corner of the tank unless otherwise specified by the tank manufacturer to the purchaser. The tower shall have a 1/4" thick removable polypropylene screen and a PT3 polypropylene hinged cover. The capacity of the tank shall be engraved on the top of the fill tower lid. Inside the fill tower there shall be a combination vent/overflow pipe.

OVERFLOW AND VENT PIPE

First Choice Fire & Safety Inc.

The fill tower shall be fitted with an integral 6" ID schedule 40 P.V.C. combination overflow/vent pipe that is designed to run through the tank, and shall be piped to discharge water behind the rear wheels as required in NFPA 1901 so as to not interfere with rear tire traction.

TANK SUMP

There shall be one (1) sump standard per tank. The sump shall be constructed of a minimum of 1/2" PT3™ polypropylene and be located in the left front quarter of the tank, unless specified otherwise. On all tanks that require a front suction, a 3" schedule 40 polypropylene pipe shall be installed that will incorporate a dip tube from the front of the tank to the sump location. The sump shall have a minimum 3" N.P.T. threaded outlet on the bottom for a drain plug per NFPA.

This shall be used as a combination clean-out and drain. All tanks shall have an anti-swirl plate located approximately 3" above the inside floor.

TANK OUTLETS

There will be two (2) standard tank outlets: one for the tank-to-pump suction line, which shall be a minimum of 4" coupling and one for a tank fill line which shall be a minimum of a 2" N.P.T. coupling. All tank fill couplings shall be backed with flow deflectors to break up the stream of water entering the tank.

WATER TANK MOUNTING

The tank shall rest on the body cross members spaced a maximum of 22" apart, and shall be isolated from the cross members through the use of 1/4" to 1/2" rubber, 2-1/2" wide. The tank shall sit cradle-mounted using four (4) stainless steel corner angles 3" x 3" x 1/4" thick. Angles are welded directly to the body cross members. The angles shall keep the tank from shifting left to right or front to rear. The angles are also isolated from the tank through the use of 1/4" to 1/2" rubber. The tank is designed on the free-floating suspension principle and shall not require the use of hold downs. The tank shall be completely removable without disturbing or dismantling the apparatus body structure. The body or hose bed cross braces shall act as water tank retainers.

Apparatus Body Single Axle

Y__N__

One (1)
36-00-0100

STAINLESS STEEL BODY & COMPARTMENT CONSTRUCTION

The complete apparatus body and sub frame shall be fabricated of 12 gauge type 304 grade stainless steel sheeting with a tensile strength of 87,000 psi and a yield strength of 39,000 psi.

First Choice Fire & Safety Inc.

All body and compartment components shall be break form design. Compartments are constructed of 12 gauge type 304 stainless steel. This shall include compartment floors, side walls and ceiling. No Exception. Compartments shall be formed from a single sheet of metal when possible. The exterior of the compartments shall be solid seam welded. The corner seams shall be caulked with Gray silicone caulking. All burrs shall be removed to eliminate sharp edges.

Interior of compartments are to be left natural stainless steel with a swirl finish applied to give a lasting and pleasing appearance.

COMPARTMENT SUPPORTS

Compartment floor supports shall be provided fabricated of 12 gauge stainless steel 2.00" x 4.00" support members and shall be installed under the compartment floors. The supports shall be formed "U" sections that will extend the full width beneath the compartment floors. The upper body walkway floor will be supported in a similar fashion.

STAINLESS STEEL SUBFRAME

A 1.50" x 3.00" stainless steel tubular sub frame shall be fabricated to support the body and tank. Structural stainless steel rails shall run the full length of the body across the top of the chassis frame rails. Appropriate 3.00" stainless steel cross members shall be utilized to ensure rigidity with cross members being space no more than 24" apart.

The sub frame and cross members shall be Mig welded. All compartments and all stainless steel sheeting is TIG welded with 308 stainless steel filler wire.

The complete body structure shall be secured to the chassis frame rails with high grade 5/8" diameter U-bolts.

One inch x three inch heavy duty rubber sill will be installed between the body sub frame and chassis frame rails to prevent stress on the body and tank components. The rubber sill shall be retained by a full length stainless steel channel.

STEPPING, STANDING, & WALKING SURFACES

All stepping, standing, and walking surfaces on the body shall meet NFPA #1901 anti-slip standards.

WHEEL WELLS

First Choice Fire & Safety Inc.

12 gauge stainless steel wheel wells shall be an integral part of the body construction.

Wheel wells and cabinetry are to be designed so road debris will not be trapped on top of the cabinets.

Full one piece circular, 24" deep stainless steel wheel well liners shall be installed. The fender flares shall be bright polished stainless steel and are attached to the wheel well using stainless steel bolts.

WIRING ACCESS PANELS

Wiring access panels shall be provided in the body interior corner compartments. The panels shall be bolted in place to allow easy removal for service.

FUEL TANK ACCESS

If the apparatus is equipped with a rear frame mounted fuel tank a removable bolted on access panel will be provided in the rear compartment wall.

REMOVAL OF BODY

The completed body with all related parts will be able to be removed in its entirety and accompany the water tank when removed.

FASTENERS

All fasteners used in securing components to the body shall be type 304 stainless steel.

COMPARTMENT VENTS

Compartments shall have a minimum of two (2) 4" louvered stainless steel vents per compartment. They shall be installed in the rear wall of each compartment in a fashion to prevent foreign matter and water from entering.

COMPARTMENT DRAINS

Duckbill type rubber floor drains will be installed in the corners of the lower compartment floors.

One (1)

DWG 1: Rescue Pumper Full Depth LS & RS Hinged Doors

Y__N__

First Choice Fire & Safety Inc.

42-10-0100

RESCUE PUMPER COMPARTMENTS - FULL DEPTH & FULL HEIGHT LEFT AND RIGHT SIDE WITH HINGED DOORS

L1: 62.00" High x 26.00" Deep x 40.00" Wide
Door Opening: 58.50" High x 35.50" Wide

L2: 30.00" High x 26.00" Deep x 64.00" Wide
Door Opening: 27.00" High x 59.00" Wide

L3: 62.00" High x 26.00" Deep x 46.00" Wide
Door Opening: 58.50" High x 41.50" Wide

RR: 57.00" High x 26.00" Deep x 46.00" Wide
Door Opening: 45.75" High x 43.50" Wide

R1: 62.00" High x 26.00" Deep x 40.00" Wide
Door Opening: 58.50" High x 35.50" Wide

R2: 30.00" High x 26.00" Deep x 64.00" Wide
Door Opening: 27.00" High x 59.00" Wide

R3: 62.00" High x 26.00" Deep x 46.00" Wide
Door Opening: 58.50" High x 41.50" Wide

One (1)
42-12-4000

DWG 11: Pumper Partial Depth Rescue Style Doors LS & RS

Y___N___

DWG 11: Pumper Partial Depth Rescue Style Doors LS & RS

L1: 62.00" High x 13.00/28.00" Deep x 40.00" Wide
Door Opening: 58.50" High x 35.50" Wide

L2: 32.00" High x 13.00" Deep x 64.00" Wide
Door Opening: 29.00" High x 57.00" Wide

L3: 62.00" High x 13.00/28.00" Deep x 48.00" Wide
Door Opening: 58.50" High x 43.50" Wide

RR: 60.00" High x 26.00" Deep x 42.00" Wide
Door Opening: 50.50" High x 32.50" Wide

R1: 62.00" High x 13.00/28.00" Deep x 40.00" Wide
Door Opening: 58.50" High x 35.50" Wide

R2: 32.00" High x 13.00" Deep x 64.00" Wide

10026-0002

First Choice Fire & Safety Inc.

Door Opening: 29.00" High x 57.00" Wide

R3: 62.00" High x 13.00/28.00" Deep x 48.00" Wide

Door Opening: 58.50" High x 43.50" Wide

One (1)
46-00-0305

Square Back Body

Y__N__

SQUARE BACK BODY DESIGN

The rear side body compartments and the body side walls shall extend all the way to the rear of the apparatus and shall be squared off design.

One (1)
56-20-0004

Rear Bumper 12"

Y__N__

REAR BUMPER

The rear bumper shall be fabricated of 1.50" x 1.50" and 1.50" x 3.00" structural stainless steel tubing. The bumper shall be fully welded design and shall be welded to the rear side body compartments.

One (1)
56-30-0001

The rear bumper shall be 12" deep and run full width of the vehicle.
Aluminum Diamond Plate Step

Y__N__

BUMPER STEP SURFACE

The bumper step shall be covered with aluminum diamond plate with welded end caps. The bumper stepping surface will comply with the latest version of NFPA 1901.

One (1)
57-00-0501

Top Side Body Aluminum Trim

Y__N__

TOP SIDE BODY TRIM

The top of all side body compartments shall be covered with Aluminum diamond plate.

Top overlay edges shall be angled downward and extended over the outer body panel approximately 1.00"

One (1)
57-00-0601

Rear Body Aluminum Finish

Y__N__

REAR BODY TRIM

Any areas on the rear not covered with Chevron reflective stripping, shall be covered with Aluminum diamond plate.

One (1)
57-00-0701

Compartment Trim Aluminum Finish

Y__N__

FRONT COMPARTMENT TRIM

10026-0002

05/23/22

First Choice Fire & Safety Inc.

Front exterior wall of the front compartments shall be covered with Aluminum diamond plate.

One (1)
57-00-0801

Post Trim Aluminum Finish

Y__N__

SIDE BODY POST TRIM

Side body support posts shall be covered with Aluminum diamond plate.

One (1)
57-00-0901

Pump House Trim Aluminum Finish

Y__N__

PUMP HOUSE TRIM

The front of the pump house shall be covered with Aluminum diamond plate.

One (1)
57-20-0310

Rub Rails 1.00 x 1.50 S/S

Y__N__

STAINLESS STEEL RUB RAILS

Rub rails shall be provided and installed below each side compartment. The rub rail assembly shall be constructed of 1.00" x 1.50" heavy-duty 14-gauge 304 grade stainless steel tubing with black end caps and will be DA finished. Rub rails shall be bolted to the lower exterior edge of the apparatus body, with 0.50" nylon spacers installed between the body and the rub rail.

One (1)
58-08-0100

Hose Bed Description

Y__N__

HOSE BED

A stainless steel hose bed with swirl finish shall be located above the water tank. The hose bed front and side walls shall be free of all sharp objects to prevent hose damage. There shall be two removable floor sections constructed of fiberglass grating, model T-3500, 1" "T" bars with 35% open area. This will allow for proper ventilation and drainage of hose.

One (1)
58-08-1200

Hose Bed Dividers (3)

Y__N__

HOSE BED DIVIDERS

Three (3) full length adjustable hose bed dividers shall be located in the hose bed area and shall be fully adjustable by means of stainless steel uni-strut tracking located at the front and rear of the hose bed.

The dividers shall be of "one piece" 1/4" extruded aluminum construction with integral extruded bottom "T" bar which runs full length of the hose bed. A top 1/2" diameter smooth edge is provided to prevent damage to hose.

One (1)

The dividers shall be bolted in place with stainless steel fasteners and be easily adjusted from side to side with simple hand tools.

Hose Bed Capacity

Y__N__

10026-0002

05/23/22

First Choice Fire & Safety Inc.

58-08-2200

HOSE BED CAPACITY

The hose bed shall be capable of holding the following hose:

___ Feet of 5.00" LDH hose

___ Feet of 4.00" LDH hose

___ Feet of 3.00" DJ hose

___ Feet of 2.50" DJ hose

___ Feet of 1.75" DJ hose

One (1)
58-08-5100

Hosebed Tarp - vinyl (single axle)

Y___N___

HOSEBED TARP

A Black vinyl hosebed cover shall be provided with Velcro and twist lock fasteners on the front, shock cords fasteners on the sides with stainless steel hooks, and rear weighted flap with straps.

One (1)
58-09-0100

Hand Rails - Extruded aluminum tubing with ribbed rubber inserts

Y___N___

HAND RAILS

Access hand rails shall be 1-1/4" in diameter extruded aluminum tubing with ribbed rubber inserts. Access rail escutcheons and brackets shall be chrome plated and attached with stainless steel bolts. Anchoring of posts and framing members for handrails of all types shall capable of withstanding a load of at least 225 pounds applied in any direction at any point along the rail.

Hand rails and handholds shall be constructed so that three points of contact (two hands and one foot, or one hand and two feet) can be maintained at all times while ascending and descending.

One (1)
58-09-0200

Vertical Rear Hand Rails Standard

Y___N___

VERTICAL HAND RAILS

Two (2) 48" long hand rails shall be mounted vertically at the rear of the apparatus, one on each side of the rear compartment.

One (1)
58-09-0700

Horizontal Rear Hand Rails Standard

Y___N___

HORIZONTAL HAND RAILS

One (1) 72" long hand rail shall be mounted horizontally just below the hosebed.

One (1)
58-10-0005

Steps - (4) Innovative Controls Folding Steps

Y___N___

FOLDING ACCESS STEPS

10026-0002

First Choice Fire & Safety Inc.

There shall be four (4) Innovative Controls folding steps provided and installed. Each step shall be designed to exceed the strength, load and traction requirements of NFPA. Each step shall be chrome plated and include a molded gasket to help prevent water ingress and keep the step mount from damaging painted surfaces. The step shall include a drain at the bottom to allow any water to escape the assembly.

The folding step shall be spring loaded to hold the step in the upright stowed position while in transit and when not in use.

The step shall include a white LED step light.

Location: Rear of unit to allow easy access to the hose bed.
Suction Hose V tray - (2) - (1) Each Side

One (1)
60-00-2100

Y___N___

SUCTION HOSE MOUNTING BRACKETS

Two (2) aluminum V-Trays shall be provided and mounted on stainless steel unistrut tracking. One (1) mounted on the left side over the upper compartments and one (1) mounted on the right side over the ladders.

The hose shall be held in place with quick release holders.
Vertical Ladder Compartment

One (1)
60-00-3400

Y___N___

LADDER COMPARTMENT

A compartment will be located on right side of the booster tank under the hose bed.

Compartment shall be fabricated of 1/2" polypropylene and shall be designed to allow easy removal and storage of all specified equipment. All equipment shall be separated by dividers.

The compartment will be designed to hold a 14' roof ladder and 24' extension ladder, 10' attic ladder and two (2) pike poles.

One (1)
60-00-3450

Through Tank Ladder Compt. Doors-Aluminum

Y___N___

LADDER COMPARTMENT DOOR

Compartment will have a single vertically hinged aluminum diamond plate door with a stainless steel D'Ring latching handle. Door(s) shall be wired to the door ajar circuit.

First Choice Fire & Safety Inc.

One (1) Through Tank Ladder Compt. Doors-Painted Finish Y__N__
60-00-3454

LADDER COMPARTMENT DOOR

Compartment will have a single vertically hinged painted finish stainless steel door with a stainless steel D'Ring latching handle. Door(s) shall be wired to the door ajar circuit.

One (1) No Driver's Side Front Wheel Well Compt. Y__N__
60-00-5655

One (1) Air Bottle Compartment SS - Triple Bottle Y__N__
60-00-5670

AIR BOTTLE STORAGE COMPARTMENT (TRIPLE COMPARTMENT)

One (1) spare air bottle compartment shall be provided and located, in the front portion of the driver's side rear wheel well area. The compartment will be capable of holding three (3) spare air bottles. The compartment shall be fabricated of stainless steel and lined to prevent vibration. The compartment shall have a drain hole in the floor.

One (1) No Driver's Side Rear Wheel Well Compt. Y__N__
60-00-5705

One (1) Air Bottle Compartment SS - Triple Bottle Y__N__
60-00-5717

AIR BOTTLE STORAGE COMPARTMENT (TRIPLE COMPARTMENT)

One (1) spare air bottle compartment shall be provided and located, in the rear portion of the driver's side rear wheel well area. The compartment will be capable of holding three (3) spare air bottles. The compartment shall be fabricated of stainless steel and lined to prevent vibration. The compartment shall have a drain hole in the floor.

One (1) No Officer's Side Front Wheel Well Compt. Y__N__
60-00-5805

One (1) Air Bottle Compartment SS - Triple Bottle Y__N__
60-00-5820

AIR BOTTLE STORAGE COMPARTMENT (TRIPLE COMPARTMENT)

One (1) spare air bottle compartment shall be provided and located, in the front portion of the officer's side rear wheel well area. The compartment will be capable of holding three (3) spare air bottles. The compartment shall be fabricated of stainless steel and lined to prevent vibration. The compartment shall have a drain hole in the floor.

One (1) No Officer's Side Rear Wheel Well Compt. Y__N__
60-00-5905

First Choice Fire & Safety Inc.

One (1)
60-00-5920

Air Bottle Compartment SS - Triple Bottle

Y__N__

AIR BOTTLE STORAGE COMPARTMENT (TRIPLE COMPARTMENT)

One (1) spare air bottle compartment shall be provided and located, in the rear portion of the officer's side rear wheel well area. The compartment will be capable of holding three (3) spare air bottles. The compartment shall be fabricated of stainless steel and lined to prevent vibration. The compartment shall have a drain hole in the floor.

One (1)
60-00-6101

Wheel Well Door - Painted

Y__N__

COMPARTMENT DOOR(S)

The wheel well compartment(s) where specified will have a vertically hinged painted stainless steel door(s) with Southco #E3-17-22 all stainless steel door latch. The door(s) shall be labeled: "SPARE SCBA CYLINDER". Door(s) shall be wired to the door ajar circuit.

One (1)
60-00-6101

Wheel Well Door - Painted

Y__N__

COMPARTMENT DOOR(S)

The wheel well compartment(s) where specified will have a vertically hinged painted stainless steel door(s) with Southco #E3-17-22 all stainless steel door latch. The door(s) shall be labeled: "SPARE SCBA CYLINDER". Door(s) shall be wired to the door ajar circuit.

One (1)
60-00-6101

Wheel Well Door - Painted

Y__N__

COMPARTMENT DOOR(S)

The wheel well compartment(s) where specified will have a vertically hinged painted stainless steel door(s) with Southco #E3-17-22 all stainless steel door latch. The door(s) shall be labeled: "SPARE SCBA CYLINDER". Door(s) shall be wired to the door ajar circuit.

One (1)
60-00-6101

Wheel Well Door - Painted

Y__N__

COMPARTMENT DOOR(S)

The wheel well compartment(s) where specified will have a vertically hinged painted stainless steel door(s) with Southco #E3-17-22 all stainless steel door latch. The door(s) shall be labeled: "SPARE SCBA CYLINDER". Door(s) shall be wired to the door ajar circuit.

One (1)
60-00-6101

Wheel Well Door - Painted

Y__N__

COMPARTMENT DOOR(S)

First Choice Fire & Safety Inc.

The wheel well compartment(s) where specified will have a vertically hinged painted stainless steel door(s) with Southco #E3-17-22 all stainless steel door latch. The door(s) shall be labeled: "SPARE SCBA CYLINDER". Door(s) shall be wired to the door ajar circuit.

One (1)
60-02-1004

Shelf Tracking S/S with (1) Adjustable Shelf for 5 compartments

Y___N___

SHELVING - ADJUSTABLE

A total of five (5) adjustable shelves shall be provided and installed in customer specified location.

Shelf construction where specified shall be rigid with 2" lip on the front and rear, and fabricated of 3/16" aluminum.

The shelving shall be adjustable by means of a threaded tightener that slides in a track to allow precise adjusting height. All tracking will be stainless steel uni-strut.

One (1)
60-02-1600

Shelving Adjustable (2)

Y___N___

SHELVING - ADJUSTABLE

A total of two (2) adjustable shelves shall be provided and installed in customer specified location.

Shelf construction where specified shall be rigid with 2" reinforcement on the front and rear, and fabricated of 3/16" aluminum.

The shelving shall be adjustable by means of a threaded tightener that slide in a track to allow precise adjusting height.

LOCATION:

Four (4)
60-02-3210

Poly Equipment Mounting Board

Y___N___

POLY BOARD MOUNTING BOARD

1/2" Black poly board will installed on the back wall of the specified compartment to allow for equipment mounting. The board will be spaced 1/2" from the back wall of the compartment.

Quantity:

Location:

Two (2)
60-03-0607

Slide Master steel 100% 1,000#

Y___N___

PULL OUT TRAY

10026-0002

05/23/22

First Choice Fire & Safety Inc.

A total of one (1) Slide Master, SM3-SP 3- rail, 100% steel powder coated slide out tray shall be provided and installed in customer specified location.

Sliding tray where specified shall be mounted in a manner that provides for maximum clearance overhead.

The tray shall have a minimum capacity of 1,000 pounds in its fully extended position.

The side mounted slides are to be equipped with ball bearings for ease of operation.

Trays will have a HSL push pull lock in the open and closed positions.

One (1)
60-03-3010

Mateflex Interlocking Tiles

Y__N__

FLOOR MATTING

All compartment floors shall be lined with Black Mateflex 13" X 13" x 9/16" interlocking tiles with tapered edging at the front compartment opening.

One (1)
62-00-0500

Compartment Doors S\S 18 Gauge Standard

Y__N__

COMPARTMENT DOORS

Doors to be fabricated of 304 grade stainless steel with 18 gauge inner and outer panels.

The doors shall be 3/4" thick and reduce the compartment depth by approximately 5/8" with the door closed.

The double panel design provides strength and a tight fit with 5/8" insulation installed between the panels for sound dampening.

Doors shall be of a rigid design. Door outer panel edges will be folded and welded to the inner panel.

Welding of the inner panel directly to the outer panel face shall not be permitted due to distortion caused by welding.

The use of body filler prior to painting of the outer door panels shall not be permitted. **No Exception**

Each door is to have closed cell rubber seal to provide a weather proof seal between the door and compartment.

First Choice Fire & Safety Inc.

The compartment doors shall pivot on full length stainless steel piano hinges with a 3/16" pin diameter.

Hinges shall be welded to compartment wall and bolted to doors with 10-24 stainless steel bolts.

Compartment doors will have stainless steel flush bent "D" ring handles. Latching mechanism shall be non-locking safety slam positive latch. Gasket material is placed between the door handles and outer door panels to prevent electrolytic reaction between dissimilar metals to protect paint finish.

Mechanism is enclosed in stainless steel not exposed to equipment stored in compartment.

An inner two point latch shall be provided on the second door of all double doors with a rubber covered pull cable when applicable.

Interior of doors shall be left natural stainless with swirl finish applied to give a lasting and pleasing appearance.

One (1)
62-00-0800

Drip Rails For Hinged Compartment Doors

Y__N__

DRIP RAILS

Bright aluminum "J" channel shall be provided over each lower side body compartment and at the front and rear of the compartments.

One (1)
62-00-1500

ROM - Roll-Up Series IV Compartment Door Rear Comp

Y__N__

ROLLUP DOOR

The rear compartment shall have a R•O•M Series IV roll-up shutter door with "satin finish" installed. Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized 6063 T6 aluminum.

Shutter slats will feature a double wall extrusion 0.315" thick with a concave interior surface to minimize loose equipment jamming the shutter door closed. Shutter slats will feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal shall be a one piece PVC extrusion; seal design will be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk. Door track shall feature

First Choice Fire & Safety Inc.

an extruded Santoprene rubber double lip low profile side seal with a silicone co-extruded back to reduce friction during shutter operation.

Shutter bottom rail shall be a one piece double wall extrusion with integrated finger pull. Finger pull shall be curved upward with a linear striated surface to improve operator grip while operating the shutter door. Bottom rail shall have a smooth contoured interior surface to prevent loose equipment from jamming the shutter door. Bottom rail seal shall be made from Santoprene; it will be a double "V" seal to prevent water and debris from entering compartment. Bottom rail lift bar shall be a one piece "D" shaped aluminum extrusion with linear striations to improve operator grip during operation. Lift bar shall have a wall thickness of 0.125". Lift bar shall be supported by no less than two pivot blocks; pivot blocks shall be constructed from Type 66 Glass filled reinforced nylon for superior strength. Bottom rail end blocks shall have incorporated drain holes which will allow any moisture that collects inside the extrusion to drain out.

Shutter door shall have an enclosed counter balance system. Counter balance system shall be 4" in diameter and held in place by 2 heavy duty 18 gauge zinc plated plates. Counter balance system shall have 2 over-molded rubber guide wheels to provide a smooth transition from vertical track to counter balance system; no foam material of any kind shall be permitted or used in this area.

Magnetic door ajar switches shall be provided and installed within the shutter door strike block. Strike block will be mounted to the door track outside of the compartment. Door switch will be controlled by a magnetic end cap installed into the shutter lift bar. Door switch will provide a ground signal to a relay or multiplexing device to control compartment lighting and/or warn operator door is open.

The shutter door assembly shall be manufactured and assembled in the United States, no exceptions.

One (1)
62-00-2025

Roll-Up Door Modification - No Pull Strap Required

Y___N___

One (1)
62-00-2025

Roll-Up Door Modification - No Pull Strap Required

Y___N___

One (1)
62-01-0500

Door Closures Power Hydraulic Vertically Hinged

Y___N___

DOOR CLOSURES

All vertically hinged doors shall have power lift gas filled cylinders installed.

Closure shall assist in the closing of door once it has past the halfway point.

First Choice Fire & Safety Inc.

One (1)
62-01-1500

Door Closures Power Hydraulic Horizontally Hinged

Y___N___

DOOR CLOSURES

All horizontally hinged doors shall have power lift gas filled cylinders installed. Doors shall be held open at a 90 degree angle to the body.

One (1)
70-01-0000

Closure shall assist in the closing of door once it has past the halfway point.
Electrical - Custom Pumper

Y___N___

12 VOLT ELECTRICAL SYSTEM

All wiring and electrical equipment shall meet N.F.P.A. 1901 (2016 edition) and SAE standards.

A master optical warning device switch that energizes all of the optical warning devices shall be provided.

The optical warning system shall be capable of two separate signaling modes during emergency operations. One mode shall signal to drivers and pedestrians that the apparatus is responding to an emergency and is calling for the right of way. The other mode shall signal that the apparatus is stopped and is blocking the right of way. Switching of modes shall be controlled by the parking brake.

All wiring to be GXL ultra high temperature cross link type.
Wiring installed by the builder to be run in protective split loom where exposed to the outside.

Where wires pass through body compartments or panels grommets, snap bushings, or compression fittings shall be utilized.

All wiring harnesses and associated wiring shall be secured with nylon "ultra violet resistant" cable ties or bolted to the body with cable clamps.

Polyolefin "heat shrink" tubing with adhesive or Deutsch water tight connectors shall be used on all exterior wiring connections.

Flexible non-conductive polyurethane film shall be sprayed on all terminal studs, relays, starter, batteries, etc. To prevent corrosion.

All wiring shall be protected by automatic reset circuit breakers which conform to SAE standards. Any required exterior fuses shall be protected by an environmentally sealed fuse holder.

First Choice Fire & Safety Inc.

The breakers shall be selected to prevent wire damage when subjected to extreme current overload. Wiring to be color, function, and/or number coded.

A Class I power distribution relay board shall be utilized. Distribution board contains independently switching relays with selectable input polarity. Relays can be connected in either their normally open or normally closed positions.

Relay board features heavy duty components, visual diagnostics, and load management inputs. System is user friendly for trouble shooting.

A wiring diagram for the body electrical system shall be included with the apparatus.

JUNCTION BOX

The electrical junction box for all 12 volt wiring shall be located in a convenient location. It will be recessed into the compartment wall not to protrude into the storage area. It shall have a removable access panel.

The compartment shall be sealed and weather proof. All components in compartment shall have identification tags.

CLEARANCE LIGHTS

All required Clearance lights shall be provided at the rear and on each side of the unit to meet Federal regulations. All lights will be (LED) Light Emitting Diode type with a five (5) year warranty.

On apparatus 30 feet in length or longer, a Trucklite model 60072Y Amber LED turn signal light with stainless steel flange shall be mounted one (1) each side in rear wheel well area at approximately running board height.

LED STEP AREA LIGHTING

Four (4) step area lights shall be provided. One mounted each side on the front compartment face to illuminate the panel running board steps and two mounted at the rear of the unit to illuminate the rear tailboard step. These lights shall be activated when the parking brake is applied.

Whelen 3SCOCD CR series 3.00" round LED lights shall be utilized. Depending on body application the lights will either be mounted in a rubber grommet or surface mounted with a chrome flange.

First Choice Fire & Safety Inc.

HAZARD LIGHT

A red flashing light shall be located in the driving compartment, and shall be illuminated automatically whenever the apparatus parking brake is not fully engaged and any passenger or equipment compartment door is open, any ladder or equipment rack is not in the stowed position, a stabilizer system is deployed, a powered light tower is extended, or any other device is opened, extended, or deployed that creates a hazard or is likely to cause damage to the apparatus if the apparatus is moved. The light shall be marked "DO NOT MOVE APPARATUS WHEN LIGHT IS ON".

One (1)
70-02-1570

License Plate Light - LED

Y__N__

LICENSE PLATE LIGHT

One (1) Trucklite model 15055 LED license plate light and bracket shall be provided on the rear of the unit.

One (1)
70-02-1600

Emergency Warning Light Switches Custom Cab

Y__N__

EMERGENCY WARNING LIGHT SWITCH CONTROLS

All warning light switches shall be mounted in the cab in a readily accessible location.

The master switch and individual switches furnished with custom chassis shall be utilized to allow preselection of lights. The light switches are to be "rocker" type with an internal indicator light to show when the switch is energized. All switches to be properly identified and mounted in a removable panel for ease in servicing. Identification of the switches shall be done by either printing or etching on the switch panel.

One (1)
70-02-2800

Whelen M6 Quad Cluster LED Rear Stop, LED Turn, LED Backup

Y__N__

WHELEN M6FCV4 QUAD CLUSTER REAR DOT LIGHTING

BACKUP LIGHTS

Two (2) Whelen model M6BUW Super LED backup lights

STOP/TAIL LIGHTS

Two (2) Whelen model M6BTT series Super LED Brake/Tail lights

DIRECTIONAL LIGHTS

First Choice Fire & Safety Inc.

Two (2) Whelen model M6T series Super LED arrow directional turn signal lights

The backup lights, stop/tail lights, and directional lights along with rear lower level warning lights shall be installed on the lower rear face of the unit and shall be recessed in chrome plated flange.

One (1)
70-02-3100

Compartment Lights Soundoff Signal (1) 10"

Y__N__

COMPARTMENT LIGHTS

One (1) SoundOff Signal model ECVCLLED10, 10" strip LED compartment light shall be provided in each compartment. The lighting shall be mounted in the ceiling of the compartment.

All compartment lighting shall be automatic by the opening and closing of the door.

One (1)
70-02-3290

All main apparatus body compartments shall have door ajar switches.
Compartment Lights SoundOff Signal 21" Single For 30" H Compt.

Y__N__

COMPARTMENT LIGHTS

SoundOff Signal model ECVCLLED21, 21" LED compartment lighting shall be provided in each compartment. The lighting shall be mounted behind the door jamb on one side of the compartment.

All compartment lighting shall be automatic by the opening and closing of the door.

One (1)
71-03-0700

All main apparatus body compartments shall have door ajar switches.
Ground LED Lighting Custom Pumper

Y__N__

LED GROUND LIGHTING

The apparatus shall be equipped with lighting capable of providing illumination at a minimum level of two (2) footcandle on ground areas within 30.00" of the edge of the apparatus in areas designed for personnel to climb onto the apparatus or descend from the apparatus to the ground level. Lighting designed to provide illumination on areas under the driver and crew riding area exits, which shall be activated automatically when the parking brake is set. Lights shall be installed in a manner that illuminates all walkways and steps for safe operation of the apparatus.

TecNiq E10-WSOO-1 6.00" LED lights mounted in a stainless steel bracket shall be utilized.

First Choice Fire & Safety Inc.

One (1)
71-04-0099

Two (2) lights mounted under the rear step.
One (1) light located each side under the pump panel running boards.
(1) SoundOff LED Pump Compartment Light

Y__N__

PUMP COMPARTMENT LIGHT

One (1)
71-31-3000

One (1) SoundOff model ECVCSLLED10-10" LED pump compartment light shall be provided within the pump enclosure. The control switch shall be located on the pump operators panel.
TecNiq LED Front Hose Bed Lights

Y__N__

HOSE BED LIGHTS

One (1)
71-31-3008

There shall be two (2) TecNiq (model E10-W000-1) 6.00" LED lights with clear lens lights mounted at the front of the hose bed. The lights will be activated by a switch located on the pump panel.
Whelen Dunnage Area LED Lights

Y__N__

DUNNAGE AREA LIGHTS

One (1)
75-12-0025

There shall be two (2) Whelen 3SCOCD series 3.00" round LED lights provided and mounted in the dunnage area to provide adequate illumination of this area. The lights will be activated when the parking brake is applied.
Light Bar - Furnished With Custom Chassis

Y__N__

NFPA APPROVED UPPER LEVEL LIGHT PACKAGE

ZONE A - FRONT UPPER

One (1)
75-30-0004

A cab roof light bar will be furnished with the custom chassis.
L31H - Super Red LED Zone C

Y__N__

ZONE C - UPPER

One (1)
75-30-1018

Two (2) model L31HRFN Super Red LED 360 beacon lights mounted on the upper rear light stanchions.
Whelen M9 Zone B&D (4) Zone C (2)

Y__N__

ZONE B & D - SIDE UPPER

Two (2) Whelen M9 Super LED lights with chrome bezels will be mounted one each side on the upper front side corners of the body.

First Choice Fire & Safety Inc.

Two (2) Whelen M9 Super LED lights with chrome bezels will be mounted one each side on the upper rear side corners of the body.

ZONE C - REAR UPPER

Two (2) Whelen M9 Super LED lights with chrome bezels will be mounted on the upper rear of the body.

One (1)
75-30-1050

Whelen Upper Level Light Lens Color - Red

Y___N___

UPPER LEVEL LIGHT LENS COLOR

The upper level lights shall have red lenses.

One (1)
75-40-0620

Whelen M Series LED Lower Level Lighting Custom Cab B&D (2)

Y___N___

WHELEN LOWER LEVEL LIGHTING

ZONE A - LOWER

Two (2) LED lights provided by chassis manufacture.

ZONE B & D- SIDE LOWER

One (1) LED lights provided by the chassis manufacture.

Two (2) M7 Super LED lights with chrome bezel mounted one (1) each side in the rear body fender area.

ZONE C - LOWER

Two (2) M6 Super LED lights mounted on the lower rear of the apparatus in M6FCV4 chrome housing.

One (1)
75-40-0800

Whelen Lower Level Light Lens Color - Red

Y___N___

LOWER LEVEL LIGHT LENS COLOR

The lower level lights shall have red lenses.

One (1)
85-01-0480

Siren - Furnished with Custom Chassis

Y___N___

ELECTRONIC SIREN

The electronic siren will be furnished with the custom chassis.

One (1)
85-02-0480

Speaker - Furnished with the Custom Chassis

Y___N___

SIREN SPEAKER

First Choice Fire & Safety Inc.

One (1)
88-01-0502

The siren speaker will be furnished with the custom chassis.
Six (6) Tech Guardian Elite

Y__N__

SCENE LIGHTS

Six (6) FireTech HI-Viz model GESM Gaurdian Elite 20,500 lumens LED, (9.65" high x 10.63" wide) white scene lights will be installed on the body.

Two (2) located each side of the body, one (1) at the front and one (1) at the rear, and two (2) located on the rear face of the unit.

Lights will be controlled by three individual switches located in the cab. Rear lights will also be activated when unit is put into reverse.

One (1)
98-00-0100

Paint And Preparation - Body Only

Y__N__

PAINT AND PREPARATION

All metal surfaces will be properly sanded, prepared and finished ready for our Axalta Coating Systems pretreatment. This is done to insure optimum adhesion, corrosion resistance, and durability.

After pretreatment, 1220S Axalta Coating Systems 5000 URO primer filler is applied designed to fill any minor surface defects and provide an adhesion layer between the pretreatment and the Imron Base Coat/Clear Coat. This is also applied to improve color gloss, retention, and durability of the paint.

Next the URO primer will be sanded to a smooth prepainting surface. The surface will be decontaminated and prepared for application of High Solids Axalta Coating Systems Productive Base Coat/Clear Coat finish to complete the finished paint process.

A full inspection is performed of Defects, Depth Imagery, Gloss, Film Build, Color Match and Texture, all to meet or exceed Axalta Coating Systems OEM fleet finish specifications.

Body assemblies that cannot be finish painted upon assembly shall be painted prior to finish assembly. All doors are removed and painted separate from the body.

Prior to reassembly and reinstallation of lights, handrails, door hardware, and any miscellaneous items; a gasket material or silicone sealant shall be applied to

First Choice Fire & Safety Inc.

prevent damage to the finish painted surfaces and to protect against electrolysis between dissimilar metals.

Touch up paint shall be provided for each color paint used.

The complete apparatus body will be painted a single color to match the color of the cab. The cab shall remain as painted from the chassis supplier.

Paint Color _____ - Paint # _____
Paint Stripe Wheels Single Axle

One (1)
98-01-0100

Y__N__

PAINTED WHEELS

Vehicle wheels shall be painted to match the exterior paint.
3.00" Lettering - Gold Vinyl

One (1)
99-00-0500

Y__N__

LETTERING

Lettering shall be provided. It shall be computer generated, non-reflective, Gold Metallic Acrylic Vinyl Applique with a black border.

Computer generated lettering provides a proportional layout design and durable finish.

Included will be a maximum of sixty five (65) three (3) inch letters.
Reflective Striping - 4"

One (1)
99-01-0500

Y__N__

REFLECTIVE STRIPING

A 4" wide white reflective stripe shall be applied to the unit in a straight line.

Per NFPA 15.9.3.1 this shall include at least 50 percent of the cab and body length on each side, excluding the pump panel areas, and at least 25 percent of the width of the front of the apparatus.

One (1)
99-03-2200

Chevron Rear reflective

Y__N__

REFLECTIVE CHEVRON - NFPA 15.9.3.2

50 percent of the rear-facing vertical surfaces, visible from the rear of the apparatus, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45 degrees. Each stripe shall be 6" in width.

Stripe Colors will be Red & Yellow.
Equipment

One (1)
A0-00-0000

Y__N__

10026-0002

05/23/22

First Choice Fire & Safety Inc.

EQUIPMENT

The following equipment shall be provided along with any necessary mounting brackets.

NFPA EQUIPMENT CLARIFICATION

Any equipment specified in the "Minor Equipment" section (e.g. hose, nozzles, adapters, AED, traffic cones, traffic safety vests, etc.) of NFPA 1901 for each apparatus classification which is not specified in this proposal will be considered to be customer supplied.

One (1)
B1-10-5900 Two (2) Suction Hose - 6" x 10' Flex Y__N__

SUCTION HOSE

Two (2) Firequip Maxi-Flex 6" x 10' light weight PVC Suction hose with male and 6" long handled female couplers.

One (1)
B2-01-6000 Strainer - 6" Barrel Y__N__

SUCTION HOSE STRAINER

One (1) South Park #BS4522AC, 6.00" barrel strainer will be provided and mounted in customer specified location.

One (1)
E5-02-3000 Duo-Safety 10' Folding Attic - Model 585-A-10 Y__N__

10' FOLDING LADDER

A Duo-Safety model 585-A-10, 10' folding ladder shall consist of 1-section aluminum ladder with rubber feet shall be provided and installed in customer specified location. Ladder shall meet or exceed the latest NFPA standards.

One (1)
E5-02-5100 Duo-Safety 14' Roof - Model 775-A-14 Y__N__

14' ROOF LADDER

There shall be a 14', Duo-Safety model 775-A-14, roof ladder of single section aluminum with folding steel roof hooks on one end and steel spikes on the other end. Ladder shall meet or exceed latest NFPA standards.

One (1)
E5-02-7500 Duo-Safety 24' Extension - Model 900-A-24 Y__N__

24' EXTENSION LADDER

A Duo-Safety model 900-A-24, 24' extension ladder shall consist of 2 aluminum sections. Ladder shall meet or exceed NFPA standards.

One (1)
E5-10-3500 Pike Pole - 8' Fiberglass Y__N__

10026-0002

First Choice Fire & Safety Inc.

8' FIBERGLASS PIKE POLE

One (1) Duo-Safety Type FP, 8' fiberglass handle pike pole shall be provided consisting of a 8' hollow fiberglass pole 1-3/4" OD with a painted steel pike riveted to the pole.

One (1)
E5-10-4000

Pike Pole - 10' Fiberglass

Y___N___

PIKE POLE

One (1) Duo-Safety Type FP, 10' fiberglass handle pike pole shall be provided consisting of a 10' hollow fiberglass pole 1-3/4" OD with a painted steel pike riveted to the pole.

One (1)
F1-01-0001

Zico AC32 Wheel chocks - underbody (2)

Y___N___

WHEEL CHOCKS

Two (2) Zico AC32 wheel chocks will be provided and mounted under the left front compartment.

One (1)
O2-01-0000

Kochek Spanner wrench - with hydrant wrench

Y___N___

SPANNER WRENCH SET W/HYDRANT WRENCH

One (1) set of Kochek style K45-3Y spanner wrenches shall be provided and mounted in customer specified location. Includes (1) Hydrant wrench and (2) spanner wrenches with mounting bracket.

One (1)
O2-01-0500

Location:
Kochek Spanner wrench - (2-1/2")

Y___N___

SPANNER WRENCH SET

One (1) set of Kochek style K46-2Y spanner wrenches shall be provided and mounted in customer specified location. Includes (2) spanner wrenches with mounting bracket.

One (1)
O4-00-6100

Location:
Traffic Vest NFPA Customer Supplied

Y___N___

SAFETY FIRE VEST

The NFPA required Safety Vest will be supplied and installed by the purchaser before the truck is placed into service.

One (1)
O4-00-6110

Traffic Cones Customer Supplied

Y___N___

TRAFFIC CONES

10026-0002

05/23/22

First Choice Fire & Safety Inc.

The NFPA required traffic cones will be supplied and installed by the purchaser before the truck is placed into service.

One (1)
O4-00-6120

Automatic External Defibrillator (AED) Customer Supplied

Y___N___

AUTOMATIC EXTERNAL DEFIBRILLATOR (AED)

The NFPA required AED will be supplied and installed by the purchaser before the truck is placed into service.

One (1)
Z0-20-0000

Chassis Delivery

Y___N___