

<b>PACKAGE ARRANGEMENT (1)</b>		<b>CONTRACT IS 25% OFF BASE UNIT LIST PRICE</b>	
<b>Product</b>	<b>Approx. Weight</b>	<b>List Price</b>	
DA30	23,000.00 KG	486,289.43 USD	
DA30 Base Machine with Dump Body and Hoist Cylinders With Tailgate Differentials - Limited Slip Front and Rear Steel Cab with Integrated ROPS/FOPS Tires - Aeolus 23.5R25 AL37 E3 Radial			

<b>OPTIONAL EQUIPMENT - Factory Installed (28)</b>			<b>CONTRACT IS 20% OFF OPTIONS LIST PRICE</b>
<b>Option</b>	<b>CODE</b>	<b>Description</b>	<b>List Price</b>
C_FPRO	DA30-5-US10	Package	0.00
Elec. adjustable heated mirror	HTD	ELECTRIC ADJUSTABLE HEATED MIRROR	529.60 USD
Webasto heating system	WHS	WEBASTO HEATING SYSTEM	4,649.54 USD
First aid kit	FAK	FIRST AID KIT	420.41 USD
Rotating Beacon	STD	ROTATING BEACON	289.36 USD
Light bar LED	LTB	LIGHTBAR LED, CAB ROOF	1,050.46 USD
Work light kit	STD	WORK LIGHT KIT STANDARD (REAR AND FRONT)	505.57 USD
Work light kit	LED	WORK LIGHT KIT HIGH PERFORMANCE LED (REAR AND FRONT)	5,375.68 USD
Tailgate kit	TGT	WITH SCISSOR TYPE TAILGATE	0.00 USD
Body heating kit	BDH	BODY HEATING SYSTEM	6,011.20 USD
Body lining	BLS	BODY LINING STANDARD	9,534.93 USD
Side extensions	200	DUMP BODY SIDE EXTENSIONS 8 IN. (200MM)	6,273.27 USD
Body	STD	WITH DUMP BODY	0.00 USD
Hoist cylinders	STD	WITH HOIST CYLINDERS	0.00 USD
Fast fill	FUT	FAST FILL	4,719.42 USD
Parts catalogue(paper version)	PTC	PARTS MANUAL, PAPER	262.07 USD
Shop manual	STD	SHOP MANUAL, PAPER	358.17 USD
Tire	CO1	CONTINENTAL 23.5R25 EM-M E3 WITH PRES./TEMP. MONITOR	14,519.75 USD

Tire	CO2	CONTINENTAL 23.5R25 EM-M E4 WITH PRES./TEMP. MONITOR	16,660.83 USD
Tire	LTB	BRIDGESTONE 23.5R25 VLT E3	20,280.83 USD
Tire	75B	BRIDGESTONE 750/65R25 VLT E3	36,358.72 USD
Tire	GE3	GOODYEAR 23.5R25 TL-3A E3	18,201.75 USD
Tire	75G	GOODYEAR 750/65R25 TL-3A+ E3	36,192.74 USD
Tire	ME3	MICHELIN 23.5R25 XADN E3	23,375.41 USD
Tire	XTM	MICHELIN 23.5R25 X-SUPER E4	26,264.72 USD
Tire	M75	MICHELIN 750/65R25 XAD E3	44,376.92 USD
Tire	AL3	Aeolus 23,5 R25** AL37 E3	0.00 USD
Tire	AL7	Aeolus 750/65R25** AE36 E3	14,935.36 USD

### Attachments - Dealer Installed

Attachment	Description	Approx. Weight	List Price

### STANDARD EQUIPMENT FOR BASE MACHINE (11)

Item	Description
ENGINE	"Scania DC9, Turbocharged, Water Cooled, Air to Air Intercooled, Tier 4 Final Electronically Controlled Common Rail Direct Injected SCR, CEGR with DOC Displacement 568 cu in. (9.3 L) 5 Cylinders with Individual Heads, Bore 127 mm dia x Stroke 140 mm 375 Gross HP (ISO 3046) @ 2100 rpm 362 Net HP (ISO 14396) @ 2100 rpm Maximum Torque 1,381 ft lbs @ 1300 rpm Centrifugal Oil Cleaner Donaldson 2 Element Dry Engine Air Filter Fuel Filter with Pre-heater and Water Separator Engine Overheat and Low Oil Pressure Warning System 24V Starter, 2 x 12V Batteries (140 Ah each), 100A Alternator"
TRANSMISSION	"ZF 8EP-320 8F / 4R Gears, Lockup in All Gears Full Automatic or Manual Shift, Powershift, Countershaft Electronically Controlled with Retarder Top Speed - 34.2 mph Forward, 9.9 mph Reverse"
DRIVELINE	"Limited Slip Front and Rear Differentials 100% Lockable Inter-axle Differential Free Swinging Rear Tandems with Oil Bathed Gears"
	"High Tensile HB400 Steel with Single Stage, Double Acting Hoist Cylinders, Standard Body has 8 mm Front, 10 mm Sides, 12 mm Bottom Scissor Type Top Tailgate

BODY	<p>31 Short Ton Payload (61,730 lbs.)          Heaped Body Capacity 22.0 yd<sup>3</sup> (23.3 yd<sup>3</sup> with Tailgate)          Struck Body Capacity 17.8 yd<sup>3</sup> (18.6 yd<sup>3</sup> with Tailgate)          Body Tipping Time Up - 12 s          Body Tipping Time Down - 10 s"</p>
CABIN	<p>"Interior 71 dB(A) (ISO 6394)          ROPS/FOPS (ISO 3471, ISO 3449)          Adjustable Air Suspension Operator Seat          Instructor Seat          All Instrumentation in LCD Display          Ashtray          12V Charging Port          Retractable Roller Sunblind          Tinted Safety Glass          Sliding Window Rear Left Side and Front Right Side          Tilt Cab to Rear by Standard Hydraulic Jack          Tilting and Telescopic Steering Wheel          Electronic Retarder Control Lever          Radio/CD/MP3          Electronic Climate Control          Hand/Arm Vibrations &lt; 2.5 m/s (ISO 5349-2)          Whole Body Vibration &lt; 0.5 m/s (ISO 2631-1)          LCD Digital Information Displayed:          -Rpm          -Travel Speed          -Engine Coolant Temperature          -Transmission Oil Temperature          -Retarder Oil Temperature          -Fuel Level          -Transmission Gear Engaged          -Urea Remaining          -Fault Codes          -Gradient Meter          LCD Warning Lights          -Engine Failure          -Low Engine Oil          -Low Coolant          -Dirty Engine Air Filter          -Transmission Failure          -Parking Brake          -Brake Failure          -Hydraulic System Failure          -Emergency Steering Failure          General          -Autolube System Failure          -Battery Charge          -Body Down          -Various Lights          -Transmission Lock Up          -Auto/Manual Transmission Mode          -Retarder ON          -Engine Brake On"</p>
HYDRAULIC	<p>"1 Axial Piston, Variable Displacement Main Pump, 80.6 gpm          1 Radial Piston, Variable Displacement Emergency Steering Pump, 13.2 gpm          Main Relief Pressure 4061 psi"</p>
BRAKES	<p>"Electronic Engine Exhaust Brake and Hydraulic Transmission Retarder          Dual Circuit, Hydraulic Operated, Oil Cooled Wet Disc          Spring Applied Parking Brake, Hydraulic Released"</p>
SUSPENSION	<p>"Front - Independent with 1 Hydro-gas suspension cylinder, Each Side, with pressure accumulators          Rear - Free Swinging Tandem, Oil Bathed and Gear Driven Tandem Housings"</p>
TIRES	<p>Aeolus 23.5R25 AL37 E3 Radial</p>

<p>REFILL CAPACITIES</p>	<p>"Fuel Tank - 95.1 gal          Diesel Exhaust Fluid Tank - 18.5 gal          Cooling System - 11.9 gal          Engine Oil - 9.2 gal          Transmission - 17.7 gal          Front Differential - 2.5 gal          Front Hub - 2 x 2.9 gal          Tandem Housing, Rear Differential and Hubs - 38.4 gal          Hydraulic Tank - 16.6 gal"</p>
<p>OTHER</p>	<p>"Groeneveld Automatic Lubrication System          On Board Load Weighing System          Work Lights on Roof Cap          Light, Stop, Tail &amp; Direction Indicators          Rear View Camera          Handrails &amp; Service Platforms          Skid-Resistant Steps &amp; Service Platforms          Body Lift Support          Mud Flaps          Tow Hooks Front and Rear          Body Front Spill Guard          Windshield Washer and Wiper          Rear Window Protection          Ground Driven Emergency Steering          Engine Emergency Shutdown Switch          CD Parts Book, O&amp;M Manual          First Maintenance Kit          Doosan Connect Telematics, 3 Year Subscription          12 Months / 2,000 Hours Standard Warranty"</p>