



BIG BITE. EVEN BIGGER PROFITS.

SKID & TOW-BEHIND TRUCKLOADERS

Little Wonder Monster TruckLoaders are all bite, attacking debris with ease. These monstrous machines allow you to fit more in the truck and clear more properties between offloads for higher productivity and more profit.



18HP



29HP



35HP

STANDARD FEATURES

- Replaceable steel housing liner
- Stack gaskets seal in airflow and lock in debris moisture
- Flexible intake hose
- Flexible discharge hose
- 12V Battery
- 2-year warranty*

*Engines are warranted separately by manufacturer.

Mounting Options: Skid, Swing-Away Hitch (18HP)
or Tow-Behind (excludes 18HP)




49HP



INDUSTRY LEADING 15 TO 1
REDUCTION RATIO



What makes a Little Wonder Monster TruckLoader a real beast? A four blade steel impeller with shredding teeth on all three debris touch points provides the best shredding ratio in the industry—**UP TO A MONSTROUS 15 to 1.**



Skid & Tow-Behind TruckLoaders

Skid Mount Swing or Tow Behind	8183-04-01 8184-04-01	8293-04-01 8295-04-01	8353-04-01 8355-04-01	8493-06-01 8495-06-01
CE Product No.	8183-04-59 8184-04-59	N/A	N/A	N/A
Engine	B&S Vanguard™	B&S Vanguard™	B&S Vanguard™	Kohler® Diesel KDI
Engine Power (HP)	18	29	35	49
Fuel Capacity, gal (l) / Fuel Type	1.5 (5.6) / Gasoline	6 (22.7) / Gasoline	7 (26.4) / Gasoline	22 (83.2) / Diesel (FT4)
Emissions Compliance	EVAP / 49-state	EVAP / 49-state	EVAP / 49-state	Final Tier 4 (FT4)
Mount	Skid Mount Swing-Away	Skid Mount Tow Behind	Skid Mount Tow Behind	Skid Mount Tow Behind
Hitch Class Requirements (min)	Class III	Class III	Class III	Class III
Hitch Type	N/A Square Receiver	N/A Ball Coupler	N/A Ball Coupler	N/A Ball Coupler
Starter	Electric / Pull	Electric	Electric	Electric
Impeller Mount / Drive	Taper Lock Hub / Direct	Taper Lock Hub / Direct	Taper Lock Hub / Belt	Taper Lock Hub / PTO clutch
Impeller Diameter, in (cm) / Type	20 (50.8) / Serrated	19.75 (50.2) / Serrated	25 (63.5) / Serrated	25 (63.5) / Serrated
Impeller Blades / # Cutting Points	4 / 48	4 / 48	4 / 48	4 / 48
Impeller Material / Thickness, in (mm)	Steel / 3/8 (9.5)	Steel / 3/8 (9.5)	Steel / 1/2 (12.7)	Steel / 1/2 (12.7)
Air Flow (CFM)	3,510	4,710	6,950	7,600
Housing Liners, in (mm)	3/16 (4.7) Steel	1/4 (6.3) Steel	1/4 (6.3) Steel	1/4 (6.3) Steel
Flexible Intake Hose (D x L)	10" (25.4cm) x 10' (3m)	12" (30.4cm) x 10' (3m)	16" (40.6cm) x 10' (3m)	16" (40.6cm) x 10' (3m)
Flexible Discharge Hose (D x L)	7" (17.7cm) x 3' (0.9m)	8" (20.3cm) x 5' (1.5m)	12" (30.4cm) x 6' (1.8m)	12" (30.4cm) x 6' (1.8m)
Axle Rating, lbs (kg)	N/A	2,000 (907)	3,500 (1,587)	3,500 (1,587)
Suspension	N/A	N/A	Torflex®	Torflex®
Tire-Wheel	N/A	N/A ST205 / 75 D15	N/A ST205 / 75 D15	N/A ST205 / 75 D15
Assembled Dimensions L x W x H, in (cm)	25 x 29 x 84 (62 x 72 x 213)	40 x 37 x 98 (102 x 94 x 249) 87 x 54 x 109 (221 x 138 x 277)	46 x 51 x 94 (117 x 130 x 239) 99 x 65 x 114 (252 x 165 x 290)	
Dry Weight, lbs (kg)	460 (209) 580 (263)	727 (330) 1,090 (494)	1,155 (524) 1,555 (705)	1872 (849)* 2272 (1031)

*pre-production estimate