

VSA FVR De-Rate- Build (2024 FVR De-Rate, MW1 152"WB, 127"CA, 25,950 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank

Selected Model and Options

	Code	Description
Model	MW1 G1	FVR De-Rate 152"WB, 127"CA White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank
Vehicle Application	RQ2	Truck Application
Emissions	NG5	50 State Emission
Tires	I5H 5S8	LRR (low rolling resistance) 11R22.5 G
Engine	IE8	Cummins B6.7, diesel engine, 408 CID (6.7L), 260 HP at 2400 RPM, 660 lb.-ft. gross torque at 1600 RPM, 6-cylinder, turbocharged, inter-cooled, EGR cooler, high pressure common rail fuel system, and single module aftertreatment.
Transmission	Y6T	Allison RDS 2500 / 6 speed trans w/ PTO gear
Wheelbase	39W	152" Wheelbase 127"CA
Air Cleaner	E6U	Dry paper single element. (Donaldson)
Alternator	KW1	160 AMP. with integral regulator.
Battery	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	I0B	Single module Cummins aftertreatment w/ DPF & SCR, exhaust cooler, and electronic exhaust restriction.
Front Axle	40C	Dana E1254-W 12,000 lbs. capacity
Rear Suspension	34L SAS	21,000 lbs. capacity Multi leaf, bolted
Rear Axle	M21	Dana S21-140 single-speed axle, 21,000 lbs. capacity with synthetic lubricant
Ratio	011	5.571:1
Fuel Tank	70A	Left hand rail

Current report content is based on data as of 2023-05-16 06:17:14. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

VSA FVR De-Rate- Build (2024 FVR De-Rate, MW1 152"WB, 127"CA, 25,950 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank

Selected Model and Options

	Code	Description
Seat	THF	50 Gallon Fuel Tank Capacity
	A56	Level air suspension seat with RH armrest driver seat
Brakes	Z06	Full air dual circuit, s-cam, drum
Air Conditioning	C60	Air conditioner
Power Windows & Door Locks	IL0	Yes
Floor Mats	IQ6	Standard Floor Mats
Model Option	G1	White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank
CAB	729	Arc white color
Mirrors	DJ6	Black mirror head with black stays
Frame	7KJ	Straight frame, 80,000 PSI, 33.5 wide
Front Springs	34K	12,000 lbs. capacity
Accessories	8RP	Radio AM/FM/CD with Bluetooth
	IX2	Rear body dome lamp switch
Air Compressor	I04	17 CFM turbocharged heavy duty.

Current report content is based on data as of 2023-05-16 06:17:14. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.