

VSA NPRHD Diesel- Build (2024 NPR-HD Cab Chassis, 3F1 109"WB, 86.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description
Model	3F1	NPR-HD Cab Chassis 109"WB, 86.5"CA
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning
Tires	I5H	LRR (low rolling resistance)
Engine	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM; 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.
Transmission	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,
Wheelbase	IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in. per rail. 86.5"CA
Air Cleaner	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).
Alternator	I2C	140 AMP. with integral regulator.
Battery	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	IX7	Single horizontal with DPF/SCR exhaust system
Front Axle	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspension	ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.
Front Wheels	RBX	16" X 6", 6-hole disc, painted white.
Front Tires	I53I69	215/85R16E (10 ply) tubeless Radial, all season tread.
Rear Suspension		

Current report content is based on data as of 2023-05-16 06:50:33. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

VSA NPRHD Diesel- Build (2024 NPR-HD Cab Chassis, 3F1 109"WB, 86.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description
Rear Axle	I27	9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers
Ratio	I36	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.
Rear Wheels	005	4.56:1
Rear Tires	RBZ	16" X 6", 6-hole disc, painted white.
Fuel Tank	I53I34	215/85R16E (10 ply) tubeless Radial, all season tread.
Seat	I4I	30 Gallon Stainless Steel In-Rail Fuel Tank
Brakes	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Air Conditioning	K40 IE1	Butterfly valve type exhaust brake Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.
Power Windows & Door Locks	C60	Air conditioner
Floor Mats	IL0	Yes
Model Option	IQ6	Standard Floor Mats
Assistance System	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning
Accessories	I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)
	IX2	Rear body dome lamp switch
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2023-05-16 06:50:33. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.