

VSA NQR DSL-Build (2024 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description
Model	3R1 54	NQR Cab Chassis 109"WB, 86.5"CA White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning
Tires	I5H	LRR (low rolling resistance)
Engine	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.
Transmission	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,
Wheelbase	IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in ³ RBM 316,800 lb./ft./in. per rail. 86.5"CA
Air Cleaner	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).
Alternator	I2C	140 AMP. with integral regulator.
Battery	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	IX7	Single horizontal with DPF/SCR exhaust system
Front Axle	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspension	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar
Front Wheels	IB9	19.5" x 6", 6-hole disc, painted white
Front Tires	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season
Rear Suspension	ID9	14,550 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock

Current report content is based on data as of 2023-05-16 06:35:14. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

VSA NQR DSL-Build (2024 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description
Rear Axle		absorbers.
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
Ratio		
	098	5.125:1
Rear Wheels		
	IC1	19.5" x 6", 6-hole disc, painted white
Rear Tires		
	YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.
Fuel Tank		
	I4I	30 Gallon Stainless Steel In-Rail Fuel Tank
Seat		
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Brakes		
	K40	Butterfly valve type exhaust brake
	IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.
Air Conditioning		
	C60	Air conditioner
Power Windows & Door Locks		
	IL0	Yes
Floor Mats		
	IQ6	Standard Floor Mats
Model Option		
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning
Assistance System		
	I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)
Accessories		
	IX2	Rear body dome lamp switch
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2023-05-16 06:35:14. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.