

PR4500V Specs: - Recommended CA – 172”

4500 Gal. Vacuum Tank, Base, (78”)

Vac Pump, 866 Max Package, Liquid Cooled

Vacuum Pump Flush Kit

Liquid Cooled Vac Pump/Heated Valve – Coolant Kit

Drive Shaft, Power Transmission

Hot Shift PTO w/ Installation

20” Top Manway

Ladder To Manway w/ Safety Grip Tread

12” Low Profile Primary Shut-Off, 4” Internal

4” Internal Piping Through Tank

4” Dia. Hose Assy, Horiz. Traps

20” Rear Clean-Out MW, 6” Brass Lever Vlv & Cmlks

4” Intake Standpipe, TTMA Flange Connection w/ Brass Lever Vlv & Cmlks

Hose Hooks, Per Pair, as low as possible

Mud Flaps, Per Pair (2)

2” x 6” Tubular Rear Bumper

L.E.D. Running Light Kit w/ Fully Molded Wire Harness

L.E.D. Safety Beacon, Quad Flash Strobe, Clear w/ Yellow Flash

5” Site Eye (1/2,3/4,Full) (3)

Polished Aluminum Hose Trays, Short/Med

Mount Kit w/ Rubber Sill (Tandem & Tri Axle)

Mounting, Hook-Up & Wiring (Tandem, Tri & Quad Axle)

Super Liner, (Sides20”, Inside Hose Hooks)

Super Liner, (Hose Trays, Over Rail)

Paint, Custom Color (Code Provided By Customer)

Tool Box Installation, Each (2)

Toolbox, Alum Diamond Plt, 1 Door/Left Hinge, 24x24x24

Toolbox, Alum Diamond Plt, 2 Door/Right Hinge, 24x24x36