



Peterbilt of Richmond (H830)
 2800A Deepwater Terminal
 Richmond, Virginia 23212

Virginia Sheriffs Association
 901 East Byrd St Suite1301
 Richmond, Virginia 23219
 United States of America

David Askew
 Cell Phone:
 Office Phone:
 Email: daskew@thepetestore.com

Kaylyn Mitman
 Office Phone: 919-459-6471
 Email: kmitman@virginia sheriffs.org

Vehicle Summary

	Unit		Chassis	
Model:		Model 537	Fr Axle Load (lbs):	12000
Type:		Full Truck	Rr Axle Load (lbs):	21000
Description 1:		537 Standard Specs	G.C.W. (lbs):	33000
Description 2:				
	Application		Road Conditions:	
Intended Serv.:		City Delivery	Class A (Highway)	100
Commodity:		Other Commodity	Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	Body		Class D (Off-Road)	0
Type:		Van	Maximum Grade:	6
Length (ft):		24	Wheelbase (in):	175
Height (ft):		13.5	Overhang (in):	60
Max Laden Weight (lbs):		1000	Fr Axle to BOC (in):	67.5
	Trailer		Cab to Axle (in):	107.5
No. of Trailer Axles:		0	Cab to EOF (in):	167.5
Type:			Overall Comb. Length (in):	275
Length (ft):		0		
Height (ft):		0	Special Req.	
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	Restrictions			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/Opt	Description	\$ List	Weight
Base Model				
0005371	S	Model 537 The Peterbilt Model 537 is highly versatile to take on the big jobs. It is available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and an available all-wheel-drive configuration, the 537 is the perfect match for applications such as wrecker, tanker, beverage delivery, and municipal utilities just about any job you can throw at it.	103,943	9,870
0091200	S	Other Commodity	0	0
0093340	S	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095040	S	Van	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0515030	S	10-5/8" Steel Rails to 285" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	74
0611300	O	Heavy Duty 5-Piece Crossmember BOC IPO Standard Class 5, 6, 7	118	20
0611350	S	1-Piece Steel Frame Rail Xmbr Excludes Suspension	0	0
0612035	S	175" Wheelbase	0	0
0613095	O	3-Piece Suspension Crossmembers	117	0
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1014100	S	Hendrickson SteerTek NXT 12,000 lb 3.32 in Drop	37	0
1111160	S	Mono-Leaf Springs, Shocks, 12,000 LBS.	0	0

Price Level: January 1, 2023

Deal: 537 Standard Specs

Printed On: 6/19/2023 1:11:33 PM

Date: June 19, 2023

Quote Number: QUO-1050218-W1D3W8



Sales Code	Std/ Opt	Description	\$ List	Weight
1243040	S	Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	O	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354840	S	PHP10 Iron PreSet PLUS Hubs PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	0	0
1380550	O	Hendrickson Wide Track IPO Standard Hendrickson Wide Track in place of standard front axle 71" KPI IPO 69" front axle for improved turning radius.	0	15
1390710	O	Meritor Q+ Air Cam Front Drum Brakes 16.5 x 5 Not RSD compliant. Not for use on U.S. or Canada Tractors, other than Car Carriers.	270	0
1391410	S	Gusseted Cam Brackets, Steer Axle	0	0
Rear Axle & Equipment				
1511940	S	Meritor MS21-14X 21,000 LB MS-14X single rear drive axles have hypoid-generoid gearing options that offer long life and increased durability. Rigid differential cases offer precise gear alignment and durability. Optional driver-controlled differential lock (DCDL) maximizes traction and spinout protections in slippery conditions.	0	0
1616300	S	PHP10 Iron PreSet PLUS Hubs	0	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680750	O	Meritor Q+ Air Cam Rear Drum Brakes 16.5x7	-108	0
1680950	S	Stability System Not Selected Or Not Available	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1705290	O	Ratio 5.29 Rear Axle	0	0

Price Level: January 1, 2023

Deal: 537 Standard Specs

Printed On: 6/19/2023 1:11:33 PM

Date: June 19, 2023

Quote Number: QUO-1050218-W1D3W8



Sales Code	Std/ Opt	Description	\$ List	Weight
1816140	S	Reyco 79KB Taper Leaf 21,000 lb	0	0
Engine & Equipment				
2073116	S	PACCAR PX-7 200@2400 GOV@2600 520@1600 Efficiency (2021 Emissions) N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Ovrerrul N21440 C234 NO....Engine Protection Shutdown (N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N21430 C333 0.....Reserve Speed Limit Offset (N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)	0	0
2091130	S	VMUX Electronics Architecture	0	0
2091305	O	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092031	S	Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140200	O	CARB Engine Idling Compliance	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
		PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.		
2140460	S	Remote PTO/Throttle, 12-Pin, 250K BOC/BOS J1939, Remote Control Provision	0	0
2140590	S	14-Pin Body Lighting Connector	0	0
2140670	O	EPA Emission Warranty	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2522160	S	PACCAR 12V Starter PX-7 Engine Only	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539720	O	Low Voltage Disconnect System	0	0
2621090	S	DM Advantage ON/OFF Fan Clutch Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	S	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.	0	0
3211140	S	(1) Air Cleaner Engine Mounted	0	0

Price Level: January 1, 2023

Deal: 537 Standard Specs

Printed On: 6/19/2023 1:11:33 PM

Date: June 19, 2023

Quote Number: QUO-1050218-W1D3W8



Sales Code	Std/ Opt	Description	\$ List	Weight
3365290	S	Exhaust Single RH Horizontal DPF/SCR RH Under Frame.	0	0
Transmission & Equipment				
4058010	S	PACCAR TX-8AP560 Automatic 8-Speed, No Cooler	0	0
4210930	S	SPL100 Driveline, 1 Midship Bearing	0	0
4252610	S	Column Mounted Shifter RH Side	0	0
4256365	S	TP-650 Torque Converter PACCAR 8 Speed Transmission	0	0
Air & Trailer Equipment				
4510190	S	Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4540420	S	Nylon Chassis Hose	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
Tires & Wheels				
5004210	S	FF: CN 14ply 295/75R22.5 Conti HSL3	0	0
5104210	S	RR: CN 14ply 295/75R22.5 Conti HSL3	0	0
5190004	O	Code-rear Tire Qty 04	0	0
5211020	S	FF: Accur Stl Armor 51455PK 22.5X8.25 PHP10-5 hand holes.	0	0
5311020	S	RR: Accur Stl Armor 51455PK 22.5X8.25 PHP10-5 hand holes.	0	0
5390004	O	Code-rear Rim Qty 04	0	0
Fuel Tanks				
5584040	O	D-Shaped Aluminum 50 Gallon Fuel Tank LH U/C Non-slip step LH under cab	63	-10
5602050	O	Location LH U/C 50 Gallon	0	0

Price Level: January 1, 2023

Deal: 537 Standard Specs

Printed On: 6/19/2023 1:11:33 PM

Date: June 19, 2023

Quote Number: QUO-1050218-W1D3W8



Sales Code	Std/ Opt	Description	\$ List	Weight
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
Battery Box & Bumper				
6020040	O	MD Battery Box, Non-Slip Step RH Under Cab	145	0
6030630	O	Aluminum Battery Box Cover	158	4
6121790	S	Aero Bumper Molded One Piece Gray ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height: Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	0	0
Cab & Equipment				
6510180	S	Peterbilt Aerodynamic 107in BBC SMC Hood With molded charcoal crown and aluminum cab.	0	0
6917320	S	Seats Inc. Driver Seat	0	0
6923160	S	(2) Person Passenger Seat	0	0
6939110	S	Toolbox Under Passenger Seat Non-Suspension Seat	0	0
6939400	S	Air Ride Driver	0	0
6939430	S	Mid Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036140	S	Probilt Interior Gray/Black - Flat Roof	0	0

Price Level: January 1, 2023

Deal: 537 Standard Specs

Printed On: 6/19/2023 1:11:33 PM

Date: June 19, 2023

Quote Number: QUO-1050218-W1D3W8



Sales Code	Std/Opt	Description	\$ List	Weight
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7210550	S	1-Piece Glass Rear Cab Window Fixed	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7510070	S	Aero Rear View Mirror Housing, Molded Black	0	0
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7514090	S	Peterbilt Aero Rear View Mirror, Non-Motorized Includes top mirror with non-motorized, adjustable dual axis non-heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	0	0
7610250	S	Air Horn None Furnished	0	0
7725720	S	No Head Unit or Audio Speakers Selected	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852060	S	Solid Rear Day Cab Mounts	0	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8041200	O	Dual Scale Speedometer MPH Over KPH	0	0
8070860	S	Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8111110	S	Headlights Composite Fender Mounted Integral DRL/Park, Turn, and Side Marker	0	0
8120980	S	(5) Marker Lights, Aero LED	0	0
8134160	S	Self-Canceling Turn Signal	0	0
8140080	S	LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame	0	0
8140850	S	Moveable EOF Crossmember For Mounting Tail Lights Square end of frame with or without end of frame crossmember	0	0

Paint

Price Level: January 1, 2023

Deal: 537 Standard Specs

Printed On: 6/19/2023 1:11:33 PM

Date: June 19, 2023

Quote Number: QUO-1050218-W1D3W8



Sales Code	Std/Opt	Description	\$ List	Weight
8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

Shipping Destination

Options Not Subject To Discount

9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	S	PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs	0	0
9408703	O	Base Warr: Emissions 5YR/100K MI-EPA Engine	0	0

Miscellaneous

9409043	S	Aero Hood (MODEL 537)	0	0
9409096	O	State Registry: Virginia	0	0

Promotions

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$104,543
Marketing and Service Support Fee	\$870
Prepaid Freight	\$3,525
Total Surcharge/Options Not Subject To Discount	\$0
Total Weight	9,973

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------