



Peterbilt of Richmond (H830)  
 2800A Deepwater Terminal  
 Richmond, Virginia 23212

Virginia Sheriffs Association  
 901 East Byrd St Suite 1301  
 Richmond, Virginia 23219  
 United States of America

David Askew  
 Cell Phone: 757-408-9788  
 Office Phone: 757-819-4300  
 Email: daskew@thepetystore.com

Kaylyn Mitman  
 Office Phone: 919-459-6471  
 Email: kmitman@virginiasheriffs.org

## Vehicle Summary

	<b>Unit</b>		<b>Chassis</b>	
Model:		Model 567	Fr Axle Load (lbs):	12000
Type:		Full Truck	Rr Axle Load (lbs):	38000
Description 1:		567 Standard Unit	G.C.W. (lbs):	50000
Description 2:				
	<b>Application</b>		<b>Road Conditions:</b>	
Intended Serv.:		General Freight	Class A (Highway)	100
Commodity:		Other Commodity	Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	<b>Body</b>		Class D (Off-Road)	0
Type:		Flatbed	Maximum Grade:	6
Length (ft):		20	Wheelbase (in):	225
Height (ft):		13	Overhang (in):	60
Max Laden Weight (lbs):		52000	Fr Axle to BOC (in):	68.2
	<b>Trailer</b>		Cab to Axle (in):	156.8
No. of Trailer Axles:		0	Cab to EOF (in):	216.8
Type:			Overall Comb. Length (in):	332.23
Length (ft):		0		
Height (ft):		0	<b>Special Req.</b>	
Kingpin Inset (in):		0		
Corner Radius (in):		0		
	<b>Restrictions</b>			
Length (ft):		40		
Width (in):		102		
Height (ft):		13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0005671	S	<b>Model 567</b> The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	202,862	14,800
0091200	S	<b>Other Commodity</b>	0	0
0093170	S	<b>General Freight</b> Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0095020	O	<b>Flatbed</b>	0	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	0
<b>Frame &amp; Equipment</b>				
0515020	O	<b>10-5/8" Steel Rails 286-325"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	83	158
0611790	S	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	0	0
0644020	O	<b>EOF Square with Steel Crossmember</b>	262	43
0651010	S	<b>Peterbilt Rear Mudflaps and Straight Hangers</b> Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
<b>Front Axle &amp; Equipment</b>				
1012140	S	<b>Meritor MFS+12E 12,500 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5



Sales Code	Std/Opt	Description	\$ List	Weight
1111190	S	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0
1233100	O	<b>Power Steering TRW THP60</b> TRW THP60 Power Steering is for use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	237	-19
1250180	S	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	<b>PHP10 Aluminum PreSet PLUS Hubs Air Disc</b> PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380290	S	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380380	S	<b>Tenneco Shocks For Steer Axle</b> Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380470	O	<b>Meritor Wide Track IPO Standard, Front Axle</b> Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15

### Rear Axle & Equipment

1526150	O	<b>Meritor MT40-14X 40,000 lb</b> Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	325	174
1616290	S	<b>PHP10 Aluminum PreSet PLUS Hubs</b>	0	0
1680500	O	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	276	0
1680950	O	<b>Stability System Not Selected Or Not Available</b>	-99	0
1682710	S	<b>Anti-Lock Braking System (ABS) 6S6M</b> ABS-6. Includes air braking system.	0	0
1683225	S	<b>SmarTire Tire Pressure Monitoring System</b> Next generation TPMS.	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5



Sales Code	Std/ Opt	Description	\$ List	Weight
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	<b>Bendix Air Cam Rear Drum Brakes 16.5x7</b> Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1703900	O	<b>Ratio 3.90 Rear Axle</b>	0	0
1821700	S	<b>Peterbilt Air Leaf 38,000 lb, 52in Axle Spacing</b> Light Weight with Tracking Rods.	0	0

### Engine & Equipment

2074510	O	<b>PACCAR PX-9 350@2000 GOV@2200 1050@1200</b> Productivity (2021 Emissions)  N21350 C121 64....Maximum Accelerator Pedal Ve N21370 C128 64....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown ( N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume ( N21430 C333 0.....Reserve Speed Limit Offset ( N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)	-7,793	-907
2091130	S	<b>VMUX Electronics Architecture</b>	0	0
2091305	S	<b>Engine Idle Shutdown Timer Enabled</b>	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5



Sales Code	Std/ Opt	Description	\$ List	Weight
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091640		<b>Effective VSL Setting NA</b>	0	0
2092016	O	<b>Typical Operating Speed 62 MPH</b>	0	0
2092031	O	<b>Powertrain Optimized for Fuel Economy</b> Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140200	O	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	S	<b>Engine Brake Controls Located on RH Column</b>	0	0
2140450	O	<b>Remote PTO/Throttle, 12-Pin</b> Eng Bay Remote Control Provision	128	0
2140670	O	<b>EPA Emission Warranty</b>	0	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522110	O	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b> PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	315	0
2538040	S	<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539720	S	<b>Low Voltage Disconnect System</b>	0	0
2621090	S	<b>DM Advantage ON/OFF Fan Clutch</b> Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2723210	O	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	41	17
2921110	O	<b>PACCAR Fuel/Water Separator Standard Service</b> PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	386	0
2921210	O	<b>No Fluid Heat Option for Fuel Filter</b>	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5



Sales Code	Std/Opt	Description	\$ List	Weight
2921310	O	<b>No Electric Heat Option for Fuel Filter</b>	0	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.	0	0
3291680	S	<b>(1) Air Cleaner Firewall Mounted</b> Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	S	<b>Exhaust Single RH Side of Cab</b> DPF/SCR right-hand Under Cab.	0	0
3383040	O	<b>DPF Regeneration Switch</b> Remove Stop Position	0	0
3387670	O	<b>42" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	117	6

### Transmission & Equipment

4021900	O	<b>Eaton FRO14210C 10-Speed</b> Includes synthetic lubricant to reduce friction, improve efficiency, & extend component life. Magnetic transmission oil drain plug captures & holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: 1st-12.69, 2nd-9.29, 9th-1.00, 10th- .74. Reverser ratios: Low-13.75, High-2.80	-2,713	208
4210190	O	<b>1810 HD Driveline, 1 Midship Bearing</b> 4.5in x .180 wall tubing	611	90
4216590	O	<b>1710 Driveline Interaxle</b> For tandem rear axles	415	0
4256100	O	<b>Manual Shifter, Black</b>	-450	0

### Air & Trailer Equipment

4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4540260	O	<b>Dash Winch Brake Switch To Operate All Brakes</b> (Truck & Trailer). A&E EOF On Moveable Xmbr.	371	17
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4543320	S	<b>Steel Painted Air Tanks</b>	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5



Sales Code	Std/ Opt	Description	\$ List	Weight
		All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.		
4610920	S	<b>Self-Returning Brake Hand Valve</b> Dash mounted controls	0	0
<b>Tires &amp; Wheels</b>				
5004300	S	<b>FF: CN 16ply 295/75R22.5 Conti Eco Plus HS3+ETRTO</b>	234	6
5104300	S	<b>RR: CN 16ply 295/75R22.5 Conti Eco Plus HS3+ETRTO</b>	936	24
5190008	S	<b>Code-rear Tire Qty 08</b>	0	0
5211990	S	<b>FF: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5311990	S	<b>RR: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5390008	S	<b>Code-rear Rim Qty 08</b>	0	0
<b>Fuel Tanks</b>				
5554130	O	<b>26" Aluminum 80 Gallon Fuel Tank LH U/C</b> Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	561	20
5602080	O	<b>Location LH U/C 80 Gallon</b>	0	0
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	0
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	0
5760010	O	<b>RH Tank None Furnished</b>	-663	-86
<b>Battery Box &amp; Bumper</b>				
6010780	O	<b>Aluminum Space Saver Battery Box RH BOC</b> Battery access from side	-362	-60
6040550	S	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6111010	S	<b>Aluminum Bumper Swept Back Polished Without FEPTO</b>	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
		SBFA, two tow pins and step plates on top of bumper		
<b>Cab &amp; Equipment</b>				
6515690	S	<b>Vocational 115" BBC Alum Cab and Metton Hood SBFA</b> Stainless crown and grille with tilt assist.	0	0
6540660	O	<b>SmartSound Cab Insulation Package</b> Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	411	65
6700000	S	<b>No Sleeper Selected</b>	0	0
6911100	S	<b>Peterbilt ST Driver</b> Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standand vinyl finish - color coordinate with interior color.	0	0
6921740	S	<b>Peterbilt ST Non-Adjustable Passenger Seat</b> Standard vinyl, no suspension cover, no seat back recline.	0	0
6939110	O	<b>Toolbox Under Passenger Seat</b> Non-Suspension Seat	227	11
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	S	<b>High Back Driver</b>	0	0
6939470	S	<b>Vinyl Driver</b>	0	0
6939510	S	<b>Non-Air Ride Passenger</b>	0	0
6939520	S	<b>High Back Passenger</b>	0	0
6939570	S	<b>Vinyl Passenger</b>	0	0
7000025	S	<b>Steering Wheel With Multi-Function</b> Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	0
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7037130	S	<b>Prestige Interior - Sterling Gray</b> Features single tone dash with tough, scratch resistant materials including soft touch points on top of dash. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical grained A,B, C & D instrument panels with contoured doorpads, padded fabric headliner and vinyl wall panels. Superior ergonomics are achieved while maximizing productivity featuring: multiple power ports, (2) coat hooks, header-mounted	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5





Sales Code	Std/Opt	Description	\$ List	Weight
		domelight, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, rubber flooring, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in dash.		
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7210550	S	<b>1-Piece Glass Rear Cab Window Fixed</b>	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7510070	S	<b>Aero Rear View Mirror Housing, Molded Black</b>	0	0
7514000	S	<b>Peterbilt Aero Rear View Mirror, Non-Motorized</b> Includes top mirror with non-motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	0	0
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0	0
7610500	S	<b>Air Horn Mounted Under Cab</b>	0	0
7725720	S	<b>No Head Unit or Audio Speakers Selected</b>	0	0
7788055	S	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788057	O	<b>24 Months SmartLINQ Subscription</b> PACCAR PX Engines.	0	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b>	0	0

Price Level: January 1, 2023

Deal: 567 Standard Unit

Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023

Quote Number: QUO-1051787-D0N1Q5



Sales Code	Std/Opt	Description	\$ List	Weight
		With Intermittent Feature.		
7852060	S	<b>Solid Rear Day Cab Mounts</b>	0	0
8021800	S	<b>Air Filter Restriction Pressure Gauge</b> Located in Digital Cluster Display	0	0
8021810	S	<b>Brake Application Air Pressure (Tractor)</b> Located in Digital Cluster Display.	0	0
8070810	S	<b>Engine Manifold Pressure (Turbo Boost)</b> Located in Digital Cluster Display	0	0
8070820	S	<b>Engine Percent Torque</b> Located in Digital Cluster Display	0	0
8070830	O	<b>Main Instrumentation Panel</b> Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0	0
8110070	S	<b>Headlights Projector Module Pod</b> Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0	0
8120990	S	<b>(5) Marker Lights, Aero LED</b> On roof, visor, or fairing	0	0
8133960	S	<b>Daytime Running Lights</b> The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8140120	O	<b>Incandescent Square Stop/Turn/Tail/Backup</b> Left-hand / right-hand square end of frame or dropped a-brace	52	9
<b>Paint</b>				
8500710	S	<b>Standard Paint Color Selection</b>	-200	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0
<b>Shipping Destination</b>				
<b>Options Not Subject To Discount</b>				
9400090	S	<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0	0
9400094	O	<b>PACCAR PX-9 Standard Coverage</b> 2 yrs/250,000 mi (402,336 km)/6,250 hrs	0	0
9407147	O	<b>Fuel Price Index Factor \$99 NET</b>	99	0
9408703	O	<b>Base Warr: Emissions 5YR/100K MI-EPA Engine</b>	0	0

Price Level: January 1, 2023  
 Deal: 567 Standard Unit  
 Printed On: 7/3/2023 9:16:38 AM

Date: July 03, 2023  
 Quote Number: QUO-1051787-D0N1Q5



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
<b>Miscellaneous</b>				
9409001	S	Day Cab / Prestige Interior (DM)	0	0
9409096	O	State Registry: Virginia	0	0

**Promotions**

**Order Comments**



<b>Total List Price (W/O Freight &amp; Warranty &amp; Surcharges )</b>	\$196,570
<b>Marketing and Service Support Fee</b>	\$1,395
<b>Prepaid Freight</b>	\$3,525
<b>Total Surcharge/Options Not Subject To Discount</b>	\$99
<b>Total Weight</b>	14,591

## **Prices and Specifications Subject to Change Without Notice.**

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### ***PRICING DISCLAIMER***

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------