



Peterbilt of Richmond (H830)  
 2800A Deepwater Terminal  
 Richmond, Virginia 23212

Virginia Sheriffs Association  
 901 East Byrd St Suite1301  
 Richmond, Virginia 23219  
 United States of America

David Askew  
 Cell Phone: 757-408-9788  
 Office Phone: 757-819-4300  
 Email: daskew@thepetestore.com

Kaylyn Mitman  
 Office Phone: 919-459-6471  
 Email: kmitman@virginiasheriffs.org

## Vehicle Summary

	<b>Unit</b>		<b>Chassis</b>	
Model:		Model 567	Fr Axle Load (lbs):	20000
Type:		Full Truck	Rr Axle Load (lbs):	46000
Description 1:		567 Options	G.C.W. (lbs):	80000
Description 2:				
	<b>Application</b>		<b>Road Conditions:</b>	
Intended Serv.:	Asphalt Paver		Class A (Highway)	100
Commodity:	Construction Materials		Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	<b>Body</b>		Class D (Off-Road)	0
Type:	End Dump		Maximum Grade:	6
Length (ft):	20		Wheelbase (in):	315
Height (ft):	13		Overhang (in):	60
Max Laden Weight (lbs):	80000		Fr Axle to BOC (in):	90.1
	<b>Trailer</b>		Cab to Axle (in):	224.9
No. of Trailer Axles:	0		Cab to EOF (in):	284.9
Type:			Overall Comb. Length (in):	406
Length (ft):	0			
Height (ft):	0		<b>Special Req.</b>	
Kingpin Inset (in):	0			
Corner Radius (in):	0			
	<b>Restrictions</b>			
Length (ft):	40			
Width (in):	102			
Height (ft):	13.5			

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

**Note: All sales are F.O.B. designated plant of manufacture.**



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0005671	S	<b>Model 567</b> The Model 567 is available in both a set-forward and set-back front axle configuration to provide customers with maximum versatility for their application requirements. For weight-sensitive applications, the set-forward front axle provides optimized weight distribution and compliance with bridge laws. The Model 567 has steer axle ratings up to 22,000 lbs. The 567 also offers single, tandem or tridem drive axles and a variety of lift axles for added versatility. Available with a 115" or 121" BBC and as a day cab or with a selection of detachable sleeper configurations, the 567 is as versatile as it is reliable.	202,862	14,800
0091070	O	<b>Construction Materials</b>	0	0
0093260	O	<b>Asphalt Paver</b> Truck or tractor which transports asphalt mix, most of which require asphalt dump brake chamber clearance.	0	0
0095170	O	<b>End Dump</b>	0	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	0
<b>Frame &amp; Equipment</b>				
0514050	O	<b>10-3/4" Steel Rails 385-402"</b> 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	805	608
0601500	O	<b>Full Steel Inner Liner</b>	1,753	821
0611250	O	<b>Heavy-Duty Iron Front Spring Brackets</b> With Front Air Leaf the front spring bracket is iron but not the shackle bracket	335	35
0611330	O	<b>Zinc Coated Anti Corrosion Treated Frame Rails</b> Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	387	4
0611790	S	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	0	0
0644020	O	<b>EOF Square with Steel Crossmember</b>	262	43
0651010	S	<b>Peterbilt Rear Mudflaps and Straight Hangers</b>	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
		Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.		
0711190	O	<b>Premier 370A Hitch (Requires A-Brace Option)</b>	1,671	44
0722280	O	<b>Drop A-brace for Square EOF with Steel Xmbr</b> With Safety Chain Loops	1,865	161
<b>Front Axle &amp; Equipment</b>				
1011890	O	<b>PACCAR FX-20 Steer Axle 20,000 lbs. 4" Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 20,000 pounds. Front axle is designed for demanding applications such as construction, heavy haul, refuse, and other vocational uses. Robust forged steel beam construction for long-lasting performance. It utilizes innovative tapered kingpin roller bearings for more efficient operation and improved steering efficiency.  The PACCAR Steer Axle comes standard with the PACCAR warranty of 5 years, 750,000 miles.	2,088	137
1114030	O	<b>Taper Leaf Springs, Shocks 20,000 lb</b> Standard with Heavy Resistance Shocks.	620	119
1243020	O	<b>Power Steering Sheppard SD110 Dual Gear</b> Steering vocational and heavy haul vehicles with front axle ratings of 16,000 to 18,000 lbs. in single gear applications. Glidekote splines on steering shaft extend service life of components.	1,697	123
1250250	O	<b>Power Steering Reservoir Frame Mounted w/Cooler</b> A power steering cooler helps reduce the heat of the power steering fluid. This is commonly used with systems that may experience more stress from towing or off-road driving.	210	2
1354850	O	<b>PHP10 Iron PreSet PLUS Hubs - Air Disc</b> Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	159	42
1354870	O	<b>Severe Service Disc Brake Rotor</b> For refuse applications, providing the braking torque necessary to slow or stop the vehicle.	93	97
1380070	O	<b>Greasable Front Spring Pins</b>	70	0
1380290	S	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380380	S	<b>Tenneco Shocks For Steer Axle</b> Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380490	O	<b>PACCAR FX Wide Track IPO Standard</b> 71in KPI IPO 69in front axle for improved turning radius.	0	15

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
1391480	O	<b>Pad Dust Shields for Air Disc Brakes; Front Axle</b> Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.	31	2
<b>Rear Axle &amp; Equipment</b>				
1526120	O	<b>Meritor RT46-160 46,000 lb</b> Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. If code 1526120 (RT46-160) is ordered with 1680460 (Heavy Wall), you will get the 16 mm wall, but not the improved carrier that is in 1526130 code (RT46-160E) that also has a 16 mm wall. This could affect Heavy Haul service warranty length in Canada per Meritor.	4,532	634
1604326	O	<b>(3) Hendrickson EXS13 Self-Str Pushers</b> 13.5K Lb, Includes (3) Air Tanks	33,707	3,342
1607152	O	<b>52in Pusher Axle Spacing</b> From Centerline of Forward Drive Axle	0	0
1607204	O	<b>104" 2nd Pusher Axle Spacing</b> From Centerline Of Forward Drive Axle	0	0
1607356	O	<b>156" 3rd Pusher Axle Spacing</b> From Centerline of Forward Drive Axle	0	0
1615170	O	<b>PHP10 Aluminum PreSet PLUS Hubs, Cast Drums</b> With 13.5K or 20K Self-Steering Pusher Axles	0	0
1616305	O	<b>PHP10 Iron Preset + Hubs - Air Disc</b>	1,417	0
1680500	O	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	276	0
1680950	O	<b>Stability System Not Selected Or Not Available</b>	-99	0
1682710	S	<b>Anti-Lock Braking System (ABS) 6S6M</b> ABS-6. Includes air braking system.	0	0
1683225	S	<b>SmarTire Tire Pressure Monitoring System</b> Next generation TPMS.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
		conditions and withstand the stress from high temperatures, extending component life.		
1685260	O	<b>Lift Axle Regulator &amp; Gauge BOC</b> Lift axle regulator and gauge, back-of-cab, lower left hand corner, with switch and gauge in dash.	96	0
1685460	O	<b>Stowed Lifted Axle Higher To Maximize Ground Clearance</b>	0	0
1687040	O	<b>Air Disc Rear Brakes, Tandem Drive Axle</b> Includes Automatic Slack Adjusters.	1,482	0
1704300	O	<b>Ratio 4.30 Rear Axle</b>	0	0
1821640	O	<b>Peterbilt Air Trac 46,000 lbs, 54in Axle Spacing</b> Light Weight	1,824	291
1920385	O	<b>Air Springs, Internal Bumpers</b> Air Trac / Air Leaf suspensions	59	0

### Engine & Equipment

2059919	O	<b>X15 565V@1950 GOV@2000 1850@1000</b> Productivity Series (2021 Emissions)	15,940	465
		N21350 C121 64....Maximum Accelerator Vehicle		
		N21370 C128 64....Maximum Cruise Control Speed		
		N21460 C132 1400..PTO Maximum Engine Speed		
		N21520 C133 5.....Idle Shutdown Timer		
		N21610 C188 39....Idle Shutdown Cold Ambient A		
		N21620 C189 60....Idle Shutdown Intermediate A		
		N21630 C190 80....Idle Shutdown Hot Ambient Ai		
		N21550 C206 35....Idle Shutdown Percent Engine		
		N21340 C209 120...Maximum Vehicle Speed		
		N21510 C225 YES...Idle Shutdown with Parking B		
		N21450 C231 NO....Gear Down Protection		
		N21570 C233 NO....Idle Shutdown Manual Overrid		
		N21440 C234 NO....Engine Protection Shutdown		
		N21480 C238 NO....Cruise Control and Engine Br		
		N21470 C239 NO....Cruise Control Auto-Resume		
		N21430 C333 0.....Driver Initiated OverrideMax		
		N21410 C334 0.....Driver Initiated Override Ma		
		N21590 C382 YES...Idle Shutdown Hot Ambient Au		
		N21500 C395 0.....Green House Gas Automatic En		
		N21530 C396 YES...Idle Shutdown Warning Period		
		N21540 C397 60....Idle Shutdown Warning Period		
		N21320 C399 120...Green House Gas Vehicle Spee		
		N21400 C400 252...Driver Initiated Override Re		
		N21420 C401 10....Green House Gas Vehicle Spee		
		N21330 C402 0.....Green House Gas Vehicle Spee		
2091130	S	<b>VMUX Electronics Architecture</b>	0	0
2091305	S	<b>Engine Idle Shutdown Timer Enabled</b>	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091640		<b>Effective VSL Setting NA</b>	0	0
2092014	O	<b>Typical Operating Speed 65 MPH</b>	0	0
2092033	O	<b>Powertrain Optimized for Balance</b> Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2120160	O	<b>Cummins TRV For DAVCO Only</b> For Fuel Filter, X15	48	0
2140200	O	<b>CARB Engine Idling Compliance</b> PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140330	O	<b>Remote Throttle &amp; Wiring BOC</b> Excludes Can Communication	54	0
2140410	S	<b>Engine Brake Controls Located on RH Column</b>	0	0
2140450	O	<b>Remote PTO/Throttle, 12-Pin</b> Eng Bay Remote Control Provision	128	0
2140670	O	<b>EPA Emission Warranty</b>	0	0
2513070	O	<b>200 Amp Alternator, Standard Brush</b> Bosch Long Haul Extreme, standard brush, 170-200 Amps. Dual internal cooling fans, and externally-mounted rectifier and regulator.	158	0
2521090	S	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522090	O	<b>PACCAR Premium Starter - X15 Engines Only</b> PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 36 months / 350,000 mi / 560,000 km.	389	0
2538080	O	<b>4 PACCAR AGM 12V Batteries 3200 CCA</b> Stranded copper battery cables are double aught (00) or larger to reduce resistance.	706	62
2539410	O	<b>Battery Jumper Terminal Mounted Under Hood</b> LH Frame Rail. Not available with PX-7 engines.	135	4
2539490	O	<b>Batteries In RH BOC Box</b>	0	0
2539720	S	<b>Low Voltage Disconnect System</b>	0	0
2539740	O	<b>Kissling Battery Disconnect Switch 300AMP</b> Dual Tab Mounted on Battery Box	540	3
2621000	O	<b>2-Speed Fan Clutch For Frequent Start/Stops</b>	262	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
		A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.		
2725270	O	<b>37.4 CFM Naturally Aspirated Air Compressor</b> X15 Only	253	27
2812170	O	<b>Intebrate (Furnished on Engine)</b> Features a dedicated cam lobe design for optimum power and three-stage engine brake operation.	0	0
2921130	O	<b>DAVCO 382 Fuel/Water Separator</b> The Fuel Pro 382 is a combination of diesel fuel filtration and water separator that is recommended for heavy-duty diesel engines with flow rates up to 180 gallon/hour.	418	0
2921320	O	<b>12V Heat for Fuel Filter</b> Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	66	0
3010400	O	<b>Engine Protection Shutdown w/ Label</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	6	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.	0	0
3291680	S	<b>(1) Air Cleaner Firewall Mounted</b> Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365340	O	<b>Exhaust Dual Side of Cab, LH Side of Cab Stack</b> Aesthetic Only, DPF/SCR right-hand under cab	2,782	110
3381770	O	<b>Curved Tip Standpipe(s)</b>	43	1
3381790	O	<b>Chrome Finish Over Elbows for Dual Exhaust</b> Requires DPF tool box right-hand under cab, and battery box left-hand under cab.	596	13
3387880	O	<b>7" Dia Chrome Plated Steel Standpipe(s) IPO 5"</b>	234	4
3387890	O	<b>36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	82	4

## Transmission & Equipment

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
4052970	O	<b>Allison 4500 RDS-P Transmission, Gen 6</b> Rugged Duty Series	24,409	528
4210870	O	<b>RPL20 Driveline Interaxle</b> Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanently lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0	0
4211550	O	<b>RPL25 Driveline, 3 Midship Bearings</b> All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	2,584	315
4233910	O	<b>(1) Dash Mounted Single Acting EOH PTO Control</b> Electric-over-hydraulic, spec'ing PTO switch does not ensure the PTO will fit. Sends signal to Allison to engage PTO.	102	0
4252170	O	<b>Auto Neutral Activates With Parking Brake</b> Auto Neutral helps improve jobsite safety by reducing the possibility of the truck moving due to throttle application.	19	0
4252190	O	<b>Shifter Plate, PTO Access Hole</b>	63	0
4252890	O	<b>Allison FuelSense 2.0 Not Desired</b>	0	0
4252940	O	<b>Allison Neutral At Stop</b> Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4256740	O	<b>Allison 6-Speed Configuration, Wide Ratio Gears</b> Allison 4500 transmission only	0	0
4256870	O	<b>Allison Output Function S Neutral Indicator</b> Allison output function S Neutral Indicator for PTO. Required on Refuse Packer Applications. With this configuration NEUTRAL only, PTO engagement is permitted only when the transmission is in Neutral. Once the transmission is in Neutral, the PTO is automatically engaged and fast idle is initiated when the PTO switch is on. In addition with this configuration Pack-on-the-fly, the PTO is automatically engaged and fast idle is initiated when the PTO switch is On concurrently with shifting of the transmission to Neutral.	0	0
4256910	O	<b>Allison Transmission Fluid Test Port</b> Remote coupler. The fluid test port provides easy access to transmission fluid for testing from its location under the hood on the right-hand frame rail.	267	0
4256920	O	<b>Dash Mounted Push Button Shifter</b> Available with Allison transmissions	232	0
4256990	O	<b>Rolling Direction Change Shift Inhibit Feature</b> Allison transmissions. A programmable feature that keeps the transmission from shifting from Drive to Reverse or from Reverse to	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0





Sales Code	Std/Opt	Description	\$ List	Weight
		Drive above a preset speed. This wireless function is enabled when a switch is closed to complete the circuit between input wire 101 and ground. Frequently the function is interfaced with a switch indicating activation of another vehicle function, such as application of the service brakes. When the function is enabled, the TCM will recognize the request for a direction change shift, Reverse-to-Drive or Drive-to-Reverse. If all other operating conditions are acceptable, the TCM will command the requested shift. The enable remains in effect until the switch is opened, followed by the selection of a different direction, Reverse or Drive, at the shift selector. This could be used for doc spotters and refuse. If the function is not enabled, any shift which results in a change of direction is inhibited.		

### Air & Trailer Equipment

4510340	O	<b>(2) Bendix AD-IS Air Dryers, Everflow Switching</b> Module, coalescing filters	1,769	34
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4542330	O	<b>Central Location For Air Tank Drain Valves</b> Frame mounted BOC tanks, includes pull cords. Only available horizontal/transverse tanks	330	4
4543330	O	<b>Polished Aluminum Air Tanks Outside Frame Rails</b> Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	292	0
4543340	O	<b>Aluminum Painted Air Tanks</b> All air tanks are aluminum with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	212	-45
4543390	O	<b>High Mount Air Tanks BOC/BOS Where Possible</b> Subject to frame review	0	0
4610920	S	<b>Self-Returning Brake Hand Valve</b> Dash mounted controls	0	0
4611930	O	<b>Body Connections 5' BOC</b> Junction box contains light and power circuits for body connections located 5' from back-of-cab	191	6
4614820	O	<b>AE Connections In EOF Crossmember</b>	-80	-11

### Tires & Wheels

5050240	O	<b>FF: MN 20ply 425/65R22.5 XZE</b>	1,304	166
5156120	O	<b>RR: MN 16ply 11R22.5 X Multi D</b> Efficiency Rating: Poor Diameter= 41.4 inches; SLR= 19.4 inches	2,312	112

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
5190008	S	<b>Code-rear Tire Qty 08</b>	0	0
5220130	O	<b>FF: Alcoa 824627 22.5X12.25 High Polish Aluminum</b>	654	-2
5320770	O	<b>RR: Alcoa ULA187 22.5X8.25 High Polish Alum</b> Ultra One wheel with MagnaForce alloy.	1,228	-224
5390008	S	<b>Code-rear Rim Qty 08</b>	0	0
5407640	O	<b>FF: Mirror Polish Wheels, Outer Surface</b> Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	73	0
5407700	O	<b>PR: Mirror Polish Wheels, Outer Surface</b> All pusher axles. Mirror polish outer surface of outer wheel.	283	0
5410140	O	<b>FF: Dura-Bright Finish</b> Outer Surface of Outer Wheel, requires Polished Option	262	0
5410200	O	<b>PR: Dura-Bright Finish</b> All pusher axles - outer surface of outer wheel, requires polished option.	262	0
5492212	O	<b>PR: (6) Alcoa ULA187 22.5X8.25 High Polish Alum</b> (3) self-steering pusher axle. Ultra One wheel with MagnaForce alloy.	2,406	234
5496502	O	<b>PR:(6)MN 14PLY 275/80R22.5 XZE2</b> (3) self-steering pusher axle.	4,280	684
<b>Fuel Tanks</b>				
5554190	O	<b>26" Aluminum 100 Gallon Fuel Tank LH U/C</b> Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	409	22
5602100	O	<b>Location LH U/C 100 Gallon</b>	0	0
5650540	O	<b>Polish (1) Non-Slip Fuel Tank Step, U/C Tank Only</b>	29	0
5650810	O	<b>Polish (1) Aluminum Fuel Tank</b>	259	0
5652830	O	<b>Polish All Fuel / Hydraulic Tank Straps</b> Does not apply to rectangular DEF tank straps	83	0
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	0
5653000	O	<b>Polished Stainless Steel Cover For DEF Tank</b>	233	0
5655029	O	<b>DEF Tank Medium, 24 Gal</b>	164	22
5760010	O	<b>RH Tank None Furnished</b>	-663	-86

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/Opt	Description	\$ List	Weight
<b>Battery Box &amp; Bumper</b>				
6010780	O	<b>Aluminum Space Saver Battery Box RH BOC</b> Battery access from side	-362	-60
6030150	O	<b>Rubber Battery Pad In Bottom of (1) Battery Box</b> Mat in box that holds batteries only	12	4
6030540	O	<b>Polish Battery/Tool Box(s), Aftertreatment Cab</b> Entry complete	277	0
6040550	S	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6111130	O	<b>Aluminum Bumper Deep Tapered Polished</b> Two tow pins	-50	29
6132450	O	<b>Heavy Duty External Tow Eye</b> IPO Standard	558	42
<b>Cab &amp; Equipment</b>				
6515770	O	<b>Vocational 121 BBC Alum Cab and Metton Hood SFFA</b> Stainless steel crown and grille with tilt assist.	3,931	-30
6540160	O	<b>Thermal Insulation Package in Cab</b> The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	21	2
6540660	O	<b>SmartSound Cab Insulation Package</b> Cab acoustic insulation package for day cabs. Includes insulated inside firewall, top side floor damping, absorber treated kick panels, and insulated backwall and roof structure.	411	65
6540740	O	<b>Peterbilt Keyless Entry</b> The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	165	2
6700000	S	<b>No Sleeper Selected</b>	0	0
6800160	O	<b>Side of Hood Air Intake Bezel, Bright Finish</b>	255	0
6800330	O	<b>Rubber Fender Lips 4.5" Wide</b>	561	6
6914110	O	<b>Sears Atlas 80 Driver Seat</b> Sears Atlas 80 driver seat top with contoured backframe structure with contoured seat pans, 3 seat extension positions, 3 seat tilt positions, quad-chamber air lumbar - height adjustable, high-back, ergonomic 22" wide "luxury style" seat, full recliner backrest, stabilizer double locking slides/isolator package with 9" slide travel and 2" isolation, Atlas togglelink suspension with flat floor riser and vinyl suspension skirt. Available in mordura cloth or Ultraleather upholstery, optional driver or passenger swivel and your choice of armrest kits.	421	15

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
6924110	O	<b>Sears Atlas 80 Passenger Seat</b>	687	15
6930500	O	<b>Drivers Armrest - RH Only</b>	125	2
6930590	O	<b>Passenger Armrest - LH only</b> Required with Evolution LX seats, optional with Evolution ST Seats.	125	2
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	S	<b>High Back Driver</b>	0	0
6939500	O	<b>Air Ride Passenger</b>	0	0
6939520	S	<b>High Back Passenger</b>	0	0
6939600	O	<b>UltraLeather Driver (Atlas Only)</b>	157	0
6939610	O	<b>UltraLeather Passenger (Atlas Only)</b>	157	0
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7001630	O	<b>Premium Steering Wheel with Multi Function</b> Premium Multi-functional Leather Wrapped Steering Wheel with Peterbilt logo over horn button. Includes audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	149	5
7037175	O	<b>Platinum Interior - Sterling Gray</b> Features dual tone dash with scratch resistant materials including soft touch on top of dash highlighted by horizontal chrome accent. Top of dash, door panel uppers, and kick panel are charcoal to conceal dirt and mitigate wear. Includes unique technical patterned A,B & C instrument panels with woodgrain trim and bright accents with contoured doorpads highlighted by a woodgrain insert, padded fabric headliner and vinyl wall panels. Superior ergonomics and productivity featuring: multiple power ports, header-mounted dome light, power lift driver and passenger windows, LH and RH door mounted map pockets with built-in courtesy lights, driver and passenger dome/reading lights and footwell lighting. Comfort features include automatic temperature HVAC controls, carpeted floor covering, (3) inside sunvisors, integrated "dead pedal, cup holder and map bin in dash. <b>REQUIRES</b> these additional options, 8071340 bright bezel on gauges, 7001630 18" steering wheel and 7852080 pull-out work	1,930	25
7040150	O	<b>Rubber Floor IPO Carpet (Black Only)</b> Rubber Floor Covering in Cab. Standard in Prestige interior, optional in Platinum/Premier interiors.	-35	-6
7210510	O	<b>3-Piece Glass Rear Cab Window, All Pieces Fixed</b>	228	12
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/Opt	Description	\$ List	Weight
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	<b>Outside Sunvisor - Stainless Steel</b> Not available with 2.1M high roof sleeper.	943	8
7510060	O	<b>Aero Rear View Mirror Housing, Bright Finish</b>	330	3
7514010	O	<b>Peterbilt Aero Rear View Mirror, Motorized</b> Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	339	3
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0	0
7561190	O	<b>LH/RH Round hood Mirrors Bright Housing</b> Convex mirrors, left hand / right hand hood mirrors with Bright finish. Includes one-piece straight arms for rearward visibility.	276	8
7640400	O	<b>(4) PB Air Horns Round, (2) 23" &amp; (2) 26" Length</b> Roof mounted. Round horn shield. 23 in. LH Mtd Outboard.	1,592	24
7721050	O	<b>Satellite Radio</b> Requires USB port and bluetooth for phone and audio.	237	0
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	414	10
7725730	O	<b>Premium Speaker Package For Cab</b> (4) Speakers with 2 tweeters	537	6
7728030	O	<b>Radio Mute When In Reverse</b> For automatic or automated transmission	0	0
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	56	0
7728050	O	<b>USB Port</b>	56	0
7740140	O	<b>Cobra 29 CB Radio Mounted Center Of Header</b> Without weatherband. Mounted in center of header with sound tracker & illuminated panel. Includes wiring, microphone clip, & speaker. Must select antenna(s) option.	310	10
7748740	O	<b>(2) Antennas For Factory Installed Or F/O CB</b> Mounted RH/LH side of roof, with antenna cables	185	2
7788055	S	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
		whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.		
7788058	O	<b>24 Months SmartLINQ Subscription</b> Cummins Engines.	0	0
7850015	O	<b>Rear Wall Deep Record/Map Pocket</b>	78	2
7851040	O	<b>Removable Bugscreen Behind Grille</b>	183	2
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
7852020	O	<b>Cab Air Suspension</b>	240	15
7852080	O	<b>Pull Out Tray/Work Surface Over Glove Box</b>	240	3
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	27	13
7900310	O	<b>Fire Extinguisher, Mounted Outboard Driver Seat</b> Hazmat approval UL listed/rated ABC	68	8
7901140	O	<b>Backup Alarm (87-112 DB)</b> Variable adjusting	147	6
8011410	O	<b>Drive Axle #1 Front Oil Temperature Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	136	0
8011420	O	<b>Drive Axle #2 Rear Oil Temperature Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	148	0
8011850	O	<b>Transmission Oil Temperature (Main)</b> Located in Digital Cluster Display.	26	0
8021800	S	<b>Air Filter Restriction Pressure Gauge</b> Located in Digital Cluster Display	0	0
8021810	S	<b>Brake Application Air Pressure (Tractor)</b> Located in Digital Cluster Display.	0	0
8022160	O	<b>Fuel Filter Restriction Gauge</b> 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	204	0
8070000	O	<b>Disable Brake Light With Engine Brake</b>	0	0
8070820	S	<b>Engine Percent Torque</b> Located in Digital Cluster Display	0	0
8070830	O	<b>Main Instrumentation Panel</b>	0	0

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



Sales Code	Std/ Opt	Description	\$ List	Weight
		Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.		
8071340	O	<b>Bright Bezel Gauges</b>	39	0
8076010	O	<b>Pusher Axle Pressure 1</b> 52mm Round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6.	113	0
8076020	O	<b>Pusher Axle Pressure 2</b> 52mm Round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6.	121	0
8076030	O	<b>Pusher Axle Pressure 3</b> 52mm Round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6.	124	0
8110070	S	<b>Headlights Projector Module Pod</b> Fender mounted turn signals, projector module low beam, complex reflector high beam, pod mounted	0	0
8120990	S	<b>(5) Marker Lights, Aero LED</b> On roof, visor, or fairing	0	0
8133115	O	<b>Marker Switch Wiring FO Auxiliary Light</b> Under Cab/Sleeper (15A MAX)	30	2
8133470	O	<b>Switch &amp; Wiring for F/O Beacon/Strobe</b> Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill.	49	2
8133960	S	<b>Daytime Running Lights</b> The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8134160	O	<b>Self-Canceling Turn Signal</b>	0	0
8140120	O	<b>Incandescent Square Stop/Turn/Tail/Backup</b> Left-hand / right-hand square end of frame or dropped a-brace	52	9
8141150	O	<b>Additional LED Turn Signals</b> Mounted lower rear corners back of cab / back of sleeper	209	7
<b>Paint</b>				
8500710	S	<b>Standard Paint Color Selection</b>	-200	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

### Shipping Destination

### Options Not Subject To Discount

Price Level: January 1, 2023

Deal: 567 Options

Printed On: 7/3/2023 10:16:21 AM

Date: July 03, 2023

Quote Number: QUO-1051794-Q4T0J0



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
9400090	S	<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0	0
9407147	O	<b>Fuel Price Index Factor \$99 NET</b>	99	0
9408703	O	<b>Base Warr: Emissions 5YR/100K MI-EPA Engine</b>	0	0
<b>Miscellaneous</b>				
9409002	O	<b>Day Cab / Platinum Interior (DP)</b>	0	0
9409096	O	<b>State Registry: Virginia</b>	0	0

**Promotions**

**Order Comments**





<b>Total List Price (W/O Freight &amp; Warranty &amp; Surcharges )</b>	\$342,042
<b>Marketing and Service Support Fee</b>	\$1,395
<b>Prepaid Freight</b>	\$3,525
<b>Total Surcharge/Options Not Subject To Discount</b>	\$99
<b>Total Weight</b>	24,045

**Prices and Specifications Subject to Change Without Notice.**

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

**PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------