

# KING COBRA™


S E R I E S



## IT'S GOOD TO BE KING

With an industry leading compaction rate and its superior rear loading capabilities, the New Way® King Cobra™ has become an industry standard. Combine the fact that the King Cobra™ has one of the lowest warranty claims of any body in the industry, and you've got a refuse truck that packs one powerful bite.

# KING COBRA™



## GENERAL SPECIFICATIONS

Model	20 KC	25 KC	27 KC	32 KC
<b>Body Capacity</b>	20 yd <sup>3</sup>	25 yd <sup>3</sup>	27 yd <sup>3</sup>	32 yd <sup>3</sup>
<b>Body Width (A)</b>	96"	96"	96"	96"
<b>Body Height (B)</b>	100"	100"	100"	100"
<b>‡ Body Length (C)</b>	263"	285"	296"	315.5"
<b>* Approx. Body Weight</b>	17,000 lbs	17,900 lbs	18,260 lbs	19,200 lbs
<b>Hopper Capacity</b>	3.55 yd <sup>3</sup>	3.55 yd <sup>3</sup>	3.55 yd <sup>3</sup>	3.55 yd <sup>3</sup>
<b>Hopper Opening Width</b>	80"	80"	80"	80"
<b>Loading Sill Height</b>	3.5" below frame	3.5" below frame	3.5" below frame	3.5" below frame
<b>Hopper Cycle Time</b>	25-28 secs.	25-28 secs.	25-28 secs.	25-28 secs.

## MINIMUM CHASSIS SPECIFICATIONS

Model	20 KC	25 KC	27 KC	32 KC
<b>** Minimum GVWR</b>	58,000 lbs	62,000 lbs	64,000 lbs	66,000 lbs
<b>Cab to Trunnion</b>	140"	160"	172"	204"

## HYDRAULIC CYLINDER SPECIFICATIONS

Model	20 KC	25 KC	27 KC	32 KC
<b>Slide Cylinders (2)</b>	5.5"	5.5"	5.5"	5.5"
<b>Sweep Cylinders (2)</b>	5"	5"	5"	5"
<b>Tailgate Cylinders (2)</b>	3.5"	3.5"	3.5"	3.5"
<b>Ejection Cylinder</b>	3-Stage 7.5"	4-Stage 7.5"	4-Stage 7.5"	4-Stage 7.5"

## BODY CONSTRUCTION

<b>Roof &amp; Sides</b>	10 gauge	80K GR
<b>Floor</b>	7 gauge	100K GR
<b>Ejection Panel</b>	10 gauge	50K GR
<b>Sweep Panel</b>	1/4"	100K GR
<b>Tailgate (upper)</b>	7 gauge	50K GR
<b>Tailgate (lower)</b>	1/4"	100K GR
<b>Hopper Floor (back)</b>	1/4"	100K GR
<b>Slide Panel</b>	7 gauge	100K GR

## HYDRAULIC SYSTEMS

<b>Oil Reservoir</b>	50-70 gal
<b>Oil Flow w/std. pump</b>	36 gpm
<b>Operating Pressure</b>	2,450 psi
<b>Engine RPM for STD gpm</b>	1,275-1,550
<b>Hydraulic Hoses</b>	4-to-1 burst
<b>Return Filter</b>	10 micron

## STANDARD EQUIPMENT

- Semi automatic cycling
- Auto back pack
- Accelerator kit
- Turn buckle locks
- Back up alarm
- Light bar
- LED lights
- Sight gauge on oil tank
- Oil pressure gauge
- Chrome rod cylinders
- Side access door
- Driver alert buzzer
- Tailgate ajar indicator
- Bolt on steps on rear
- Imron elite productive paint
- Color rear vision camera system
- Talamar Extreme hydraulic fluid

## OPTIONAL EQUIPMENT

- Special lighting
- PTO & pump
- Container lifts (commercial & residential)
- Body scale system
- Auto tailgate locks
- Steel upgrades
- Extended warranties
- CNG powered

‡ Length measurement depends on options ordered

\* Approximate Body Weight empty and exclusive of options

\*\* Any Chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

AUTHORIZED NEW WAY DEALER



Sourcewell  
Formerly NJPPA  
Awarded Contract  
Contract # 091219-NWY

**NEW WAY®** Driving The Difference.®

a quality product of McLaughlin FAMILY COMPANIES • 800 831 1858 • www.newwaytrucks.com

19-1727 REV 01-20