


STAR X-Fire™ LED Beacons

* = Colors: A, B, C, G, R



LIST

Model Number Description		LIST
266TCFL-*	Tall lens, flange mount, 10-30V	141.96
266TCL-*	Tall lens, perm. mount, 10-30V	141.96
266TCLM-*	Tall lens, mag. mount, 10-16V	160.55
266TCLV-*	Tall lens, vacuum mag. mount, 10-16V	197.73
266TSFL-*	Short lens, flange mount, 10-30V	141.96
266TSL-*	Short lens, perm. mount, 10-30V	141.96
266TSLM-*	Short lens, mag. mount, 10-16V	160.55
266TSLV-*	Short lens, vacuum mag. mount, 10-16V	197.73

281-*	Four wires, three-hole perm. mount, 10-32V	139.59
281B-*	Four wires, single bolt mount, 10-32V	151.42
281DIN-*	Din mount, 10-32V	167.31
281FDIN-*	Flexi-din mount, 10-32V	181.51
281M-*	Mag. mount, 9-16V	158.18
281R-*	Five wires, rotating pattern, 9-32V	140.61
281RFP-*	Flexi-din, rotating pattern, 9-32V	180.15
281RP-*	Din mount, rotating pattern, 9-32V	166.97


200A-12V-A	Bottom plate, 1" pipe and multi-hole mount, hardwired, 9-32V	205.17
------------	--	--------

200S-12V-*	1/2" NPT mount, flush mounting kit, hardwired, 9-32V	148.38
200SM-12V-*	Mag. mount, cig. plug, 9-16V	165.62

240C-12V-*	Tall dome, default flicker flash, perm. mount, 9-32V	139.93
240CF-12V-*	Tall dome, default flicker flash, flange, 1" pipe mount, 9-32V	139.93
240CM-12V-*	Tall dome, default flicker flash, mag. mount with cig. plug, 9-16V	156.83
240S-12V-*	Short dome, default flicker flash, perm. mount, 9-32V	139.93
240SF-12V-*	Short dome, default flicker flash, flange, 1" pipe mount, 9-32V	139.93
240SM-12V-*	Short dome, default flicker flash, mag. mount with cig. plug, 9-16V	156.83

STAR HALO® LED BEACONS

* = Colors: A, B, C, G, R



LIST

Model Number Description		LIST
255H8TAL-*	Ultra high intensity LEDs, tall lens, dust cover, perm. mount, 10-30V	209.22
255H8TALV-*	Ultra high intensity LEDs, tall lens, dust cover, vacuum mag. mount, 10-16V	253.50
255H8TCFL-*	Ultra high intensity LEDs, tall lens, flange mount, 10-30V	197.73
255H8TCL-*	Ultra high intensity LEDs, tall lens, perm. mount, 10-30V	197.73
255H8TCLM-*	Ultra high intensity LEDs, tall lens, mag. mount, 10-16V	209.22
255H8TCLV-*	Ultra high intensity LEDs, tall lens, vacuum mag. mount, 10-16V	244.04
255H8TSFL-*	Ultra high intensity LEDs, short lens, flange mount, 10-30V	197.73
255H8TSL-*	Ultra high intensity LEDs, short lens, perm. mount, 10-30V	197.73
255H8TSLM-*	Ultra high intensity LEDs, short lens, mag. mount, 10-16V	209.22
255H8TSLV-*	Ultra high intensity LEDs, short lens, vacuum mag. mount, 10-16V	244.04
255HTCFL-*	High intensity LEDs, tall lens, flange mount, 10-30V	170.01
255HTCL-*	High intensity LEDs, tall lens, perm. mount, 10-30V	170.01
255HTCLM-*	High intensity LEDs, tall lens, mag. mount, 10-16V	185.90
255HTCLV-*	High intensity LEDs, tall lens, vacuum mag. mount, 10-16V	244.04
255HTSFL-*	High intensity LEDs, short lens, flange mount, 10-30V	170.01
255HTSL-*	High intensity LEDs, short lens, perm. mount, 10-30V	170.01
255HTSLM-*	High intensity LEDs, short lens, mag. mount, 10-16V	185.90
255HTSLV-*	High intensity LEDs, short lens, vacuum mag. mount, 10-16V	220.71

STAR HALO® LED BEACONS (CONTINUED)

* = Colors: A, B, C, G, R



Model Number Description

List

257H8TAL-*	Ultra high intensity LEDs, tall lens, dust cover, perm. mount, 10-30V	228.15
257H8TALV-*	Ultra high intensity LEDs, tall lens, dust cover, vacuum mag. mount, 10-16V	289.33
257H8TCL-*	Ultra high intensity LEDs, tall lens, perm. mount, 10-30V	218.35
257H8TCLV-*	Ultra high intensity LEDs, tall lens, vacuum mag. mount, 10-16V	279.53
257H8TSL-*	Ultra high intensity LEDs, short lens, perm. mount, 10-30V	218.35
257H8TSVL-*	Ultra high intensity LEDs, short lens, vacuum mag. mount, 10-16V	279.53
257HTCL-*	High intensity LEDs, tall lens, perm. mount, 10-30V	189.96
257HTCLV-*	High intensity LEDs, tall lens, vacuum mag. mount, 10-16V	251.13
257HTSL-*	High intensity LEDs, short lens, perm. mount, 10-30V	189.96
257HTSVL-*	High intensity LEDs, short lens, vacuum mag. mount, 10-16V	251.13

251H8TAL-*	Ultra high intensity LEDs, tall lens, dust cover, perm. mount, 10-30V	257.56
251H8TAL-BG-*	Ultra high intensity LEDs, tall lens, dust cover, branch guard, perm. mount, 10-30V	283.58
251H8TCL-*	Ultra high intensity LEDs, tall lens, perm. mount, 10-30V	246.06
251H8TCL-BG-*	Ultra high intensity LEDs, tall lens, branch guard, perm. mount, 10-30V	272.09
251H8TSL-*	Ultra high intensity LEDs, short lens, perm. mount, 10-30V	246.06
251H8TSL-BG-*	Ultra high intensity LEDs, short lens, branch guard, perm. mount, 10-30V	272.09
251HTAL-*	High intensity LEDs, tall lens, dust cover, perm. mount, 10-30V	242.35
251HTAL-BG-*	High intensity LEDs, tall lens, dust cover, branch guard, perm. mount, 10-30V	273.78
251HTCL-*	High intensity LEDs, tall lens, perm. mount, 10-30V	236.26
251HTCL-BG-*	High intensity LEDs, tall lens, branch guard, perm. mount, 10-30V	261.95
251HTSL-*	High intensity LEDs, short lens, perm. mount, 10-30V	236.26
251HTSL-BG-*	High intensity LEDs, short lens, branch guard, perm. mount, 10-30V	261.95
BB274-251DK	Target tech adaptor kit, includes bottom dish, case spinning, gasket, and hardware	75.71
BB274-251K	Target tech adaptor kit, includes case spinning, J bolts, rubber bottom gasket, and hardware	56.11

200AH8L-*	Ultra high intensity LEDs, perm. mount, 10-30V	290.34
200AHL-*	High intensity LEDs, perm. mount, 10-30V	267.02

200BH8L-*	Ultra high intensity LEDs, perm. mount, 3/4" pipe mount, 10-30V	310.28
200BHL-*	High intensity LEDs, perm. mount, 3/4" pipe mount, 10-30V	285.27

200CFH8L-*	Ultra high intensity LEDs, perm. mount, three hole flange base, 10-30V	267.70
200CFHL-*	High intensity LEDs, perm. mount, three hole flange base, 10-30V	243.36
200CH8L-*	Ultra high intensity LEDs, perm. mount, 10-30V	255.53
200CHL-*	High intensity LEDs, perm. mount, 10-30V	234.91

200SH8L-*	Ultra high intensity LEDs, perm. mount, 1/2" pipe mount, 10-30V	243.36
200SH8LM-*	Ultra high intensity LEDs, mag. mount, 10-16V	260.94
200SHL-*	High intensity LEDs, perm. mount, 1/2" pipe mount, 10-30V	231.19
200SHLM-*	High intensity LEDs, mag. mount, 10-16V	248.09

242CFL-12V-*	Tall lens, photocell, die cast base, flange perm. mount, 1" pipe mount, 9-32V	150.41
242CL-12V-*	Tall lens, photocell, die cast base, perm. mount, 1" pipe mount, 9-32V	150.41
242CLM-12V-*	Tall lens, photocell, die cast base, mag. mount, 9-16V	169.68
242SFL-12V-*	Short lens, photocell, die cast flange perm. mount, 1" pipe mount, 12-24V	150.41
242SL-12V-*	Short lens, photocell, die cast base, perm. mount, 1" pipe mount, 12-24V	150.41
242SLM-12V-*	Short lens, photocell, die cast base, mag. mount, 12V	169.68

STAR HALO® LED BEACONS (CONTINUED)

* = Colors: A, B, C, G, R



COMPACT LED BEACONS

* = Dome colors: A, B, C, G, R

Model Number	Description	Lists
201ZL-	360° beacon, perm. mount, $\frac{1}{2}$ " pipe mount, 10-30V	75.0.
201ZLM-	360° beacon, mag. mount, 10-16V	91.9.
203MLM-	360° beacon, flange base, perm. mount, $\frac{1}{2}$ " pipe mount, 10-110V	87.9.
204ML-	360° beacon, flange base, perm. mount, 10-110V	67.9.
200E-110V-	Single flash, high/low, perm. mount, or $\frac{3}{4}$ " mount, 117V	201.1
200B-12V-	Single/double/quad flash, tall lens, dust cover, perm. mount, 12-24V	218.0.
200E-110V-	Single/double/quad flash, tall lens, dust cover, perm. mount, 12-24V	218.0.
211R-12V-	C2LED warming beacon, rubber base, perm. mount on two studs on $\frac{4}{15}$ " centres, 10-30V	99.3.

Add \$10.00 for AC voltage option (not available for all lights)

STROBE BEACONS

* = Dome colors: A, B, C, G, R

Model Number	Description	Lists
241S-12V-	Single/double/quad flash, perm. mount, $\frac{1}{2}$ " pipe mount, 12-24V	139.9.
241SF-12V-	Single/double/quad flash, range perm. mount, $\frac{1}{2}$ " pipe mount, 12-24V	142.9.
241SM-12V-	Single/double/quad flash, mag. mount, 12V	156.8.
200U-	Single flash, medium profile, perm. mount, $\frac{1}{2}$ " pipe mount, 110V	169.0.
200U-1-	Single flash, outer dome, medium profile, perm. mount, $\frac{1}{2}$ " pipe mount, 110V	213.0.
735PS-	Single flash, portable strobe, 360° lens Safety Orange plastic base, perm. mount, requires (2) 6V batteries	174.7.
735PSM-	Single flash, portable strobe, 360° lens Safety Orange plastic base, perm. mount, requires (2) 6V batteries	198.0.

REVOLVING AND FLASHING BEACONS

* = Dome colors: A, B, C, G, R, M

Model Number	Description	Lists
450A-12V-	Standard duty, rotating, open base, perm. mount, 12V	148.75.
450B-12V-	Standard duty, rotating, enclosed base, perm. mount, 12V	148.75.
450B-12V-	Halogen, high intensity, rotating, open base, perm. mount, 12V	223.06.
450BH-12V-	Halogen, high intensity, rotating, enclosed base, perm. mount, 12V	223.06.
20RH-12V-	Halogen, high intensity, rotating, die cast base, perm. mount, 12V	101.4C
20RHF-12V-	Halogen, high intensity, fast rotator, die cast base, perm. mount, 12V	101.4C
20RHM-12V-	Halogen, high intensity, rotating, die cast base, mag. mount, 12V	118.98.

HALOGEN DASH LIGHTS AND ACCESSORIES

* = Dome colors: A, B, C, G, R, M

Model Number	Description	Lists
1188H-	Hostot II, halogen, perm. mount, 12V	103.09
1188HM-	Hostot II, halogen, mag. mount, 12V	113.23
1166HM-	Teardrop, halogen, mag. mount, 12V	113.23
274-874	Dash bracket, suction cups	86.16
274-878	Multiple flash adapter, mirror array for 1188H series	86.16

LED LIGHTS

** = LED colors: A, B, G, R, W

Model Number	Description	List
ULB9E-..	Eight mid power LEDs, c/w plug, 10-16V	139.59
ULB9E-1-..	Eight mid power LEDs, c/w plug, 10-16V	139.59
RLKULB9E-1-..	Flashing light kit, dual head, rear mounting, 12 cable, sync, capability, 10-16V	272.77
ULB9D-..	Lumen X™, dual color, c/w plug, 10-16V	267.02
ULB9LDC-1-..	Lumen X™, dual color, 12 cable, 10-16V	290.34
ULB9LDC-..	MicroStar™, three LED, wide spread, black die cast base, flush mount, 10-16V	63.88
DLT3-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount 10-16V	109.17
DLT4-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT5-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT6-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT7-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT8-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT9-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT10-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT11-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT12-..	MicroStar™, wide spread, black die cast base, spot, black die cast base, flush mount, 10-16V	109.17
DLT13-..	DLT3 universal mounting bracket	18.93
DLT14-..	Quad license plate bracket kit for DLT's	67.26
DLT15-..	MicroSiar™, license plate bracket kit	33.80
DLT16-..	MicroSiar™, universal bracket kit	18.93
DLT17-..	Ford Interceptor SUV front grille bracket kit for DLT3 lights	30.08
DLS306-..	Mini-Comet™, spherical, black bezel, 10-30V	127.76
DLS306C-..	Mini-Comet™, spherical, chrome bezel, 10-30V	139.59
DLX3-..	Versa Star®, three LED array, black bezel, flush or bracket mount, 10-16V	81.46
DLX4-..	Versa Star®, high power, three LED array, black bezel, amber only flush or bracket mount, 10-16V	90.92
DLX4C-..	Versa Star®, four LED array, black bezel, flush or bracket mount, 10-16V	98.02
DLX5-..	Versa Star®, six LED array, chrome bezel, bracket mount, 10-30V	109.17
DLX5C-..	Versa Star®, six LED array, chrome bezel, bracket mount, 10-30V	139.59
DLX6-..	Versa Star®, six LED array, black bezel, flush mount, 10-30V	105.12
DLX6C-..	Versa Star®, six LED array, chrome bezel, flush mount, 10-30V	116.27

FLASHING BEACONS VERY LOW PROFILE

* = Dome colors: A, B, C, G, R

Model Number	Description	List
21ZM-12V-.	Flashing incandescent, polycarbonate base, perm, mount, 12V	66.59
21ZM-12V-.	Flashing incandescent, clear outer dome, die cast base, retaining ring, 12V	83.49
20FL-1-..	Flashing incandescent, die cast base, retaining ring, 12V	87.20
20FL-..	Flashing incandescent, clear outer dome, die cast base, retaining ring, 12V	85.51
735FLSB-PC-.	Portable strobe, steady burn/flashing/on/off, Safety Orange case, 6V - steady burn	89.57

LED LIGHTS (CONTINUED)

Model Number Description

LED LIGHTS (CONTINUED)

** = LED colors: A, B, G, R, W