

## **NEW BUILD SHEET - TYPE III L FORD E-450 GAS**

237 **CHASSIS: STANDARD SPECIFICATIONS**

238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385

The chassis model year shall be: 2025

The chassis engine shall be a gas - powered engine.

( 1 ) The cab for the chassis will be ordered "**standard OEM white**" from the chassis manufacturer.

( 1 ) The chassis will be SUPPLIED BY EXCELLANCE.

Note: Excellence is entitled to OEM concessions on any chassis supplied by Excellence.

**FORD E-SERIES** (XL TRIM LEVEL, #47A AMBULANCE PREP PKG.)

\* Includes battery compartment with sliding tray.

( 1 ) **E-450 (SD) Type III LSD** 96" x 166" box  
CA = 100"

**CUSTOMER NOTES / SPECIAL REQUESTS regarding chassis**

**\*\* REF. Lines 293 & 294: The chassis price included in this quote is pricing for a 2025 model year. Chassis price increases will be applied for any subsequent year model thereafter for the remaining contract term.**

**CHASSIS: SPECIAL OPTIONS**

The vehicle will be ready for delivery w/ electrical diagrams, cleaned, inspected, fuel tanks full, vehicle serviced, certified weight ticket, and copies of all warranties and owners manuals.

Air tanks installed by Excellence will have manual moisture relief valves.

( 1 ) \* Ford Chassis service manuals: [fleet.ford.com/truckbbas](http://fleet.ford.com/truckbbas)

( 1 ) \* Running Boards, Diamond Plate with grating and Excellance logo welded into step area for Type III

**CUSTOMER NOTES / SPECIAL REQUESTS**

**\*\* Install an engraved aluminum plate with "EXCELLANCE", Unit #, and date of manufacture on the forward wall of the L4 compartment. (CAAS Req.)**

**CHASSIS: TIRE / WHEEL OPTIONS**

OEM Steel-belted All-Weather Radial tires per chassis specifications

( 1 ) \* A spare OEM tire will be ordered with the chassis.

( 1 ) \* Spare tire shall be "shipped loose"

( 1 ) \* Wheel Inserts for E-series "Phoenix" stainless steel w/ rear air valve extension

**CHASSIS: EXTERIOR OPTIONS**

( 1 ) \* Mud Flaps, 2 Rear

**CHASSIS: INTERIOR CAB OPTIONS**

( 1 ) Ford E-series: medium gray interior cab color is the only choice available

( 1 ) Cab floorboard to have rubber matting

**CHASSIS ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**

Module disconnect power switch

( 1 ) Type III light duty includes addition of exterior battery compartment in R4-2

OEM alternator(s) with internal regulator

Back-up alarm, reverse activated

687 **CHASSIS ELECTRICAL SYSTEM: INTERIOR CAB OPTIONS**

688

- 689 ( 1 ) Engine cover mounted console on Type III units
- 700 ( 1 ) Map Light, Flex-head Littlelite with red lens (12" shaft) located on front console
- 708 ( 1 ) Volt Meter with Dual USB port installed on console switch panel.

710

- 724 ( 1 ) \* Pro-Vision TV-205 rear camera system with 5" LCD flat screen monitor on the cab console. (CAAS Req.)

725

735

736

**CUSTOMER NOTES / SPECIAL REQUESTS**

**\*\* Install a Tremco anti-theft, ignition security device. This device automatically engages when vehicle is placed in the park position. (CAAS Req.)**

737

738

745

746

**MODULAR BODY: STANDARD SPECIFICATIONS**

747

748

All aluminum modular ambulance body with 1/4-inch thick aluminum corner extrusions

749 ( 1 )

Module headroom shall be 69 inches for this non-EHD unit.

753

All aluminum framework with special anti-corrosion barrier applied to all fasteners, hinges, and components

754

Aluminum exterior skin shall be .125" thick, attached by continuous welds at all seams and corners

755

Aluminum exterior roof skin shall be .125" thick aluminum

757

3/4-inch thick composite floor with .063" aluminum subfloor insulated with Polystyrene foam planking

758

Install .125" thick Aluminum overlay to the top of the Coosa Board floor

762

3 module entry doors and all exterior compartment doors insulated with 2" Styrofoam planking

763 ( 1 )

Left rear door shall close with an automatic "slam latch"

764

2 key locking module entry door handles all keyed alike

765 ( 1 )

Curbside entry door equipped with gas shock and nylon restraint strap to reduce opening and closing force

769

Number of grabber / hold-open devices with gaskets: 2

770

Polished extruded aluminum drip rails over all module entry doors and exterior compartment doors

771 ( 1 )

\* Polished Aluminum Drip Rail around entire module roof perimeter. (CAAS Req.)

772 ( 1 )

Fuel fill housing for chassis to be: recessed cast aluminum housing(s)

776

1 set aluminum diamondplate stone guards for front of unit

778

1 set diamondplate rub rails with aluminum tubular support & plastic spacers off body

779

2 aluminum wheelwells

780 ( 1 )

1 set polished cast aluminum module fenderettes

783

1 diamondplate rear kick panel

785 ( 1 )

10 body mounting 5/8" diameter Grade 8 bolts w/ heavy duty wear point spacers

788

1 custom-made aluminum diamondplate rear bumper with the following features:

789

angled rear corners

790

folding step built into bumper

791

1 dock bumper(s) each side of bumper

792

All windows installed in the patient compartment come with "privacy glass"

793

Fixed window for each rear entry door. Specify size: 12" x 24"

795 ( 1 )

Fixed curbside entry door window. Specify size: 18" x 24"

813

814

**MODULAR BODY: OPTIONS**

815

819 ( 1 )

Type III: Walk-thru between cab and module with sliding lockable door

869

870

**CAB / MODULE PAINT AND LETTERING: STANDARD SPECIFICATIONS**

871

874 ( 1 )

\* DELETION CREDIT: Do not paint the 4 outer wheels

875

Include one touch up paint kit for each color used

880 ( 1 )

\* DELETION CREDIT: Delete Federal ambulance markings

881

882

**PAINT OPTIONS**

883

884

The cab for the chassis will be ordered and painted standard OEM white.

885 ( 1 )

The module shall be painted the same color to match the chassis.

898 ( 1 )

\* Metallic paint will not be used anywhere on this unit.

911

912

**BELTLINE**

914 ( 1 )

\* DELETE standard 11" reflective beltline stripe

959  
 960 [PINSTRIPE](#)  
 964 ( 1 ) \* DELETION: No pinstripe tape AND no painted beltline to be applied by factory  
 1030  
 1031 **LETTERING OPTIONS**  
 1032  
 1033 ( 1 ) **Excellance-supplied/installed lettering is not included but can be provided for an additional cost.**

1052 **EXTERIOR COMPARTMENTS: STANDARD SPECIFICATIONS**

1053  
 1054  
 1055 All exterior compartment doors insulated with 2" styrofoam  
 1056 206 latch w/ key locking stainless steel 9000 series D-ring handles with gaskets (where possible)  
 1058 ( 1 ) Doors equipped with gas shocks to reduce opening and closing force  
 1065 Machine louvered or plastic venting, as needed, in all exterior compartments  
 1066 ( 1 ) Battery storage compartment below R4, WITH sliding tray (standard only on Type III)  
 1074 Note: Battery storage compartment R4-2 to have 52C door latch in lieu of 206 latch  
 1087

1088 **EXTERIOR COMPARTMENTS: OPTIONS**

1089 All aluminum unistruts to be welded into exterior compartments (no screws or rivets)  
 1090 \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)  
 1091

1092 [Compartment L1: \(Streetside Rear\)](#)

1093 ( 1 ) Tall L1 version - standard for 146" & 166" modules  
 1094 ( 1 ) \* Backboard storage in L1 will have 2 adjustable vertical dividers

| Type of shelves in L1:           | Quantity | Thickness of aluminum |
|----------------------------------|----------|-----------------------|
| Adjustable shelves with unistrut | 3        | 0.125"                |
| Fixed shelves                    | 0        | 0.125"                |

1100 ( 1 ) Inside / Outside access with interior cabinet door  
 1106 ( 1 ) One standard LED light in compartment - to be door activated  
 1127

1128 [Compartment L3/1: \(Outside electrical compartment for power distribution panel\)](#)

1135 ( 1 ) One standard LED light in compartment - to be door activated  
 1144

1145 [Compartment L3/2: \(Streetside Intermediate\)](#)

| Type of shelves in L3/2:         | Quantity | Thickness of aluminum |
|----------------------------------|----------|-----------------------|
| Adjustable shelves with unistrut | 1        | 0.125"                |
| Fixed shelves                    | 0        | 0.125"                |

1156 ( 1 ) One standard LED light in compartment - to be door activated  
 1177

1178 [Compartment L4: \(Streetside Forward\)](#)

| Type of shelves in L4:           | Quantity | Thickness of aluminum |
|----------------------------------|----------|-----------------------|
| Adjustable shelves with unistrut | 0        | 0.125"                |
| Fixed shelves                    | 0        | 0.125"                |

1185 ( 1 ) One standard LED light in compartment - to be door activated  
 1203

1205 [Compartment R1: \(Curbside Rear\)](#)

1222 ( 1 ) Tall R1 - standard on 166" & over boxes - includes short R2 unless deleted at

1225 ( 1 ) \* Backboard storage in Tall R1. # of adjust. dividers: 2

| Type of shelves in Tall R1:      | Quantity | Thickness of aluminum |
|----------------------------------|----------|-----------------------|
| Adjustable shelves with unistrut | 0        | 0.125"                |
| Fixed shelves                    | 0        | 0.125"                |

1232 ( 1 ) Outside access for Tall R1  
 1235 ( 1 ) One standard LED light in R1 compartment - to be door activated  
 1252

1253 ( 1 ) [Compartment Short R2: \(Curbside Rear\)](#) Only available if Tall R1 is selected.

1255 ( 1 ) Inside / Outside access for Short R2

| Type of shelves in R2:           | Quantity | Thickness of aluminum |
|----------------------------------|----------|-----------------------|
| Adjustable shelves with unistrut | 1        | 0.125"                |
| Fixed shelves                    | 0        | 0.125"                |

1263 ( 1 ) One standard LED light in compartment - to be door activated  
 1279

1280 [Compartment R4: \(Curbside Forward\)](#)

- 1281 ( 1 ) Inside / Outside access for full height of R4 compartment
- 1295 ( 1 ) Drug box storage in R4 shall have a locking Painted Aluminum
- 1296 ( 1 ) Cabinet beside the drug box storage in R4 will have inside / outside
- 1297 access with a non-locking Painted Aluminum
- 1298 The vertically-hinged doors will be individually latching doors

| Type of shelves in R4:           | Quantity | Thickness of aluminum |
|----------------------------------|----------|-----------------------|
| Adjustable shelves with unistrut | 2        | 0.125"                |
| Fixed shelves                    | 0        | 0.125"                |

- 1318 ( 1 ) One standard LED light in compartment - to be door activated
- 1334
- 1417 ( 5 ) Number of exterior compartment(s) to be finished in Excellence texturized paint.
- 1418 Specify each compartment here: ALL - EXCEPT R4 which is to be finished white
- 1489

**PATIENT COMPARTMENT: STANDARD SPECIFICATIONS**

- 1492
- 1493 Install clear polycarbonate throughout the unit.
- 1497 Full seam-welded NFPA-compliant anti-skid aluminum diamondplate stepwell with flush sweep-out design
- 1498 Door-activated flush-mounted stepwell light, LED
- 1499 3 interior entry door panels, aluminum painted white
- 1500 ( 1 ) Alternating red/white 10" reflective diagonal stripes on each Personnel Door
- 1505 Grab handles for module doors to be: 1.25" diameter seamless stainless steel
- 1506 ( 1 ) Grab handle(s) for the inside of the side entry door: 18" long
- 1508 ( 1 ) Grab handle(s) on each rear door inside the module: "L" shape 33" x 17.5"
- 1509 Aluminum walls painted white
- 1510 Aluminum ceiling finish painted white
- 1511 ( 1 ) Insulation in the module walls and ceiling
- 1513 Welded tubular aluminum cabinet framework with cabinet tubular faces painted white
- 1514 Sliding medical cabinet doors of 1/4" polycarbonate with full height extruded aluminum handles
- 1515 All cabinet interiors are to be painted white
- 1516 Cabinets have Austin latches on hinged cabinet doors and Safety Pins on sliding doors (KKK compliant)
- 1517 Cabinets will be labeled with their rated weight capacity
- 1518 Streetside action area with solid surface counter top
- 1519 The color for all counter tops will be: light gray w/ white & charcoal speckles
- 1527 Action area shelf to have lip
- 1528 Oxygen compartment shall have one polycarbonate hinged access door for "M" & "H" size cylinders
- 1529 Squad bench w/vinyl covered padded split seat cushion and with a hinged lid
- 1530 two 6-point seat belt harnesses: red
- 1531 sets of patient restraint straps: 3 red
- 1532 Squad bench to have a solid vinyl covered padded back rest and head rest
- 1533 2 "No smoking oxygen equipped / Fasten your seatbelt" decals, one in cab and one in module
- 1534 Removable wiring access panels, vinyl padded down the center of the ceiling w/ 1" x 2" tubular supports
- 1536 ( 1 ) # of 96" x 1.25" diameter stainless steel overhead grab rails on 166" module: 2
- 1539 1 CPR seat with vinyl covered padded seat and head protectors
- 1540 CPR seat to have 6-point seat belt harness

**PATIENT COMPARTMENT: OPTIONS**

- 1562
- 1563 Painted white interior
- 1564
- 1565 \* High back EMT Captains Chair (Bucket Seat) at Action Area w/ these features:
- 1571 Built-in Child-Safety Seat? No
- 1572 # of seat belt harness points: 6
- 1573 # of arm rests: 0 no arm rests
- 1577 ( 1 ) \* Sewn upholstery
- 1579 ( 1 ) \* WISE brand

| Type of IV holder                | Quantity | Mounting location for IV holders: |
|----------------------------------|----------|-----------------------------------|
| Rubber shaft fold-down w/ velcro | 1        | head of primary cot               |
| Rubber shaft fold-down w/ velcro | 1        | head of squad bench               |

- 1619
- 1620 Cabinet over Action Area to have...
- 1621 ( 1 ) Sliding doors that are made of polycarbonate
- 1687

1688 **BIO-HAZARD / TRASH CONTAINERS:**

1689

1693 ( 1 ) **DELETE both wall mounted Maxim kits**

1712 ( 1 ) \* Shorten the curbside squad bench and install an access door for two  
 1713 one-gallon containers (one Sharps and one Trash). Each container will  
 1714 have its own hinged surface-mounted polycarbonate lid (one red and one clear,  
 1715 each with a knob) built into the access door. The access door will have a flush-  
 1716 mounted stainless steel key locking latch for container removal.  
 1753

1754 **SEATING / UPHOLSTERY: OPTIONS**

1755

1756 Padded vinyl head protectors over module entryways, color coordinated to match interior

1759 ( 1 ) **Gray color for upholstery (Gray)**

1768 ( 1 ) **Net at head of Squad Bench, standard 58" x 17" (Red unless specified in Customer Notes)**

1784

1785 **FLOOR COVERING: OPTIONS**

1786

1787 Heavy duty vinyl floor covering will be installed inside patient compartment

1788 ( 1 ) \* **Lonseal / Lonplate II flooring (this flooring will extend up the side walls)**

|                                  |             |                           |
|----------------------------------|-------------|---------------------------|
| Type of floor selected above:    | Floor color | Curbside wall covered in: |
| * Lonseal / Lonplate II flooring | 421 Mica    | Floor covering            |

|                             |
|-----------------------------|
| Streetside wall covered in: |
| Floor covering              |

1807

1808 **HANDRAILS / MOUNTING BRACKETS: OPTIONS**

1809

1810 ( 1 ) All handrails will be stainless steel, knurled, antimicrobial rails painted (powder coated) yellow.

1823

1824

1825 **COT / LITTER MOUNT: OPTIONS**

1826

1827 The cot used in this unit will be a: ( Brand ) TBD ( Model ) TBD

1828 The cot will be supplied by: **Customer**

1829 The retention system will be supplied by: **Customer**

1830 *Purchaser / Customer agrees to indemnify and hold Excellence harmless for the installation of any*  
 1831 *cot retention system specified by the Customer that is not compliant with any governmental authority.*

1832

1833 **The mounting position for the cot shall be:**

1834 ( 1 ) \* Center mount for one cot

1836

1838 ( 1 ) **Post and wheel cups will NOT be installed in the patient compartment.**

1844

1845 **THE COT WILL BE SUPPLIED BY CUSTOMER**

1849 **THE RETENTION SYSTEM WILL BE SUPPLIED BY CUSTOMER**

1850 **\*\* Install customer-supplied cot retention system. Excellence can supply upon request**  
 1851 **for an additional cost.**

1867

1868 **MODULE ELECTRICAL SYSTEM: STANDARD SPECIFICATIONS**

1869

1870 12 VDC electrical distribution system

1871 Color and function coded wiring

1872 GXL high temperature wiring insulation

1873 Automatic reset circuit breakers

1874 Heat shrink tubing on all terminals

1875 Lighted rocker switches

1876 Engraved backlit switch labels

1877 1 labeled power distribution panel will be located in the exterior L3/1 compartment

1879 Patient compartment control console with hinged access panels in action area

1880 12 VDC Medical outlets to be installed as follows:

|                 |          |                         |
|-----------------|----------|-------------------------|
| Type of outlet: | Quantity | Location for outlet(s): |
| Cigarette       | 2        | Action Area             |

1889

1890 Magnetically controlled, hermetically sealed door switches

1891 "Module Entry Door Open" warning circuit w/ warning light in cab console

1895 Door activated exterior compartment lighting

1896 All of the dome lights located on the curbside to turn on to low intensity when  
 1897 module entry doors are opened and/or switch on cab console is activated  
 1898 All switches, indicators and control devices shall be labeled in accordance w/ current KKK-A-1822  
 1900

1901 **MODULE ELECTRICAL SYSTEM: OPTIONS**

1902  
 1903 1 Kussmaul #091-32 Load Manager / Sequencer.  
 1904 Load Manager and status indicator to be located in cab console.  
 1905 ( 1 ) Excellance will determine load manager circuits and sequence of priority.  
 1914

1927 2 #RG58U coax antenna cables from center wiring trough to behind driver's seat  
 1929 \* Location for origination of first "std" coax cable: module center trough  
 1930 \* Location for termination of first "std" coax cable: behind the cab seat  
 1931 \* Location for origination of 2nd "std" coax cable: module center trough  
 1932 \* Location for termination of 2nd "std" coax cable: behind the cab seat

1977 ( 1 ) TruckLite LEDs # 80162C EMT ("Standard" in action area)

1983  
 1985 ( 1 ) Four 8-inch LED dome lights mounted in ceiling on streetside  
 1986 ( 1 ) Four 8-inch LED dome lights mounted in ceiling on curbside  
 1996 ( 1 ) \* All ceiling lights to operate with two switches (one for streetside & one for curbside lights).  
 2048

2049 **125 VAC ELECTRICAL: STANDARD SPECIFICATIONS**

2050 Location for each 125 VAC duplex receptacle (interior to be lighted; exterior to be weatherproof):  
 2051  
 2052 ( 1 ) In Action Area  
 2053 ( 1 ) lower section of the R-4 ALS cabinet  
 2060 GFI circuit breaker box to be located: mounted in GFI box in electrical panel  
 2061 First GFI circuit breaker to be wired to: the engine block heater  
 2062 Second GFI circuit breaker wired to: the 125V electrical system  
 2077

2078 **SHORELINE OPTIONS**

2079  
 2080 ( 1 ) One 30 amp / 125 volt Twist Lock Shoreline Plug with  
 2081 weatherproof lift cover (with female Shoreline Input Adapter)  
 2114  
 2125 ( 1 ) \* **Shoreline to be mounted :** Side of module forward of L4 hinge  
 2140

2142 **125 VAC ELECTRICAL EQUIPMENT: OPTIONS**

2143  
 2148 ( 1 ) DELETION CREDIT: Delete the "standard" on-board battery charger  
 2164 **Specify the location for the inverter:** L3/2 compartment  
 2171 ( 1 ) \* Vanner 1100 watt inverter (model LSC12-1100) with transfer switch WITH  
 2172 battery charger  
 2200

2202 **SCENE AND EXTERIOR LIGHTS: STANDARD SPECIFICATIONS**

2203  
 2204 2 backup lights wired to operate with rear scene / load lights  
 2205 Rear license plate bracket shall be surface mounted on rear of unit with light  
 2206 1 set of red rear turn marker lights on each side of module using:  
 2207 ( 1 ) L.E.D. 4" round turn marker lights (part # 44350R)  
 2211

2212 **WORKLIGHTS / FLOODLIGHTS / SPOTLIGHT: OPTIONS**

2213  
 2214 The hand-held spotlight will be: recess-mounted on passenger side of front console  
 2215 ( 1 ) Minimum 100,000 CP lamp handheld spotlight w/ momentary switch (Standard)  
 2225  
 2229 ( 1 ) \* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome  
 2230 flange) on each side of module (in lieu of halogen lights).  
 2231 **Work / scene light on curbside of module activated by side entry door.**  
 2241 ( 1 ) \* 2 Whelen 900 Super-LED work / scene lights (surface mount with chrome  
 2242 flange) on rear wall of module.  
 2243 **Rear lights activated when rear doors are opened or transmission is put into reverse.**  
 2245 **Note: Scene lights on rear of module will be deleted when rear light bar has scene light option.**

2283  
2284  
2285  
2286  
2287  
2288  
2289  
2290  
2291  
2417  
2419  
2435  
2436  
2437  
2439  
2440  
2441  
2442  
2455  
2456  
2479  
2480  
2481  
2482  
2484  
2485  
2486  
2487  
2489  
2500  
2501  
2502  
2504  
2505  
2506  
2507  
2509  
2510  
2511  
2512  
2513  
2514  
2515  
2516  
2518  
2540  
2541  
2543  
2544  
2549  
2552  
2555  
2590  
2592  
2593  
2594  
2595  
2617  
2618  
2619  
2620

**TURN SIGNAL / TAIL LIGHTS: OPTIONS**

**Primary brake, turn signal & backup lighting**

The Primary brake, turn signal, and backup lights on the rear of the module will be:  
600 series L.E.D. lights as turn signals set in a triple Horizontal Casting  
600 series L.E.D. lights as brake lights set in a triple Horizontal Casting  
600 series L.E.D. lights as backup lights set in a triple Horizontal Casting

**GRILL LIGHTS / INTERSECTION LIGHTS**

**Grill Lights** shall be:

- ( 505 ) Whelen 500 Red L.E.D. w/o flange Lens color: clear
- ( 705 ) **Intersection Lights** on the driver's side shall be: Whelen 700 Red L.E.D. w/o flange
- ( 705 ) **Intersection Lights** on passenger's side shall be: Whelen 700 Red L.E.D. w/o flange

|              |
|--------------|
| Lens color:  |
| <u>clear</u> |
| <u>clear</u> |

**OTHER VISUAL WARNING LIGHTS: STANDARD SPECIFICATIONS**

Flashing light installed at the top center of front module wall shall be:

- ( 904 ) Whelen 900 series White LED with flange
- The color of the lens for this light is: clear

Flashing lights in each upper corner of the front module wall (2 total) shall be:

- ( 901 ) Whelen 900 series Red LED w/ flange
- The color of the lens for this light is: clear

Flashing lights in each upper corner of the curbside module wall (2 total) are:

- ( 901 ) Whelen 900 series Red LED w/ flange
- The color of the lens for this light is: clear

Flashing lights in each upper corner of streetside module wall (2 total) are:

- ( 901 ) Whelen 900 series Red LED w/ flange
- The color of the lens for this light is: clear

\* **Wheel well lights** on each side of module (2 total) shall be:

- ( 701 ) Whelen 700 series Red LED w/ flange
- The wheel well light lens color is: clear

Flashing lights in the upper corners of module rear wall (2 total) shall be:

- ( 901 ) Whelen 900 series Red LED w/ flange
- The color of the lens for this light is: clear

Flashing light installed at the top center of rear module wall shall be:

- ( 702 ) Whelen 700 series Amber LED w/ flange
- Color for this lens shall be: clear

**EMERGENCY AUDIBLE WARNING SYSTEM: OPTIONS**

- ( 1 ) 1 Whelen hands free electronic siren with cab console mounted controls w/ PA microphone
- Siren tones to be programmed in "default" mode.

**Speaker Options**

- ( 1 ) Two through-the-bumper mounted speakers ("standard" on E-350, E-450, G3500, G4500).

2651  
2653  
2654  
2655  
2656  
2657  
2658  
2659  
2662  
2663  
2674  
2677  
2678  
2693  
2694  
2722  
2742  
2743  
2744  
2745  
2746  
2780  
2782  
2783  
2784  
2785  
2786  
2787  
2788  
2789  
2820  
2821  
2822  
2823  
2824  
2908  
2910  
2911  
2912  
2914  
2970  
2974  
2975  
2976  
2977  
2995  
2996  
2997  
2998  
2999  
3000  
3001  
3002  
3003  
3004  
3005  
3006

**OXYGEN AND SUCTION SYSTEMS: STANDARD SPECIFICATIONS**

Oxygen system plumbing with cylinder wrench chained in oxygen compartment

**Tank Brackets: Options**

( 1 ) \* Oxygen tank(s) shall be located in compartment L4 (Streetside Forward)

( 1 ) \* Zico "MultiVersal" restraint system with adjustable bracket for a "M" tank  
1 oxygen regulator, 50 PSI

**Oxygen Systems: Options**

Ohio-Diamond type oxygen outlets.

( 1 ) \* 2 oxygen outlets located at EMT panel, 1 at curbside

**Vacuum System: Options**

Scor suction system with 1 canister and lid, on-off power switch, 5-foot exhaust hose,  
vacuum gauge and internal regulator (no vacuum outlet needed) - to be installed...

( 1 ) ... aft of action area control panel on the streetside interior wall.

**HVAC SYSTEMS: STANDARD SPECIFICATIONS**

12 VDC multi-speed exhaust fan at rear of module

1 static air intake at front curbside of module

Floor-level return air plenum with replaceable filter for A/C-heat unit

**HVAC SYSTEMS: OPTIONS**

**Ford E-series and Chevy G-series Type III Chassis**

12 Volt HVAC systems:

( 1 ) Heavy duty combination heater / air conditioner system w / digital  
electronic thermostat with digital temperature display.

( 1 ) \* Add under-body-mounted auxiliary A/C condenser

**FIRE EXTINGUISHER: OPTIONS**

( 2 ) 5# ABC fire extinguishers

\* Extinguisher mounting instructions: Mount at Delivery (CAAS Req.)

**SPECIAL REQUIREMENTS and/or OUTSOURCED ITEMS:**

**\*\* NCSA fee is included in the price of the vehicle.**

**\*\* For NC customers, A Division of Motor Vehicle Title Application Form will be with  
the delivery paperwork.**

**\*\* Delivery of the completed unit driven by driver to the end user's location.**

**CUSTOMER SUPPLIED PARTS**

It is Excellence policy for all parts to be supplied by Excellence. The reasons for this policy are to allow Excellence: (1) to better engineer and manufacture the vehicle by obtaining the parts in advance, (2) provide better control over tracking the delivery of all parts and getting the part to the correct vehicle for which it is intended, and (3) it allows Excellence to better adhere to its production schedule. Disruptions in our production schedule are very costly and wasteful in terms of labor. Therefore, exceptions to this policy will result in a charge of \$250.00 **per part** supplied by any dealer or customer PLUS the appropriate labor charge for installing any such part. Note: Excellence does not warrant the installation of customer supplied parts installed by Excellence! Excellence waives the \$250 "parts charge" for two-way radio equipment, radio antenna, and cots.